

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: NEO-RAY

Report Number: P1029661

Luminaire Tested: S122DIW-B675D435UB2750-4F0-XX-W2A-A_3000K

Issue Date: 5/6/2025

Test Information

Test Method: LM-79-2019
Report Number: P1029661
REPORT IS A COMBINATION OF REPORTS P986568 AND P1007351
Test Lab: INNOVATION CENTER
Issue Date: 5/6/2025
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: NEO-RAY
Catalog Number: S122DIW-B675D435UB2750-4F0-XX-W2A-A_3000K
Description: Define 2 Direct/Indirect Wall Mount with 3000K BioUP LEDs {m-DER=0.589} {m-EER=0.647}
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 4698.0 lumens
Efficiency: N/A
Efficacy: 95.7 lumens/watt
Spacing Criteria (0/90/45): 1.16 / 1.09 / 1.23
Luminous Opening: Rectangular w/ Sides (W: 0.17' x L: 4' x H: 0.1')
CIE Type: Semi-Direct

Input Watts (W): 49.1
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1029661

CATALOG NUMBER: S122DIW-B675D435UB2750-4F0-XX-W2A-A_3000K

Luminous Intensity Polar Plot



TEST NUMBER: P1029661

CATALOG NUMBER: S122DIW-B675D435UB2750-4F0-XX-W2A-A_3000K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20					20					20					20
RC	80				70					50					30					10
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10
RCR																				
0	110	110	110	110	103	103	103	103	90	90	90	79	79	79	68	68	68	68	68	68
1	101	97	93	90	95	91	88	85	80	78	76	70	68	67	61	60	58	58	58	58
2	93	85	80	75	87	80	75	71	71	67	64	62	59	57	54	52	50	50	50	50
3	85	76	69	63	79	71	65	60	63	58	54	56	52	49	49	46	43	43	43	43
4	78	67	60	54	73	64	57	51	57	51	47	50	46	42	44	41	38	38	38	38
5	72	61	53	47	67	57	50	45	51	45	41	45	41	37	40	36	34	34	34	34
6	67	55	47	41	62	52	45	39	46	40	36	41	37	33	36	33	30	30	30	30
7	62	50	42	36	58	47	40	35	42	36	32	38	33	29	33	30	27	27	27	27
8	58	45	38	32	54	43	36	31	39	33	29	35	30	26	31	27	24	24	24	24
9	54	42	34	29	50	40	33	28	36	30	26	32	27	24	29	25	22	22	22	22
10	50	38	31	26	47	36	30	25	33	27	24	30	25	22	27	23	20	20	20	20

AVERAGE LUMINANCE (cd/sqm):

	0°	90°	180°	270°
0°	21137	21137	21137	21137
5°	21187	22537	21268	17929
10°	20941	24603	21073	14781
15°	20433	25949	20718	12452
20°	20114	24365	20114	10822
25°	19473	20932	19562	9678
30°	18418	16454	18769	8766
35°	17484	11378	17776	8020
40°	16410	8590	16596	7427
45°	15085	7060	15332	6785
50°	13942	6196	13965	6211
55°	12636	5279	12716	5588
60°	11243	4410	11397	4877
65°	9996	3587	10178	4165
70°	8757	2815	8978	3359
75°	7351	2042	7636	2437
80°	5732	1295	6148	1446
85°	3772	651	4054	482

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 157.5°

Vertical Angle: 45°

Luminance: 21850 cd/sqm

TEST NUMBER: P1029661

CATALOG NUMBER: S122DIW-B675D435UB2750-4F0-XX-W2A-A_3000K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	127.2	2.7
10°-20°	370.2	7.9
20°-30°	537.2	11.4
30°-40°	566.3	12.1
40°-50°	501.2	10.7
50°-60°	400.2	8.5
60°-70°	271.8	5.8
70°-80°	139.1	3.0
80°-90°	33.9	0.7
90°-100°	19.7	0.4
100°-110°	73.4	1.6
110°-120°	194.7	4.1
120°-130°	322.9	6.9
130°-140°	343.0	7.3
140°-150°	318.8	6.8
150°-160°	256.3	5.5
160°-170°	165.2	3.5
170°-180°	56.8	1.2
0°-30°	1034.6	22.0
0°-40°	1600.9	34.1
0°-60°	2502.3	53.3
0°-90°	2947.0	62.7
90°-120°	287.8	6.1
90°-150°	1272.6	27.1
90°-180°	1751.0	37.3
0°-180°	4698.0	100.0

CANDELA DISTRIBUTION:

	0°	90°	180°	270°	360°	Flux
0°	1335	1335	1335	1335	1335	
5°	1336	1491	1341	1186	1336	127
15°	1255	1833	1273	880	1255	355
25°	1128	1527	1133	706	1128	516
35°	921	831	936	586	921	576
45°	691	501	702	481	691	536
55°	474	352	477	373	474	423
65°	281	217	286	252	281	280
75°	131	107	136	127	131	141
85°	27	28	29	20	27	31
90°	0	12	0	12	0	3
95°	28	19	28	19	28	33
105°	131	33	131	33	131	140
115°	248	35	248	35	248	245
125°	351	370	351	370	351	313
135°	435	449	435	449	435	336
145°	504	512	504	512	504	315
155°	555	556	555	556	555	256
165°	585	584	585	584	585	165
175°	599	595	599	595	599	57
180°	597	597	597	597	597	

TEST NUMBER: P1029661

CATALOG NUMBER: S122DIW-B675D435UB2750-4F0-XX-W2A-A_3000K

CANDELA DISTRIBUTION (FULL):

	0°	5°	10°	15°	20°	22.5°	25°	30°	35°	40°	45°
0°	1335.3	1335.3	1335.3	1335.3	1335.3	1335.3	1335.3	1335.3	1335.3	1335.3	1335.3
2.5°	1342.4	1345.5	1350.7	1351.7	1361.9	1370.2	1379.4	1379.4	1382.5	1381.4	1373.2
5°	1336.3	1345.5	1358.9	1370.2	1388.6	1396.8	1409.2	1418.4	1426.6	1432.8	1431.7
7.5°	1326.0	1342.4	1361.9	1383.5	1408.1	1422.5	1440.0	1456.4	1467.7	1477.9	1485.1
10°	1308.6	1336.3	1363.0	1391.7	1423.5	1443.0	1463.6	1485.1	1502.6	1522.1	1540.5
12.5°	1285.0	1325.0	1357.8	1395.8	1434.8	1456.4	1489.2	1505.6	1539.5	1588.8	1602.1
15°	1255.2	1309.6	1340.4	1388.6	1440.0	1457.4	1502.6	1529.2	1599.0	1629.8	1666.8
17.5°	1227.5	1288.1	1329.1	1384.5	1434.8	1468.7	1512.8	1567.2	1625.7	1669.9	1710.9
20°	1204.9	1263.4	1312.7	1374.3	1437.9	1481.0	1527.2	1592.9	1656.5	1701.7	1733.5
22.5°	1153.6	1228.5	1286.0	1354.8	1431.7	1491.3	1535.4	1607.2	1676.0	1703.7	1731.4
25°	1127.9	1192.6	1259.3	1337.3	1427.6	1498.5	1536.4	1616.5	1677.0	1687.3	1693.5
27.5°	1080.7	1153.6	1231.6	1320.9	1426.6	1486.1	1534.4	1607.2	1655.5	1648.3	1629.8
30°	1022.2	1111.5	1197.7	1294.2	1412.2	1476.9	1522.1	1588.8	1613.4	1576.5	1543.6
32.5°	979.1	1063.3	1158.7	1270.6	1395.8	1457.4	1501.5	1553.9	1559.0	1492.3	1436.9
35°	920.6	1014.0	1121.8	1239.8	1368.1	1423.5	1464.6	1496.4	1471.8	1378.4	1312.7
37.5°	868.3	960.7	1075.6	1195.7	1330.1	1384.5	1417.4	1422.5	1361.9	1279.8	1183.4
40°	810.8	906.3	1026.3	1152.6	1288.1	1335.3	1355.8	1340.4	1253.2	1157.7	1045.8
42.5°	753.3	847.8	977.1	1106.4	1234.7	1274.7	1282.9	1240.8	1134.1	1022.2	892.9
45°	690.7	789.3	918.6	1048.9	1173.1	1195.7	1196.7	1136.2	1009.9	892.9	772.8
47.5°	639.4	730.8	859.0	989.4	1094.1	1109.5	1103.3	1033.5	896.0	764.6	659.9
50°	583.0	670.2	797.5	925.8	1015.0	1019.2	1003.8	904.2	769.8	649.7	566.5
52.5°	522.4	610.7	727.7	850.8	930.9	924.7	895.0	788.2	662.0	562.4	498.8
55°	474.2	552.2	662.0	782.1	838.5	821.1	788.2	679.4	579.9	495.7	440.3
57.5°	420.8	489.6	597.3	702.0	734.9	718.4	685.6	584.0	491.6	428.0	391.0
60°	370.5	433.1	527.5	614.8	640.4	623.0	585.0	493.7	427.0	373.6	345.9
62.5°	324.3	378.7	457.7	537.8	548.1	530.6	497.8	423.9	366.4	324.3	303.8
65°	281.2	332.5	396.2	456.7	466.0	447.5	413.6	360.2	312.0	285.3	265.8
67.5°	239.1	280.2	336.6	380.8	385.9	368.5	340.7	297.6	267.9	239.1	224.8
70°	202.2	233.0	277.1	313.0	315.1	298.7	284.3	245.3	222.7	202.2	190.9
72.5°	166.3	187.8	221.7	248.4	249.4	239.1	225.8	201.2	181.7	167.3	156.0
75°	131.4	149.8	170.4	194.0	193.0	184.7	174.5	159.1	142.7	133.4	128.3
77.5°	100.6	111.9	128.3	143.7	143.7	139.6	133.4	122.1	111.9	102.6	97.5
80°	71.8	79.0	92.4	97.5	99.6	98.5	93.4	85.2	81.1	73.9	71.8
82.5°	46.2	51.3	57.5	62.6	65.7	63.6	62.6	58.5	52.3	50.3	48.2
85°	26.7	28.7	31.8	34.9	35.9	34.9	36.9	33.9	30.8	30.8	29.8
87.5°	11.3	12.3	14.4	14.4	15.4	15.4	14.4	15.4	15.4	14.4	13.3
90°	0.4	1.5	2.5	3.6	4.7	5.2	5.6	6.3	7.1	7.8	8.6
92.5°	10.8	10.4	10.0	9.7	9.3	9.1	9.2	9.5	9.8	10.1	10.4
95°	28.1	24.9	21.7	18.6	15.4	13.8	14.1	14.8	15.5	16.2	16.9
97.5°	50.6	42.7	34.8	26.9	19.0	15.1	15.9	17.4	18.9	20.5	22.0
100°	76.5	63.3	50.2	37.0	23.9	17.3	18.1	19.7	21.4	23.0	24.6
102.5°	105.0	104.8	104.6	104.5	104.3	104.2	95.5	78.0	60.5	43.0	25.5
105°	131.4	134.3	137.1	140.0	142.9	144.3	131.2	105.0	78.8	52.6	26.4
107.5°	162.1	164.5	166.9	169.3	171.7	172.9	156.7	124.3	92.0	59.6	27.2
110°	191.5	193.5	195.5	197.5	199.5	200.5	186.6	158.9	131.1	103.4	75.6

TEST NUMBER: P1029661

CATALOG NUMBER: S122DIW-B675D435UB2750-4F0-XX-W2A-A_3000K

CANDELA DISTRIBUTION (continued):

	0°	5°	10°	15°	20°	22.5°	25°	30°	35°	40°	45°
112.5°	219.1	220.8	222.6	224.3	226.0	226.9	226.1	224.4	222.8	221.1	219.5
115°	248.5	250.1	251.7	253.4	255.0	255.8	257.0	259.4	261.8	264.2	266.6
117.5°	274.0	275.9	277.8	279.7	281.6	282.6	283.4	285.1	286.7	288.4	290.0
120°	302.5	303.9	305.4	306.8	308.3	309.0	309.9	311.6	313.3	315.1	316.8
122.5°	326.7	328.2	329.8	331.3	332.8	333.6	334.6	336.5	338.4	340.4	342.3
125°	351.4	352.6	353.9	355.1	356.4	357.0	357.9	359.7	361.6	363.4	365.2
127.5°	373.8	375.2	376.5	377.9	379.2	379.9	380.6	382.1	383.5	385.0	386.4
130°	395.0	396.5	398.1	399.6	401.1	401.9	402.4	403.5	404.6	405.6	406.7
132.5°	416.6	417.8	419.1	420.3	421.6	422.2	422.7	423.8	424.9	425.9	427.0
135°	434.8	436.3	437.9	439.4	440.9	441.7	442.1	443.0	443.9	444.7	445.6
137.5°	453.8	455.0	456.1	457.3	458.4	459.0	459.5	460.4	461.4	462.3	463.3
140°	472.4	473.2	473.9	474.7	475.4	475.8	476.3	477.4	478.5	479.5	480.6
142.5°	487.9	488.6	489.2	489.9	490.6	490.9	491.5	492.8	494.1	495.3	496.6
145°	504.3	504.2	504.1	504.0	503.9	503.9	504.7	506.4	508.0	509.7	511.3
147.5°	518.6	518.3	518.0	517.7	517.4	517.3	518.1	519.8	521.4	523.1	524.7
150°	532.4	531.7	531.1	530.4	529.7	529.4	530.2	531.7	533.2	534.8	536.3
152.5°	544.1	543.3	542.5	541.8	541.0	540.6	541.3	542.8	544.2	545.7	547.1
155°	555.3	554.4	553.6	552.7	551.8	551.4	552.0	553.1	554.3	555.4	556.6
157.5°	564.4	563.6	562.9	562.1	561.4	561.0	561.4	562.3	563.1	564.0	564.8
160°	572.2	571.6	571.0	570.5	569.9	569.6	569.9	570.5	571.0	571.6	572.2
162.5°	579.1	578.5	577.9	577.4	576.8	576.5	576.7	577.2	577.7	578.2	578.7
165°	585.2	584.6	584.0	583.5	582.9	582.6	582.7	583.0	583.3	583.6	583.9
167.5°	589.9	589.3	588.7	588.2	587.6	587.3	587.4	587.7	588.0	588.3	588.6
170°	593.8	593.2	592.6	592.1	591.5	591.2	591.3	591.5	591.7	591.9	592.1
172.5°	596.4	595.8	595.2	594.7	594.1	593.8	593.9	594.1	594.3	594.5	594.7
175°	598.6	597.9	597.2	596.5	595.8	595.5	595.6	595.8	596.0	596.2	596.4
177.5°	599.4	598.7	598.1	597.4	596.7	596.4	596.4	596.5	596.6	596.7	596.8
180°	597.3	597.3	597.3	597.3	597.3	597.3	597.3	597.3	597.3	597.3	597.3

TEST NUMBER: P1029661

CATALOG NUMBER: S122DIW-B675D435UB2750-4F0-XX-W2A-A_3000K

CANDELA DISTRIBUTION (continued):

	50°	55°	60°	65°	67.5°	70°	75°	80°	85°	90°	95°
0°	1335.3	1335.3	1335.3	1335.3	1335.3	1335.3	1335.3	1335.3	1335.3	1335.3	1335.3
2.5°	1387.6	1388.6	1390.7	1400.9	1406.1	1407.1	1403.0	1412.2	1415.3	1412.2	1410.2
5°	1453.3	1459.5	1471.8	1485.1	1484.1	1485.1	1491.3	1497.4	1499.5	1491.3	1494.3
7.5°	1510.8	1523.1	1536.4	1557.0	1557.0	1567.2	1571.3	1576.5	1588.8	1582.6	1580.6
10°	1576.5	1592.9	1617.5	1650.3	1651.4	1661.6	1671.9	1688.3	1693.5	1689.4	1691.4
12.5°	1658.6	1690.4	1692.4	1728.4	1744.8	1746.8	1763.2	1760.2	1770.4	1770.4	1787.9
15°	1694.5	1743.7	1771.5	1806.4	1816.6	1804.3	1817.6	1832.0	1833.0	1833.0	1832.0
17.5°	1759.1	1778.6	1806.4	1824.8	1828.9	1828.9	1830.0	1836.1	1832.0	1823.8	1830.0
20°	1772.5	1780.7	1791.0	1788.9	1791.0	1780.7	1770.4	1760.2	1761.2	1756.1	1771.5
22.5°	1747.9	1745.8	1722.2	1706.8	1706.8	1686.3	1666.8	1657.5	1648.3	1651.4	1656.5
25°	1686.3	1654.5	1625.7	1603.1	1598.0	1565.2	1538.5	1530.3	1514.9	1527.2	1529.2
27.5°	1587.7	1551.8	1505.6	1486.1	1459.5	1446.1	1427.6	1403.0	1371.2	1389.7	1386.6
30°	1482.0	1428.7	1390.7	1343.5	1301.4	1298.3	1263.4	1222.4	1205.9	1205.9	1215.2
32.5°	1364.0	1293.2	1237.8	1171.1	1130.0	1112.5	1070.5	1029.4	1038.7	1007.9	1019.2
35°	1226.5	1133.1	1063.3	998.6	967.8	947.3	892.9	870.3	845.7	831.3	858.0
37.5°	1095.1	987.3	898.0	827.2	815.9	779.0	742.0	727.7	713.3	719.5	718.4
40°	935.0	839.5	759.5	704.1	684.6	667.1	642.5	625.0	615.8	620.9	622.0
42.5°	790.3	710.2	650.7	611.7	595.3	583.0	570.6	556.3	553.2	553.2	557.3
45°	678.4	612.7	572.7	540.9	531.6	522.4	513.2	507.0	505.0	500.9	503.9
47.5°	589.1	536.8	512.1	488.5	478.3	476.2	468.0	464.9	460.8	459.8	460.8
50°	514.2	481.4	458.8	445.4	438.2	435.2	431.1	424.9	422.9	428.0	425.9
52.5°	461.9	431.1	418.7	405.4	401.3	397.2	391.0	392.1	391.0	389.0	389.0
55°	409.5	390.0	377.7	367.4	366.4	362.3	357.2	355.1	354.1	352.0	355.1
57.5°	367.4	352.0	340.7	331.5	327.4	327.4	322.3	318.2	318.2	317.1	318.2
60°	325.3	310.0	302.8	293.5	290.5	289.4	286.3	284.3	281.2	281.2	281.2
62.5°	286.3	274.0	265.8	257.6	258.6	253.5	249.4	247.3	247.3	248.4	248.4
65°	249.4	241.2	230.9	223.7	221.7	220.7	218.6	217.6	214.5	216.6	216.6
67.5°	215.5	204.2	198.1	195.0	191.9	190.9	188.8	186.8	185.8	184.7	186.8
70°	181.7	172.4	167.3	165.2	162.2	161.1	160.1	157.0	158.1	159.1	160.1
72.5°	150.9	142.7	141.6	135.5	135.5	135.5	131.4	133.4	132.4	130.3	132.4
75°	119.1	114.9	112.9	109.8	110.8	109.8	108.8	105.7	105.7	106.7	107.8
77.5°	94.4	90.3	89.3	86.2	84.2	86.2	84.2	83.1	83.1	84.2	84.2
80°	69.8	67.7	64.7	64.7	64.7	63.6	63.6	63.6	62.6	61.6	62.6
82.5°	46.2	46.2	45.2	44.1	45.2	43.1	44.1	44.1	44.1	44.1	44.1
85°	29.8	28.7	28.7	27.7	27.7	27.7	28.7	26.7	26.7	27.7	27.7
87.5°	13.3	13.3	13.3	14.4	13.3	13.3	13.3	14.4	13.3	13.3	13.3
90°	9.1	9.6	10.1	10.6	10.8	10.9	11.1	11.3	11.5	11.7	11.5
92.5°	10.6	10.8	10.9	11.1	11.2	11.3	11.4	11.5	11.6	11.7	11.6
95°	17.4	17.8	18.3	18.8	19.0	19.0	18.9	18.8	18.7	18.6	18.7
97.5°	22.3	22.6	22.9	23.2	23.3	23.4	23.5	23.6	23.7	23.8	23.7
100°	25.4	26.2	26.9	27.7	28.1	28.2	28.4	28.6	28.8	29.0	28.8
102.5°	26.6	27.6	28.7	29.8	30.3	30.4	30.7	31.0	31.2	31.5	31.2
105°	27.4	28.5	29.5	30.6	31.1	31.3	31.7	32.0	32.4	32.8	32.4
107.5°	28.3	29.3	30.4	31.5	32.0	32.2	32.6	32.9	33.3	33.7	33.3
110°	66.0	56.4	46.8	37.2	32.4	32.6	33.0	33.3	33.7	34.1	33.7

TEST NUMBER: P1029661

CATALOG NUMBER: S122DIW-B675D435UB2750-4F0-XX-W2A-A_3000K

CANDELA DISTRIBUTION (continued):

	50°	55°	60°	65°	67.5°	70°	75°	80°	85°	90°	95°
112.5°	178.1	136.7	95.4	54.0	33.3	33.4	33.7	34.0	34.3	34.6	34.3
115°	222.2	177.7	133.3	88.8	66.6	63.1	56.2	49.3	42.3	35.4	42.3
117.5°	276.3	262.5	248.8	235.1	228.2	215.6	190.5	165.3	140.2	115.0	140.2
120°	318.0	319.1	320.3	321.4	322.0	315.5	302.5	289.6	276.6	263.6	276.6
122.5°	342.9	343.5	344.0	344.6	344.9	344.9	345.0	345.1	345.2	345.3	345.2
125°	365.9	366.5	367.2	367.9	368.2	368.3	368.6	368.9	369.2	369.5	369.2
127.5°	387.4	388.3	389.3	390.2	390.7	390.7	390.8	390.9	391.0	391.1	391.0
130°	407.7	408.8	409.8	410.9	411.4	411.4	411.3	411.2	411.1	411.0	411.1
132.5°	427.9	428.7	429.6	430.5	430.9	430.8	430.7	430.6	430.5	430.4	430.5
135°	446.6	447.5	448.5	449.4	449.9	449.8	449.6	449.4	449.2	449.0	449.2
137.5°	464.3	465.2	466.2	467.1	467.6	467.5	467.2	466.9	466.6	466.3	466.6
140°	481.5	482.3	483.2	484.1	484.5	484.3	483.8	483.3	482.8	482.3	482.8
142.5°	497.4	498.1	498.9	499.6	500.0	499.8	499.3	498.8	498.4	497.9	498.4
145°	512.0	512.6	513.3	514.0	514.3	514.1	513.6	513.1	512.6	512.1	512.6
147.5°	525.2	525.6	526.1	526.6	526.8	526.6	526.2	525.9	525.5	525.1	525.5
150°	536.9	537.5	538.0	538.6	538.9	538.7	538.2	537.7	537.3	536.8	537.3
152.5°	547.7	548.3	548.8	549.4	549.7	549.4	548.7	548.0	547.4	546.7	547.4
155°	557.2	557.8	558.3	558.9	559.2	558.8	558.1	557.3	556.6	555.8	556.6
157.5°	565.5	566.2	566.9	567.6	567.9	567.5	566.7	566.0	565.2	564.4	565.2
160°	572.8	573.4	573.9	574.5	574.8	574.5	573.8	573.1	572.5	571.8	572.5
162.5°	579.4	580.0	580.7	581.4	581.7	581.3	580.4	579.5	578.7	577.8	578.7
165°	584.6	585.2	585.9	586.6	586.9	586.6	585.9	585.2	584.6	583.9	584.6
167.5°	589.3	589.9	590.6	591.3	591.6	591.2	590.3	589.4	588.6	587.7	588.6
170°	592.8	593.4	594.1	594.8	595.1	594.7	593.8	592.9	592.1	591.2	592.1
172.5°	595.4	596.0	596.7	597.4	597.7	597.3	596.4	595.5	594.7	593.8	594.7
175°	597.1	597.7	598.4	599.1	599.4	598.9	598.0	597.0	596.1	595.1	596.1
177.5°	597.5	598.2	598.9	599.6	599.9	599.5	598.6	597.7	596.9	596.0	596.9
180°	597.3	597.3	597.3	597.3	597.3	597.3	597.3	597.3	597.3	597.3	597.3

TEST NUMBER: P1029661

CATALOG NUMBER: S122DIW-B675D435UB2750-4F0-XX-W2A-A_3000K

CANDELA DISTRIBUTION (continued):

	100°	105°	110°	112.5°	115°	120°	125°	130°	135°	140°	145°
0°	1335.3	1335.3	1335.3	1335.3	1335.3	1335.3	1335.3	1335.3	1335.3	1335.3	1335.3
2.5°	1415.3	1408.1	1402.0	1403.0	1408.1	1404.0	1393.8	1380.4	1375.3	1369.1	1375.3
5°	1500.5	1494.3	1482.0	1483.1	1480.0	1475.9	1459.5	1438.9	1438.9	1422.5	1420.5
7.5°	1584.7	1575.4	1567.2	1565.2	1553.9	1545.7	1531.3	1502.6	1491.3	1471.8	1460.5
10°	1679.1	1671.9	1662.7	1651.4	1645.2	1630.8	1607.2	1565.2	1544.6	1518.0	1498.5
12.5°	1774.5	1773.5	1753.0	1730.4	1729.4	1706.8	1690.4	1633.9	1606.2	1570.3	1524.1
15°	1835.1	1830.0	1818.7	1807.4	1810.5	1785.8	1748.9	1682.2	1663.7	1620.6	1571.3
17.5°	1834.1	1834.1	1831.0	1828.9	1825.9	1818.7	1798.1	1754.0	1724.2	1669.9	1623.7
20°	1775.6	1788.9	1792.0	1791.0	1801.2	1806.4	1805.3	1777.6	1754.0	1705.8	1658.6
22.5°	1658.6	1689.4	1702.7	1710.9	1732.5	1743.7	1770.4	1760.2	1754.0	1718.1	1678.1
25°	1549.8	1560.0	1600.1	1602.1	1631.9	1659.6	1686.3	1703.7	1726.3	1713.0	1679.1
27.5°	1409.2	1432.8	1461.5	1483.1	1489.2	1545.7	1589.8	1622.6	1674.0	1678.1	1666.8
30°	1250.1	1261.4	1308.6	1337.3	1370.2	1411.2	1474.8	1531.3	1577.5	1619.6	1633.9
32.5°	1056.1	1102.3	1130.0	1164.9	1193.6	1266.5	1344.5	1417.4	1470.7	1541.6	1572.3
35°	878.5	914.5	961.7	976.0	1028.4	1090.0	1191.6	1285.0	1366.1	1437.9	1500.5
37.5°	731.8	760.5	810.8	833.4	864.2	943.2	1028.4	1144.4	1241.9	1330.1	1408.1
40°	631.2	652.8	690.7	697.9	723.6	795.4	864.2	973.0	1102.3	1221.3	1306.5
42.5°	562.4	572.7	598.4	607.6	624.0	672.3	733.8	836.5	956.5	1079.7	1199.8
45°	513.2	520.4	535.7	544.0	564.5	586.0	636.3	718.4	812.9	937.0	1066.4
47.5°	469.0	478.3	484.4	489.6	500.9	524.5	557.3	617.9	708.2	822.1	947.3
50°	432.1	435.2	446.5	447.5	454.7	470.1	500.9	537.8	609.6	702.0	823.1
52.5°	395.1	398.2	405.4	412.6	415.7	428.0	448.5	479.3	532.7	605.5	713.3
55°	358.2	362.3	369.5	374.6	377.7	388.0	400.3	430.0	472.1	523.4	611.7
57.5°	321.2	330.5	332.5	335.6	340.7	352.0	363.3	380.8	413.6	460.8	525.5
60°	286.3	289.4	296.6	299.7	304.8	311.0	325.3	338.7	362.3	399.2	457.7
62.5°	250.4	257.6	260.7	263.8	267.9	275.1	284.3	298.7	319.2	349.0	395.1
65°	219.6	220.7	226.8	230.9	235.0	240.2	249.4	262.7	275.1	302.8	336.6
67.5°	189.9	191.9	194.0	198.1	203.2	208.3	216.6	223.7	239.1	257.6	284.3
70°	161.1	161.1	166.3	169.3	168.3	174.5	180.6	188.8	200.1	217.6	239.1
72.5°	135.5	134.5	138.6	139.6	141.6	145.7	149.8	158.1	164.2	177.6	194.0
75°	107.8	109.8	111.9	111.9	114.9	118.0	122.1	126.2	133.4	141.6	154.0
77.5°	85.2	85.2	87.2	88.3	91.3	90.3	94.4	98.5	103.7	110.8	120.1
80°	62.6	64.7	64.7	64.7	65.7	66.7	70.8	73.9	77.0	82.1	86.2
82.5°	44.1	44.1	46.2	46.2	46.2	48.2	48.2	49.3	51.3	54.4	57.5
85°	27.7	27.7	27.7	28.7	27.7	28.7	30.8	29.8	30.8	32.8	32.8
87.5°	13.3	13.3	13.3	13.3	13.3	14.4	13.3	14.4	15.4	15.4	15.4
90°	11.3	11.1	10.9	10.8	10.6	10.1	9.6	9.1	8.6	7.8	7.1
92.5°	11.5	11.4	11.3	11.2	11.1	10.9	10.8	10.6	10.4	10.1	9.8
95°	18.8	18.9	19.0	19.0	18.8	18.3	17.8	17.4	16.9	16.2	15.5
97.5°	23.6	23.5	23.4	23.3	23.2	22.9	22.6	22.3	22.0	20.5	18.9
100°	28.6	28.4	28.2	28.1	27.7	26.9	26.2	25.4	24.6	23.0	21.4
102.5°	31.0	30.7	30.4	30.3	29.8	28.7	27.6	26.6	25.5	43.0	60.5
105°	32.0	31.7	31.3	31.1	30.6	29.5	28.5	27.4	26.4	52.6	78.8
107.5°	32.9	32.6	32.2	32.0	31.5	30.4	29.3	28.3	27.2	59.6	92.0
110°	33.3	33.0	32.6	32.4	37.2	46.8	56.4	66.0	75.6	103.4	131.1

TEST NUMBER: P1029661

CATALOG NUMBER: S122DIW-B675D435UB2750-4F0-XX-W2A-A_3000K

CANDELA DISTRIBUTION (continued):

	100°	105°	110°	112.5°	115°	120°	125°	130°	135°	140°	145°
112.5°	34.0	33.7	33.4	33.3	54.0	95.4	136.7	178.1	219.5	221.1	222.8
115°	49.3	56.2	63.1	66.6	88.8	133.3	177.7	222.2	266.6	264.2	261.8
117.5°	165.3	190.5	215.6	228.2	235.1	248.8	262.5	276.3	290.0	288.4	286.7
120°	289.6	302.5	315.5	322.0	321.4	320.3	319.1	318.0	316.8	315.1	313.3
122.5°	345.1	345.0	344.9	344.9	344.6	344.0	343.5	342.9	342.3	340.4	338.4
125°	368.9	368.6	368.3	368.2	367.9	367.2	366.5	365.9	365.2	363.4	361.6
127.5°	390.9	390.8	390.7	390.7	390.2	389.3	388.3	387.4	386.4	385.0	383.5
130°	411.2	411.3	411.4	411.4	410.9	409.8	408.8	407.7	406.7	405.6	404.6
132.5°	430.6	430.7	430.8	430.9	430.5	429.6	428.7	427.9	427.0	425.9	424.9
135°	449.4	449.6	449.8	449.9	449.4	448.5	447.5	446.6	445.6	444.7	443.9
137.5°	466.9	467.2	467.5	467.6	467.1	466.2	465.2	464.3	463.3	462.3	461.4
140°	483.3	483.8	484.3	484.5	484.1	483.2	482.3	481.5	480.6	479.5	478.5
142.5°	498.8	499.3	499.8	500.0	499.6	498.9	498.1	497.4	496.6	495.3	494.1
145°	513.1	513.6	514.1	514.3	514.0	513.3	512.6	512.0	511.3	509.7	508.0
147.5°	525.9	526.2	526.6	526.8	526.6	526.1	525.6	525.2	524.7	523.1	521.4
150°	537.7	538.2	538.7	538.9	538.6	538.0	537.5	536.9	536.3	534.8	533.2
152.5°	548.0	548.7	549.4	549.7	549.4	548.8	548.3	547.7	547.1	545.7	544.2
155°	557.3	558.1	558.8	559.2	558.9	558.3	557.8	557.2	556.6	555.4	554.3
157.5°	566.0	566.7	567.5	567.9	567.6	566.9	566.2	565.5	564.8	564.0	563.1
160°	573.1	573.8	574.5	574.8	574.5	573.9	573.4	572.8	572.2	571.6	571.0
162.5°	579.5	580.4	581.3	581.7	581.4	580.7	580.0	579.4	578.7	578.2	577.7
165°	585.2	585.9	586.6	586.9	586.6	585.9	585.2	584.6	583.9	583.6	583.3
167.5°	589.4	590.3	591.2	591.6	591.3	590.6	589.9	589.3	588.6	588.3	588.0
170°	592.9	593.8	594.7	595.1	594.8	594.1	593.4	592.8	592.1	591.9	591.7
172.5°	595.5	596.4	597.3	597.7	597.4	596.7	596.0	595.4	594.7	594.5	594.3
175°	597.0	598.0	598.9	599.4	599.1	598.4	597.7	597.1	596.4	596.2	596.0
177.5°	597.7	598.6	599.5	599.9	599.6	598.9	598.2	597.5	596.8	596.7	596.6
180°	597.3	597.3	597.3	597.3	597.3	597.3	597.3	597.3	597.3	597.3	597.3

TEST NUMBER: P1029661

CATALOG NUMBER: S122DIW-B675D435UB2750-4F0-XX-W2A-A_3000K

CANDELA DISTRIBUTION (continued):

	150°	155°	157.5°	160°	165°	170°	175°	180°	185°	190°	195°
0°	1335.3	1335.3	1335.3	1335.3	1335.3	1335.3	1335.3	1335.3	1335.3	1335.3	1335.3
2.5°	1370.2	1365.0	1361.9	1364.0	1357.8	1342.4	1342.4	1347.6	1341.4	1335.3	1326.0
5°	1408.1	1397.9	1391.7	1390.7	1376.3	1351.7	1346.6	1341.4	1328.1	1313.7	1298.3
7.5°	1445.1	1426.6	1416.3	1409.2	1388.6	1356.8	1343.5	1332.2	1310.6	1289.1	1269.6
10°	1475.9	1449.2	1436.9	1425.6	1398.9	1358.9	1337.3	1316.8	1289.1	1261.4	1236.7
12.5°	1500.5	1469.7	1454.3	1437.9	1405.1	1352.7	1326.0	1293.2	1265.5	1228.5	1203.9
15°	1541.6	1477.9	1463.6	1448.2	1414.3	1342.4	1309.6	1272.7	1234.7	1185.4	1158.7
17.5°	1574.4	1489.2	1488.2	1455.3	1411.2	1338.3	1288.1	1239.8	1198.8	1149.5	1107.4
20°	1593.9	1506.7	1490.2	1456.4	1400.9	1310.6	1258.3	1204.9	1160.8	1101.3	1059.2
22.5°	1610.3	1531.3	1488.2	1447.1	1379.4	1301.4	1224.4	1174.1	1113.6	1048.9	1008.9
25°	1616.5	1536.4	1491.3	1444.1	1364.0	1274.7	1187.5	1133.1	1065.3	1006.8	952.4
27.5°	1617.5	1535.4	1480.0	1430.7	1342.4	1239.8	1150.5	1093.0	1018.1	950.4	896.0
30°	1607.2	1524.1	1473.8	1420.5	1321.9	1208.0	1105.4	1041.7	961.7	893.9	837.5
32.5°	1576.5	1501.5	1460.5	1402.0	1295.2	1163.9	1062.3	991.4	907.3	840.6	786.2
35°	1525.1	1473.8	1428.7	1374.3	1260.3	1122.8	1019.2	936.0	850.8	787.2	735.9
37.5°	1461.5	1433.8	1391.7	1338.3	1220.3	1085.9	970.9	878.5	793.4	731.8	681.5
40°	1375.3	1382.5	1341.4	1293.2	1173.1	1035.6	908.3	820.0	740.0	682.5	633.2
42.5°	1281.9	1311.7	1288.1	1241.9	1120.8	980.2	862.1	764.6	686.6	627.1	586.0
45°	1181.3	1232.6	1218.3	1184.4	1066.4	921.7	796.4	702.0	633.2	575.8	539.9
47.5°	1071.5	1144.4	1144.4	1119.7	1005.8	863.1	740.0	643.5	575.8	534.7	499.8
50°	959.6	1041.7	1055.1	1038.7	938.1	796.4	671.2	584.0	525.5	485.5	459.8
52.5°	842.6	938.1	962.7	954.5	866.2	732.8	614.8	529.6	476.2	441.3	418.7
55°	730.8	841.6	868.3	871.4	789.3	663.0	552.2	477.2	425.9	402.3	382.8
57.5°	625.0	731.8	761.5	766.7	711.3	599.4	493.7	428.0	381.8	362.3	346.9
60°	534.7	624.0	663.0	674.3	626.1	525.5	439.3	375.6	340.7	322.3	307.9
62.5°	460.8	532.7	573.7	576.8	555.2	460.8	382.8	329.5	299.7	283.3	276.1
65°	389.0	453.6	478.3	490.6	473.1	399.2	330.5	286.3	262.7	248.4	241.2
67.5°	331.5	372.6	393.1	409.5	392.1	336.6	281.2	245.3	227.8	213.5	209.4
70°	272.0	305.8	321.2	337.7	322.3	280.2	240.2	207.3	191.9	180.6	175.5
72.5°	217.6	244.3	258.6	268.9	259.7	224.8	191.9	169.3	158.1	149.8	146.8
75°	172.4	190.9	199.1	206.3	202.2	175.5	155.0	136.5	126.2	119.1	117.0
77.5°	131.4	144.7	154.0	156.0	150.9	133.4	116.0	104.7	96.5	92.4	90.3
80°	93.4	101.6	106.7	109.8	104.7	97.5	85.2	77.0	69.8	64.7	63.6
82.5°	62.6	66.7	70.8	69.8	67.7	61.6	54.4	50.3	47.2	43.1	43.1
85°	35.9	36.9	39.0	40.0	39.0	34.9	30.8	28.7	26.7	23.6	23.6
87.5°	15.4	16.4	16.4	17.4	15.4	15.4	13.3	11.3	11.3	10.3	9.2
90°	6.3	5.6	5.2	4.7	3.6	2.5	1.5	0.4	1.5	2.5	3.6
92.5°	9.5	9.2	9.1	9.3	9.7	10.0	10.4	10.8	10.4	10.0	9.7
95°	14.8	14.1	13.8	15.4	18.6	21.7	24.9	28.1	24.9	21.7	18.6
97.5°	17.4	15.9	15.1	19.0	26.9	34.8	42.7	50.6	42.7	34.8	26.9
100°	19.7	18.1	17.3	23.9	37.0	50.2	63.3	76.5	63.3	50.2	37.0
102.5°	78.0	95.5	104.2	104.3	104.5	104.6	104.8	105.0	104.8	104.6	104.5
105°	105.0	131.2	144.3	142.9	140.0	137.1	134.3	131.4	134.3	137.1	140.0
107.5°	124.3	156.7	172.9	171.7	169.3	166.9	164.5	162.1	164.5	166.9	169.3
110°	158.9	186.6	200.5	199.5	197.5	195.5	193.5	191.5	193.5	195.5	197.5



TEST NUMBER: P1029661

CATALOG NUMBER: S122DIW-B675D435UB2750-4F0-XX-W2A-A_3000K

CANDELA DISTRIBUTION (continued):

	150°	155°	157.5°	160°	165°	170°	175°	180°	185°	190°	195°
112.5°	224.4	226.1	226.9	226.0	224.3	222.6	220.8	219.1	220.8	222.6	224.3
115°	259.4	257.0	255.8	255.0	253.4	251.7	250.1	248.5	250.1	251.7	253.4
117.5°	285.1	283.4	282.6	281.6	279.7	277.8	275.9	274.0	275.9	277.8	279.7
120°	311.6	309.9	309.0	308.3	306.8	305.4	303.9	302.5	303.9	305.4	306.8
122.5°	336.5	334.6	333.6	332.8	331.3	329.8	328.2	326.7	328.2	329.8	331.3
125°	359.7	357.9	357.0	356.4	355.1	353.9	352.6	351.4	352.6	353.9	355.1
127.5°	382.1	380.6	379.9	379.2	377.9	376.5	375.2	373.8	375.2	376.5	377.9
130°	403.5	402.4	401.9	401.1	399.6	398.1	396.5	395.0	396.5	398.1	399.6
132.5°	423.8	422.7	422.2	421.6	420.3	419.1	417.8	416.6	417.8	419.1	420.3
135°	443.0	442.1	441.7	440.9	439.4	437.9	436.3	434.8	436.3	437.9	439.4
137.5°	460.4	459.5	459.0	458.4	457.3	456.1	455.0	453.8	455.0	456.1	457.3
140°	477.4	476.3	475.8	475.4	474.7	473.9	473.2	472.4	473.2	473.9	474.7
142.5°	492.8	491.5	490.9	490.6	489.9	489.2	488.6	487.9	488.6	489.2	489.9
145°	506.4	504.7	503.9	503.9	504.0	504.1	504.2	504.3	504.2	504.1	504.0
147.5°	519.8	518.1	517.3	517.4	517.7	518.0	518.3	518.6	518.3	518.0	517.7
150°	531.7	530.2	529.4	529.7	530.4	531.1	531.7	532.4	531.7	531.1	530.4
152.5°	542.8	541.3	540.6	541.0	541.8	542.5	543.3	544.1	543.3	542.5	541.8
155°	553.1	552.0	551.4	551.8	552.7	553.6	554.4	555.3	554.4	553.6	552.7
157.5°	562.3	561.4	561.0	561.4	562.1	562.9	563.6	564.4	563.6	562.9	562.1
160°	570.5	569.9	569.6	569.9	570.5	571.0	571.6	572.2	571.6	571.0	570.5
162.5°	577.2	576.7	576.5	576.8	577.4	577.9	578.5	579.1	578.5	577.9	577.4
165°	583.0	582.7	582.6	582.9	583.5	584.0	584.6	585.2	584.6	584.0	583.5
167.5°	587.7	587.4	587.3	587.6	588.2	588.7	589.3	589.9	589.3	588.7	588.2
170°	591.5	591.3	591.2	591.5	592.1	592.6	593.2	593.8	593.2	592.6	592.1
172.5°	594.1	593.9	593.8	594.1	594.7	595.2	595.8	596.4	595.8	595.2	594.7
175°	595.8	595.6	595.5	595.8	596.5	597.2	597.9	598.6	597.9	597.2	596.5
177.5°	596.5	596.4	596.4	596.7	597.4	598.1	598.7	599.4	598.7	598.1	597.4
180°	597.3	597.3	597.3	597.3	597.3	597.3	597.3	597.3	597.3	597.3	597.3

TEST NUMBER: P1029661

CATALOG NUMBER: S122DIW-B675D435UB2750-4F0-XX-W2A-A_3000K

CANDELA DISTRIBUTION (continued):

	200°	202.5°	205°	210°	215°	220°	225°	230°	235°	240°	245°
0°	1335.3	1335.3	1335.3	1335.3	1335.3	1335.3	1335.3	1335.3	1335.3	1335.3	1335.3
2.5°	1320.9	1326.0	1325.0	1314.7	1303.4	1294.2	1276.8	1278.8	1272.7	1273.7	1279.8
5°	1288.1	1288.1	1283.9	1269.6	1251.1	1240.8	1221.3	1216.2	1203.9	1202.9	1201.8
7.5°	1253.2	1248.0	1242.9	1222.4	1199.8	1183.4	1156.7	1150.5	1138.2	1130.0	1125.9
10°	1212.1	1204.9	1194.7	1171.1	1143.3	1122.8	1095.1	1086.9	1063.3	1053.0	1046.9
12.5°	1166.9	1162.8	1146.4	1126.9	1081.8	1059.2	1019.2	1027.4	1003.8	983.2	980.2
15°	1121.8	1106.4	1097.2	1065.3	1010.9	1000.7	968.9	952.4	930.9	914.5	914.5
17.5°	1077.7	1054.0	1033.5	999.7	959.6	930.9	907.3	899.1	872.4	856.0	852.9
20°	1019.2	992.5	987.3	939.1	911.4	879.6	857.0	836.5	817.0	809.8	804.6
22.5°	963.7	932.9	924.7	883.7	856.0	824.1	801.6	787.2	772.8	767.7	758.5
25°	904.2	885.7	873.4	829.3	798.5	768.7	753.3	743.1	729.7	728.7	722.5
27.5°	846.7	829.3	817.0	774.9	752.3	724.6	712.3	701.0	693.8	690.7	687.6
30°	797.5	778.0	763.6	732.8	705.1	682.5	672.3	665.1	661.0	655.8	654.8
32.5°	743.1	731.8	712.3	688.7	667.1	645.6	639.4	634.3	628.1	626.1	625.0
35°	696.9	681.5	669.2	642.5	633.2	614.8	607.6	603.5	595.3	593.2	591.2
37.5°	651.7	637.4	624.0	607.6	590.1	579.9	575.8	569.6	565.5	566.5	564.5
40°	606.6	595.3	585.0	567.6	557.3	552.2	544.0	537.8	535.7	536.8	535.7
42.5°	562.4	552.2	546.0	532.7	522.4	517.3	512.1	506.0	509.1	509.1	512.1
45°	522.4	513.2	509.1	498.8	492.6	484.4	479.3	478.3	482.4	481.4	481.4
47.5°	481.4	478.3	473.1	463.9	455.7	450.6	449.5	449.5	453.6	455.7	454.7
50°	449.5	443.4	437.2	430.0	423.9	421.8	418.7	420.8	424.9	424.9	427.0
52.5°	409.5	405.4	403.4	397.2	393.1	393.1	393.1	394.1	397.2	400.3	399.2
55°	374.6	371.5	369.5	366.4	361.3	362.3	361.3	363.3	366.4	369.5	371.5
57.5°	337.7	336.6	334.6	329.5	329.5	328.4	331.5	332.5	337.7	339.7	342.8
60°	304.8	301.7	301.7	297.6	297.6	297.6	300.7	303.8	307.9	308.9	311.0
62.5°	269.9	269.9	268.9	265.8	265.8	268.9	269.9	274.0	276.1	276.1	279.2
65°	237.1	236.1	235.0	236.1	237.1	237.1	240.2	242.2	244.3	245.3	246.3
67.5°	204.2	203.2	205.3	204.2	206.3	210.4	209.4	212.5	215.5	215.5	216.6
70°	173.5	175.5	174.5	176.5	175.5	177.6	180.6	181.7	181.7	182.7	185.8
72.5°	144.7	144.7	144.7	143.7	144.7	146.8	148.8	149.8	151.9	152.9	156.0
75°	117.0	117.0	114.9	117.0	117.0	119.1	121.1	121.1	121.1	123.2	126.2
77.5°	88.3	89.3	88.3	90.3	90.3	91.3	93.4	92.4	94.4	95.4	96.5
80°	64.7	63.6	63.6	63.6	64.7	64.7	66.7	67.7	67.7	70.8	68.8
82.5°	41.1	42.1	41.1	42.1	42.1	43.1	42.1	43.1	44.1	46.2	45.2
85°	23.6	22.6	22.6	23.6	22.6	22.6	23.6	22.6	23.6	22.6	23.6
87.5°	9.2	8.2	8.2	8.2	8.2	7.2	7.2	6.2	6.2	6.2	5.1
90°	4.7	5.2	5.6	6.3	7.1	7.8	8.6	9.1	9.6	10.1	10.6
92.5°	9.3	9.1	9.2	9.5	9.8	10.1	10.4	10.6	10.8	10.9	11.1
95°	15.4	13.8	14.1	14.8	15.5	16.2	16.9	17.4	17.8	18.3	18.8
97.5°	19.0	15.1	15.9	17.4	18.9	20.5	22.0	22.3	22.6	22.9	23.2
100°	23.9	17.3	18.1	19.7	21.4	23.0	24.6	25.4	26.2	26.9	27.7
102.5°	104.3	104.2	95.5	78.0	60.5	43.0	25.5	26.6	27.6	28.7	29.8
105°	142.9	144.3	131.2	105.0	78.8	52.6	26.4	27.4	28.5	29.5	30.6
107.5°	171.7	172.9	156.7	124.3	92.0	59.6	27.2	28.3	29.3	30.4	31.5
110°	199.5	200.5	186.6	158.9	131.1	103.4	75.6	66.0	56.4	46.8	37.2

TEST NUMBER: P1029661

CATALOG NUMBER: S122DIW-B675D435UB2750-4F0-XX-W2A-A_3000K

CANDELA DISTRIBUTION (continued):

	200°	202.5°	205°	210°	215°	220°	225°	230°	235°	240°	245°
112.5°	226.0	226.9	226.1	224.4	222.8	221.1	219.5	178.1	136.7	95.4	54.0
115°	255.0	255.8	257.0	259.4	261.8	264.2	266.6	222.2	177.7	133.3	88.8
117.5°	281.6	282.6	283.4	285.1	286.7	288.4	290.0	276.3	262.5	248.8	235.1
120°	308.3	309.0	309.9	311.6	313.3	315.1	316.8	318.0	319.1	320.3	321.4
122.5°	332.8	333.6	334.6	336.5	338.4	340.4	342.3	342.9	343.5	344.0	344.6
125°	356.4	357.0	357.9	359.7	361.6	363.4	365.2	365.9	366.5	367.2	367.9
127.5°	379.2	379.9	380.6	382.1	383.5	385.0	386.4	387.4	388.3	389.3	390.2
130°	401.1	401.9	402.4	403.5	404.6	405.6	406.7	407.7	408.8	409.8	410.9
132.5°	421.6	422.2	422.7	423.8	424.9	425.9	427.0	427.9	428.7	429.6	430.5
135°	440.9	441.7	442.1	443.0	443.9	444.7	445.6	446.6	447.5	448.5	449.4
137.5°	458.4	459.0	459.5	460.4	461.4	462.3	463.3	464.3	465.2	466.2	467.1
140°	475.4	475.8	476.3	477.4	478.5	479.5	480.6	481.5	482.3	483.2	484.1
142.5°	490.6	490.9	491.5	492.8	494.1	495.3	496.6	497.4	498.1	498.9	499.6
145°	503.9	503.9	504.7	506.4	508.0	509.7	511.3	512.0	512.6	513.3	514.0
147.5°	517.4	517.3	518.1	519.8	521.4	523.1	524.7	525.2	525.6	526.1	526.6
150°	529.7	529.4	530.2	531.7	533.2	534.8	536.3	536.9	537.5	538.0	538.6
152.5°	541.0	540.6	541.3	542.8	544.2	545.7	547.1	547.7	548.3	548.8	549.4
155°	551.8	551.4	552.0	553.1	554.3	555.4	556.6	557.2	557.8	558.3	558.9
157.5°	561.4	561.0	561.4	562.3	563.1	564.0	564.8	565.5	566.2	566.9	567.6
160°	569.9	569.6	569.9	570.5	571.0	571.6	572.2	572.8	573.4	573.9	574.5
162.5°	576.8	576.5	576.7	577.2	577.7	578.2	578.7	579.4	580.0	580.7	581.4
165°	582.9	582.6	582.7	583.0	583.3	583.6	583.9	584.6	585.2	585.9	586.6
167.5°	587.6	587.3	587.4	587.7	588.0	588.3	588.6	589.3	589.9	590.6	591.3
170°	591.5	591.2	591.3	591.5	591.7	591.9	592.1	592.8	593.4	594.1	594.8
172.5°	594.1	593.8	593.9	594.1	594.3	594.5	594.7	595.4	596.0	596.7	597.4
175°	595.8	595.5	595.6	595.8	596.0	596.2	596.4	597.1	597.7	598.4	599.1
177.5°	596.7	596.4	596.4	596.5	596.6	596.7	596.8	597.5	598.2	598.9	599.6
180°	597.3	597.3	597.3	597.3	597.3	597.3	597.3	597.3	597.3	597.3	597.3

TEST NUMBER: P1029661

CATALOG NUMBER: S122DIW-B675D435UB2750-4F0-XX-W2A-A_3000K

CANDELA DISTRIBUTION (continued):

	247.5°	250°	255°	260°	265°	270°	275°	280°	285°	290°	292.5°
0°	1335.3	1335.3	1335.3	1335.3	1335.3	1335.3	1335.3	1335.3	1335.3	1335.3	1335.3
2.5°	1272.7	1275.7	1268.6	1266.5	1268.6	1261.4	1263.4	1265.5	1265.5	1268.6	1270.6
5°	1198.8	1194.7	1187.5	1185.4	1183.4	1186.4	1184.4	1187.5	1188.5	1195.7	1196.7
7.5°	1125.9	1119.7	1113.6	1107.4	1105.4	1100.2	1105.4	1105.4	1112.5	1110.5	1115.6
10°	1039.7	1038.7	1030.4	1027.4	1023.3	1015.0	1026.3	1023.3	1028.4	1037.6	1039.7
12.5°	976.0	964.8	969.9	955.5	960.7	952.4	953.5	953.5	961.7	962.7	960.7
15°	915.5	906.3	892.9	886.8	883.7	879.6	892.9	893.9	887.8	902.2	897.0
17.5°	853.9	853.9	841.6	838.5	830.3	834.4	832.4	833.4	831.3	841.6	846.7
20°	800.5	795.4	791.3	792.3	782.1	780.0	778.0	780.0	787.2	794.4	796.4
22.5°	757.4	754.4	744.1	746.1	737.9	741.0	739.0	744.1	745.1	745.1	752.3
25°	716.4	712.3	713.3	709.2	706.1	706.1	703.0	706.1	710.2	712.3	713.3
27.5°	685.6	682.5	677.4	674.3	676.4	671.2	675.3	678.4	678.4	676.4	678.4
30°	648.6	650.7	650.7	640.4	644.5	642.5	645.6	647.6	647.6	648.6	646.6
32.5°	624.0	617.9	616.8	615.8	615.8	611.7	611.7	614.8	615.8	616.8	619.9
35°	591.2	591.2	586.0	589.1	585.0	586.0	585.0	586.0	588.1	585.0	588.1
37.5°	561.4	562.4	560.4	562.4	563.5	561.4	559.4	563.5	561.4	561.4	559.4
40°	535.7	534.7	535.7	535.7	535.7	536.8	534.7	534.7	534.7	532.7	530.6
42.5°	514.2	508.0	510.1	511.1	508.0	508.0	509.1	508.0	511.1	505.0	505.0
45°	483.4	481.4	482.4	482.4	484.4	481.4	483.4	484.4	481.4	480.3	478.3
47.5°	455.7	457.7	455.7	457.7	457.7	459.8	455.7	456.7	457.7	453.6	450.6
50°	428.0	428.0	431.1	430.0	431.1	429.0	429.0	428.0	429.0	427.0	423.9
52.5°	402.3	399.2	404.4	403.4	402.3	401.3	400.3	401.3	399.2	397.2	397.2
55°	370.5	370.5	373.6	374.6	374.6	372.6	370.5	371.5	370.5	369.5	368.5
57.5°	344.8	340.7	342.8	343.8	343.8	340.7	342.8	340.7	340.7	341.8	338.7
60°	312.0	312.0	310.0	313.0	313.0	311.0	311.0	312.0	310.0	308.9	307.9
62.5°	277.1	278.1	281.2	282.2	283.3	281.2	279.2	280.2	280.2	277.1	278.1
65°	247.3	249.4	253.5	252.5	250.4	251.5	249.4	250.4	247.3	248.4	245.3
67.5°	218.6	217.6	218.6	218.6	220.7	219.6	217.6	217.6	216.6	219.6	216.6
70°	187.8	187.8	187.8	187.8	188.8	189.9	187.8	185.8	186.8	184.7	183.7
72.5°	156.0	157.0	156.0	158.1	155.0	157.0	157.0	156.0	155.0	155.0	155.0
75°	126.2	128.3	125.2	126.2	125.2	127.3	126.2	126.2	124.2	123.2	124.2
77.5°	96.5	97.5	95.4	96.5	95.4	96.5	96.5	95.4	95.4	95.4	95.4
80°	68.8	69.8	68.8	67.7	66.7	68.8	66.7	67.7	68.8	67.7	69.8
82.5°	44.1	44.1	43.1	44.1	42.1	42.1	43.1	43.1	42.1	44.1	42.1
85°	21.6	21.6	23.6	21.6	20.5	20.5	20.5	21.6	20.5	22.6	21.6
87.5°	5.1	4.1	5.1	5.1	4.1	4.1	5.1	4.1	5.1	6.2	4.1
90°	10.8	10.9	11.1	11.3	11.5	11.7	11.5	11.3	11.1	10.9	10.8
92.5°	11.2	11.3	11.4	11.5	11.6	11.7	11.6	11.5	11.4	11.3	11.2
95°	19.0	19.0	18.9	18.8	18.7	18.6	18.7	18.8	18.9	19.0	19.0
97.5°	23.3	23.4	23.5	23.6	23.7	23.8	23.7	23.6	23.5	23.4	23.3
100°	28.1	28.2	28.4	28.6	28.8	29.0	28.8	28.6	28.4	28.2	28.1
102.5°	30.3	30.4	30.7	31.0	31.2	31.5	31.2	31.0	30.7	30.4	30.3
105°	31.1	31.3	31.7	32.0	32.4	32.8	32.4	32.0	31.7	31.3	31.1
107.5°	32.0	32.2	32.6	32.9	33.3	33.7	33.3	32.9	32.6	32.2	32.0
110°	32.4	32.6	33.0	33.3	33.7	34.1	33.7	33.3	33.0	32.6	32.4

TEST NUMBER: P1029661

CATALOG NUMBER: S122DIW-B675D435UB2750-4F0-XX-W2A-A_3000K

CANDELA DISTRIBUTION (continued):

	247.5°	250°	255°	260°	265°	270°	275°	280°	285°	290°	292.5°
112.5°	33.3	33.4	33.7	34.0	34.3	34.6	34.3	34.0	33.7	33.4	33.3
115°	66.6	63.1	56.2	49.3	42.3	35.4	42.3	49.3	56.2	63.1	66.6
117.5°	228.2	215.6	190.5	165.3	140.2	115.0	140.2	165.3	190.5	215.6	228.2
120°	322.0	315.5	302.5	289.6	276.6	263.6	276.6	289.6	302.5	315.5	322.0
122.5°	344.9	344.9	345.0	345.1	345.2	345.3	345.2	345.1	345.0	344.9	344.9
125°	368.2	368.3	368.6	368.9	369.2	369.5	369.2	368.9	368.6	368.3	368.2
127.5°	390.7	390.7	390.8	390.9	391.0	391.1	391.0	390.9	390.8	390.7	390.7
130°	411.4	411.4	411.3	411.2	411.1	411.0	411.1	411.2	411.3	411.4	411.4
132.5°	430.9	430.8	430.7	430.6	430.5	430.4	430.5	430.6	430.7	430.8	430.9
135°	449.9	449.8	449.6	449.4	449.2	449.0	449.2	449.4	449.6	449.8	449.9
137.5°	467.6	467.5	467.2	466.9	466.6	466.3	466.6	466.9	467.2	467.5	467.6
140°	484.5	484.3	483.8	483.3	482.8	482.3	482.8	483.3	483.8	484.3	484.5
142.5°	500.0	499.8	499.3	498.8	498.4	497.9	498.4	498.8	499.3	499.8	500.0
145°	514.3	514.1	513.6	513.1	512.6	512.1	512.6	513.1	513.6	514.1	514.3
147.5°	526.8	526.6	526.2	525.9	525.5	525.1	525.5	525.9	526.2	526.6	526.8
150°	538.9	538.7	538.2	537.7	537.3	536.8	537.3	537.7	538.2	538.7	538.9
152.5°	549.7	549.4	548.7	548.0	547.4	546.7	547.4	548.0	548.7	549.4	549.7
155°	559.2	558.8	558.1	557.3	556.6	555.8	556.6	557.3	558.1	558.8	559.2
157.5°	567.9	567.5	566.7	566.0	565.2	564.4	565.2	566.0	566.7	567.5	567.9
160°	574.8	574.5	573.8	573.1	572.5	571.8	572.5	573.1	573.8	574.5	574.8
162.5°	581.7	581.3	580.4	579.5	578.7	577.8	578.7	579.5	580.4	581.3	581.7
165°	586.9	586.6	585.9	585.2	584.6	583.9	584.6	585.2	585.9	586.6	586.9
167.5°	591.6	591.2	590.3	589.4	588.6	587.7	588.6	589.4	590.3	591.2	591.6
170°	595.1	594.7	593.8	592.9	592.1	591.2	592.1	592.9	593.8	594.7	595.1
172.5°	597.7	597.3	596.4	595.5	594.7	593.8	594.7	595.5	596.4	597.3	597.7
175°	599.4	598.9	598.0	597.0	596.1	595.1	596.1	597.0	598.0	598.9	599.4
177.5°	599.9	599.5	598.6	597.7	596.9	596.0	596.9	597.7	598.6	599.5	599.9
180°	597.3	597.3	597.3	597.3	597.3	597.3	597.3	597.3	597.3	597.3	597.3

TEST NUMBER: P1029661

CATALOG NUMBER: S122DIW-B675D435UB2750-4F0-XX-W2A-A_3000K

CANDELA DISTRIBUTION (continued):

	295°	300°	305°	310°	315°	320°	325°	330°	335°	337.5°	340°
0°	1335.3	1335.3	1335.3	1335.3	1335.3	1335.3	1335.3	1335.3	1335.3	1335.3	1335.3
2.5°	1267.5	1275.7	1272.7	1261.4	1274.7	1274.7	1283.9	1283.9	1295.2	1299.3	1305.5
5°	1195.7	1201.8	1207.0	1201.8	1211.1	1225.4	1233.7	1240.8	1256.2	1262.4	1271.6
7.5°	1118.7	1130.0	1135.1	1135.1	1150.5	1166.9	1183.4	1193.6	1215.2	1223.4	1232.6
10°	1043.8	1057.1	1067.4	1066.4	1092.0	1102.3	1122.8	1146.4	1168.0	1180.3	1193.6
12.5°	964.8	971.9	986.3	1006.8	1013.0	1031.5	1055.1	1084.8	1123.8	1135.1	1154.6
15°	899.1	918.6	929.9	939.1	953.5	970.9	996.6	1025.3	1064.3	1088.9	1109.5
17.5°	843.6	869.3	876.5	874.4	892.9	919.6	949.4	970.9	1005.8	1035.6	1055.1
20°	798.5	808.8	821.1	826.2	840.6	869.3	898.0	922.7	951.4	975.0	997.6
22.5°	753.3	761.5	771.8	781.0	792.3	808.8	836.5	867.3	895.0	917.5	943.2
25°	716.4	721.5	730.8	737.9	750.3	761.5	781.0	814.9	847.8	861.1	883.7
27.5°	680.5	684.6	690.7	698.9	705.1	716.4	733.8	761.5	795.4	808.8	839.5
30°	648.6	651.7	657.9	662.0	665.1	678.4	691.8	713.3	739.0	757.4	780.0
32.5°	618.9	622.0	628.1	629.1	633.2	640.4	652.8	672.3	694.8	710.2	729.7
35°	586.0	588.1	594.2	596.3	599.4	605.5	614.8	629.1	649.7	661.0	678.4
37.5°	560.4	559.4	563.5	566.5	570.6	573.7	576.8	591.2	606.6	616.8	630.2
40°	532.7	530.6	531.6	535.7	537.8	541.9	541.9	556.3	566.5	574.7	585.0
42.5°	505.0	503.9	501.9	503.9	506.0	507.0	508.0	518.3	528.6	535.7	547.0
45°	477.2	476.2	474.2	475.2	475.2	477.2	480.3	484.4	491.6	497.8	503.9
47.5°	451.6	449.5	446.5	445.4	447.5	447.5	447.5	451.6	458.8	460.8	467.0
50°	424.9	421.8	417.7	415.7	415.7	414.6	416.7	417.7	423.9	425.9	431.1
52.5°	396.2	394.1	390.0	385.9	386.9	384.9	385.9	386.9	389.0	392.1	395.1
55°	367.4	363.3	360.2	359.2	356.1	356.1	353.1	357.2	356.1	357.2	361.3
57.5°	339.7	335.6	330.5	328.4	325.3	324.3	322.3	321.2	322.3	325.3	328.4
60°	306.9	304.8	301.7	298.7	296.6	293.5	291.5	291.5	290.5	290.5	291.5
62.5°	275.1	274.0	269.9	268.9	266.8	264.8	261.7	259.7	259.7	261.7	262.7
65°	244.3	243.2	240.2	239.1	234.0	232.0	230.9	229.9	227.8	227.8	227.8
67.5°	215.5	212.5	212.5	207.3	203.2	201.2	199.1	198.1	198.1	198.1	199.1
70°	183.7	183.7	180.6	177.6	173.5	174.5	171.4	168.3	168.3	166.3	167.3
72.5°	152.9	151.9	148.8	147.8	144.7	141.6	139.6	141.6	138.6	137.5	138.6
75°	123.2	122.1	120.1	118.0	119.1	116.0	112.9	111.9	111.9	109.8	109.8
77.5°	94.4	96.5	92.4	91.3	89.3	87.2	86.2	85.2	85.2	85.2	87.2
80°	65.7	66.7	66.7	64.7	65.7	62.6	62.6	62.6	59.5	60.6	61.6
82.5°	42.1	42.1	41.1	42.1	41.1	41.1	40.0	40.0	39.0	39.0	40.0
85°	23.6	22.6	21.6	23.6	22.6	22.6	21.6	21.6	21.6	21.6	21.6
87.5°	5.1	6.2	6.2	6.2	6.2	7.2	7.2	7.2	8.2	8.2	8.2
90°	10.6	10.1	9.6	9.1	8.6	7.8	7.1	6.3	5.6	5.2	4.7
92.5°	11.1	10.9	10.8	10.6	10.4	10.1	9.8	9.5	9.2	9.1	9.3
95°	18.8	18.3	17.8	17.4	16.9	16.2	15.5	14.8	14.1	13.8	15.4
97.5°	23.2	22.9	22.6	22.3	22.0	20.5	18.9	17.4	15.9	15.1	19.0
100°	27.7	26.9	26.2	25.4	24.6	23.0	21.4	19.7	18.1	17.3	23.9
102.5°	29.8	28.7	27.6	26.6	25.5	43.0	60.5	78.0	95.5	104.2	104.3
105°	30.6	29.5	28.5	27.4	26.4	52.6	78.8	105.0	131.2	144.3	142.9
107.5°	31.5	30.4	29.3	28.3	27.2	59.6	92.0	124.3	156.7	172.9	171.7
110°	37.2	46.8	56.4	66.0	75.6	103.4	131.1	158.9	186.6	200.5	199.5

TEST NUMBER: P1029661

CATALOG NUMBER: S122DIW-B675D435UB2750-4F0-XX-W2A-A_3000K

CANDELA DISTRIBUTION (continued):

	295°	300°	305°	310°	315°	320°	325°	330°	335°	337.5°	340°
112.5°	54.0	95.4	136.7	178.1	219.5	221.1	222.8	224.4	226.1	226.9	226.0
115°	88.8	133.3	177.7	222.2	266.6	264.2	261.8	259.4	257.0	255.8	255.0
117.5°	235.1	248.8	262.5	276.3	290.0	288.4	286.7	285.1	283.4	282.6	281.6
120°	321.4	320.3	319.1	318.0	316.8	315.1	313.3	311.6	309.9	309.0	308.3
122.5°	344.6	344.0	343.5	342.9	342.3	340.4	338.4	336.5	334.6	333.6	332.8
125°	367.9	367.2	366.5	365.9	365.2	363.4	361.6	359.7	357.9	357.0	356.4
127.5°	390.2	389.3	388.3	387.4	386.4	385.0	383.5	382.1	380.6	379.9	379.2
130°	410.9	409.8	408.8	407.7	406.7	405.6	404.6	403.5	402.4	401.9	401.1
132.5°	430.5	429.6	428.7	427.9	427.0	425.9	424.9	423.8	422.7	422.2	421.6
135°	449.4	448.5	447.5	446.6	445.6	444.7	443.9	443.0	442.1	441.7	440.9
137.5°	467.1	466.2	465.2	464.3	463.3	462.3	461.4	460.4	459.5	459.0	458.4
140°	484.1	483.2	482.3	481.5	480.6	479.5	478.5	477.4	476.3	475.8	475.4
142.5°	499.6	498.9	498.1	497.4	496.6	495.3	494.1	492.8	491.5	490.9	490.6
145°	514.0	513.3	512.6	512.0	511.3	509.7	508.0	506.4	504.7	503.9	503.9
147.5°	526.6	526.1	525.6	525.2	524.7	523.1	521.4	519.8	518.1	517.3	517.4
150°	538.6	538.0	537.5	536.9	536.3	534.8	533.2	531.7	530.2	529.4	529.7
152.5°	549.4	548.8	548.3	547.7	547.1	545.7	544.2	542.8	541.3	540.6	541.0
155°	558.9	558.3	557.8	557.2	556.6	555.4	554.3	553.1	552.0	551.4	551.8
157.5°	567.6	566.9	566.2	565.5	564.8	564.0	563.1	562.3	561.4	561.0	561.4
160°	574.5	573.9	573.4	572.8	572.2	571.6	571.0	570.5	569.9	569.6	569.9
162.5°	581.4	580.7	580.0	579.4	578.7	578.2	577.7	577.2	576.7	576.5	576.8
165°	586.6	585.9	585.2	584.6	583.9	583.6	583.3	583.0	582.7	582.6	582.9
167.5°	591.3	590.6	589.9	589.3	588.6	588.3	588.0	587.7	587.4	587.3	587.6
170°	594.8	594.1	593.4	592.8	592.1	591.9	591.7	591.5	591.3	591.2	591.5
172.5°	597.4	596.7	596.0	595.4	594.7	594.5	594.3	594.1	593.9	593.8	594.1
175°	599.1	598.4	597.7	597.1	596.4	596.2	596.0	595.8	595.6	595.5	595.8
177.5°	599.6	598.9	598.2	597.5	596.8	596.7	596.6	596.5	596.4	596.4	596.7
180°	597.3	597.3	597.3	597.3	597.3	597.3	597.3	597.3	597.3	597.3	597.3

TEST NUMBER: P1029661

CATALOG NUMBER: S122DIW-B675D435UB2750-4F0-XX-W2A-A_3000K

CANDELA DISTRIBUTION (continued):

	345°	350°	355°	360°
0°	1335.3	1335.3	1335.3	1335.3
2.5°	1310.6	1310.6	1326.0	1342.4
5°	1281.9	1289.1	1313.7	1336.3
7.5°	1254.2	1266.5	1297.3	1326.0
10°	1220.3	1236.7	1274.7	1308.6
12.5°	1187.5	1202.9	1247.0	1285.0
15°	1141.3	1160.8	1208.0	1255.2
17.5°	1095.1	1114.6	1172.1	1227.5
20°	1040.7	1066.4	1131.0	1204.9
22.5°	990.4	1022.2	1094.1	1153.6
25°	935.0	984.3	1051.0	1127.9
27.5°	885.7	935.0	1002.7	1080.7
30°	830.3	880.6	950.4	1022.2
32.5°	776.9	823.1	890.9	979.1
35°	721.5	765.6	831.3	920.6
37.5°	671.2	714.3	786.2	868.3
40°	622.0	667.1	728.7	810.8
42.5°	575.8	615.8	671.2	753.3
45°	533.7	562.4	613.7	690.7
47.5°	489.6	515.2	562.4	639.4
50°	448.5	470.1	511.1	583.0
52.5°	408.5	427.0	464.9	522.4
55°	372.6	390.0	417.7	474.2
57.5°	335.6	349.0	375.6	420.8
60°	299.7	312.0	333.6	370.5
62.5°	263.8	274.0	294.6	324.3
65°	232.0	240.2	255.6	281.2
67.5°	201.2	206.3	218.6	239.1
70°	171.4	175.5	185.8	202.2
72.5°	139.6	143.7	155.0	166.3
75°	112.9	113.9	122.1	131.4
77.5°	88.3	87.2	93.4	100.6
80°	60.6	63.6	68.8	71.8
82.5°	41.1	42.1	44.1	46.2
85°	22.6	23.6	23.6	26.7
87.5°	9.2	10.3	10.3	11.3
90°	3.6	2.5	1.5	0.4
92.5°	9.7	10.0	10.4	10.8
95°	18.6	21.7	24.9	28.1
97.5°	26.9	34.8	42.7	50.6
100°	37.0	50.2	63.3	76.5
102.5°	104.5	104.6	104.8	105.0
105°	140.0	137.1	134.3	131.4
107.5°	169.3	166.9	164.5	162.1
110°	197.5	195.5	193.5	191.5

TEST NUMBER: P1029661

CATALOG NUMBER: S122DIW-B675D435UB2750-4F0-XX-W2A-A_3000K

CANDELA DISTRIBUTION (continued):

	345°	350°	355°	360°
112.5°	224.3	222.6	220.8	219.1
115°	253.4	251.7	250.1	248.5
117.5°	279.7	277.8	275.9	274.0
120°	306.8	305.4	303.9	302.5
122.5°	331.3	329.8	328.2	326.7
125°	355.1	353.9	352.6	351.4
127.5°	377.9	376.5	375.2	373.8
130°	399.6	398.1	396.5	395.0
132.5°	420.3	419.1	417.8	416.6
135°	439.4	437.9	436.3	434.8
137.5°	457.3	456.1	455.0	453.8
140°	474.7	473.9	473.2	472.4
142.5°	489.9	489.2	488.6	487.9
145°	504.0	504.1	504.2	504.3
147.5°	517.7	518.0	518.3	518.6
150°	530.4	531.1	531.7	532.4
152.5°	541.8	542.5	543.3	544.1
155°	552.7	553.6	554.4	555.3
157.5°	562.1	562.9	563.6	564.4
160°	570.5	571.0	571.6	572.2
162.5°	577.4	577.9	578.5	579.1
165°	583.5	584.0	584.6	585.2
167.5°	588.2	588.7	589.3	589.9
170°	592.1	592.6	593.2	593.8
172.5°	594.7	595.2	595.8	596.4
175°	596.5	597.2	597.9	598.6
177.5°	597.4	598.1	598.7	599.4
180°	597.3	597.3	597.3	597.3

(END OF REPORT)