

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: NEO-RAY

Report Number: P1030706

Luminaire Tested: S123DIW-B1000D755UB2750-4F0-XX-W2A-D_3000K

Issue Date: 5/7/2025

Test Information

Test Method: LM-79-2019
Report Number: P1030706
REPORT IS A COMBINATION OF REPORTS P990802 AND P1007351
Test Lab: INNOVATION CENTER
Issue Date: 5/7/2025
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: NEO-RAY
Catalog Number: S123DIW-B1000D755UB2750-4F0-XX-W2A-D_3000K
Description: Define 3 Direct/Indirect Wall Mount with 3000K BioUP LEDs {m-DER=0.589} {m-EER=0.647}
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 7248.0 lumens
Efficiency: N/A
Efficacy: 103.5 lumens/watt
Spacing Criteria (0/90/45): 1.2 / 1.25 / 1.37
Luminous Opening: Rectangular w/ Sides (W: 0.25' x L: 4' x H: 0.1')
CIE Type: General Diffuse

Input Watts (W): 70
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1030706

CATALOG NUMBER: S123DIW-B1000D755UB2750-4F0-XX-W2A-D_3000K

Luminous Intensity Polar Plot



TEST NUMBER: P1030706

CATALOG NUMBER: S123DIW-B1000D755UB2750-4F0-XX-W2A-D_3000K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	108	108	108	108	100	100	100	100	85	85	85		71	71	71		59
1	97	92	88	84	90	86	82	78	73	70	67		61	59	57		50
2	88	80	73	68	81	74	68	63	63	59	55		53	50	47		43
3	80	70	62	56	74	65	58	53	55	50	46		46	42	39		38
4	73	62	53	47	67	57	50	44	49	43	39		41	37	33		34
5	67	55	46	40	62	51	43	38	44	38	33		37	32	29		30
6	62	49	41	35	57	46	38	33	39	33	29		33	29	25		28
7	57	44	36	30	53	41	34	29	36	30	25		30	25	22		25
8	53	40	32	27	49	38	30	25	32	27	22		28	23	20		23
9	49	37	29	24	45	34	27	23	30	24	20		25	21	18		21
10	46	34	26	21	42	31	25	20	27	22	18		23	19	16		20

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	13369	13369	13369
5°	13405	12976	12966
10°	13279	12625	12529
15°	13104	12237	12065
20°	12854	11804	11566
25°	12548	11317	11051
30°	12233	10876	10532
35°	11881	10413	10110
40°	11544	9989	9664
45°	11171	9580	9297
50°	10802	9175	8898
55°	10393	8758	8531
60°	9993	8332	8156
65°	9582	7879	7716
70°	8964	7369	7261
75°	8182	6788	6793
80°	7269	6203	6260
85°	6368	5725	5878

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 11171 cd/sqm

TEST NUMBER: P1030706

CATALOG NUMBER: S123DIW-B1000D755UB2750-4F0-XX-W2A-D_3000K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	117.8	1.6
10°-20°	335.9	4.6
20°-30°	502.3	6.9
30°-40°	599.7	8.3
40°-50°	627.4	8.7
50°-60°	588.8	8.1
60°-70°	491.8	6.8
70°-80°	351.7	4.9
80°-90°	211.3	2.9
90°-100°	167.0	2.3
100°-110°	268.5	3.7
110°-120°	485.6	6.7
120°-130°	571.3	7.9
130°-140°	587.5	8.1
140°-150°	537.4	7.4
150°-160°	430.7	5.9
160°-170°	277.9	3.8
170°-180°	95.8	1.3
0°-30°	955.9	13.2
0°-40°	1555.6	21.5
0°-60°	2771.8	38.2
0°-90°	3826.5	52.8
90°-120°	921.0	12.7
90°-150°	2617.2	36.1
90°-180°	3422.0	47.2
0°-180°	7248.0	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	1242	1242	1242	1242	1242	
5°	1243	1241	1232	1243	1242	118
15°	1184	1188	1186	1200	1199	333
25°	1069	1082	1086	1104	1104	493
35°	920	942	959	980	985	575
45°	752	785	818	844	855	580
55°	574	618	667	704	714	514
65°	396	449	509	549	563	392
75°	215	279	346	391	407	230
85°	66	134	206	252	265	68
90°	18	92	171	220	235	15
95°	61	83	157	204	218	66
105°	234	275	266	171	184	247
115°	425	446	501	541	555	420
125°	594	600	642	672	683	531
135°	737	740	758	785	789	568
145°	849	853	854	866	872	531
155°	934	932	933	937	932	430
165°	984	982	982	988	982	278
175°	1008	1004	1005	1010	1004	96
180°	1008	1008	1008	1008	1008	

TEST NUMBER: P1030706

CATALOG NUMBER: S123DIW-B1000D755UB2750-4F0-XX-W2A-D_3000K

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	1242.0	1242.0	1242.0	1242.0	1242.0
2.5°	1248.7	1244.7	1233.9	1244.7	1243.3
5°	1243.3	1240.6	1232.5	1243.3	1242.0
7.5°	1233.9	1233.9	1225.7	1239.3	1237.9
10°	1220.3	1223.0	1216.3	1229.8	1227.1
12.5°	1204.1	1208.1	1204.1	1216.3	1213.6
15°	1183.8	1187.9	1186.5	1200.0	1198.7
17.5°	1159.4	1167.6	1166.2	1178.4	1175.7
20°	1132.4	1140.5	1143.2	1155.4	1156.7
22.5°	1104.0	1112.1	1116.2	1132.4	1131.0
25°	1068.8	1082.3	1086.4	1104.0	1104.0
27.5°	1035.0	1049.9	1058.0	1072.9	1074.2
30°	998.4	1016.0	1026.9	1043.1	1043.1
32.5°	957.9	978.2	993.0	1010.6	1014.7
35°	920.0	941.6	959.2	979.5	984.9
37.5°	879.4	903.7	924.0	947.0	951.1
40°	838.8	863.2	890.2	913.2	918.6
42.5°	794.2	825.3	853.7	879.4	887.5
45°	752.2	784.7	818.5	844.2	855.0
47.5°	707.6	744.1	782.0	810.4	818.5
50°	664.3	702.2	744.1	775.2	784.7
52.5°	618.3	658.9	706.2	738.7	750.9
55°	573.6	618.3	667.0	703.5	714.3
57.5°	530.3	576.3	629.1	665.6	677.8
60°	484.3	533.0	588.5	626.4	641.3
62.5°	441.0	491.1	550.6	588.5	602.0
65°	396.4	449.2	508.7	549.3	562.8
67.5°	351.8	407.2	466.8	511.4	522.2
70°	304.4	362.6	427.5	470.8	484.3
72.5°	261.1	319.3	386.9	431.6	445.1
75°	215.1	278.7	346.3	391.0	407.2
77.5°	175.9	239.5	307.1	354.5	366.6
80°	133.9	200.2	270.6	316.6	330.1
82.5°	97.4	165.1	236.8	282.8	296.3
85°	66.3	133.9	205.6	251.6	265.2
87.5°	40.6	108.2	177.2	223.2	236.8
90°	18.3	92.1	170.9	219.9	234.9
92.5°	33.4	87.1	161.6	211.4	224.4
95°	60.6	82.6	157.1	204.3	217.8
97.5°	96.6	124.3	149.8	196.3	210.6
100°	138.7	197.0	142.4	187.6	201.9
102.5°	186.7	234.4	165.0	178.2	193.2
105°	233.9	274.6	265.5	170.7	184.4
107.5°	282.8	317.9	384.6	305.8	220.0
110°	331.5	361.9	424.2	434.7	338.5



TEST NUMBER: P1030706

CATALOG NUMBER: S123DIW-B1000D755UB2750-4F0-XX-W2A-D_3000K

CANDELA DISTRIBUTION (continued):

	0°	22.5°	45°	67.5°	90°
112.5°	379.4	403.7	463.3	503.8	514.5
115°	425.3	446.0	501.4	541.4	555.2
117.5°	471.7	487.7	537.5	576.0	587.5
120°	513.0	526.5	573.4	610.5	620.0
122.5°	556.4	564.3	609.3	642.8	653.0
125°	594.0	600.0	642.2	672.1	683.1
127.5°	633.0	637.6	675.1	704.4	712.4
130°	668.9	673.5	703.6	732.3	738.9
132.5°	701.9	707.9	730.5	757.9	765.0
135°	737.1	740.3	758.1	784.8	789.3
137.5°	767.1	771.8	782.7	808.1	813.3
140°	795.7	800.2	806.5	829.7	835.0
142.5°	823.4	826.5	828.8	848.6	853.2
145°	848.9	852.7	854.2	866.5	871.9
147.5°	872.2	875.9	877.4	883.0	884.7
150°	894.6	896.9	898.4	899.9	900.3
152.5°	914.8	915.6	916.3	919.3	915.6
155°	933.6	932.1	932.8	936.6	932.1
157.5°	948.5	948.5	947.8	952.3	946.3
160°	962.0	961.3	960.5	965.0	959.8
162.5°	974.7	972.5	971.7	977.0	972.5
165°	984.5	982.2	981.5	987.5	982.2
167.5°	992.7	989.7	989.7	995.7	989.7
170°	999.4	996.4	996.4	1002.4	996.4
172.5°	1003.9	1000.2	1000.9	1006.9	1000.2
175°	1007.7	1003.9	1004.7	1009.9	1003.9
177.5°	1009.2	1005.4	1006.2	1012.2	1004.7
180°	1007.7	1007.7	1007.7	1007.7	1007.7

(END OF REPORT)