

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: NEO-RAY

Report Number: P1031280

Luminaire Tested: S123DIW-B1000D1030UB35-4F0-XX-W2A-F

Issue Date: 5/7/2025

Test Information

Test Method: LM-79-2019
Report Number: P1031280
REPORT IS A COMBINATION OF REPORTS P990564 AND P1007351
Test Lab: INNOVATION CENTER
Issue Date: 5/7/2025
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: NEO-RAY
Catalog Number: S123DIW-B1000D1030UB35-4F0-XX-W2A-F
Description: Define 3 Direct/Indirect Wall Mount with 3500K BioUP LEDs {m-DER=0.721} {m-EER=0.792}
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 8314.0 lumens
Efficiency: N/A
Efficacy: 106.2 lumens/watt
Spacing Criteria (0/90/45): 1.21 / 1.18 / 1.3
Luminous Opening: Rectangular w/ Sides (W: 0.25' x L: 4' x H: 0.1')
CIE Type: General Diffuse

Input Watts (W): 78.3
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1031280

CATALOG NUMBER: S123DIW-B1000D1030UB35-4F0-XX-W2A-F

Luminous Intensity Polar Plot



TEST NUMBER: P1031280

CATALOG NUMBER: S123DIW-B1000D1030UB35-4F0-XX-W2A-F

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10
RCR																	
0	107	107	107	107	99	99	99	99	83	83	83	69	69	69	56	56	56
1	98	93	89	86	90	86	83	80	73	70	68	60	59	57	49	48	47
2	89	81	75	70	82	75	70	65	64	60	56	53	50	48	43	41	39
3	81	72	64	58	74	66	60	55	56	51	47	47	43	40	38	36	34
4	74	63	55	49	68	59	52	46	50	45	40	42	38	34	34	31	29
5	68	56	48	42	62	52	45	40	45	39	35	37	33	30	31	28	25
6	63	51	42	37	58	47	40	34	40	34	30	34	29	26	28	25	22
7	58	46	38	32	53	42	35	30	36	31	27	31	26	23	25	22	20
8	54	41	34	28	49	39	32	27	33	28	24	28	24	21	23	20	18
9	50	38	30	25	46	35	28	24	30	25	21	26	22	19	22	18	16
10	47	35	27	23	43	32	26	21	28	23	19	24	20	17	20	17	14

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	17011	17011	17011
5°	17053	16424	16400
10°	16902	15868	15705
15°	16666	15289	14948
20°	16397	14649	14199
25°	16048	13971	13398
30°	15667	13270	12555
35°	15267	12554	11718
40°	14848	11803	10894
45°	14389	11071	10033
50°	13921	10253	9168
55°	13321	9403	8294
60°	12702	8465	7362
65°	12121	7450	6390
70°	11285	6325	5257
75°	10080	5009	4081
80°	8703	3521	2886
85°	6791	1891	1445

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 14389 cd/sqm

TEST NUMBER: P1031280

CATALOG NUMBER: S123DIW-B1000D1030UB35-4F0-XX-W2A-F

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	149.0	1.8
10°-20°	420.7	5.1
20°-30°	621.3	7.5
30°-40°	725.6	8.7
40°-50°	729.5	8.8
50°-60°	640.8	7.7
60°-70°	477.3	5.7
70°-80°	271.6	3.3
80°-90°	80.0	1.0
90°-100°	48.6	0.6
100°-110°	234.8	2.8
110°-120°	575.4	6.9
120°-130°	730.4	8.8
130°-140°	780.3	9.4
140°-150°	729.6	8.8
150°-160°	588.5	7.1
160°-170°	379.8	4.6
170°-180°	130.9	1.6
0°-30°	1191.0	14.3
0°-40°	1916.6	23.1
0°-60°	3286.9	39.5
0°-90°	4115.8	49.5
90°-120°	858.7	10.3
90°-150°	3099.0	37.3
90°-180°	4198.0	50.5
0°-180°	8314.0	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	1580	1580	1580	1580	1580	
5°	1582	1575	1560	1574	1571	150
15°	1506	1500	1482	1493	1485	425
25°	1367	1359	1341	1343	1338	630
35°	1182	1174	1156	1148	1142	740
45°	969	963	946	930	923	748
55°	735	734	716	701	694	659
65°	501	495	481	470	466	495
75°	265	260	256	249	245	283
85°	71	68	68	65	65	76
90°	1	11	25	29	31	8
95°	62	20	32	39	39	75
105°	305	316	224	43	45	323
115°	572	578	587	598	602	565
125°	806	814	818	820	823	720
135°	1004	1010	1014	1017	1014	773
145°	1158	1165	1167	1169	1169	725
155°	1276	1274	1275	1280	1274	588
165°	1345	1342	1341	1350	1342	380
175°	1377	1372	1373	1380	1372	131
180°	1377	1377	1377	1377	1377	

TEST NUMBER: P1031280

CATALOG NUMBER: S123DIW-B1000D1030UB35-4F0-XX-W2A-F

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	1580.4	1580.4	1580.4	1580.4	1580.4
2.5°	1587.2	1581.7	1566.8	1580.4	1579.0
5°	1581.7	1574.9	1560.0	1573.6	1570.9
7.5°	1569.5	1562.7	1547.8	1560.0	1558.6
10°	1553.2	1546.4	1528.7	1541.0	1538.2
12.5°	1531.4	1526.0	1509.7	1517.9	1516.5
15°	1505.6	1500.2	1482.5	1493.4	1485.2
17.5°	1477.1	1470.3	1452.6	1460.8	1458.1
20°	1444.5	1436.3	1418.7	1424.1	1420.0
22.5°	1407.8	1399.6	1382.0	1386.1	1380.6
25°	1367.0	1358.9	1341.2	1342.6	1338.5
27.5°	1324.9	1316.7	1297.7	1299.1	1295.0
30°	1278.7	1271.9	1252.9	1252.9	1243.4
32.5°	1232.5	1223.0	1209.4	1199.9	1195.8
35°	1182.2	1174.1	1156.4	1148.2	1141.5
37.5°	1131.9	1121.1	1103.4	1093.9	1089.8
40°	1078.9	1070.8	1051.8	1040.9	1035.5
42.5°	1025.9	1016.4	997.4	986.5	981.1
45°	968.9	963.4	945.8	929.5	922.7
47.5°	913.2	905.0	888.7	872.4	867.0
50°	856.1	849.3	831.6	816.7	808.5
52.5°	796.3	792.2	773.2	761.0	752.8
55°	735.2	733.8	716.1	701.2	694.4
57.5°	678.1	672.6	659.1	645.5	637.3
60°	615.6	614.2	597.9	585.7	578.9
62.5°	559.9	555.8	539.5	527.2	523.2
65°	501.4	494.6	481.0	470.2	466.1
67.5°	438.9	433.5	422.6	413.1	407.7
70°	383.2	375.0	366.9	357.4	350.6
72.5°	324.8	319.3	309.8	301.7	299.0
75°	265.0	259.5	255.5	248.7	244.6
77.5°	212.0	209.3	203.8	198.4	198.4
80°	160.3	156.3	153.6	152.2	152.2
82.5°	110.1	110.1	110.1	107.4	106.0
85°	70.7	67.9	67.9	65.2	65.2
87.5°	35.3	31.3	29.9	28.5	28.5
90°	1.0	11.3	24.6	28.6	30.7
92.5°	23.5	17.4	26.6	33.8	34.8
95°	62.4	20.5	31.7	38.9	38.9
97.5°	113.6	84.9	32.7	40.9	41.9
100°	172.9	193.4	33.8	41.9	43.0
102.5°	240.4	253.7	75.7	41.9	44.0
105°	304.9	316.1	224.1	43.0	45.0
107.5°	373.4	382.6	398.0	240.4	106.4
110°	442.0	450.2	461.4	427.7	281.4

TEST NUMBER: P1031280

CATALOG NUMBER: S123DIW-B1000D1030UB35-4F0-XX-W2A-F

CANDELA DISTRIBUTION (continued):

	0°	22.5°	45°	67.5°	90°
112.5°	507.5	514.6	525.9	535.1	533.0
115°	571.9	578.1	587.3	597.5	601.6
117.5°	635.4	642.5	647.6	655.8	656.8
120°	693.7	702.9	706.0	714.1	714.1
122.5°	753.0	760.2	764.3	769.4	770.4
125°	806.2	814.4	818.5	820.5	822.6
127.5°	859.4	867.6	872.7	875.8	873.7
130°	908.5	916.7	920.8	924.9	922.9
132.5°	955.6	963.8	966.8	970.9	967.9
135°	1003.7	1009.8	1013.9	1017.0	1013.9
137.5°	1044.6	1052.8	1054.8	1059.9	1057.9
140°	1085.5	1091.7	1094.7	1098.8	1096.8
142.5°	1123.4	1129.5	1132.6	1135.7	1132.6
145°	1158.2	1165.3	1167.4	1169.4	1169.4
147.5°	1191.9	1197.0	1199.1	1201.1	1196.0
150°	1222.6	1225.7	1227.7	1229.8	1226.7
152.5°	1250.2	1251.3	1252.3	1256.4	1251.3
155°	1275.8	1273.8	1274.8	1279.9	1273.8
157.5°	1296.3	1296.3	1295.3	1301.4	1293.2
160°	1314.7	1313.7	1312.7	1318.8	1311.6
162.5°	1332.1	1329.0	1328.0	1335.2	1329.0
165°	1345.4	1342.3	1341.3	1349.5	1342.3
167.5°	1356.7	1352.6	1352.6	1360.7	1352.6
170°	1365.9	1361.8	1361.8	1370.0	1361.8
172.5°	1372.0	1366.9	1367.9	1376.1	1366.9
175°	1377.1	1372.0	1373.0	1380.2	1372.0
177.5°	1379.2	1374.0	1375.1	1383.3	1373.0
180°	1377.1	1377.1	1377.1	1377.1	1377.1

(END OF REPORT)