

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: NEO-RAY

Report Number: P1032065

Luminaire Tested: S123RDIW-B1000D755UB30-4F0-XX-W2A-A1

Issue Date: 5/7/2025

Test Information

Test Method: LM-79-2019
Report Number: P1032065
REPORT IS A COMBINATION OF REPORTS P993916 AND P1007351
Test Lab: INNOVATION CENTER
Issue Date: 5/7/2025
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: NEO-RAY
Catalog Number: S123RDIW-B1000D755UB30-4F0-XX-W2A-A1
Description: Define 3 Regressed Direct/Indirect Wall Mount with 3000K BioUP LEDs {m-DER=0.589}
{m-EER=0.647}
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 6600.0 lumens
Efficiency: N/A
Efficacy: 94.3 lumens/watt
Spacing Criteria (0/90/45): 1.22 / 1.2 / 1.34
Luminous Opening: Rectangular w/ Sides (W: 0.25' x L: 4' x H: 0.1')
CIE Type: General Diffuse

Input Watts (W): 70
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1032065

CATALOG NUMBER: S123RDIW-B1000D755UB30-4F0-XX-W2A-A1

Luminous Intensity Polar Plot



TEST NUMBER: P1032065

CATALOG NUMBER: S123RDIW-B1000D755UB30-4F0-XX-W2A-A1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10
RCR																	
0	109	109	109	109	102	102	102	102	89	89	89	76	76	76	65	65	65
1	101	97	93	90	94	90	87	84	79	77	74	68	67	65	59	57	56
2	92	85	79	74	86	80	75	70	70	66	63	61	58	55	52	50	48
3	85	75	68	63	79	71	65	60	62	58	54	54	51	48	47	44	42
4	78	67	60	54	72	63	57	51	56	51	46	49	45	41	42	39	37
5	72	60	52	47	67	57	50	44	50	45	40	44	40	36	39	35	33
6	66	54	46	41	62	51	44	39	46	40	36	40	36	32	35	32	29
7	61	49	42	36	57	47	40	35	42	36	32	37	32	29	32	29	26
8	57	45	37	32	53	43	36	31	38	32	28	34	29	26	30	26	23
9	53	41	34	29	50	39	32	28	35	29	26	31	27	23	28	24	21
10	50	38	31	26	47	36	30	25	32	27	23	29	24	21	26	22	19

AVERAGE LUMINANCE (cd/sqm):

	0°	90°	180°	270°
0°	17010	17010	17010	17010
5°	17023	19591	17067	14534
10°	16873	23649	16947	12695
15°	16699	26840	16699	11194
20°	16356	28951	16448	9930
25°	16106	27505	16074	9060
30°	15814	19058	15781	8210
35°	15464	12236	15394	7570
40°	15027	8640	14952	6932
45°	14266	6914	14247	6311
50°	13333	5784	13289	5585
55°	12281	4767	12183	4734
60°	11252	3940	11138	4026
65°	10042	3153	10107	3412
70°	8926	2191	9164	2759
75°	7566	1625	7874	2122
80°	6021	1077	6536	1591
85°	4284	510	4678	989

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 30°

Vertical Angle: 45°

Luminance: 22709 cd/sqm

TEST NUMBER: P1032065

CATALOG NUMBER: S123RDIW-B1000D755UB30-4F0-XX-W2A-A1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	155.2	2.4
10°-20°	485.8	7.4
20°-30°	765.1	11.6
30°-40°	795.6	12.1
40°-50°	680.7	10.3
50°-60°	518.9	7.9
60°-70°	332.5	5.0
70°-80°	159.3	2.4
80°-90°	43.9	0.7
90°-100°	61.9	0.9
100°-110°	187.3	2.8
110°-120°	318.8	4.8
120°-130°	419.4	6.4
130°-140°	471.4	7.1
140°-150°	463.4	7.0
150°-160°	390.2	5.9
160°-170°	259.7	3.9
170°-180°	91.0	1.4
0°-30°	1406.1	21.3
0°-40°	2201.7	33.4
0°-60°	3401.4	51.5
0°-90°	3937.0	59.7
90°-120°	567.9	8.6
90°-150°	1922.1	29.1
90°-180°	2663.0	40.3
0°-180°	6600.0	100.0

CANDELA DISTRIBUTION:

	0°	90°	180°	270°	360°	Flux
0°	1580	1580	1580	1580	1580	
5°	1579	1877	1583	1392	1579	150
15°	1509	2667	1509	1112	1509	424
25°	1372	2748	1369	905	1372	632
35°	1197	1192	1192	737	1197	749
45°	961	636	959	580	961	740
55°	678	399	672	396	678	607
65°	415	230	418	249	415	415
75°	199	97	207	127	199	215
85°	45	23	49	45	45	50
90°	1	23	1	23	1	6
95°	44	59	44	59	44	49
105°	170	180	170	180	170	182
115°	321	322	321	322	321	318
125°	470	464	470	464	470	419
135°	609	608	609	608	609	469
145°	739	739	739	739	739	462
155°	846	845	846	845	846	390
165°	922	919	922	919	922	260
175°	959	955	959	955	959	91
180°	961	961	961	961	961	

TEST NUMBER: P1032065

CATALOG NUMBER: S123RDIW-B1000D755UB30-4F0-XX-W2A-A1

CANDELA DISTRIBUTION (FULL):

	0°	5°	10°	15°	20°	22.5°	25°	30°	35°	40°	45°
0°	1580.3	1580.3	1580.3	1580.3	1580.3	1580.3	1580.3	1580.3	1580.3	1580.3	1580.3
2.5°	1584.3	1595.2	1603.3	1608.7	1622.2	1630.3	1637.1	1649.3	1649.3	1652.0	1657.4
5°	1578.9	1601.9	1618.2	1639.8	1668.2	1681.8	1700.7	1716.9	1739.9	1752.1	1764.3
7.5°	1566.8	1599.2	1633.1	1665.5	1707.5	1734.5	1753.5	1795.4	1825.2	1861.7	1890.1
10°	1550.5	1595.2	1638.5	1688.5	1745.4	1785.9	1814.4	1869.8	1926.7	1978.1	2021.4
12.5°	1530.2	1584.3	1646.6	1707.5	1787.3	1827.9	1873.9	1942.9	2024.1	2089.0	2147.2
15°	1508.6	1570.8	1641.2	1715.6	1815.7	1872.5	1938.8	2022.7	2113.4	2206.7	2286.5
17.5°	1474.8	1553.2	1631.7	1739.9	1857.6	1891.5	1948.3	2063.3	2175.6	2259.5	2356.9
20°	1440.9	1528.9	1627.6	1725.1	1852.2	1930.7	1983.5	2105.2	2225.7	2327.1	2420.5
22.5°	1409.8	1501.8	1604.6	1727.8	1846.8	1925.3	1991.6	2118.8	2258.1	2371.8	2486.8
25°	1371.9	1472.0	1585.7	1702.1	1846.8	1906.4	1979.4	2126.9	2274.4	2405.6	2547.7
27.5°	1331.3	1432.8	1545.1	1664.2	1796.8	1884.7	1956.4	2114.7	2294.7	2435.4	2581.5
30°	1290.7	1394.9	1503.2	1610.1	1758.9	1842.8	1925.3	2099.8	2305.5	2466.5	2578.8
32.5°	1251.5	1339.5	1446.3	1550.5	1698.0	1790.0	1883.4	2084.9	2309.5	2444.8	2499.0
35°	1197.4	1289.4	1376.0	1486.9	1635.8	1726.4	1836.0	2083.6	2292.0	2375.8	2348.8
37.5°	1147.3	1224.5	1307.0	1405.8	1558.6	1676.3	1790.0	2048.4	2233.8	2239.2	2086.3
40°	1091.9	1155.4	1224.5	1328.6	1493.7	1610.1	1733.2	1994.3	2128.2	2048.4	1779.2
42.5°	1028.3	1085.1	1139.2	1240.7	1420.6	1550.5	1683.1	1926.7	1975.4	1791.4	1511.3
45°	960.6	1006.6	1056.7	1163.6	1343.5	1472.0	1604.6	1822.5	1772.4	1512.6	1246.1
47.5°	890.3	929.5	978.2	1075.6	1261.0	1392.2	1518.0	1673.6	1546.5	1267.7	1044.5
50°	819.9	851.0	898.4	998.5	1177.1	1296.2	1412.5	1514.0	1335.4	1087.8	863.2
52.5°	750.9	775.3	824.0	909.2	1082.4	1196.0	1279.9	1319.2	1137.9	898.4	749.6
55°	677.8	704.9	737.4	824.0	995.8	1079.7	1135.2	1133.8	947.1	761.7	619.7
57.5°	607.5	631.8	660.3	746.8	886.2	943.0	990.4	967.4	790.1	623.7	531.7
60°	545.3	558.8	589.9	663.0	768.5	817.2	844.3	805.0	645.4	526.3	439.7
62.5°	477.6	491.1	516.8	585.8	650.8	676.5	699.5	649.4	533.1	428.9	376.1
65°	415.4	433.0	449.2	504.7	539.8	571.0	568.3	526.3	416.7	349.1	305.8
67.5°	361.2	368.0	381.5	415.4	431.6	454.6	456.0	408.6	335.5	284.1	258.4
70°	303.1	309.8	319.3	335.5	346.4	351.8	349.1	307.1	253.0	221.9	198.9
72.5°	253.0	251.7	258.4	258.4	269.2	267.9	259.8	227.3	192.1	166.4	152.9
75°	198.9	200.2	201.6	198.9	194.8	189.4	182.7	158.3	135.3	123.1	110.9
77.5°	155.6	152.9	154.2	144.8	139.4	133.9	124.5	112.3	93.4	90.6	85.2
80°	110.9	109.6	108.2	104.2	92.0	86.6	79.8	73.1	69.0	66.3	64.9
82.5°	74.4	74.4	71.7	63.6	56.8	52.8	51.4	48.7	44.6	44.6	43.3
85°	44.6	43.3	40.6	32.5	28.4	28.4	28.4	28.4	25.7	25.7	24.4
87.5°	17.6	16.2	12.2	12.2	10.8	10.8	10.8	9.5	9.5	8.1	8.1
90°	0.8	2.5	4.1	5.8	7.5	8.3	9.4	11.6	13.7	15.9	18.1
92.5°	22.6	23.6	24.6	25.7	26.7	27.2	27.7	28.7	29.7	30.7	31.7
95°	44.5	45.7	46.9	48.0	49.2	49.8	50.5	51.8	53.2	54.5	55.9
97.5°	73.2	74.0	74.9	75.7	76.6	77.0	77.5	78.5	79.5	80.5	81.5
100°	102.7	103.7	104.7	105.7	106.7	107.2	107.6	108.5	109.3	110.2	111.0
102.5°	136.6	137.1	137.6	138.1	138.6	138.9	139.5	140.7	141.8	143.0	144.2
105°	169.9	170.2	170.6	170.9	171.2	171.4	172.2	173.7	175.2	176.7	178.2
107.5°	209.1	209.3	209.5	209.6	209.8	209.9	210.2	210.9	211.6	212.2	212.9
110°	245.4	245.7	246.1	246.4	246.7	246.9	247.1	247.4	247.7	248.1	248.4

TEST NUMBER: P1032065

CATALOG NUMBER: S123RDIW-B1000D755UB30-4F0-XX-W2A-A1

CANDELA DISTRIBUTION (continued):

	0°	5°	10°	15°	20°	22.5°	25°	30°	35°	40°	45°
112.5°	283.1	283.3	283.5	283.6	283.8	283.9	283.9	283.9	283.9	283.9	283.9
115°	320.9	321.4	321.9	322.4	322.9	323.1	322.9	322.6	322.3	321.9	321.6
117.5°	359.4	359.6	359.7	359.9	360.0	360.1	359.9	359.6	359.3	358.9	358.6
120°	394.8	395.8	396.8	397.9	398.9	399.4	399.0	398.1	397.3	396.4	395.6
122.5°	431.8	432.5	433.2	433.9	434.6	434.9	434.7	434.4	434.1	433.7	433.4
125°	469.6	470.1	470.6	471.1	471.6	471.9	471.7	471.4	471.0	470.7	470.3
127.5°	504.3	505.3	506.3	507.3	508.3	508.8	508.6	508.3	508.0	507.6	507.3
130°	539.0	540.4	541.7	543.1	544.4	545.1	544.8	544.3	543.8	543.3	542.8
132.5°	573.8	575.1	576.5	577.8	579.1	579.8	579.6	579.3	579.0	578.6	578.3
135°	609.3	610.3	611.3	612.3	613.3	613.8	613.7	613.5	613.4	613.2	613.0
137.5°	641.7	642.5	643.4	644.2	645.1	645.5	645.8	646.3	646.8	647.3	647.8
140°	675.7	676.5	677.4	678.2	679.1	679.5	679.6	679.7	679.9	680.0	680.2
142.5°	706.7	707.5	708.3	709.2	710.0	710.4	710.6	710.9	711.2	711.6	711.9
145°	739.1	739.4	739.8	740.1	740.4	740.6	740.9	741.4	741.9	742.4	742.9
147.5°	767.0	767.7	768.4	769.1	769.8	770.1	770.3	770.8	771.3	771.8	772.3
150°	796.5	796.8	797.2	797.5	797.8	798.0	798.2	798.5	798.8	799.2	799.5
152.5°	820.7	821.2	821.7	822.2	822.7	822.9	823.0	823.2	823.3	823.5	823.7
155°	846.3	846.3	846.3	846.3	846.3	846.3	846.4	846.6	846.7	846.9	847.1
157.5°	868.2	868.0	867.9	867.7	867.6	867.5	867.6	867.7	867.9	868.0	868.2
160°	888.6	888.3	887.9	887.6	887.3	887.1	887.1	887.1	887.1	887.1	887.1
162.5°	906.7	906.2	905.7	905.2	904.7	904.5	904.6	904.7	904.9	905.0	905.2
165°	921.8	921.3	920.8	920.3	919.8	919.6	919.6	919.6	919.6	919.6	919.6
167.5°	934.7	934.0	933.3	932.6	931.9	931.6	931.7	931.9	932.0	932.2	932.4
170°	945.2	944.5	943.9	943.2	942.5	942.2	942.2	942.2	942.2	942.2	942.2
172.5°	953.5	952.8	952.2	951.5	950.8	950.5	950.5	950.5	950.5	950.5	950.5
175°	958.8	958.1	957.5	956.8	956.1	955.8	955.8	955.8	955.8	955.8	955.8
177.5°	961.8	961.1	960.5	959.8	959.1	958.8	958.8	958.8	958.8	958.8	958.8
180°	961.1	961.1	961.1	961.1	961.1	961.1	961.1	961.1	961.1	961.1	961.1

TEST NUMBER: P1032065

CATALOG NUMBER: S123RDIW-B1000D755UB30-4F0-XX-W2A-A1

CANDELA DISTRIBUTION (continued):

	50°	55°	60°	65°	67.5°	70°	75°	80°	85°	90°	95°
0°	1580.3	1580.3	1580.3	1580.3	1580.3	1580.3	1580.3	1580.3	1580.3	1580.3	1580.3
2.5°	1668.2	1668.2	1680.4	1692.6	1685.8	1689.9	1704.8	1699.3	1710.2	1708.8	1712.9
5°	1794.1	1808.9	1821.1	1846.8	1850.9	1846.8	1872.5	1879.3	1891.5	1876.6	1883.4
7.5°	1936.1	1967.2	1997.0	2034.9	2047.1	2049.8	2063.3	2082.2	2098.5	2068.7	2083.6
10°	2074.1	2121.5	2182.4	2216.2	2246.0	2256.8	2267.6	2279.8	2298.7	2316.3	2302.8
12.5°	2223.0	2292.0	2350.1	2411.0	2447.5	2443.5	2474.6	2482.7	2497.6	2501.7	2507.1
15°	2344.7	2442.1	2478.7	2569.3	2577.4	2604.5	2639.7	2670.8	2674.9	2666.7	2666.7
17.5°	2461.1	2545.0	2609.9	2683.0	2697.9	2720.9	2765.5	2780.4	2785.8	2784.4	2784.4
20°	2555.8	2611.3	2720.9	2781.7	2806.1	2835.9	2867.0	2885.9	2890.0	2895.4	2887.3
22.5°	2618.0	2701.9	2791.2	2841.3	2861.6	2872.4	2892.7	2898.1	2891.3	2892.7	2894.0
25°	2666.7	2749.3	2803.4	2816.9	2815.6	2802.0	2787.1	2761.4	2758.7	2747.9	2726.3
27.5°	2680.3	2711.4	2704.6	2649.1	2593.7	2588.3	2499.0	2450.3	2394.8	2402.9	2371.8
30°	2607.2	2566.6	2470.6	2329.8	2271.7	2177.0	2076.8	1972.7	1932.1	1887.4	1969.9
32.5°	2428.6	2283.8	2113.4	1930.7	1833.3	1749.4	1642.5	1566.8	1523.5	1486.9	1557.3
35°	2159.4	1933.4	1707.5	1534.3	1454.5	1378.7	1278.6	1240.7	1186.6	1192.0	1198.7
37.5°	1813.0	1564.1	1393.6	1223.1	1170.3	1139.2	1066.2	1008.0	989.0	983.6	983.6
40°	1488.3	1284.0	1132.4	998.5	957.9	932.2	874.0	847.0	826.7	821.3	828.0
42.5°	1231.2	1056.7	939.0	849.7	821.3	788.8	764.4	730.6	726.6	717.1	729.3
45°	1033.7	882.1	794.2	729.3	704.9	692.7	665.7	645.4	637.3	635.9	645.4
47.5°	876.7	759.0	681.9	641.3	622.4	610.2	587.2	579.1	571.0	573.7	569.6
50°	736.0	648.1	598.0	561.5	549.3	537.1	522.3	514.1	510.1	510.1	508.7
52.5°	631.8	558.8	526.3	492.5	487.1	480.3	464.1	458.7	451.9	450.5	456.0
55°	541.2	491.1	458.7	438.4	433.0	419.4	412.7	405.9	401.8	399.1	400.5
57.5°	462.7	424.8	403.2	385.6	376.1	370.7	358.5	357.2	354.5	354.5	353.1
60°	397.8	370.7	345.0	334.2	327.4	320.7	319.3	311.2	307.1	309.8	308.5
62.5°	336.9	315.2	300.4	288.2	284.1	278.7	274.7	271.9	267.9	269.2	269.2
65°	281.4	263.8	253.0	242.2	240.8	235.4	234.1	231.4	231.4	230.0	232.7
67.5°	231.4	219.2	209.7	202.9	198.9	200.2	194.8	190.8	190.8	189.4	193.5
70°	184.0	177.2	167.8	159.7	154.2	154.2	147.5	146.1	146.1	146.1	144.8
72.5°	142.1	129.9	125.8	123.1	123.1	123.1	120.4	120.4	119.1	120.4	119.1
75°	105.5	104.2	101.5	100.1	100.1	98.8	97.4	97.4	97.4	97.4	97.4
77.5°	82.5	82.5	79.8	78.5	78.5	78.5	77.1	77.1	75.8	75.8	75.8
80°	60.9	60.9	58.2	58.2	58.2	56.8	56.8	56.8	58.2	56.8	56.8
82.5°	41.9	41.9	40.6	41.9	40.6	39.2	39.2	39.2	37.9	39.2	39.2
85°	24.4	24.4	23.0	21.6	23.0	23.0	21.6	23.0	21.6	23.0	21.6
87.5°	9.5	8.1	8.1	8.1	6.8	8.1	6.8	6.8	8.1	6.8	8.1
90°	18.8	19.4	20.1	20.8	21.1	21.3	21.6	21.9	22.3	22.6	22.3
92.5°	32.2	32.7	33.2	33.7	34.0	33.8	33.5	33.2	32.8	32.5	32.8
95°	56.6	57.2	57.9	58.6	58.9	58.9	58.9	58.9	58.9	58.9	58.9
97.5°	82.3	83.2	84.0	84.9	85.3	85.2	85.1	84.9	84.8	84.6	84.8
100°	111.5	112.0	112.5	113.0	113.2	113.4	113.7	114.1	114.4	114.8	114.4
102.5°	144.7	145.2	145.7	146.2	146.5	146.4	146.2	146.1	145.9	145.7	145.9
105°	178.2	178.2	178.2	178.2	178.2	178.4	178.7	179.0	179.4	179.7	179.4
107.5°	213.4	213.9	214.4	214.9	215.2	215.1	214.9	214.8	214.6	214.4	214.6
110°	249.1	249.7	250.4	251.1	251.4	251.2	250.9	250.6	250.2	249.9	250.2



TEST NUMBER: P1032065

CATALOG NUMBER: S123RDIW-B1000D755UB30-4F0-XX-W2A-A1

CANDELA DISTRIBUTION (continued):

	50°	55°	60°	65°	67.5°	70°	75°	80°	85°	90°	95°
112.5°	284.7	285.5	286.4	287.2	287.6	287.6	287.6	287.6	287.6	287.6	287.6
115°	321.8	322.0	322.1	322.3	322.4	322.3	322.1	322.0	321.8	321.6	321.8
117.5°	358.6	358.6	358.6	358.6	358.6	358.3	357.8	357.3	356.8	356.3	356.8
120°	395.4	395.2	395.1	394.9	394.8	394.6	394.3	394.0	393.6	393.3	393.6
122.5°	432.9	432.4	431.9	431.4	431.1	430.8	430.3	429.8	429.3	428.8	429.3
125°	469.6	469.0	468.3	467.6	467.3	467.0	466.3	465.6	465.0	464.3	465.0
127.5°	506.3	505.3	504.3	503.3	502.8	502.5	501.8	501.1	500.5	499.8	500.5
130°	542.1	541.5	540.8	540.1	539.8	539.2	538.0	536.9	535.7	534.5	535.7
132.5°	577.5	576.6	575.8	574.9	574.5	574.1	573.3	572.4	571.6	570.8	571.6
135°	612.3	611.7	611.0	610.3	610.0	609.8	609.5	609.2	608.8	608.5	608.8
137.5°	647.0	646.1	645.3	644.4	644.0	643.7	643.2	642.7	642.2	641.7	642.2
140°	680.0	679.9	679.7	679.6	679.5	678.9	677.7	676.6	675.4	674.2	675.4
142.5°	711.7	711.6	711.4	711.3	711.2	710.8	709.9	709.1	708.2	707.4	708.2
145°	742.7	742.5	742.4	742.2	742.1	741.8	741.1	740.4	739.8	739.1	739.8
147.5°	772.3	772.3	772.3	772.3	772.3	771.8	770.8	769.8	768.8	767.8	768.8
150°	799.5	799.5	799.5	799.5	799.5	799.0	798.0	797.0	796.0	795.0	796.0
152.5°	824.0	824.4	824.7	825.0	825.2	824.8	823.9	823.1	822.2	821.4	822.2
155°	847.8	848.4	849.1	849.8	850.1	849.5	848.3	847.2	846.0	844.8	846.0
157.5°	868.9	869.5	870.2	870.9	871.2	870.7	869.7	868.7	867.7	866.7	867.7
160°	887.9	888.8	889.6	890.5	890.9	890.6	889.9	889.2	888.5	887.8	888.5
162.5°	906.0	906.9	907.7	908.6	909.0	908.4	907.2	906.1	904.9	903.7	904.9
165°	920.6	921.6	922.6	923.6	924.1	923.5	922.3	921.2	920.0	918.8	920.0
167.5°	933.4	934.4	935.4	936.4	936.9	936.4	935.4	934.4	933.4	932.4	933.4
170°	943.4	944.6	945.7	946.9	947.5	946.9	945.7	944.6	943.4	942.2	943.4
172.5°	951.5	952.5	953.5	954.5	955.0	954.4	953.3	952.1	951.0	949.8	951.0
175°	956.8	957.8	958.8	959.8	960.3	959.7	958.5	957.4	956.2	955.0	956.2
177.5°	959.8	960.8	961.8	962.8	963.3	962.7	961.6	960.4	959.3	958.1	959.3
180°	961.1	961.1	961.1	961.1	961.1	961.1	961.1	961.1	961.1	961.1	961.1

TEST NUMBER: P1032065

CATALOG NUMBER: S123RDIW-B1000D755UB30-4F0-XX-W2A-A1

CANDELA DISTRIBUTION (continued):

	100°	105°	110°	112.5°	115°	120°	125°	130°	135°	140°	145°
0°	1580.3	1580.3	1580.3	1580.3	1580.3	1580.3	1580.3	1580.3	1580.3	1580.3	1580.3
2.5°	1706.1	1698.0	1692.6	1688.5	1684.5	1696.6	1680.4	1662.8	1650.6	1642.5	1639.8
5°	1884.7	1867.1	1852.2	1840.1	1842.8	1842.8	1814.4	1783.2	1756.2	1741.3	1725.1
7.5°	2091.7	2072.8	2043.0	2036.2	2030.8	1997.0	1968.6	1911.8	1877.9	1844.1	1814.4
10°	2297.4	2273.0	2244.6	2235.1	2221.6	2179.7	2136.4	2063.3	2021.4	1959.1	1919.9
12.5°	2489.5	2459.7	2431.3	2424.5	2404.3	2367.7	2293.3	2217.5	2145.8	2079.5	2010.5
15°	2650.5	2642.4	2599.1	2572.0	2527.4	2477.3	2461.1	2358.3	2267.6	2198.6	2074.1
17.5°	2785.8	2747.9	2707.3	2689.7	2672.1	2614.0	2555.8	2450.3	2352.8	2251.4	2171.5
20°	2894.0	2852.1	2823.7	2798.0	2789.9	2723.6	2631.6	2538.2	2431.3	2317.7	2213.5
22.5°	2899.4	2894.0	2875.1	2860.2	2844.0	2800.7	2727.6	2611.3	2497.6	2373.1	2236.5
25°	2787.1	2779.0	2833.2	2819.6	2830.4	2814.2	2775.0	2677.6	2545.0	2398.8	2260.8
27.5°	2448.9	2531.4	2616.7	2646.4	2666.7	2724.9	2743.9	2689.7	2582.8	2427.3	2273.0
30°	1988.9	2098.5	2236.5	2310.9	2367.7	2476.0	2616.7	2634.3	2584.2	2459.7	2270.3
32.5°	1561.3	1661.5	1772.4	1860.4	1936.1	2158.0	2347.4	2484.1	2508.4	2443.5	2277.1
35°	1258.3	1301.6	1407.1	1491.0	1593.8	1783.2	2006.5	2227.0	2375.8	2384.0	2256.8
37.5°	1037.7	1060.7	1152.7	1200.1	1261.0	1427.4	1635.8	1923.9	2155.3	2264.9	2200.0
40°	859.1	911.9	964.7	991.7	1035.0	1150.0	1350.3	1576.2	1863.1	2066.0	2112.0
42.5°	745.5	768.5	802.3	840.2	867.3	967.4	1101.3	1308.3	1566.8	1849.5	1976.7
45°	657.6	665.7	700.8	725.2	753.6	824.0	918.7	1091.9	1319.2	1597.9	1814.4
47.5°	584.5	600.7	619.7	634.5	653.5	707.6	788.8	914.6	1114.9	1363.8	1596.5
50°	519.5	529.0	553.4	560.1	573.7	611.5	673.8	769.8	934.9	1133.8	1374.6
52.5°	458.7	476.3	485.7	495.2	507.4	538.5	579.1	657.6	782.0	968.7	1173.0
55°	411.3	416.7	430.2	438.4	447.8	469.5	504.7	562.8	660.3	809.1	1002.6
57.5°	365.3	365.3	378.8	385.6	395.1	411.3	442.4	487.1	557.4	668.4	845.6
60°	316.6	318.0	328.8	336.9	339.6	355.8	381.5	416.7	470.8	552.0	696.8
62.5°	273.3	280.1	285.5	288.2	297.7	307.1	328.8	353.1	391.0	462.7	565.5
65°	236.8	238.1	242.2	244.9	248.9	259.8	276.0	292.2	324.7	377.5	461.4
67.5°	194.8	200.2	205.7	205.7	209.7	215.1	231.4	244.9	269.2	300.4	357.2
70°	146.1	148.8	156.9	161.0	166.4	175.9	184.0	192.1	211.1	234.1	277.4
72.5°	121.8	121.8	124.5	125.8	125.8	132.6	144.8	152.9	162.4	178.6	208.4
75°	97.4	97.4	101.5	100.1	102.8	105.5	106.9	112.3	117.7	129.9	147.5
77.5°	77.1	78.5	78.5	79.8	79.8	81.2	82.5	85.2	87.9	94.7	102.8
80°	56.8	58.2	58.2	59.5	59.5	60.9	62.2	63.6	66.3	69.0	73.1
82.5°	39.2	40.6	40.6	41.9	40.6	41.9	43.3	43.3	44.6	47.4	48.7
85°	23.0	23.0	24.4	23.0	23.0	23.0	24.4	24.4	25.7	29.8	29.8
87.5°	6.8	8.1	6.8	8.1	8.1	8.1	8.1	9.5	9.5	10.8	12.2
90°	21.9	21.6	21.3	21.1	20.8	20.1	19.4	18.8	18.1	15.9	13.7
92.5°	33.2	33.5	33.8	34.0	33.7	33.2	32.7	32.2	31.7	30.7	29.7
95°	58.9	58.9	58.9	58.9	58.6	57.9	57.2	56.6	55.9	54.5	53.2
97.5°	84.9	85.1	85.2	85.3	84.9	84.0	83.2	82.3	81.5	80.5	79.5
100°	114.1	113.7	113.4	113.2	113.0	112.5	112.0	111.5	111.0	110.2	109.3
102.5°	146.1	146.2	146.4	146.5	146.2	145.7	145.2	144.7	144.2	143.0	141.8
105°	179.0	178.7	178.4	178.2	178.2	178.2	178.2	178.2	178.2	176.7	175.2
107.5°	214.8	214.9	215.1	215.2	214.9	214.4	213.9	213.4	212.9	212.2	211.6
110°	250.6	250.9	251.2	251.4	251.1	250.4	249.7	249.1	248.4	248.1	247.7

TEST NUMBER: P1032065

CATALOG NUMBER: S123RDIW-B1000D755UB30-4F0-XX-W2A-A1

CANDELA DISTRIBUTION (continued):

	100°	105°	110°	112.5°	115°	120°	125°	130°	135°	140°	145°
112.5°	287.6	287.6	287.6	287.6	287.2	286.4	285.5	284.7	283.9	283.9	283.9
115°	322.0	322.1	322.3	322.4	322.3	322.1	322.0	321.8	321.6	321.9	322.3
117.5°	357.3	357.8	358.3	358.6	358.6	358.6	358.6	358.6	358.6	358.9	359.3
120°	394.0	394.3	394.6	394.8	394.9	395.1	395.2	395.4	395.6	396.4	397.3
122.5°	429.8	430.3	430.8	431.1	431.4	431.9	432.4	432.9	433.4	433.7	434.1
125°	465.6	466.3	467.0	467.3	467.6	468.3	469.0	469.6	470.3	470.7	471.0
127.5°	501.1	501.8	502.5	502.8	503.3	504.3	505.3	506.3	507.3	507.6	508.0
130°	536.9	538.0	539.2	539.8	540.1	540.8	541.5	542.1	542.8	543.3	543.8
132.5°	572.4	573.3	574.1	574.5	574.9	575.8	576.6	577.5	578.3	578.6	579.0
135°	609.2	609.5	609.8	610.0	610.3	611.0	611.7	612.3	613.0	613.2	613.4
137.5°	642.7	643.2	643.7	644.0	644.4	645.3	646.1	647.0	647.8	647.3	646.8
140°	676.6	677.7	678.9	679.5	679.6	679.7	679.9	680.0	680.2	680.0	679.9
142.5°	709.1	709.9	710.8	711.2	711.3	711.4	711.6	711.7	711.9	711.6	711.2
145°	740.4	741.1	741.8	742.1	742.2	742.4	742.5	742.7	742.9	742.4	741.9
147.5°	769.8	770.8	771.8	772.3	772.3	772.3	772.3	772.3	772.3	771.8	771.3
150°	797.0	798.0	799.0	799.5	799.5	799.5	799.5	799.5	799.5	799.2	798.8
152.5°	823.1	823.9	824.8	825.2	825.0	824.7	824.4	824.0	823.7	823.5	823.3
155°	847.2	848.3	849.5	850.1	849.8	849.1	848.4	847.8	847.1	846.9	846.7
157.5°	868.7	869.7	870.7	871.2	870.9	870.2	869.5	868.9	868.2	868.0	867.9
160°	889.2	889.9	890.6	890.9	890.5	889.6	888.8	887.9	887.1	887.1	887.1
162.5°	906.1	907.2	908.4	909.0	908.6	907.7	906.9	906.0	905.2	905.0	904.9
165°	921.2	922.3	923.5	924.1	923.6	922.6	921.6	920.6	919.6	919.6	919.6
167.5°	934.4	935.4	936.4	936.9	936.4	935.4	934.4	933.4	932.4	932.2	932.0
170°	944.6	945.7	946.9	947.5	946.9	945.7	944.6	943.4	942.2	942.2	942.2
172.5°	952.1	953.3	954.4	955.0	954.5	953.5	952.5	951.5	950.5	950.5	950.5
175°	957.4	958.5	959.7	960.3	959.8	958.8	957.8	956.8	955.8	955.8	955.8
177.5°	960.4	961.6	962.7	963.3	962.8	961.8	960.8	959.8	958.8	958.8	958.8
180°	961.1	961.1	961.1	961.1	961.1	961.1	961.1	961.1	961.1	961.1	961.1

TEST NUMBER: P1032065

CATALOG NUMBER: S123RDIW-B1000D755UB30-4F0-XX-W2A-A1

CANDELA DISTRIBUTION (continued):

	150°	155°	157.5°	160°	165°	170°	175°	180°	185°	190°	195°
0°	1580.3	1580.3	1580.3	1580.3	1580.3	1580.3	1580.3	1580.3	1580.3	1580.3	1580.3
2.5°	1635.8	1629.0	1622.2	1622.2	1607.3	1593.8	1587.1	1589.8	1581.6	1570.8	1560.0
5°	1707.5	1680.4	1675.0	1660.1	1639.8	1611.4	1596.5	1583.0	1566.8	1545.1	1524.8
7.5°	1773.8	1738.6	1719.6	1704.8	1665.5	1626.3	1593.8	1572.2	1543.8	1511.3	1486.9
10°	1860.4	1795.4	1775.1	1741.3	1685.8	1630.3	1592.5	1557.3	1518.0	1480.2	1447.7
12.5°	1929.4	1854.9	1817.1	1783.2	1711.5	1641.2	1577.6	1534.3	1486.9	1445.0	1403.0
15°	2007.8	1923.9	1857.6	1817.1	1726.4	1641.2	1569.5	1508.6	1455.8	1404.4	1367.9
17.5°	2045.7	1940.2	1910.4	1852.2	1721.0	1635.8	1547.8	1482.9	1419.3	1359.7	1316.5
20°	2105.2	1982.1	1907.7	1868.5	1752.1	1626.3	1523.5	1449.0	1382.8	1319.2	1273.2
22.5°	2109.3	1975.4	1926.7	1852.2	1708.8	1597.9	1501.8	1411.2	1334.0	1274.5	1227.2
25°	2099.8	1963.2	1895.5	1836.0	1716.9	1581.6	1458.5	1369.2	1293.5	1224.5	1169.0
27.5°	2095.8	1928.0	1864.4	1804.9	1670.9	1534.3	1432.8	1331.3	1244.7	1183.9	1127.0
30°	2090.4	1890.1	1813.0	1744.0	1620.9	1497.8	1376.0	1288.0	1205.5	1128.4	1071.6
32.5°	2055.2	1838.7	1760.2	1687.2	1554.6	1431.5	1335.4	1242.0	1152.7	1081.0	1029.6
35°	2044.4	1791.4	1688.5	1610.1	1480.2	1370.6	1269.1	1192.0	1108.1	1036.4	975.5
37.5°	2013.2	1742.6	1631.7	1531.6	1396.3	1292.1	1217.7	1140.6	1059.4	982.3	933.6
40°	1959.1	1685.8	1560.0	1457.2	1317.8	1212.3	1143.3	1086.4	1006.6	937.6	878.1
42.5°	1879.3	1627.6	1492.3	1384.1	1229.9	1131.1	1074.3	1020.2	952.5	880.8	832.1
45°	1787.3	1550.5	1424.7	1304.3	1147.3	1051.3	991.7	959.3	897.0	836.1	779.3
47.5°	1661.5	1470.7	1346.2	1221.7	1062.1	968.7	921.4	888.9	845.6	779.3	733.3
50°	1503.2	1367.9	1250.2	1139.2	978.2	888.9	841.6	817.2	780.7	733.3	688.7
52.5°	1327.3	1248.8	1151.4	1048.6	893.0	809.1	765.8	746.8	719.8	675.1	637.3
55°	1150.0	1116.2	1049.9	948.4	803.7	734.7	696.8	672.4	652.1	619.7	587.2
57.5°	991.7	975.5	929.5	851.0	729.3	657.6	625.1	608.8	592.6	568.3	535.8
60°	828.0	845.6	798.3	759.0	648.1	585.8	557.4	539.8	531.7	510.1	489.8
62.5°	686.0	702.2	675.1	645.4	566.9	511.4	493.8	477.6	472.2	453.2	433.0
65°	557.4	577.7	557.4	541.2	493.8	447.8	426.2	418.1	412.7	400.5	384.2
67.5°	443.8	464.1	454.6	434.3	419.4	381.5	369.4	361.2	358.5	349.1	335.5
70°	334.2	362.6	365.3	353.1	339.6	322.0	313.9	311.2	304.4	296.3	288.2
72.5°	240.8	273.3	274.7	274.7	266.5	266.5	258.4	254.4	254.4	246.2	236.8
75°	177.2	198.9	201.6	204.3	208.4	212.4	207.0	207.0	205.7	197.5	193.5
77.5°	117.7	136.7	143.4	152.9	158.3	158.3	161.0	163.7	161.0	156.9	154.2
80°	75.8	89.3	97.4	102.8	110.9	115.0	119.1	120.4	117.7	116.4	112.3
82.5°	50.1	54.1	58.2	64.9	74.4	81.2	81.2	79.8	82.5	81.2	79.8
85°	28.4	31.1	32.5	33.8	39.2	46.0	47.4	48.7	51.4	48.7	46.0
87.5°	10.8	12.2	12.2	12.2	14.9	16.2	20.3	25.7	24.4	21.6	21.6
90°	11.6	9.4	8.3	7.5	5.8	4.1	2.5	0.8	2.5	4.1	5.8
92.5°	28.7	27.7	27.2	26.7	25.7	24.6	23.6	22.6	23.6	24.6	25.7
95°	51.8	50.5	49.8	49.2	48.0	46.9	45.7	44.5	45.7	46.9	48.0
97.5°	78.5	77.5	77.0	76.6	75.7	74.9	74.0	73.2	74.0	74.9	75.7
100°	108.5	107.6	107.2	106.7	105.7	104.7	103.7	102.7	103.7	104.7	105.7
102.5°	140.7	139.5	138.9	138.6	138.1	137.6	137.1	136.6	137.1	137.6	138.1
105°	173.7	172.2	171.4	171.2	170.9	170.6	170.2	169.9	170.2	170.6	170.9
107.5°	210.9	210.2	209.9	209.8	209.6	209.5	209.3	209.1	209.3	209.5	209.6
110°	247.4	247.1	246.9	246.7	246.4	246.1	245.7	245.4	245.7	246.1	246.4

TEST NUMBER: P1032065

CATALOG NUMBER: S123RDIW-B1000D755UB30-4F0-XX-W2A-A1

CANDELA DISTRIBUTION (continued):

	150°	155°	157.5°	160°	165°	170°	175°	180°	185°	190°	195°
112.5°	283.9	283.9	283.9	283.8	283.6	283.5	283.3	283.1	283.3	283.5	283.6
115°	322.6	322.9	323.1	322.9	322.4	321.9	321.4	320.9	321.4	321.9	322.4
117.5°	359.6	359.9	360.1	360.0	359.9	359.7	359.6	359.4	359.6	359.7	359.9
120°	398.1	399.0	399.4	398.9	397.9	396.8	395.8	394.8	395.8	396.8	397.9
122.5°	434.4	434.7	434.9	434.6	433.9	433.2	432.5	431.8	432.5	433.2	433.9
125°	471.4	471.7	471.9	471.6	471.1	470.6	470.1	469.6	470.1	470.6	471.1
127.5°	508.3	508.6	508.8	508.3	507.3	506.3	505.3	504.3	505.3	506.3	507.3
130°	544.3	544.8	545.1	544.4	543.1	541.7	540.4	539.0	540.4	541.7	543.1
132.5°	579.3	579.6	579.8	579.1	577.8	576.5	575.1	573.8	575.1	576.5	577.8
135°	613.5	613.7	613.8	613.3	612.3	611.3	610.3	609.3	610.3	611.3	612.3
137.5°	646.3	645.8	645.5	645.1	644.2	643.4	642.5	641.7	642.5	643.4	644.2
140°	679.7	679.6	679.5	679.1	678.2	677.4	676.5	675.7	676.5	677.4	678.2
142.5°	710.9	710.6	710.4	710.0	709.2	708.3	707.5	706.7	707.5	708.3	709.2
145°	741.4	740.9	740.6	740.4	740.1	739.8	739.4	739.1	739.4	739.8	740.1
147.5°	770.8	770.3	770.1	769.8	769.1	768.4	767.7	767.0	767.7	768.4	769.1
150°	798.5	798.2	798.0	797.8	797.5	797.2	796.8	796.5	796.8	797.2	797.5
152.5°	823.2	823.0	822.9	822.7	822.2	821.7	821.2	820.7	821.2	821.7	822.2
155°	846.6	846.4	846.3	846.3	846.3	846.3	846.3	846.3	846.3	846.3	846.3
157.5°	867.7	867.6	867.5	867.6	867.7	867.9	868.0	868.2	868.0	867.9	867.7
160°	887.1	887.1	887.1	887.3	887.6	887.9	888.3	888.6	888.3	887.9	887.6
162.5°	904.7	904.6	904.5	904.7	905.2	905.7	906.2	906.7	906.2	905.7	905.2
165°	919.6	919.6	919.6	919.8	920.3	920.8	921.3	921.8	921.3	920.8	920.3
167.5°	931.9	931.7	931.6	931.9	932.6	933.3	934.0	934.7	934.0	933.3	932.6
170°	942.2	942.2	942.2	942.5	943.2	943.9	944.5	945.2	944.5	943.9	943.2
172.5°	950.5	950.5	950.5	950.8	951.5	952.2	952.8	953.5	952.8	952.2	951.5
175°	955.8	955.8	955.8	956.1	956.8	957.5	958.1	958.8	958.1	957.5	956.8
177.5°	958.8	958.8	958.8	959.1	959.8	960.5	961.1	961.8	961.1	960.5	959.8
180°	961.1	961.1	961.1	961.1	961.1	961.1	961.1	961.1	961.1	961.1	961.1

TEST NUMBER: P1032065

CATALOG NUMBER: S123RDIW-B1000D755UB30-4F0-XX-W2A-A1

CANDELA DISTRIBUTION (continued):

	200°	202.5°	205°	210°	215°	220°	225°	230°	235°	240°	245°
0°	1580.3	1580.3	1580.3	1580.3	1580.3	1580.3	1580.3	1580.3	1580.3	1580.3	1580.3
2.5°	1560.0	1553.2	1550.5	1543.8	1527.5	1516.7	1504.5	1496.4	1497.8	1491.0	1495.0
5°	1511.3	1509.9	1500.5	1486.9	1463.9	1451.8	1430.1	1419.3	1413.9	1415.2	1407.1
7.5°	1470.7	1458.5	1451.8	1430.1	1408.5	1382.8	1365.2	1355.7	1347.6	1339.5	1334.0
10°	1424.7	1413.9	1403.0	1380.0	1350.3	1325.9	1301.6	1292.1	1279.9	1274.5	1270.5
12.5°	1376.0	1369.2	1355.7	1328.6	1294.8	1271.8	1243.4	1238.0	1221.7	1210.9	1208.2
15°	1331.3	1327.3	1302.9	1271.8	1238.0	1215.0	1190.6	1174.4	1147.3	1152.7	1143.3
17.5°	1284.0	1266.4	1251.5	1209.6	1193.3	1158.2	1129.7	1121.6	1102.7	1090.5	1078.3
20°	1231.2	1220.4	1201.5	1174.4	1135.2	1094.6	1072.9	1059.4	1048.6	1029.6	1024.2
22.5°	1181.2	1167.6	1151.4	1116.2	1082.4	1048.6	1018.8	1006.6	993.1	979.6	971.4
25°	1141.9	1121.6	1104.0	1060.7	1026.9	998.5	979.6	959.3	940.3	932.2	929.5
27.5°	1081.0	1068.9	1051.3	1010.7	979.6	948.4	930.9	917.3	897.0	887.6	879.4
30°	1041.8	1017.4	997.1	964.7	933.6	899.7	883.5	867.3	855.1	842.9	833.4
32.5°	989.0	970.1	953.9	921.4	890.3	859.1	841.6	817.2	810.4	801.0	790.1
35°	937.6	925.4	907.9	872.7	838.9	817.2	798.3	775.3	767.1	760.4	750.9
37.5°	888.9	871.3	859.1	825.3	795.6	769.8	755.0	736.0	730.6	722.5	715.7
40°	847.0	829.4	817.2	783.4	752.3	725.2	715.7	696.8	688.7	679.2	675.1
42.5°	799.6	784.7	768.5	744.1	711.7	684.6	665.7	654.8	644.0	640.0	631.8
45°	749.6	736.0	723.8	696.8	663.0	644.0	627.8	612.9	604.8	598.0	592.6
47.5°	706.3	694.1	677.8	648.1	621.0	603.4	587.2	572.3	564.2	556.1	549.3
50°	656.2	649.4	631.8	603.4	577.7	557.4	542.5	529.0	523.6	514.1	503.3
52.5°	611.5	599.4	584.5	561.5	538.5	514.1	493.8	485.7	476.3	470.8	461.4
55°	558.8	550.7	534.4	514.1	489.8	469.5	454.6	443.8	431.6	426.2	414.0
57.5°	514.1	499.3	491.1	465.4	442.4	422.1	411.3	400.5	387.0	378.8	373.4
60°	465.4	451.9	439.7	418.1	401.8	380.2	364.0	354.5	345.0	334.2	328.8
62.5°	418.1	407.2	392.4	374.8	354.5	336.9	324.7	311.2	305.8	295.0	290.9
65°	366.7	358.5	346.4	326.1	309.8	295.0	282.8	271.9	266.5	262.5	259.8
67.5°	320.7	309.8	301.7	284.1	266.5	254.4	247.6	240.8	234.1	230.0	225.9
70°	273.3	265.2	257.1	240.8	228.7	217.8	212.4	207.0	202.9	198.9	194.8
72.5°	224.6	220.5	212.4	201.6	192.1	184.0	179.9	173.2	169.1	162.4	159.7
75°	185.4	178.6	174.5	165.1	156.9	150.2	144.8	136.7	131.2	128.5	127.2
77.5°	146.1	143.4	138.0	129.9	125.8	119.1	110.9	108.2	105.5	105.5	104.2
80°	109.6	105.5	101.5	94.7	90.6	85.2	85.2	85.2	83.9	85.2	83.9
82.5°	74.4	71.7	69.0	64.9	63.6	63.6	64.9	64.9	64.9	64.9	64.9
85°	43.3	43.3	43.3	44.6	43.3	43.3	44.6	46.0	44.6	44.6	43.3
87.5°	20.3	20.3	21.6	21.6	23.0	23.0	23.0	23.0	23.0	23.0	24.4
90°	7.5	8.3	9.4	11.6	13.7	15.9	18.1	18.8	19.4	20.1	20.8
92.5°	26.7	27.2	27.7	28.7	29.7	30.7	31.7	32.2	32.7	33.2	33.7
95°	49.2	49.8	50.5	51.8	53.2	54.5	55.9	56.6	57.2	57.9	58.6
97.5°	76.6	77.0	77.5	78.5	79.5	80.5	81.5	82.3	83.2	84.0	84.9
100°	106.7	107.2	107.6	108.5	109.3	110.2	111.0	111.5	112.0	112.5	113.0
102.5°	138.6	138.9	139.5	140.7	141.8	143.0	144.2	144.7	145.2	145.7	146.2
105°	171.2	171.4	172.2	173.7	175.2	176.7	178.2	178.2	178.2	178.2	178.2
107.5°	209.8	209.9	210.2	210.9	211.6	212.2	212.9	213.4	213.9	214.4	214.9
110°	246.7	246.9	247.1	247.4	247.7	248.1	248.4	249.1	249.7	250.4	251.1

TEST NUMBER: P1032065

CATALOG NUMBER: S123RDIW-B1000D755UB30-4F0-XX-W2A-A1

CANDELA DISTRIBUTION (continued):

	200°	202.5°	205°	210°	215°	220°	225°	230°	235°	240°	245°
112.5°	283.8	283.9	283.9	283.9	283.9	283.9	283.9	284.7	285.5	286.4	287.2
115°	322.9	323.1	322.9	322.6	322.3	321.9	321.6	321.8	322.0	322.1	322.3
117.5°	360.0	360.1	359.9	359.6	359.3	358.9	358.6	358.6	358.6	358.6	358.6
120°	398.9	399.4	399.0	398.1	397.3	396.4	395.6	395.4	395.2	395.1	394.9
122.5°	434.6	434.9	434.7	434.4	434.1	433.7	433.4	432.9	432.4	431.9	431.4
125°	471.6	471.9	471.7	471.4	471.0	470.7	470.3	469.6	469.0	468.3	467.6
127.5°	508.3	508.8	508.6	508.3	508.0	507.6	507.3	506.3	505.3	504.3	503.3
130°	544.4	545.1	544.8	544.3	543.8	543.3	542.8	542.1	541.5	540.8	540.1
132.5°	579.1	579.8	579.6	579.3	579.0	578.6	578.3	577.5	576.6	575.8	574.9
135°	613.3	613.8	613.7	613.5	613.4	613.2	613.0	612.3	611.7	611.0	610.3
137.5°	645.1	645.5	645.8	646.3	646.8	647.3	647.8	647.0	646.1	645.3	644.4
140°	679.1	679.5	679.6	679.7	679.9	680.0	680.2	680.0	679.9	679.7	679.6
142.5°	710.0	710.4	710.6	710.9	711.2	711.6	711.9	711.7	711.6	711.4	711.3
145°	740.4	740.6	740.9	741.4	741.9	742.4	742.9	742.7	742.5	742.4	742.2
147.5°	769.8	770.1	770.3	770.8	771.3	771.8	772.3	772.3	772.3	772.3	772.3
150°	797.8	798.0	798.2	798.5	798.8	799.2	799.5	799.5	799.5	799.5	799.5
152.5°	822.7	822.9	823.0	823.2	823.3	823.5	823.7	824.0	824.4	824.7	825.0
155°	846.3	846.3	846.4	846.6	846.7	846.9	847.1	847.8	848.4	849.1	849.8
157.5°	867.6	867.5	867.6	867.7	867.9	868.0	868.2	868.9	869.5	870.2	870.9
160°	887.3	887.1	887.1	887.1	887.1	887.1	887.1	887.9	888.8	889.6	890.5
162.5°	904.7	904.5	904.6	904.7	904.9	905.0	905.2	906.0	906.9	907.7	908.6
165°	919.8	919.6	919.6	919.6	919.6	919.6	919.6	920.6	921.6	922.6	923.6
167.5°	931.9	931.6	931.7	931.9	932.0	932.2	932.4	933.4	934.4	935.4	936.4
170°	942.5	942.2	942.2	942.2	942.2	942.2	942.2	943.4	944.6	945.7	946.9
172.5°	950.8	950.5	950.5	950.5	950.5	950.5	950.5	951.5	952.5	953.5	954.5
175°	956.1	955.8	955.8	955.8	955.8	955.8	955.8	956.8	957.8	958.8	959.8
177.5°	959.1	958.8	958.8	958.8	958.8	958.8	958.8	959.8	960.8	961.8	962.8
180°	961.1	961.1	961.1	961.1	961.1	961.1	961.1	961.1	961.1	961.1	961.1

TEST NUMBER: P1032065

CATALOG NUMBER: S123RDIW-B1000D755UB30-4F0-XX-W2A-A1

CANDELA DISTRIBUTION (continued):

	247.5°	250°	255°	260°	265°	270°	275°	280°	285°	290°	292.5°
0°	1580.3	1580.3	1580.3	1580.3	1580.3	1580.3	1580.3	1580.3	1580.3	1580.3	1580.3
2.5°	1493.7	1495.0	1491.0	1482.9	1481.5	1484.2	1492.3	1489.6	1482.9	1495.0	1484.2
5°	1411.2	1404.4	1401.7	1404.4	1396.3	1392.2	1400.3	1396.3	1400.3	1401.7	1405.8
7.5°	1331.3	1332.7	1324.6	1325.9	1315.1	1317.8	1317.8	1317.8	1321.9	1324.6	1330.0
10°	1262.3	1265.0	1255.6	1256.9	1248.8	1243.4	1247.5	1255.6	1255.6	1255.6	1258.3
12.5°	1206.9	1194.7	1187.9	1186.6	1177.1	1174.4	1182.5	1185.2	1192.0	1192.0	1196.0
15°	1137.9	1135.2	1129.7	1129.7	1106.7	1112.2	1114.9	1124.3	1137.9	1127.0	1129.7
17.5°	1075.6	1068.9	1062.1	1059.4	1056.7	1048.6	1059.4	1058.0	1066.2	1067.5	1071.6
20°	1020.2	1014.7	1001.2	1002.6	1005.3	993.1	999.9	999.9	1008.0	1016.1	1025.6
22.5°	966.0	960.6	953.9	956.6	948.4	945.7	945.7	952.5	962.0	968.7	967.4
25°	924.1	914.6	910.6	906.5	902.4	905.1	901.1	907.9	914.6	918.7	914.6
27.5°	876.7	872.7	864.6	860.5	853.7	856.4	859.1	864.6	868.6	868.6	872.7
30°	830.7	825.3	822.6	818.6	818.6	813.1	814.5	819.9	824.0	828.0	833.4
32.5°	786.1	782.0	778.0	778.0	775.3	773.9	772.6	780.7	780.7	788.8	788.8
35°	749.6	742.8	742.8	736.0	738.7	737.4	734.7	740.1	741.4	746.8	745.5
37.5°	709.0	709.0	706.3	699.5	694.1	695.4	702.2	702.2	706.3	704.9	709.0
40°	668.4	665.7	665.7	661.6	660.3	658.9	660.3	661.6	668.4	667.0	668.4
42.5°	627.8	629.1	622.4	622.4	622.4	618.3	619.7	621.0	623.7	626.4	630.5
45°	588.5	585.8	584.5	581.8	579.1	580.4	579.1	584.5	583.1	585.8	589.9
47.5°	546.6	542.5	541.2	535.8	535.8	538.5	537.1	541.2	542.5	546.6	543.9
50°	506.0	500.6	496.5	497.9	489.8	492.5	492.5	496.5	500.6	502.0	504.7
52.5°	458.7	457.3	456.0	449.2	447.8	446.5	447.8	449.2	454.6	458.7	460.0
55°	412.7	411.3	403.2	400.5	396.4	396.4	399.1	400.5	410.0	411.3	416.7
57.5°	370.7	366.7	357.2	355.8	355.8	355.8	351.8	357.2	359.9	366.7	366.7
60°	324.7	324.7	316.6	316.6	318.0	316.6	316.6	318.0	318.0	323.4	326.1
62.5°	288.2	286.8	286.8	284.1	282.8	284.1	282.8	282.8	284.1	288.2	292.2
65°	255.7	254.4	253.0	251.7	248.9	248.9	250.3	253.0	253.0	255.7	257.1
67.5°	224.6	224.6	221.9	221.9	220.5	219.2	220.5	219.2	224.6	224.6	225.9
70°	193.5	192.1	188.1	186.7	182.7	184.0	184.0	188.1	189.4	192.1	194.8
72.5°	155.6	155.6	152.9	150.2	151.5	148.8	148.8	150.2	150.2	154.2	155.6
75°	128.5	125.8	124.5	125.8	124.5	127.2	124.5	124.5	127.2	127.2	127.2
77.5°	105.5	105.5	104.2	104.2	105.5	104.2	105.5	105.5	105.5	104.2	105.5
80°	86.6	85.2	85.2	85.2	83.9	83.9	83.9	83.9	83.9	83.9	83.9
82.5°	64.9	64.9	63.6	64.9	64.9	63.6	64.9	63.6	63.6	64.9	64.9
85°	43.3	46.0	43.3	43.3	44.6	44.6	46.0	44.6	46.0	43.3	44.6
87.5°	23.0	24.4	24.4	23.0	23.0	24.4	24.4	24.4	25.7	23.0	24.4
90°	21.1	21.3	21.6	21.9	22.3	22.6	22.3	21.9	21.6	21.3	21.1
92.5°	34.0	33.8	33.5	33.2	32.8	32.5	32.8	33.2	33.5	33.8	34.0
95°	58.9	58.9	58.9	58.9	58.9	58.9	58.9	58.9	58.9	58.9	58.9
97.5°	85.3	85.2	85.1	84.9	84.8	84.6	84.8	84.9	85.1	85.2	85.3
100°	113.2	113.4	113.7	114.1	114.4	114.8	114.4	114.1	113.7	113.4	113.2
102.5°	146.5	146.4	146.2	146.1	145.9	145.7	145.9	146.1	146.2	146.4	146.5
105°	178.2	178.4	178.7	179.0	179.4	179.7	179.4	179.0	178.7	178.4	178.2
107.5°	215.2	215.1	214.9	214.8	214.6	214.4	214.6	214.8	214.9	215.1	215.2
110°	251.4	251.2	250.9	250.6	250.2	249.9	250.2	250.6	250.9	251.2	251.4

TEST NUMBER: P1032065

CATALOG NUMBER: S123RDIW-B1000D755UB30-4F0-XX-W2A-A1

CANDELA DISTRIBUTION (continued):

	247.5°	250°	255°	260°	265°	270°	275°	280°	285°	290°	292.5°
112.5°	287.6	287.6	287.6	287.6	287.6	287.6	287.6	287.6	287.6	287.6	287.6
115°	322.4	322.3	322.1	322.0	321.8	321.6	321.8	322.0	322.1	322.3	322.4
117.5°	358.6	358.3	357.8	357.3	356.8	356.3	356.8	357.3	357.8	358.3	358.6
120°	394.8	394.6	394.3	394.0	393.6	393.3	393.6	394.0	394.3	394.6	394.8
122.5°	431.1	430.8	430.3	429.8	429.3	428.8	429.3	429.8	430.3	430.8	431.1
125°	467.3	467.0	466.3	465.6	465.0	464.3	465.0	465.6	466.3	467.0	467.3
127.5°	502.8	502.5	501.8	501.1	500.5	499.8	500.5	501.1	501.8	502.5	502.8
130°	539.8	539.2	538.0	536.9	535.7	534.5	535.7	536.9	538.0	539.2	539.8
132.5°	574.5	574.1	573.3	572.4	571.6	570.8	571.6	572.4	573.3	574.1	574.5
135°	610.0	609.8	609.5	609.2	608.8	608.5	608.8	609.2	609.5	609.8	610.0
137.5°	644.0	643.7	643.2	642.7	642.2	641.7	642.2	642.7	643.2	643.7	644.0
140°	679.5	678.9	677.7	676.6	675.4	674.2	675.4	676.6	677.7	678.9	679.5
142.5°	711.2	710.8	709.9	709.1	708.2	707.4	708.2	709.1	709.9	710.8	711.2
145°	742.1	741.8	741.1	740.4	739.8	739.1	739.8	740.4	741.1	741.8	742.1
147.5°	772.3	771.8	770.8	769.8	768.8	767.8	768.8	769.8	770.8	771.8	772.3
150°	799.5	799.0	798.0	797.0	796.0	795.0	796.0	797.0	798.0	799.0	799.5
152.5°	825.2	824.8	823.9	823.1	822.2	821.4	822.2	823.1	823.9	824.8	825.2
155°	850.1	849.5	848.3	847.2	846.0	844.8	846.0	847.2	848.3	849.5	850.1
157.5°	871.2	870.7	869.7	868.7	867.7	866.7	867.7	868.7	869.7	870.7	871.2
160°	890.9	890.6	889.9	889.2	888.5	887.8	888.5	889.2	889.9	890.6	890.9
162.5°	909.0	908.4	907.2	906.1	904.9	903.7	904.9	906.1	907.2	908.4	909.0
165°	924.1	923.5	922.3	921.2	920.0	918.8	920.0	921.2	922.3	923.5	924.1
167.5°	936.9	936.4	935.4	934.4	933.4	932.4	933.4	934.4	935.4	936.4	936.9
170°	947.5	946.9	945.7	944.6	943.4	942.2	943.4	944.6	945.7	946.9	947.5
172.5°	955.0	954.4	953.3	952.1	951.0	949.8	951.0	952.1	953.3	954.4	955.0
175°	960.3	959.7	958.5	957.4	956.2	955.0	956.2	957.4	958.5	959.7	960.3
177.5°	963.3	962.7	961.6	960.4	959.3	958.1	959.3	960.4	961.6	962.7	963.3
180°	961.1	961.1	961.1	961.1	961.1	961.1	961.1	961.1	961.1	961.1	961.1

TEST NUMBER: P1032065

CATALOG NUMBER: S123RDIW-B1000D755UB30-4F0-XX-W2A-A1

CANDELA DISTRIBUTION (continued):

	295°	300°	305°	310°	315°	320°	325°	330°	335°	337.5°	340°
0°	1580.3	1580.3	1580.3	1580.3	1580.3	1580.3	1580.3	1580.3	1580.3	1580.3	1580.3
2.5°	1495.0	1500.5	1495.0	1484.2	1495.0	1501.8	1508.6	1519.4	1524.8	1524.8	1532.9
5°	1409.8	1420.6	1416.6	1413.9	1424.7	1431.5	1442.3	1455.8	1470.7	1480.2	1491.0
7.5°	1334.0	1340.8	1347.6	1347.6	1358.4	1373.3	1389.5	1405.8	1424.7	1438.2	1446.3
10°	1267.7	1273.2	1277.2	1282.6	1298.9	1315.1	1336.7	1357.0	1373.3	1388.2	1401.7
12.5°	1204.2	1212.3	1221.7	1225.8	1238.0	1258.3	1278.6	1302.9	1328.6	1343.5	1357.0
15°	1143.3	1147.3	1158.2	1170.3	1181.2	1202.8	1228.5	1254.2	1275.9	1298.9	1311.0
17.5°	1081.0	1082.4	1110.8	1104.0	1139.2	1159.5	1173.0	1197.4	1232.6	1251.5	1270.5
20°	1020.2	1033.7	1045.9	1052.6	1071.6	1094.6	1133.8	1152.7	1181.2	1198.7	1215.0
22.5°	972.8	993.1	993.1	1009.3	1018.8	1040.4	1068.9	1105.4	1136.5	1148.7	1171.7
25°	930.9	940.3	956.6	962.0	979.6	998.5	1017.4	1056.7	1090.5	1106.7	1123.0
27.5°	876.7	888.9	910.6	910.6	933.6	953.9	976.9	1002.6	1036.4	1059.4	1077.0
30°	834.8	847.0	856.4	871.3	880.8	899.7	940.3	959.3	989.0	1009.3	1031.0
32.5°	795.6	805.0	813.1	829.4	840.2	861.9	883.5	917.3	943.0	962.0	985.0
35°	752.3	761.7	772.6	784.7	801.0	821.3	841.6	870.0	895.7	913.3	932.2
37.5°	711.7	718.4	734.7	742.8	756.3	775.3	801.0	830.7	853.7	867.3	886.2
40°	672.4	677.8	690.0	704.9	714.4	729.3	756.3	782.0	810.4	826.7	841.6
42.5°	630.5	637.3	648.1	663.0	677.8	694.1	709.0	738.7	764.4	778.0	794.2
45°	594.0	598.0	606.1	621.0	635.9	648.1	671.1	698.1	722.5	733.3	750.9
47.5°	550.7	554.7	566.9	573.7	589.9	606.1	629.1	656.2	677.8	688.7	704.9
50°	506.0	510.1	518.2	533.1	543.9	561.5	581.8	604.8	631.8	646.7	656.2
52.5°	462.7	470.8	477.6	489.8	503.3	520.9	539.8	561.5	584.5	599.4	610.2
55°	419.4	426.2	434.3	441.1	457.3	473.5	495.2	515.5	535.8	549.3	561.5
57.5°	370.7	380.2	388.3	401.8	414.0	427.5	451.9	468.1	492.5	502.0	512.8
60°	328.8	338.2	345.0	355.8	366.7	384.2	400.5	420.8	441.1	453.2	466.8
62.5°	293.6	297.7	301.7	312.5	323.4	339.6	355.8	376.1	397.8	404.5	415.4
65°	258.4	262.5	269.2	278.7	286.8	296.3	313.9	330.1	350.4	361.2	365.3
67.5°	228.7	232.7	234.1	240.8	247.6	258.4	267.9	284.1	303.1	309.8	318.0
70°	194.8	201.6	202.9	208.4	211.1	217.8	228.7	240.8	255.7	267.9	274.7
72.5°	155.6	165.1	167.8	175.9	179.9	186.7	194.8	204.3	213.8	219.2	224.6
75°	127.2	129.9	131.2	138.0	144.8	154.2	158.3	163.7	171.8	178.6	184.0
77.5°	105.5	106.9	108.2	108.2	109.6	115.0	123.1	129.9	135.3	138.0	142.1
80°	85.2	83.9	83.9	85.2	85.2	85.2	87.9	97.4	100.1	106.9	105.5
82.5°	66.3	63.6	64.9	63.6	63.6	63.6	63.6	64.9	64.9	69.0	71.7
85°	43.3	44.6	43.3	43.3	41.9	43.3	41.9	41.9	40.6	40.6	39.2
87.5°	23.0	24.4	23.0	23.0	21.6	23.0	21.6	21.6	20.3	20.3	17.6
90°	20.8	20.1	19.4	18.8	18.1	15.9	13.7	11.6	9.4	8.3	7.5
92.5°	33.7	33.2	32.7	32.2	31.7	30.7	29.7	28.7	27.7	27.2	26.7
95°	58.6	57.9	57.2	56.6	55.9	54.5	53.2	51.8	50.5	49.8	49.2
97.5°	84.9	84.0	83.2	82.3	81.5	80.5	79.5	78.5	77.5	77.0	76.6
100°	113.0	112.5	112.0	111.5	111.0	110.2	109.3	108.5	107.6	107.2	106.7
102.5°	146.2	145.7	145.2	144.7	144.2	143.0	141.8	140.7	139.5	138.9	138.6
105°	178.2	178.2	178.2	178.2	178.2	176.7	175.2	173.7	172.2	171.4	171.2
107.5°	214.9	214.4	213.9	213.4	212.9	212.2	211.6	210.9	210.2	209.9	209.8
110°	251.1	250.4	249.7	249.1	248.4	248.1	247.7	247.4	247.1	246.9	246.7

TEST NUMBER: P1032065

CATALOG NUMBER: S123RDIW-B1000D755UB30-4F0-XX-W2A-A1

CANDELA DISTRIBUTION (continued):

	295°	300°	305°	310°	315°	320°	325°	330°	335°	337.5°	340°
112.5°	287.2	286.4	285.5	284.7	283.9	283.9	283.9	283.9	283.9	283.9	283.8
115°	322.3	322.1	322.0	321.8	321.6	321.9	322.3	322.6	322.9	323.1	322.9
117.5°	358.6	358.6	358.6	358.6	358.6	358.9	359.3	359.6	359.9	360.1	360.0
120°	394.9	395.1	395.2	395.4	395.6	396.4	397.3	398.1	399.0	399.4	398.9
122.5°	431.4	431.9	432.4	432.9	433.4	433.7	434.1	434.4	434.7	434.9	434.6
125°	467.6	468.3	469.0	469.6	470.3	470.7	471.0	471.4	471.7	471.9	471.6
127.5°	503.3	504.3	505.3	506.3	507.3	507.6	508.0	508.3	508.6	508.8	508.3
130°	540.1	540.8	541.5	542.1	542.8	543.3	543.8	544.3	544.8	545.1	544.4
132.5°	574.9	575.8	576.6	577.5	578.3	578.6	579.0	579.3	579.6	579.8	579.1
135°	610.3	611.0	611.7	612.3	613.0	613.2	613.4	613.5	613.7	613.8	613.3
137.5°	644.4	645.3	646.1	647.0	647.8	647.3	646.8	646.3	645.8	645.5	645.1
140°	679.6	679.7	679.9	680.0	680.2	680.0	679.9	679.7	679.6	679.5	679.1
142.5°	711.3	711.4	711.6	711.7	711.9	711.6	711.2	710.9	710.6	710.4	710.0
145°	742.2	742.4	742.5	742.7	742.9	742.4	741.9	741.4	740.9	740.6	740.4
147.5°	772.3	772.3	772.3	772.3	772.3	771.8	771.3	770.8	770.3	770.1	769.8
150°	799.5	799.5	799.5	799.5	799.5	799.2	798.8	798.5	798.2	798.0	797.8
152.5°	825.0	824.7	824.4	824.0	823.7	823.5	823.3	823.2	823.0	822.9	822.7
155°	849.8	849.1	848.4	847.8	847.1	846.9	846.7	846.6	846.4	846.3	846.3
157.5°	870.9	870.2	869.5	868.9	868.2	868.0	867.9	867.7	867.6	867.5	867.6
160°	890.5	889.6	888.8	887.9	887.1	887.1	887.1	887.1	887.1	887.1	887.3
162.5°	908.6	907.7	906.9	906.0	905.2	905.0	904.9	904.7	904.6	904.5	904.7
165°	923.6	922.6	921.6	920.6	919.6	919.6	919.6	919.6	919.6	919.6	919.8
167.5°	936.4	935.4	934.4	933.4	932.4	932.2	932.0	931.9	931.7	931.6	931.9
170°	946.9	945.7	944.6	943.4	942.2	942.2	942.2	942.2	942.2	942.2	942.5
172.5°	954.5	953.5	952.5	951.5	950.5	950.5	950.5	950.5	950.5	950.5	950.8
175°	959.8	958.8	957.8	956.8	955.8	955.8	955.8	955.8	955.8	955.8	956.1
177.5°	962.8	961.8	960.8	959.8	958.8	958.8	958.8	958.8	958.8	958.8	959.1
180°	961.1	961.1	961.1	961.1	961.1	961.1	961.1	961.1	961.1	961.1	961.1

TEST NUMBER: P1032065

CATALOG NUMBER: S123RDIW-B1000D755UB30-4F0-XX-W2A-A1

CANDELA DISTRIBUTION (continued):

	345°	350°	355°	360°
0°	1580.3	1580.3	1580.3	1580.3
2.5°	1539.7	1549.2	1568.1	1584.3
5°	1507.2	1522.1	1550.5	1578.9
7.5°	1468.0	1491.0	1527.5	1566.8
10°	1430.1	1459.9	1504.5	1550.5
12.5°	1392.2	1423.3	1470.7	1530.2
15°	1347.6	1380.0	1436.9	1508.6
17.5°	1308.3	1351.6	1403.0	1474.8
20°	1266.4	1298.9	1365.2	1440.9
22.5°	1213.6	1267.7	1330.0	1409.8
25°	1171.7	1219.0	1281.3	1371.9
27.5°	1120.3	1175.7	1251.5	1331.3
30°	1078.3	1124.3	1194.7	1290.7
32.5°	1029.6	1083.7	1156.8	1251.5
35°	986.3	1032.3	1101.3	1197.4
37.5°	934.9	985.0	1062.1	1147.3
40°	890.3	939.0	1012.0	1091.9
42.5°	836.1	887.6	960.6	1028.3
45°	792.8	840.2	898.4	960.6
47.5°	740.1	790.1	847.0	890.3
50°	692.7	738.7	783.4	819.9
52.5°	641.3	683.3	723.8	750.9
55°	594.0	626.4	658.9	677.8
57.5°	538.5	569.6	596.7	607.5
60°	489.8	515.5	533.1	545.3
62.5°	438.4	457.3	470.8	477.6
65°	388.3	401.8	408.6	415.4
67.5°	336.9	349.1	353.1	361.2
70°	282.8	296.3	299.0	303.1
72.5°	242.2	242.2	247.6	253.0
75°	193.5	196.2	198.9	198.9
77.5°	151.5	151.5	154.2	155.6
80°	110.9	112.3	112.3	110.9
82.5°	75.8	78.5	75.8	74.4
85°	41.9	47.4	44.6	44.6
87.5°	17.6	17.6	20.3	17.6
90°	5.8	4.1	2.5	0.8
92.5°	25.7	24.6	23.6	22.6
95°	48.0	46.9	45.7	44.5
97.5°	75.7	74.9	74.0	73.2
100°	105.7	104.7	103.7	102.7
102.5°	138.1	137.6	137.1	136.6
105°	170.9	170.6	170.2	169.9
107.5°	209.6	209.5	209.3	209.1
110°	246.4	246.1	245.7	245.4

TEST NUMBER: P1032065

CATALOG NUMBER: S123RDIW-B1000D755UB30-4F0-XX-W2A-A1

CANDELA DISTRIBUTION (continued):

	345°	350°	355°	360°
112.5°	283.6	283.5	283.3	283.1
115°	322.4	321.9	321.4	320.9
117.5°	359.9	359.7	359.6	359.4
120°	397.9	396.8	395.8	394.8
122.5°	433.9	433.2	432.5	431.8
125°	471.1	470.6	470.1	469.6
127.5°	507.3	506.3	505.3	504.3
130°	543.1	541.7	540.4	539.0
132.5°	577.8	576.5	575.1	573.8
135°	612.3	611.3	610.3	609.3
137.5°	644.2	643.4	642.5	641.7
140°	678.2	677.4	676.5	675.7
142.5°	709.2	708.3	707.5	706.7
145°	740.1	739.8	739.4	739.1
147.5°	769.1	768.4	767.7	767.0
150°	797.5	797.2	796.8	796.5
152.5°	822.2	821.7	821.2	820.7
155°	846.3	846.3	846.3	846.3
157.5°	867.7	867.9	868.0	868.2
160°	887.6	887.9	888.3	888.6
162.5°	905.2	905.7	906.2	906.7
165°	920.3	920.8	921.3	921.8
167.5°	932.6	933.3	934.0	934.7
170°	943.2	943.9	944.5	945.2
172.5°	951.5	952.2	952.8	953.5
175°	956.8	957.5	958.1	958.8
177.5°	959.8	960.5	961.1	961.8
180°	961.1	961.1	961.1	961.1

(END OF REPORT)