

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: NEO-RAY

Report Number: P1032100

Luminaire Tested: S123RDIW-B1165D1320UB27-4F0-XX-W2A-F

Issue Date: 5/7/2025

Test Information

Test Method: LM-79-2019
Report Number: P1032100
REPORT IS A COMBINATION OF REPORTS P993986 AND P1007351
Test Lab: INNOVATION CENTER
Issue Date: 5/7/2025
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: NEO-RAY
Catalog Number: S123RDIW-B1165D1320UB27-4F0-XX-W2A-F
Description: Define 3 Regressed Direct/Indirect Wall Mount with 2700K BioUP LEDs {m-DER=0.473}
{m-EER=0.52}
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 9588.0 lumens
Efficiency: N/A
Efficacy: 92.7 lumens/watt
Spacing Criteria (0/90/45): 1.21 / 1.07 / 1.22
Luminous Opening: Rectangular w/ Sides (W: 0.25' x L: 4' x H: 0.1')
CIE Type: General Diffuse

Input Watts (W): 103.4
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1032100

CATALOG NUMBER: S123RDIW-B1165D1320UB27-4F0-XX-W2A-F

Luminous Intensity Polar Plot



TEST NUMBER: P1032100

CATALOG NUMBER: S123RDIW-B1165D1320UB27-4F0-XX-W2A-F

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10
RCR																	
0	106	106	106	106	97	97	97	97	81	81	81	66	66	66	52	52	52
1	97	93	89	86	89	85	82	79	71	69	67	58	57	55	46	45	44
2	89	81	75	71	81	75	70	66	63	59	56	52	49	47	41	39	38
3	81	72	65	59	74	66	60	55	56	51	47	46	43	40	37	34	33
4	74	64	56	50	68	59	52	47	50	44	40	41	37	34	33	30	28
5	68	57	49	43	62	53	46	40	44	39	35	37	33	30	30	27	25
6	63	51	43	37	58	47	40	35	40	35	31	33	29	26	27	24	22
7	58	46	38	33	53	43	36	31	36	31	27	30	26	23	25	22	20
8	54	42	34	29	49	39	32	27	33	28	24	28	24	21	23	20	18
9	50	38	31	26	46	36	29	25	30	25	22	26	22	19	21	18	16
10	47	35	28	23	43	33	26	22	28	23	20	24	20	17	20	17	15

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	20730	20730	20730
5°	20764	19997	19943
10°	20601	19245	18866
15°	20334	18316	17686
20°	19983	17305	16368
25°	19621	16255	15119
30°	19156	15137	13642
35°	18679	14040	12298
40°	18230	12848	10813
45°	17654	11683	9477
50°	17017	10438	8094
55°	16358	9106	6828
60°	15727	7740	5542
65°	14915	6338	4325
70°	13891	4792	3092
75°	12420	3246	2449
80°	10597	2255	1718
85°	7953	1217	900

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 17654 cd/sqm

TEST NUMBER: P1032100

CATALOG NUMBER: S123RDIW-B1165D1320UB27-4F0-XX-W2A-F

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	181.0	1.9
10°-20°	503.7	5.3
20°-30°	725.2	7.6
30°-40°	816.6	8.5
40°-50°	781.2	8.1
50°-60°	639.4	6.7
60°-70°	431.1	4.5
70°-80°	216.2	2.3
80°-90°	60.0	0.6
90°-100°	60.6	0.6
100°-110°	292.7	3.1
110°-120°	717.2	7.5
120°-130°	910.5	9.5
130°-140°	972.7	10.1
140°-150°	909.6	9.5
150°-160°	733.7	7.7
160°-170°	473.5	4.9
170°-180°	163.2	1.7
0°-30°	1409.9	14.7
0°-40°	2226.5	23.2
0°-60°	3647.1	38.0
0°-90°	4354.4	45.4
90°-120°	1070.5	11.2
90°-150°	3863.3	40.3
90°-180°	5234.0	54.6
0°-180°	9588.0	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	1926	1926	1926	1926	1926	
5°	1926	1918	1899	1913	1910	183
15°	1837	1820	1776	1768	1757	518
25°	1671	1632	1560	1528	1510	769
35°	1446	1390	1293	1226	1198	905
45°	1189	1118	998	909	872	917
55°	903	826	694	603	572	810
65°	617	531	409	333	316	611
75°	326	252	166	150	147	348
85°	83	48	44	41	41	91
90°	1	14	31	36	38	10
95°	78	26	40	48	48	93
105°	380	394	279	54	56	403
115°	713	721	732	745	750	704
125°	1005	1015	1020	1023	1025	898
135°	1251	1259	1264	1268	1264	963
145°	1444	1453	1455	1458	1458	904
155°	1590	1588	1589	1596	1588	733
165°	1677	1673	1672	1682	1673	474
175°	1717	1710	1712	1720	1710	163
180°	1717	1717	1717	1717	1717	

TEST NUMBER: P1032100

CATALOG NUMBER: S123RDIW-B1165D1320UB27-4F0-XX-W2A-F

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	1925.9	1925.9	1925.9	1925.9	1925.9
2.5°	1933.7	1927.5	1908.7	1925.9	1922.8
5°	1925.9	1918.1	1899.4	1913.4	1910.3
7.5°	1911.9	1904.1	1880.6	1890.0	1885.3
10°	1893.1	1882.2	1854.1	1855.6	1847.8
12.5°	1866.6	1854.1	1818.1	1816.6	1807.2
15°	1836.9	1819.7	1776.0	1768.2	1757.2
17.5°	1801.0	1782.2	1727.6	1711.9	1696.3
20°	1760.4	1735.4	1676.0	1655.7	1637.0
22.5°	1715.1	1685.4	1621.3	1594.8	1577.6
25°	1671.3	1632.3	1560.4	1527.6	1510.4
27.5°	1618.2	1576.0	1497.9	1454.2	1427.7
30°	1563.5	1516.7	1429.2	1376.1	1351.1
32.5°	1508.9	1454.2	1360.5	1301.1	1274.6
35°	1446.4	1390.2	1293.3	1226.2	1198.0
37.5°	1383.9	1323.0	1221.5	1146.5	1112.1
40°	1324.6	1255.8	1144.9	1063.7	1027.8
42.5°	1257.4	1188.7	1073.1	982.5	951.2
45°	1188.7	1118.4	998.1	909.1	871.6
47.5°	1121.5	1043.4	924.7	827.8	795.0
50°	1046.5	973.1	846.6	749.8	713.8
52.5°	979.4	898.1	773.2	671.7	640.4
55°	902.8	826.3	693.5	602.9	571.7
57.5°	834.1	751.3	617.0	531.1	504.5
60°	762.2	676.3	546.7	462.3	435.8
62.5°	690.4	604.5	474.8	396.7	368.6
65°	617.0	531.1	409.2	332.7	315.5
67.5°	543.6	456.1	337.4	279.6	260.9
70°	471.7	387.4	278.0	223.4	206.2
72.5°	399.9	317.1	220.2	178.1	173.4
75°	326.5	251.5	165.6	150.0	146.8
77.5°	259.3	190.6	129.6	120.3	117.1
80°	195.2	131.2	98.4	93.7	90.6
82.5°	134.3	81.2	70.3	65.6	65.6
85°	82.8	48.4	43.7	40.6	40.6
87.5°	37.5	20.3	20.3	18.7	17.2
90°	1.3	14.0	30.6	35.7	38.3
92.5°	29.3	21.7	33.2	42.1	43.4
95°	77.8	25.5	39.5	48.5	48.5
97.5°	141.6	105.9	40.8	51.0	52.3
100°	215.5	241.1	42.1	52.3	53.6
102.5°	299.7	316.3	94.4	52.3	54.8
105°	380.1	394.1	279.3	53.6	56.1
107.5°	465.5	477.0	496.1	299.7	132.6
110°	551.0	561.2	575.2	533.1	350.7



TEST NUMBER: P1032100

CATALOG NUMBER: S123RDIW-B1165D1320UB27-4F0-XX-W2A-F

CANDELA DISTRIBUTION (continued):

	0°	22.5°	45°	67.5°	90°
112.5°	632.6	641.5	655.6	667.0	664.5
115°	713.0	720.6	732.1	744.8	749.9
117.5°	792.0	801.0	807.3	817.5	818.8
120°	864.7	876.2	880.0	890.2	890.2
122.5°	938.7	947.6	952.7	959.1	960.4
125°	1005.0	1015.2	1020.3	1022.9	1025.4
127.5°	1071.4	1081.6	1087.9	1091.8	1089.2
130°	1132.6	1142.8	1147.9	1153.0	1150.4
132.5°	1191.2	1201.5	1205.3	1210.4	1206.6
135°	1251.2	1258.8	1263.9	1267.8	1263.9
137.5°	1302.2	1312.4	1315.0	1321.3	1318.8
140°	1353.2	1360.9	1364.7	1369.8	1367.3
142.5°	1400.4	1408.1	1411.9	1415.7	1411.9
145°	1443.8	1452.7	1455.3	1457.8	1457.8
147.5°	1485.9	1492.2	1494.8	1497.3	1491.0
150°	1524.1	1528.0	1530.5	1533.1	1529.2
152.5°	1558.6	1559.8	1561.1	1566.2	1559.8
155°	1590.5	1587.9	1589.2	1595.6	1587.9
157.5°	1616.0	1616.0	1614.7	1622.3	1612.1
160°	1638.9	1637.6	1636.4	1644.0	1635.1
162.5°	1660.6	1656.8	1655.5	1664.4	1656.8
165°	1677.2	1673.4	1672.1	1682.3	1673.4
167.5°	1691.2	1686.1	1686.1	1696.3	1686.1
170°	1702.7	1697.6	1697.6	1707.8	1697.6
172.5°	1710.3	1704.0	1705.2	1715.4	1704.0
175°	1716.7	1710.3	1711.6	1720.5	1710.3
177.5°	1719.3	1712.9	1714.2	1724.4	1711.6
180°	1716.7	1716.7	1716.7	1716.7	1716.7

(END OF REPORT)