

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: NEO-RAY

Report Number: P1032238

Luminaire Tested: S123RDIW-B340D460UB30-4F0-XX-W2A-F

Issue Date: 5/7/2025

Test Information

Test Method: LM-79-2019
Report Number: P1032238
REPORT IS A COMBINATION OF REPORTS P994314 AND P1007351
Test Lab: INNOVATION CENTER
Issue Date: 5/7/2025
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: NEO-RAY
Catalog Number: S123RDIW-B340D460UB30-4F0-XX-W2A-F
Description: Define 3 Regressed Direct/Indirect Wall Mount with 3000K BioUP LEDs {m-DER=0.589}
{m-EER=0.647}
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 3128.0 lumens
Efficiency: N/A
Efficacy: 119.4 lumens/watt
Spacing Criteria (0/90/45): 1.21 / 1.07 / 1.22
Luminous Opening: Rectangular w/ Sides (W: 0.25' x L: 4' x H: 0.1')
CIE Type: General Diffuse

Input Watts (W): 26.2
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1032238

CATALOG NUMBER: S123RDIW-B340D460UB30-4F0-XX-W2A-F

Luminous Intensity Polar Plot



TEST NUMBER: P1032238

CATALOG NUMBER: S123RDIW-B340D460UB30-4F0-XX-W2A-F

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10
RCR																	
0	105	105	105	105	95	95	95	95	78	78	78	62	62	62	47	47	47
1	96	92	88	85	87	84	81	78	69	67	65	55	53	52	42	41	40
2	88	80	74	70	80	73	68	64	60	57	54	49	46	44	37	36	34
3	80	71	64	58	73	65	59	54	54	49	45	43	40	37	33	31	30
4	73	63	55	49	66	58	51	46	48	43	39	39	35	32	30	28	26
5	67	56	48	42	61	51	45	39	43	38	34	35	31	28	27	25	23
6	62	50	42	37	56	46	39	34	39	33	29	31	28	25	25	22	20
7	57	45	38	32	52	42	35	30	35	30	26	29	25	22	23	20	18
8	53	41	34	28	48	38	31	27	32	27	23	26	22	19	21	18	16
9	49	38	30	25	45	35	28	24	29	24	21	24	20	18	19	16	14
10	46	34	27	23	42	32	26	21	27	22	19	22	19	16	18	15	13

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	6018	6018	6018
5°	6028	5804	5789
10°	5980	5586	5477
15°	5902	5316	5134
20°	5801	5023	4752
25°	5695	4719	4388
30°	5561	4394	3960
35°	5423	4075	3570
40°	5292	3729	3138
45°	5124	3391	2751
50°	4940	3029	2350
55°	4749	2643	1981
60°	4566	2247	1609
65°	4329	1840	1256
70°	4032	1391	897
75°	3606	943	711
80°	3078	656	499
85°	2305	354	262

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 5124 cd/sqm

TEST NUMBER: P1032238

CATALOG NUMBER: S123RDIW-B340D460UB30-4F0-XX-W2A-F

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	52.6	1.7
10°-20°	146.2	4.7
20°-30°	210.5	6.7
30°-40°	237.1	7.6
40°-50°	226.7	7.2
50°-60°	185.6	5.9
60°-70°	125.1	4.0
70°-80°	62.8	2.0
80°-90°	17.6	0.6
90°-100°	21.6	0.7
100°-110°	104.2	3.3
110°-120°	255.4	8.2
120°-130°	324.3	10.4
130°-140°	346.4	11.1
140°-150°	323.9	10.4
150°-160°	261.3	8.4
160°-170°	168.6	5.4
170°-180°	58.1	1.9
0°-30°	409.2	13.1
0°-40°	646.3	20.7
0°-60°	1058.7	33.8
0°-90°	1264.2	40.4
90°-120°	381.2	12.2
90°-150°	1375.8	44.0
90°-180°	1864.0	59.6
0°-180°	3128.0	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	559	559	559	559	559	
5°	559	557	551	555	554	53
15°	533	528	516	513	510	150
25°	485	474	453	443	438	223
35°	420	404	375	356	348	263
45°	345	325	290	264	253	266
55°	262	240	201	175	166	235
65°	179	154	119	97	92	177
75°	95	73	48	44	43	101
85°	24	14	13	12	12	26
90°	0	5	11	13	14	3
95°	28	9	14	17	17	33
105°	135	140	100	19	20	144
115°	254	257	261	265	267	251
125°	358	362	363	364	365	320
135°	446	448	450	452	450	343
145°	514	517	518	519	519	322
155°	566	566	566	568	566	261
165°	597	596	596	599	596	169
175°	611	609	610	613	609	58
180°	611	611	611	611	611	

TEST NUMBER: P1032238

CATALOG NUMBER: S123RDIW-B340D460UB30-4F0-XX-W2A-F

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	559.1	559.1	559.1	559.1	559.1
2.5°	561.3	559.5	554.1	559.1	558.1
5°	559.1	556.8	551.3	555.4	554.5
7.5°	555.0	552.7	545.9	548.6	547.3
10°	549.5	546.4	538.2	538.6	536.4
12.5°	541.8	538.2	527.8	527.3	524.6
15°	533.2	528.2	515.5	513.3	510.1
17.5°	522.8	517.3	501.5	496.9	492.4
20°	511.0	503.7	486.5	480.6	475.2
22.5°	497.8	489.2	470.6	462.9	457.9
25°	485.1	473.8	453.0	443.4	438.4
27.5°	469.7	457.5	434.8	422.1	414.4
30°	453.9	440.3	414.9	399.5	392.2
32.5°	438.0	422.1	394.9	377.7	370.0
35°	419.9	403.5	375.4	355.9	347.8
37.5°	401.7	384.0	354.6	332.8	322.8
40°	384.5	364.5	332.3	308.8	298.3
42.5°	365.0	345.0	311.5	285.2	276.1
45°	345.0	324.6	289.7	263.9	253.0
47.5°	325.5	302.9	268.4	240.3	230.8
50°	303.8	282.5	245.7	217.6	207.2
52.5°	284.3	260.7	224.4	195.0	185.9
55°	262.1	239.9	201.3	175.0	165.9
57.5°	242.1	218.1	179.1	154.2	146.5
60°	221.3	196.3	158.7	134.2	126.5
62.5°	200.4	175.5	137.8	115.2	107.0
65°	179.1	154.2	118.8	96.6	91.6
67.5°	157.8	132.4	97.9	81.2	75.7
70°	136.9	112.4	80.7	64.8	59.8
72.5°	116.1	92.0	63.9	51.7	50.3
75°	94.8	73.0	48.1	43.5	42.6
77.5°	75.3	55.3	37.6	34.9	34.0
80°	56.7	38.1	28.6	27.2	26.3
82.5°	39.0	23.6	20.4	19.0	19.0
85°	24.0	14.1	12.7	11.8	11.8
87.5°	10.9	5.9	5.9	5.4	5.0
90°	0.5	5.0	10.9	12.7	13.6
92.5°	10.4	7.7	11.8	15.0	15.4
95°	27.7	9.1	14.1	17.3	17.3
97.5°	50.4	37.7	14.5	18.2	18.6
100°	76.8	85.8	15.0	18.6	19.1
102.5°	106.7	112.6	33.6	18.6	19.5
105°	135.4	140.3	99.5	19.1	20.0
107.5°	165.8	169.9	176.7	106.7	47.2
110°	196.2	199.8	204.8	189.9	124.9

TEST NUMBER: P1032238

CATALOG NUMBER: S123RDIW-B340D460UB30-4F0-XX-W2A-F

CANDELA DISTRIBUTION (continued):

	0°	22.5°	45°	67.5°	90°
112.5°	225.3	228.5	233.5	237.5	236.6
115°	253.9	256.6	260.7	265.3	267.1
117.5°	282.1	285.2	287.5	291.1	291.6
120°	308.0	312.0	313.4	317.0	317.0
122.5°	334.3	337.5	339.3	341.6	342.0
125°	357.9	361.5	363.4	364.3	365.2
127.5°	381.5	385.2	387.4	388.8	387.9
130°	403.3	407.0	408.8	410.6	409.7
132.5°	424.2	427.9	429.2	431.0	429.7
135°	445.6	448.3	450.1	451.5	450.1
137.5°	463.7	467.4	468.3	470.6	469.6
140°	481.9	484.6	486.0	487.8	486.9
142.5°	498.7	501.4	502.8	504.2	502.8
145°	514.2	517.3	518.2	519.2	519.2
147.5°	529.1	531.4	532.3	533.2	531.0
150°	542.8	544.1	545.0	546.0	544.6
152.5°	555.0	555.5	555.9	557.8	555.5
155°	566.4	565.5	565.9	568.2	565.5
157.5°	575.5	575.5	575.0	577.7	574.1
160°	583.7	583.2	582.7	585.5	582.3
162.5°	591.4	590.0	589.6	592.7	590.0
165°	597.3	595.9	595.5	599.1	595.9
167.5°	602.3	600.5	600.5	604.1	600.5
170°	606.4	604.5	604.5	608.2	604.5
172.5°	609.1	606.8	607.3	610.9	606.8
175°	611.4	609.1	609.5	612.7	609.1
177.5°	612.3	610.0	610.5	614.1	609.5
180°	611.4	611.4	611.4	611.4	611.4

(END OF REPORT)