

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: NEO-RAY

Report Number: P1032271

Luminaire Tested: S123RDIW-B340D755UB50-4F0-XX-W2A-F1

Issue Date: 5/6/2025

Test Information

Test Method: LM-79-2019
Report Number: P1032271
REPORT IS A COMBINATION OF REPORTS P994377 AND P1007351
Test Lab: INNOVATION CENTER
Issue Date: 5/6/2025
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: NEO-RAY
Catalog Number: S123RDIW-B340D755UB50-4F0-XX-W2A-F1
Description: Define 3 Regressed Direct/Indirect Wall Mount with 5000K BioUP LEDs {m-DER=1.015}
{m-EER=1.115}
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 3778.0 lumens
Efficiency: N/A
Efficacy: 104.4 lumens/watt
Spacing Criteria (0/90/45): 1.21 / 1.07 / 1.22
Luminous Opening: Rectangular w/ Sides (W: 0.25' x L: 4' x H: 0.1')
CIE Type: Semi-Indirect

Input Watts (W): 36.2
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1032271

CATALOG NUMBER: S123RDIW-B340D755UB50-4F0-XX-W2A-F1

Luminous Intensity Polar Plot



TEST NUMBER: P1032271

CATALOG NUMBER: S123RDIW-B340D755UB50-4F0-XX-W2A-F1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10
RCR																	
0	103	103	103	103	93	93	93	93	73	73	73	56	56	56	40	40	40
1	94	90	86	83	85	81	78	75	65	62	61	49	48	47	35	35	34
2	86	79	73	68	77	71	66	62	57	53	50	44	41	39	31	30	29
3	78	69	62	57	70	63	57	52	50	46	43	39	36	34	28	26	25
4	72	61	54	48	64	56	49	44	45	40	36	35	31	29	25	23	22
5	66	55	47	41	59	50	43	38	40	35	31	31	28	25	23	21	19
6	61	49	41	36	54	44	38	33	36	31	27	28	25	22	21	18	17
7	56	44	36	31	50	40	33	29	33	28	24	26	22	19	19	17	15
8	52	40	33	27	47	36	30	25	30	25	21	23	20	17	17	15	13
9	48	36	29	24	43	33	27	23	27	22	19	21	18	15	16	14	12
10	45	33	26	22	41	30	24	20	25	20	17	20	16	14	15	13	11

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	5789	5789	5789
5°	5798	5584	5569
10°	5752	5374	5268
15°	5678	5114	4939
20°	5580	4832	4571
25°	5479	4539	4222
30°	5349	4227	3810
35°	5216	3921	3434
40°	5091	3588	3019
45°	4929	3262	2647
50°	4752	2915	2260
55°	4568	2543	1906
60°	4393	2162	1548
65°	4165	1770	1208
70°	3878	1338	864
75°	3469	906	684
80°	2959	630	480
85°	2219	340	250

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 4929 cd/sqm

TEST NUMBER: P1032271

CATALOG NUMBER: S123RDIW-B340D755UB50-4F0-XX-W2A-F1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	50.6	1.3
10°-20°	140.6	3.7
20°-30°	202.5	5.4
30°-40°	228.0	6.0
40°-50°	218.1	5.8
50°-60°	178.6	4.7
60°-70°	120.4	3.2
70°-80°	60.4	1.6
80°-90°	17.7	0.5
90°-100°	59.5	1.6
100°-110°	180.1	4.8
110°-120°	306.6	8.1
120°-130°	403.3	10.7
130°-140°	453.4	12.0
140°-150°	445.7	11.8
150°-160°	375.2	9.9
160°-170°	249.8	6.6
170°-180°	87.5	2.3
0°-30°	393.7	10.4
0°-40°	621.7	16.5
0°-60°	1018.4	27.0
0°-90°	1217.0	32.2
90°-120°	546.2	14.5
90°-150°	1848.5	48.9
90°-180°	2561.0	67.8
0°-180°	3778.0	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	538	538	538	538	538	
5°	538	536	530	534	533	51
15°	513	508	496	494	491	145
25°	467	456	436	427	422	215
35°	404	388	361	342	334	253
45°	332	312	279	254	243	256
55°	252	231	194	168	160	226
65°	172	148	114	93	88	171
75°	91	70	46	42	41	97
85°	23	14	12	11	11	25
90°	1	8	17	20	22	5
95°	43	48	54	57	57	47
105°	163	165	171	171	173	175
115°	309	311	309	310	309	305
125°	452	454	452	449	446	403
135°	586	590	590	587	585	451
145°	711	712	714	714	711	444
155°	814	814	815	818	812	375
165°	886	884	884	889	884	250
175°	922	919	919	924	918	88
180°	924	924	924	924	924	

TEST NUMBER: P1032271

CATALOG NUMBER: S123RDIW-B340D755UB50-4F0-XX-W2A-F1

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	537.8	537.8	537.8	537.8	537.8
2.5°	540.0	538.2	533.0	537.8	536.9
5°	537.8	535.6	530.4	534.3	533.4
7.5°	533.9	531.7	525.2	527.8	526.5
10°	528.6	525.6	517.7	518.2	516.0
12.5°	521.2	517.7	507.7	507.3	504.7
15°	512.9	508.1	495.9	493.8	490.7
17.5°	502.9	497.7	482.4	478.1	473.7
20°	491.6	484.6	468.0	462.3	457.1
22.5°	478.9	470.6	452.8	445.3	440.5
25°	466.7	455.8	435.7	426.6	421.8
27.5°	451.9	440.1	418.3	406.1	398.7
30°	436.6	423.5	399.1	384.3	377.3
32.5°	421.3	406.1	379.9	363.3	355.9
35°	403.9	388.2	361.2	342.4	334.5
37.5°	386.5	369.4	341.1	320.2	310.6
40°	369.9	350.7	319.7	297.0	287.0
42.5°	351.1	331.9	299.7	274.4	265.6
45°	331.9	312.3	278.7	253.9	243.4
47.5°	313.2	291.4	258.2	231.2	222.0
50°	292.2	271.7	236.4	209.4	199.3
52.5°	273.5	250.8	215.9	187.6	178.8
55°	252.1	230.7	193.7	168.4	159.6
57.5°	232.9	209.8	172.3	148.3	140.9
60°	212.9	188.9	152.7	129.1	121.7
62.5°	192.8	168.8	132.6	110.8	102.9
65°	172.3	148.3	114.3	92.9	88.1
67.5°	151.8	127.4	94.2	78.1	72.8
70°	131.7	108.2	77.6	62.4	57.6
72.5°	111.7	88.5	61.5	49.7	48.4
75°	91.2	70.2	46.2	41.9	41.0
77.5°	72.4	53.2	36.2	33.6	32.7
80°	54.5	36.6	27.5	26.2	25.3
82.5°	37.5	22.7	19.6	18.3	18.3
85°	23.1	13.5	12.2	11.3	11.3
87.5°	10.5	5.7	5.7	5.2	4.8
90°	0.7	8.0	17.4	20.3	21.8
92.5°	21.8	26.1	30.5	32.7	31.2
95°	42.8	47.9	53.7	56.6	56.6
97.5°	70.4	74.1	78.4	82.0	81.3
100°	98.7	103.1	106.7	108.9	110.4
102.5°	131.4	133.6	138.7	140.9	140.1
105°	163.4	164.8	171.4	171.4	172.8
107.5°	201.1	201.8	204.8	206.9	206.2
110°	236.0	237.4	238.9	241.8	240.3

TEST NUMBER: P1032271

CATALOG NUMBER: S123RDIW-B340D755UB50-4F0-XX-W2A-F1

CANDELA DISTRIBUTION (continued):

	0°	22.5°	45°	67.5°	90°
112.5°	272.3	273.0	273.0	276.6	276.6
115°	308.6	310.8	309.3	310.0	309.3
117.5°	345.6	346.3	344.9	344.9	342.7
120°	379.7	384.1	380.5	379.7	378.3
122.5°	415.3	418.2	416.8	414.6	412.4
125°	451.6	453.8	452.3	449.4	446.5
127.5°	485.0	489.4	487.9	483.6	480.7
130°	518.4	524.2	522.0	519.1	514.1
132.5°	551.8	557.6	556.2	552.5	548.9
135°	585.9	590.3	589.6	586.7	585.2
137.5°	617.2	620.8	623.0	619.3	617.2
140°	649.8	653.5	654.2	653.5	648.4
142.5°	679.6	683.2	684.7	684.0	680.3
145°	710.8	712.3	714.5	713.7	710.8
147.5°	737.7	740.6	742.8	742.8	738.4
150°	766.0	767.5	768.9	768.9	764.6
152.5°	789.2	791.4	792.1	793.6	790.0
155°	813.9	813.9	814.7	817.6	812.5
157.5°	835.0	834.3	835.0	837.9	833.5
160°	854.6	853.1	853.1	856.8	853.9
162.5°	872.0	869.8	870.6	874.2	869.1
165°	886.5	884.4	884.4	888.7	883.6
167.5°	898.9	896.0	896.7	901.1	896.7
170°	909.0	906.1	906.1	911.2	906.1
172.5°	917.0	914.1	914.1	918.5	913.4
175°	922.1	919.2	919.2	923.6	918.5
177.5°	925.0	922.1	922.1	926.5	921.4
180°	924.3	924.3	924.3	924.3	924.3

(END OF REPORT)