

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: NEO-RAY

Report Number: P1032463

Luminaire Tested: S123RDIW-B775D755UB50-4F0-XX-W2A-F1

Issue Date: 5/6/2025

Test Information

Test Method: LM-79-2019
Report Number: P1032463
REPORT IS A COMBINATION OF REPORTS P994817 AND P1007351
Test Lab: INNOVATION CENTER
Issue Date: 5/6/2025
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: NEO-RAY
Catalog Number: S123RDIW-B775D755UB50-4F0-XX-W2A-F1
Description: Define 3 Regressed Direct/Indirect Wall Mount with 5000K BioUP LEDs {m-DER=1.015}
{m-EER=1.115}
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 5382.0 lumens
Efficiency: N/A
Efficacy: 91.1 lumens/watt
Spacing Criteria (0/90/45): 1.21 / 1.07 / 1.22
Luminous Opening: Rectangular w/ Sides (W: 0.25' x L: 4' x H: 0.1')
CIE Type: General Diffuse

Input Watts (W): 59.1
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1032463

CATALOG NUMBER: S123RDIW-B775D755UB50-4F0-XX-W2A-F1

Luminous Intensity Polar Plot



TEST NUMBER: P1032463

CATALOG NUMBER: S123RDIW-B775D755UB50-4F0-XX-W2A-F1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10
RCR																	
0	108	108	108	108	100	100	100	100	85	85	85	71	71	71	58	58	58
1	99	94	91	87	91	88	84	81	75	72	70	63	61	60	52	51	50
2	90	83	77	72	83	77	72	67	66	62	59	56	53	50	46	44	43
3	82	73	66	60	76	68	62	57	58	54	50	50	46	43	41	39	37
4	76	65	57	51	70	61	54	48	52	47	43	44	40	37	37	34	32
5	69	58	50	44	64	54	47	42	47	41	37	40	36	32	34	30	28
6	64	52	44	38	59	49	42	36	42	37	32	36	32	29	31	27	25
7	59	47	39	34	55	44	37	32	38	33	29	33	29	25	28	25	22
8	55	43	35	30	51	40	33	29	35	30	26	30	26	23	26	22	20
9	51	39	32	27	48	37	30	26	32	27	23	28	24	20	24	20	18
10	48	36	29	24	45	34	27	23	30	24	21	26	22	19	22	19	16

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	13431	13431	13431
5°	13453	12956	12921
10°	13347	12468	12223
15°	13174	11866	11459
20°	12946	11212	10605
25°	12712	10531	9795
30°	12412	9808	8839
35°	12102	9096	7968
40°	11811	8324	7005
45°	11437	7570	6140
50°	11025	6763	5245
55°	10598	5900	4424
60°	10191	5015	3590
65°	9662	4106	2802
70°	9000	3105	2003
75°	8045	2103	1587
80°	6868	1462	1113
85°	5149	788	583

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 11437 cd/sqm

TEST NUMBER: P1032463

CATALOG NUMBER: S123RDIW-B775D755UB50-4F0-XX-W2A-F1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	117.3	2.2
10°-20°	326.3	6.1
20°-30°	469.8	8.7
30°-40°	529.1	9.8
40°-50°	506.1	9.4
50°-60°	414.3	7.7
60°-70°	279.3	5.2
70°-80°	140.1	2.6
80°-90°	38.6	0.7
90°-100°	59.5	1.1
100°-110°	180.1	3.3
110°-120°	306.6	5.7
120°-130°	403.3	7.5
130°-140°	453.4	8.4
140°-150°	445.7	8.3
150°-160°	375.2	7.0
160°-170°	249.8	4.6
170°-180°	87.5	1.6
0°-30°	913.4	17.0
0°-40°	1442.6	26.8
0°-60°	2363.0	43.9
0°-90°	2820.9	52.4
90°-120°	546.2	10.1
90°-150°	1848.5	34.3
90°-180°	2561.0	47.6
0°-180°	5382.0	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	1248	1248	1248	1248	1248	
5°	1248	1243	1231	1240	1238	118
15°	1190	1179	1151	1146	1138	335
25°	1083	1058	1011	990	979	498
35°	937	901	838	794	776	587
45°	770	725	647	589	565	594
55°	585	535	449	391	370	525
65°	400	344	265	216	204	396
75°	212	163	107	97	95	225
85°	54	31	28	26	26	59
90°	1	8	17	20	22	7
95°	43	48	54	57	57	47
105°	163	165	171	171	173	175
115°	309	311	309	310	309	305
125°	452	454	452	449	446	403
135°	586	590	590	587	585	451
145°	711	712	714	714	711	444
155°	814	814	815	818	812	375
165°	886	884	884	889	884	250
175°	922	919	919	924	918	88
180°	924	924	924	924	924	

TEST NUMBER: P1032463

CATALOG NUMBER: S123RDIW-B775D755UB50-4F0-XX-W2A-F1

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	1247.8	1247.8	1247.8	1247.8	1247.8
2.5°	1252.9	1248.8	1236.7	1247.8	1245.8
5°	1247.8	1242.7	1230.6	1239.7	1237.7
7.5°	1238.7	1233.6	1218.5	1224.5	1221.5
10°	1226.5	1219.5	1201.2	1202.3	1197.2
12.5°	1209.3	1201.2	1178.0	1177.0	1170.9
15°	1190.1	1179.0	1150.6	1145.6	1138.5
17.5°	1166.8	1154.7	1119.3	1109.2	1099.0
20°	1140.5	1124.3	1085.9	1072.7	1060.6
22.5°	1111.2	1092.0	1050.5	1033.3	1022.1
25°	1082.8	1057.5	1011.0	989.7	978.6
27.5°	1048.4	1021.1	970.5	942.2	925.0
30°	1013.0	982.7	926.0	891.6	875.4
32.5°	977.6	942.2	881.5	843.0	825.8
35°	937.1	900.7	837.9	794.4	776.2
37.5°	896.6	857.2	791.4	742.8	720.5
40°	858.2	813.7	741.8	689.2	665.9
42.5°	814.7	770.1	695.2	636.5	616.3
45°	770.1	724.6	646.7	589.0	564.7
47.5°	726.6	676.0	599.1	536.4	515.1
50°	678.0	630.5	548.5	485.8	462.5
52.5°	634.5	581.9	500.9	435.2	414.9
55°	584.9	535.3	449.3	390.6	370.4
57.5°	540.4	486.8	399.7	344.1	326.9
60°	493.9	438.2	354.2	299.6	282.3
62.5°	447.3	391.6	307.6	257.0	238.8
65°	399.7	344.1	265.1	215.6	204.4
67.5°	352.2	295.5	218.6	181.1	169.0
70°	305.6	251.0	180.1	144.7	133.6
72.5°	259.1	205.4	142.7	115.4	112.3
75°	211.5	162.9	107.3	97.2	95.1
77.5°	168.0	123.5	84.0	77.9	75.9
80°	126.5	85.0	63.8	60.7	58.7
82.5°	87.0	52.6	45.5	42.5	42.5
85°	53.6	31.4	28.3	26.3	26.3
87.5°	24.3	13.2	13.2	12.1	11.1
90°	0.7	8.0	17.4	20.3	21.8
92.5°	21.8	26.1	30.5	32.7	31.2
95°	42.8	47.9	53.7	56.6	56.6
97.5°	70.4	74.1	78.4	82.0	81.3
100°	98.7	103.1	106.7	108.9	110.4
102.5°	131.4	133.6	138.7	140.9	140.1
105°	163.4	164.8	171.4	171.4	172.8
107.5°	201.1	201.8	204.8	206.9	206.2
110°	236.0	237.4	238.9	241.8	240.3



TEST NUMBER: P1032463

CATALOG NUMBER: S123RDIW-B775D755UB50-4F0-XX-W2A-F1

CANDELA DISTRIBUTION (continued):

	0°	22.5°	45°	67.5°	90°
112.5°	272.3	273.0	273.0	276.6	276.6
115°	308.6	310.8	309.3	310.0	309.3
117.5°	345.6	346.3	344.9	344.9	342.7
120°	379.7	384.1	380.5	379.7	378.3
122.5°	415.3	418.2	416.8	414.6	412.4
125°	451.6	453.8	452.3	449.4	446.5
127.5°	485.0	489.4	487.9	483.6	480.7
130°	518.4	524.2	522.0	519.1	514.1
132.5°	551.8	557.6	556.2	552.5	548.9
135°	585.9	590.3	589.6	586.7	585.2
137.5°	617.2	620.8	623.0	619.3	617.2
140°	649.8	653.5	654.2	653.5	648.4
142.5°	679.6	683.2	684.7	684.0	680.3
145°	710.8	712.3	714.5	713.7	710.8
147.5°	737.7	740.6	742.8	742.8	738.4
150°	766.0	767.5	768.9	768.9	764.6
152.5°	789.2	791.4	792.1	793.6	790.0
155°	813.9	813.9	814.7	817.6	812.5
157.5°	835.0	834.3	835.0	837.9	833.5
160°	854.6	853.1	853.1	856.8	853.9
162.5°	872.0	869.8	870.6	874.2	869.1
165°	886.5	884.4	884.4	888.7	883.6
167.5°	898.9	896.0	896.7	901.1	896.7
170°	909.0	906.1	906.1	911.2	906.1
172.5°	917.0	914.1	914.1	918.5	913.4
175°	922.1	919.2	919.2	923.6	918.5
177.5°	925.0	922.1	922.1	926.5	921.4
180°	924.3	924.3	924.3	924.3	924.3

(END OF REPORT)