

Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269



Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions

Brand: NEO-RAY

Report Number: P982993

Luminaire Tested: S123IW-B460UB35-4F0-XX-W2A

Issue Date: 5/2/2025

**Test Information**

Test Method: LM-79-2019  
Report Number: P982993  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-1807-864-5)  
Test Lab: INNOVATION CENTER  
Issue Date: 5/2/2025  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: NEO-RAY  
Catalog Number: S123IW-B460UB35-4F0-XX-W2A  
Description: Define 3 Indirect Wall Mount with 3500K BioUP LEDs {m-DER=0.721} {m-EER=0.792}  
Light Source: -  
Ballast/Driver: -

**Summary**


Lumens per Lamp: N/A  
Luminaire Lumens: 1873.0 lumens  
Efficiency: N/A  
Efficacy: 141.9 lumens/watt  
Spacing Criteria (0/90/45): - / - / -  
Luminous Opening: Rectangular (W 0.25' x L: 4' x H: 0')  
CIE Type: Indirect

Input Watts (W): 13.2  
Input Voltage (V):  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT

TEST NUMBER: P982993

CATALOG NUMBER: S123IW-B460UB35-4F0-XX-W2A

### Luminous Intensity Polar Plot



TEST NUMBER: P982993

CATALOG NUMBER: S123IW-B460UB35-4F0-XX-W2A

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

|     |    |    |    |    |    |    |    |    |    |    |    |    |    |    |    |    |    |
|-----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|
| RF  | 20 |    |    |    | 20 |    |    |    | 20 |    |    |    | 20 |    |    |    | 20 |
| RC  | 80 |    |    |    | 70 |    |    |    | 50 |    |    |    | 30 |    |    |    | 10 |
| RW  | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 |
| RCR |    |    |    |    |    |    |    |    |    |    |    |    |    |    |    |    |    |
| 0   | 95 | 95 | 95 | 95 | 81 | 81 | 81 | 81 | 56 | 56 | 56 | 32 | 32 | 32 | 10 | 10 | 10 |
| 1   | 87 | 83 | 79 | 76 | 74 | 71 | 68 | 65 | 48 | 47 | 45 | 28 | 27 | 26 | 9  | 9  | 8  |
| 2   | 79 | 72 | 66 | 62 | 67 | 62 | 57 | 53 | 42 | 40 | 37 | 24 | 23 | 22 | 8  | 7  | 7  |
| 3   | 72 | 63 | 56 | 51 | 61 | 54 | 49 | 44 | 37 | 34 | 31 | 21 | 20 | 18 | 7  | 6  | 6  |
| 4   | 65 | 56 | 48 | 43 | 56 | 48 | 42 | 37 | 33 | 29 | 26 | 19 | 17 | 16 | 6  | 6  | 5  |
| 5   | 60 | 49 | 42 | 36 | 51 | 42 | 36 | 32 | 29 | 25 | 22 | 17 | 15 | 13 | 5  | 5  | 4  |
| 6   | 55 | 44 | 36 | 31 | 47 | 38 | 32 | 27 | 26 | 22 | 19 | 15 | 13 | 11 | 5  | 4  | 4  |
| 7   | 50 | 39 | 32 | 27 | 43 | 34 | 28 | 23 | 23 | 19 | 17 | 14 | 11 | 10 | 4  | 4  | 3  |
| 8   | 47 | 35 | 28 | 23 | 40 | 30 | 24 | 20 | 21 | 17 | 14 | 12 | 10 | 9  | 4  | 3  | 3  |
| 9   | 43 | 32 | 25 | 20 | 37 | 27 | 22 | 18 | 19 | 15 | 13 | 11 | 9  | 8  | 4  | 3  | 3  |
| 10  | 40 | 29 | 22 | 18 | 34 | 25 | 19 | 16 | 17 | 14 | 11 | 10 | 8  | 7  | 3  | 3  | 2  |

**AVERAGE LUMINANCE (cd/sqm):**

|     | 0° | 45° | 90° |
|-----|----|-----|-----|
| 0°  | 0  | 0   | 0   |
| 5°  | 0  | 0   | 0   |
| 10° | 0  | 0   | 0   |
| 15° | 0  | 0   | 0   |
| 20° | 0  | 0   | 0   |
| 25° | 0  | 0   | 0   |
| 30° | 0  | 0   | 0   |
| 35° | 0  | 0   | 0   |
| 40° | 0  | 0   | 0   |
| 45° | 0  | 0   | 0   |
| 50° | 0  | 0   | 0   |
| 55° | 0  | 0   | 0   |
| 60° | 0  | 0   | 0   |
| 65° | 0  | 0   | 0   |
| 70° | 0  | 0   | 0   |
| 75° | 0  | 0   | 0   |
| 80° | 0  | 0   | 0   |
| 85° | 0  | 0   | 0   |

**MAXIMUM LUMINANCE 45°-90°:**

Horizontal Angle: 0°  
Vertical Angle: 0°  
Luminance: 0 cd/sqm

TEST NUMBER: P982993

CATALOG NUMBER: S123IW-B460UB35-4F0-XX-W2A

**ZONAL LUMENS:**

| Zone      | Lumens | % Fixture |
|-----------|--------|-----------|
| 0°-10°    | 0.0    | 0.0       |
| 10°-20°   | 0.0    | 0.0       |
| 20°-30°   | 0.0    | 0.0       |
| 30°-40°   | 0.0    | 0.0       |
| 40°-50°   | 0.0    | 0.0       |
| 50°-60°   | 0.0    | 0.0       |
| 60°-70°   | 0.0    | 0.0       |
| 70°-80°   | 0.0    | 0.0       |
| 80°-90°   | 1.2    | 0.1       |
| 90°-100°  | 21.7   | 1.2       |
| 100°-110° | 104.7  | 5.6       |
| 110°-120° | 256.5  | 13.7      |
| 120°-130° | 325.6  | 17.4      |
| 130°-140° | 347.9  | 18.6      |
| 140°-150° | 325.3  | 17.4      |
| 150°-160° | 262.4  | 14.0      |
| 160°-170° | 169.3  | 9.0       |
| 170°-180° | 58.4   | 3.1       |
| 0°-30°    | 0.0    | 0.0       |
| 0°-40°    | 0.0    | 0.0       |
| 0°-60°    | 0.0    | 0.0       |
| 0°-90°    | 1.2    | 0.1       |
| 90°-120°  | 382.9  | 20.4      |
| 90°-150°  | 1381.7 | 73.8      |
| 90°-180°  | 1872.0 | 99.9      |
| 0°-180°   | 1873.0 | 100.0     |

**CANDELA DISTRIBUTION:**

|      | 0°  | 22.5° | 45° | 67.5° | 90° | Flux |
|------|-----|-------|-----|-------|-----|------|
| 0°   | 0   | 0     | 0   | 0     | 0   |      |
| 5°   | 0   | 0     | 0   | 0     | 0   | 0    |
| 15°  | 0   | 0     | 0   | 0     | 0   | 0    |
| 25°  | 0   | 0     | 0   | 0     | 0   | 0    |
| 35°  | 0   | 0     | 0   | 0     | 0   | 0    |
| 45°  | 0   | 0     | 0   | 0     | 0   | 0    |
| 55°  | 0   | 0     | 0   | 0     | 0   | 0    |
| 65°  | 0   | 0     | 0   | 0     | 0   | 0    |
| 75°  | 0   | 0     | 0   | 0     | 0   | 0    |
| 85°  | 0   | 0     | 0   | 0     | 0   | 0    |
| 90°  | 0   | 5     | 11  | 13    | 14  | 2    |
| 95°  | 28  | 9     | 14  | 17    | 17  | 33   |
| 105° | 136 | 141   | 100 | 19    | 20  | 144  |
| 115° | 255 | 258   | 262 | 266   | 268 | 252  |
| 125° | 359 | 363   | 365 | 366   | 367 | 321  |
| 135° | 448 | 450   | 452 | 453   | 452 | 345  |
| 145° | 516 | 520   | 520 | 521   | 521 | 323  |
| 155° | 569 | 568   | 568 | 571   | 568 | 262  |
| 165° | 600 | 598   | 598 | 602   | 598 | 169  |
| 175° | 614 | 612   | 612 | 615   | 612 | 58   |
| 180° | 614 | 614   | 614 | 614   | 614 |      |

TEST NUMBER: P982993

CATALOG NUMBER: S123IW-B460UB35-4F0-XX-W2A

**CANDELA DISTRIBUTION (FULL):**

|        | 0°    | 22.5° | 45°   | 67.5° | 90°   |
|--------|-------|-------|-------|-------|-------|
| 0°     | 0.0   | 0.0   | 0.0   | 0.0   | 0.0   |
| 2.5°   | 0.0   | 0.0   | 0.0   | 0.0   | 0.0   |
| 5°     | 0.0   | 0.0   | 0.0   | 0.0   | 0.0   |
| 7.5°   | 0.0   | 0.0   | 0.0   | 0.0   | 0.0   |
| 10°    | 0.0   | 0.0   | 0.0   | 0.0   | 0.0   |
| 12.5°  | 0.0   | 0.0   | 0.0   | 0.0   | 0.0   |
| 15°    | 0.0   | 0.0   | 0.0   | 0.0   | 0.0   |
| 17.5°  | 0.0   | 0.0   | 0.0   | 0.0   | 0.0   |
| 20°    | 0.0   | 0.0   | 0.0   | 0.0   | 0.0   |
| 22.5°  | 0.0   | 0.0   | 0.0   | 0.0   | 0.0   |
| 25°    | 0.0   | 0.0   | 0.0   | 0.0   | 0.0   |
| 27.5°  | 0.0   | 0.0   | 0.0   | 0.0   | 0.0   |
| 30°    | 0.0   | 0.0   | 0.0   | 0.0   | 0.0   |
| 32.5°  | 0.0   | 0.0   | 0.0   | 0.0   | 0.0   |
| 35°    | 0.0   | 0.0   | 0.0   | 0.0   | 0.0   |
| 37.5°  | 0.0   | 0.0   | 0.0   | 0.0   | 0.0   |
| 40°    | 0.0   | 0.0   | 0.0   | 0.0   | 0.0   |
| 42.5°  | 0.0   | 0.0   | 0.0   | 0.0   | 0.0   |
| 45°    | 0.0   | 0.0   | 0.0   | 0.0   | 0.0   |
| 47.5°  | 0.0   | 0.0   | 0.0   | 0.0   | 0.0   |
| 50°    | 0.0   | 0.0   | 0.0   | 0.0   | 0.0   |
| 52.5°  | 0.0   | 0.0   | 0.0   | 0.0   | 0.0   |
| 55°    | 0.0   | 0.0   | 0.0   | 0.0   | 0.0   |
| 57.5°  | 0.0   | 0.0   | 0.0   | 0.0   | 0.0   |
| 60°    | 0.0   | 0.0   | 0.0   | 0.0   | 0.0   |
| 62.5°  | 0.0   | 0.0   | 0.0   | 0.0   | 0.0   |
| 65°    | 0.0   | 0.0   | 0.0   | 0.0   | 0.0   |
| 67.5°  | 0.0   | 0.0   | 0.0   | 0.0   | 0.0   |
| 70°    | 0.0   | 0.0   | 0.0   | 0.0   | 0.0   |
| 72.5°  | 0.0   | 0.0   | 0.0   | 0.0   | 0.0   |
| 75°    | 0.0   | 0.0   | 0.0   | 0.0   | 0.0   |
| 77.5°  | 0.0   | 0.0   | 0.0   | 0.0   | 0.0   |
| 80°    | 0.0   | 0.0   | 0.0   | 0.0   | 0.0   |
| 82.5°  | 0.0   | 0.0   | 0.0   | 0.0   | 0.0   |
| 85°    | 0.0   | 0.0   | 0.0   | 0.0   | 0.0   |
| 87.5°  | 0.0   | 0.0   | 0.0   | 0.0   | 0.0   |
| 90°    | 0.5   | 5.0   | 10.9  | 12.8  | 13.7  |
| 92.5°  | 10.5  | 7.8   | 11.9  | 15.1  | 15.5  |
| 95°    | 27.8  | 9.1   | 14.1  | 17.3  | 17.3  |
| 97.5°  | 50.6  | 37.9  | 14.6  | 18.2  | 18.7  |
| 100°   | 77.1  | 86.2  | 15.1  | 18.7  | 19.2  |
| 102.5° | 107.2 | 113.1 | 33.8  | 18.7  | 19.6  |
| 105°   | 135.9 | 141.0 | 99.9  | 19.2  | 20.1  |
| 107.5° | 166.5 | 170.6 | 177.4 | 107.2 | 47.4  |
| 110°   | 197.1 | 200.7 | 205.7 | 190.7 | 125.4 |



TEST NUMBER: P982993

CATALOG NUMBER: S123IW-B460UB35-4F0-XX-W2A

**CANDELA DISTRIBUTION (continued):**

|        | 0°    | 22.5° | 45°   | 67.5° | 90°   |
|--------|-------|-------|-------|-------|-------|
| 112.5° | 226.3 | 229.4 | 234.5 | 238.6 | 237.7 |
| 115°   | 255.0 | 257.7 | 261.8 | 266.4 | 268.2 |
| 117.5° | 283.3 | 286.5 | 288.7 | 292.4 | 292.8 |
| 120°   | 309.3 | 313.4 | 314.7 | 318.4 | 318.4 |
| 122.5° | 335.7 | 338.9 | 340.7 | 343.0 | 343.5 |
| 125°   | 359.4 | 363.1 | 364.9 | 365.8 | 366.7 |
| 127.5° | 383.2 | 386.8 | 389.1 | 390.5 | 389.6 |
| 130°   | 405.1 | 408.7 | 410.5 | 412.4 | 411.4 |
| 132.5° | 426.0 | 429.7 | 431.1 | 432.9 | 431.5 |
| 135°   | 447.5 | 450.2 | 452.0 | 453.4 | 452.0 |
| 137.5° | 465.7 | 469.4 | 470.3 | 472.6 | 471.7 |
| 140°   | 484.0 | 486.7 | 488.1 | 489.9 | 489.0 |
| 142.5° | 500.9 | 503.6 | 505.0 | 506.3 | 505.0 |
| 145°   | 516.4 | 519.6 | 520.5 | 521.4 | 521.4 |
| 147.5° | 531.4 | 533.7 | 534.6 | 535.5 | 533.2 |
| 150°   | 545.1 | 546.5 | 547.4 | 548.3 | 546.9 |
| 152.5° | 557.4 | 557.9 | 558.3 | 560.2 | 557.9 |
| 155°   | 568.8 | 567.9 | 568.4 | 570.6 | 567.9 |
| 157.5° | 577.9 | 577.9 | 577.5 | 580.2 | 576.6 |
| 160°   | 586.2 | 585.7 | 585.2 | 588.0 | 584.8 |
| 162.5° | 593.9 | 592.5 | 592.1 | 595.3 | 592.5 |
| 165°   | 599.8 | 598.5 | 598.0 | 601.7 | 598.5 |
| 167.5° | 604.9 | 603.0 | 603.0 | 606.7 | 603.0 |
| 170°   | 609.0 | 607.1 | 607.1 | 610.8 | 607.1 |
| 172.5° | 611.7 | 609.4 | 609.9 | 613.5 | 609.4 |
| 175°   | 614.0 | 611.7 | 612.2 | 615.3 | 611.7 |
| 177.5° | 614.9 | 612.6 | 613.1 | 616.7 | 612.2 |
| 180°   | 614.0 | 614.0 | 614.0 | 614.0 | 614.0 |

TEST NUMBER: P982993

CATALOG NUMBER: S123IW-B460UB35-4F0-XX-W2A

**CIE UGR TABLE:**

| Reflectances:   |      |                  |      |      |      |      |                |      |      |      |      |
|-----------------|------|------------------|------|------|------|------|----------------|------|------|------|------|
| Ceiling         |      | 0.7              | 0.7  | 0.5  | 0.5  | 0.3  | 0.7            | 0.7  | 0.5  | 0.5  | 0.3  |
| Wall            |      | 0.5              | 0.3  | 0.5  | 0.3  | 0.3  | 0.5            | 0.3  | 0.5  | 0.3  | 0.3  |
| Reference plane |      | 0.2              | 0.2  | 0.2  | 0.2  | 0.2  | 0.2            | 0.2  | 0.2  | 0.2  | 0.2  |
| Room dimensions |      | Viewed crosswise |      |      |      |      | Viewed endwise |      |      |      |      |
| X=2H            | Y=2H | 0.00             | 0.00 | 0.00 | 0.00 | 0.00 | 0.00           | 0.00 | 0.00 | 0.00 | 0.00 |
|                 | 3H   | 0.00             | 0.00 | 0.00 | 0.00 | 0.00 | 0.00           | 0.00 | 0.00 | 0.00 | 0.00 |
|                 | 4H   | 0.00             | 0.00 | 0.00 | 0.00 | 0.00 | 0.00           | 0.00 | 0.00 | 0.00 | 0.00 |
|                 | 6H   | 0.00             | 0.00 | 0.00 | 0.00 | 0.00 | 0.00           | 0.00 | 0.00 | 0.00 | 0.00 |
|                 | 8H   | 0.00             | 0.00 | 0.00 | 0.00 | 0.00 | 0.00           | 0.00 | 0.00 | 0.00 | 0.00 |
|                 | 12H  | 0.00             | 0.00 | 0.00 | 0.00 | 0.00 | 0.00           | 0.00 | 0.00 | 0.00 | 0.00 |
| 4H              | 2H   | 0.00             | 0.00 | 0.00 | 0.00 | 0.00 | 0.00           | 0.00 | 0.00 | 0.00 | 0.00 |
|                 | 3H   | 0.00             | 0.00 | 0.00 | 0.00 | 0.00 | 0.00           | 0.00 | 0.00 | 0.00 | 0.00 |
|                 | 4H   | 0.00             | 0.00 | 0.00 | 0.00 | 0.00 | 0.00           | 0.00 | 0.00 | 0.00 | 0.00 |
|                 | 6H   | 0.00             | 0.00 | 0.00 | 0.00 | 0.00 | 0.00           | 0.00 | 0.00 | 0.00 | 0.00 |
|                 | 8H   | 0.00             | 0.00 | 0.00 | 0.00 | 0.00 | 0.00           | 0.00 | 0.00 | 0.00 | 0.00 |
|                 | 12H  | 0.00             | 0.00 | 0.00 | 0.00 | 0.00 | 0.00           | 0.00 | 0.00 | 0.00 | 0.00 |
| 8H              | 4H   | 0.00             | 0.00 | 0.00 | 0.00 | 0.00 | 0.00           | 0.00 | 0.00 | 0.00 | 0.00 |
|                 | 6H   | 0.00             | 0.00 | 0.00 | 0.00 | 0.00 | 0.00           | 0.00 | 0.00 | 0.00 | 0.00 |
|                 | 8H   | 0.00             | 0.00 | 0.00 | 0.00 | 0.00 | 0.00           | 0.00 | 0.00 | 0.00 | 0.00 |
|                 | 12H  | 0.00             | 0.00 | 0.00 | 0.00 | 0.00 | 0.00           | 0.00 | 0.00 | 0.00 | 0.00 |
| 12H             | 4H   | 0.00             | 0.00 | 0.00 | 0.00 | 0.00 | 0.00           | 0.00 | 0.00 | 0.00 | 0.00 |
|                 | 6H   | 0.00             | 0.00 | 0.00 | 0.00 | 0.00 | 0.00           | 0.00 | 0.00 | 0.00 | 0.00 |
|                 | 8H   | 0.00             | 0.00 | 0.00 | 0.00 | 0.00 | 0.00           | 0.00 | 0.00 | 0.00 | 0.00 |

END OF REPORT