

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: NEO-RAY

Report Number: P1032469

Luminaire Tested: S124DIW-B1020D1050UB2750-4F0-XX-W2A-D1_5000K

Issue Date: 5/7/2025

Test Information

Test Method: LM-79-2019
Report Number: P1032469
REPORT IS A COMBINATION OF REPORTS P996635 AND P1007351
Test Lab: INNOVATION CENTER
Issue Date: 5/7/2025
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: NEO-RAY
Catalog Number: S124DIW-B1020D1050UB2750-4F0-XX-W2A-D1_5000K
Description: Define 4 Direct/Indirect Wall Mount with 5000K BioUP LEDs {m-DER=1.015} {m-EER=1.115}
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 7570.0 lumens
Efficiency: N/A
Efficacy: 96.7 lumens/watt
Spacing Criteria (0/90/45): 1.23 / 1.28 / 1.39
Luminous Opening: Rectangular w/ Sides (W: 0.33' x L: 4' x H: 0.1')
CIE Type: General Diffuse

Input Watts (W): 78.3
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1032469

CATALOG NUMBER: S124DIW-B1020D1050UB2750-4F0-XX-W2A-D1_5000K

Luminous Intensity Polar Plot



TEST NUMBER: P1032469

CATALOG NUMBER: S124DIW-B1020D1050UB2750-4F0-XX-W2A-D1_5000K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	107	107	107	107	99	99	99	99	83	83	83		69	69	69		55
1	97	92	88	84	89	85	81	78	71	68	66		59	57	55		47
2	88	80	73	68	80	73	68	63	62	57	54		51	48	45		41
3	80	70	62	56	73	64	57	52	54	49	45		45	41	38		36
4	73	61	53	47	66	57	49	44	48	42	38		40	35	32		32
5	67	55	46	40	61	50	43	37	43	37	32		35	31	28		29
6	61	49	40	34	56	45	38	32	38	32	28		32	27	24		26
7	57	44	36	30	52	41	33	28	35	29	25		29	24	21		24
8	52	40	32	26	48	37	30	25	32	26	22		26	22	19		22
9	49	36	29	23	45	34	27	22	29	23	19		24	20	17		20
10	46	33	26	21	42	31	24	20	27	21	17		22	18	15		18

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	9622	9622	9622
5°	9649	9371	9388
10°	9586	9187	9160
15°	9496	8980	8904
20°	9363	8755	8654
25°	9213	8507	8386
30°	9052	8262	8112
35°	8868	8012	7867
40°	8720	7771	7614
45°	8503	7545	7391
50°	8318	7289	7155
55°	8126	7042	6883
60°	7829	6734	6628
65°	7501	6402	6320
70°	7103	6023	5965
75°	6550	5602	5627
80°	5923	5172	5272
85°	5094	4741	4985

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 8503 cd/sqm

TEST NUMBER: P1032469

CATALOG NUMBER: S124DIW-B1020D1050UB2750-4F0-XX-W2A-D1_5000K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	111.8	1.5
10°-20°	320.3	4.2
20°-30°	484.4	6.4
30°-40°	586.0	7.7
40°-50°	619.5	8.2
50°-60°	583.0	7.7
60°-70°	483.8	6.4
70°-80°	339.5	4.5
80°-90°	194.1	2.6
90°-100°	197.2	2.6
100°-110°	333.8	4.4
110°-120°	480.3	6.3
120°-130°	590.6	7.8
130°-140°	641.3	8.5
140°-150°	619.5	8.2
150°-160°	518.8	6.9
160°-170°	345.2	4.6
170°-180°	120.9	1.6
0°-30°	916.5	12.1
0°-40°	1502.5	19.8
0°-60°	2705.0	35.7
0°-90°	3722.4	49.2
90°-120°	1011.3	13.4
90°-150°	2862.8	37.8
90°-180°	3848.0	50.8
0°-180°	7570.0	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	1180	1180	1180	1180	1180	
5°	1181	1177	1168	1179	1177	112
15°	1132	1134	1130	1142	1140	319
25°	1036	1044	1048	1062	1064	477
35°	906	922	936	954	958	568
45°	756	781	806	828	835	584
55°	592	620	659	686	694	528
65°	410	452	497	530	540	406
75°	227	276	332	369	381	241
85°	70	126	185	225	238	73
90°	24	88	152	197	209	19
95°	76	129	190	229	240	78
105°	242	270	322	358	372	258
115°	439	450	491	519	527	433
125°	633	631	663	686	692	564
135°	812	818	827	846	851	628
145°	984	987	988	995	997	616
155°	1126	1126	1125	1129	1125	518
165°	1226	1223	1221	1227	1223	346
175°	1275	1270	1270	1276	1270	121
180°	1277	1277	1277	1277	1277	

TEST NUMBER: P1032469

CATALOG NUMBER: S124DIW-B1020D1050UB2750-4F0-XX-W2A-D1_5000K

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	1180.0	1180.0	1180.0	1180.0	1180.0
2.5°	1185.3	1181.3	1170.7	1180.0	1178.6
5°	1181.3	1177.3	1168.1	1178.6	1177.3
7.5°	1173.4	1170.7	1162.8	1174.7	1173.4
10°	1162.8	1161.5	1154.9	1166.8	1165.4
12.5°	1148.3	1148.3	1144.3	1154.9	1154.9
15°	1132.4	1133.7	1129.8	1141.7	1140.3
17.5°	1111.3	1115.2	1113.9	1125.8	1124.5
20°	1088.8	1092.8	1094.1	1107.3	1107.3
22.5°	1063.7	1069.0	1071.6	1084.8	1087.5
25°	1035.9	1043.9	1047.8	1062.4	1063.7
27.5°	1005.6	1017.4	1022.7	1035.9	1037.3
30°	975.2	985.7	995.0	1009.5	1012.2
32.5°	942.1	955.3	965.9	983.1	985.7
35°	906.4	922.3	935.5	954.0	958.0
37.5°	870.8	889.3	905.1	923.6	927.6
40°	836.4	853.6	872.1	891.9	897.2
42.5°	796.8	816.6	839.1	861.5	865.5
45°	755.8	780.9	806.0	828.5	835.1
47.5°	717.5	742.6	771.7	794.1	802.1
50°	675.2	704.3	733.4	759.8	767.7
52.5°	632.9	662.0	696.4	722.8	730.7
55°	592.0	619.7	659.4	685.8	693.7
57.5°	545.7	580.1	618.4	650.1	656.7
60°	500.8	535.1	578.8	609.1	619.7
62.5°	457.2	495.5	539.1	569.5	580.1
65°	409.6	451.9	496.8	529.9	540.4
67.5°	364.7	409.6	457.2	490.2	500.8
70°	318.4	363.4	413.6	449.3	458.5
72.5°	273.5	319.8	373.9	408.3	418.9
75°	227.3	276.2	331.7	368.7	380.6
77.5°	183.7	235.2	293.3	330.3	343.6
80°	144.0	196.9	255.0	294.7	305.2
82.5°	104.4	159.9	218.0	259.0	270.9
85°	70.0	125.5	185.0	224.6	237.8
87.5°	43.6	97.8	155.9	194.2	206.1
90°	24.1	87.8	152.5	196.8	209.3
92.5°	45.5	104.6	166.4	206.3	217.9
95°	76.5	129.0	190.1	228.6	240.5
97.5°	110.7	156.9	219.0	257.3	269.2
100°	152.8	191.2	251.6	289.2	298.4
102.5°	198.3	228.3	286.4	323.8	335.3
105°	242.1	269.5	322.3	358.3	371.9
107.5°	290.5	314.0	361.2	398.1	406.4
110°	338.6	359.1	404.3	432.7	446.3

TEST NUMBER: P1032469

CATALOG NUMBER: S124DIW-B1020D1050UB2750-4F0-XX-W2A-D1_5000K

CANDELA DISTRIBUTION (continued):

	0°	22.5°	45°	67.5°	90°
112.5°	388.6	404.5	446.1	475.2	485.8
115°	438.6	450.5	490.9	519.0	527.2
117.5°	487.0	495.0	533.7	558.4	566.0
120°	534.2	542.1	577.4	598.9	611.5
122.5°	584.5	585.5	620.2	643.7	648.0
125°	632.6	631.3	663.3	686.5	692.4
127.5°	677.1	678.8	703.2	725.0	733.2
130°	723.2	724.8	746.0	767.8	771.7
132.5°	771.6	772.2	787.1	807.6	814.5
135°	811.7	817.6	826.9	846.1	851.1
137.5°	858.1	859.8	867.1	883.9	891.5
140°	904.6	905.2	906.5	922.8	928.4
142.5°	945.8	947.7	945.4	959.9	965.2
145°	984.3	986.9	987.9	994.8	997.2
147.5°	1023.8	1027.4	1026.5	1026.8	1031.1
150°	1059.4	1062.0	1062.0	1062.0	1061.0
152.5°	1091.7	1093.6	1094.6	1097.6	1094.6
155°	1126.2	1126.2	1125.2	1129.2	1125.2
157.5°	1155.9	1153.9	1153.9	1156.9	1153.9
160°	1181.6	1180.6	1179.6	1182.5	1177.6
162.5°	1205.3	1202.3	1201.3	1207.2	1202.3
165°	1226.0	1223.0	1221.1	1227.0	1223.0
167.5°	1242.8	1238.9	1238.9	1244.8	1238.9
170°	1256.6	1251.7	1252.7	1258.6	1251.7
172.5°	1266.5	1262.6	1262.6	1269.5	1262.6
175°	1275.4	1270.5	1269.5	1276.4	1269.5
177.5°	1279.4	1274.4	1274.4	1281.3	1273.4
180°	1277.4	1277.4	1277.4	1277.4	1277.4

(END OF REPORT)