

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: NEO-RAY

Report Number: P1032548

Luminaire Tested: S124DIW-B1195D1050UB2750-4F0-XX-W2A-D_5000K

Issue Date: 5/7/2025

Test Information

Test Method: LM-79-2019
Report Number: P1032548
REPORT IS A COMBINATION OF REPORTS P996971 AND P1007351
Test Lab: INNOVATION CENTER
Issue Date: 5/7/2025
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: NEO-RAY
Catalog Number: S124DIW-B1195D1050UB2750-4F0-XX-W2A-D_5000K
Description: Define 4 Direct/Indirect Wall Mount with 5000K BioUP LEDs {m-DER=1.015} {m-EER=1.115}
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 8775.0 lumens
Efficiency: N/A
Efficacy: 94.6 lumens/watt
Spacing Criteria (0/90/45): 1.23 / 1.28 / 1.39
Luminous Opening: Rectangular w/ Sides (W: 0.33' x L: 4' x H: 0.1')
CIE Type: General Diffuse

Input Watts (W): 92.8
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1032548

CATALOG NUMBER: S124DIW-B1195D1050UB2750-4F0-XX-W2A-D_5000K

Luminous Intensity Polar Plot



TEST NUMBER: P1032548

CATALOG NUMBER: S124DIW-B1195D1050UB2750-4F0-XX-W2A-D_5000K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	107	107	107	107	99	99	99	99	83	83	83		69	69	69		56
1	97	92	88	84	89	85	81	78	71	69	66		59	57	55		48
2	88	80	73	68	80	73	68	63	62	58	54		51	48	45		41
3	80	70	62	56	73	64	58	52	54	49	45		45	41	38		36
4	73	61	53	47	67	57	49	44	48	42	38		40	36	32		32
5	67	55	46	40	61	50	43	37	43	37	32		36	31	28		29
6	61	49	40	34	56	45	38	32	38	32	28		32	27	24		26
7	57	44	36	30	52	41	33	28	35	29	25		29	25	21		24
8	52	40	32	26	48	37	30	25	32	26	22		27	22	19		22
9	49	36	29	23	45	34	27	22	29	23	19		24	20	17		20
10	46	33	26	21	42	31	24	20	27	21	17		22	18	15		19

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	11205	11205	11205
5°	11236	10913	10933
10°	11163	10699	10668
15°	11059	10457	10369
20°	10904	10196	10078
25°	10729	9908	9765
30°	10541	9622	9446
35°	10327	9330	9162
40°	10156	9050	8867
45°	9903	8787	8607
50°	9686	8488	8332
55°	9463	8201	8017
60°	9117	7842	7719
65°	8735	7456	7361
70°	8272	7013	6947
75°	7628	6522	6553
80°	6897	6023	6141
85°	5938	5520	5806

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 9903 cd/sqm

TEST NUMBER: P1032548

CATALOG NUMBER: S124DIW-B1195D1050UB2750-4F0-XX-W2A-D_5000K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	130.2	1.5
10°-20°	373.1	4.3
20°-30°	564.1	6.4
30°-40°	682.4	7.8
40°-50°	721.4	8.2
50°-60°	678.9	7.7
60°-70°	563.4	6.4
70°-80°	395.4	4.5
80°-90°	225.6	2.6
90°-100°	176.5	2.0
100°-110°	387.0	4.4
110°-120°	617.3	7.0
120°-130°	737.1	8.4
130°-140°	764.9	8.7
140°-150°	703.4	8.0
150°-160°	564.7	6.4
160°-170°	364.2	4.1
170°-180°	125.5	1.4
0°-30°	1067.3	12.2
0°-40°	1749.7	19.9
0°-60°	3150.1	35.9
0°-90°	4334.4	49.4
90°-120°	1180.9	13.5
90°-150°	3386.2	38.6
90°-180°	4441.0	50.6
0°-180°	8775.0	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	1374	1374	1374	1374	1374	
5°	1376	1371	1360	1373	1371	131
15°	1319	1320	1316	1330	1328	372
25°	1206	1216	1220	1237	1239	556
35°	1056	1074	1090	1111	1116	661
45°	880	909	939	965	972	680
55°	689	722	768	799	808	614
65°	477	526	579	617	629	473
75°	265	322	386	429	443	281
85°	82	146	215	262	277	85
90°	28	100	174	225	239	20
95°	74	92	156	203	218	83
105°	311	348	410	457	434	327
115°	564	581	630	665	676	556
125°	787	789	826	858	868	703
135°	971	970	985	1012	1023	749
145°	1118	1119	1119	1130	1138	699
155°	1224	1225	1222	1226	1223	565
165°	1291	1286	1286	1294	1285	365
175°	1321	1315	1316	1325	1313	126
180°	1321	1321	1321	1321	1321	

TEST NUMBER: P1032548

CATALOG NUMBER: S124DIW-B1195D1050UB2750-4F0-XX-W2A-D_5000K

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	1374.1	1374.1	1374.1	1374.1	1374.1
2.5°	1380.3	1375.7	1363.4	1374.1	1372.6
5°	1375.7	1371.1	1360.3	1372.6	1371.1
7.5°	1366.4	1363.4	1354.1	1368.0	1366.4
10°	1354.1	1352.6	1344.9	1358.8	1357.2
12.5°	1337.2	1337.2	1332.6	1344.9	1344.9
15°	1318.7	1320.3	1315.7	1329.5	1328.0
17.5°	1294.1	1298.7	1297.2	1311.0	1309.5
20°	1268.0	1272.6	1274.1	1289.5	1289.5
22.5°	1238.7	1244.9	1248.0	1263.3	1266.4
25°	1206.4	1215.6	1220.3	1237.2	1238.7
27.5°	1171.0	1184.9	1191.0	1206.4	1207.9
30°	1135.6	1147.9	1158.7	1175.6	1178.7
32.5°	1097.2	1112.5	1124.9	1144.9	1147.9
35°	1055.6	1074.1	1089.5	1111.0	1115.6
37.5°	1014.1	1035.6	1054.1	1075.6	1080.2
40°	974.1	994.1	1015.6	1038.7	1044.8
42.5°	927.9	951.0	977.1	1003.3	1007.9
45°	880.2	909.4	938.7	964.8	972.5
47.5°	835.6	864.8	898.7	924.8	934.0
50°	786.3	820.2	854.0	884.8	894.0
52.5°	737.1	770.9	810.9	841.7	850.9
55°	689.4	721.7	767.9	798.6	807.9
57.5°	635.5	675.5	720.2	757.1	764.8
60°	583.2	623.2	674.0	709.4	721.7
62.5°	532.4	577.0	627.8	663.2	675.5
65°	477.0	526.3	578.6	617.1	629.4
67.5°	424.7	477.0	532.4	570.9	583.2
70°	370.8	423.2	481.6	523.2	534.0
72.5°	318.5	372.4	435.5	475.5	487.8
75°	264.7	321.6	386.2	429.3	443.2
77.5°	213.9	273.9	341.6	384.7	400.1
80°	167.7	229.3	297.0	343.1	355.5
82.5°	121.6	186.2	253.9	301.6	315.5
85°	81.6	146.2	215.4	261.6	277.0
87.5°	50.8	113.9	181.6	226.2	240.1
90°	27.6	100.0	174.0	224.7	238.9
92.5°	37.9	89.7	163.8	212.9	225.2
95°	74.3	91.5	155.6	203.1	218.0
97.5°	122.2	188.6	147.9	192.9	207.7
100°	178.9	236.7	160.4	185.2	197.0
102.5°	244.1	289.9	360.2	178.0	190.3
105°	311.2	347.9	409.8	457.1	433.9
107.5°	375.4	404.6	465.4	508.7	523.5
110°	439.1	463.7	523.4	560.8	576.0

TEST NUMBER: P1032548

CATALOG NUMBER: S124DIW-B1195D1050UB2750-4F0-XX-W2A-D_5000K

CANDELA DISTRIBUTION (continued):

	0°	22.5°	45°	67.5°	90°
112.5°	500.8	525.1	577.9	610.8	627.1
115°	564.4	581.3	629.5	665.4	676.1
117.5°	622.7	636.0	685.0	716.3	728.7
120°	680.5	689.0	732.7	765.4	775.8
122.5°	735.8	737.8	781.3	813.1	821.9
125°	786.7	789.0	825.6	857.7	868.0
127.5°	837.1	836.4	872.2	898.9	908.7
130°	883.9	883.4	910.9	939.6	948.8
132.5°	928.3	928.8	951.2	978.3	986.6
135°	971.3	970.3	984.9	1011.6	1022.8
137.5°	1010.8	1009.2	1020.3	1045.4	1052.1
140°	1049.3	1049.7	1053.3	1076.2	1084.9
142.5°	1082.3	1086.3	1085.8	1104.6	1110.8
145°	1117.9	1119.3	1119.3	1129.5	1137.7
147.5°	1145.5	1150.0	1149.0	1151.5	1158.7
150°	1176.2	1178.6	1177.6	1177.6	1178.6
152.5°	1200.4	1203.3	1201.3	1203.3	1202.3
155°	1224.1	1225.1	1222.1	1226.0	1223.1
157.5°	1244.8	1244.8	1240.9	1245.8	1240.9
160°	1262.6	1259.6	1258.6	1264.6	1258.6
162.5°	1278.4	1274.4	1273.5	1279.4	1272.5
165°	1291.2	1286.3	1286.3	1294.2	1285.3
167.5°	1302.1	1297.2	1296.2	1305.1	1295.2
170°	1311.0	1305.1	1306.1	1314.0	1304.1
172.5°	1316.9	1311.0	1312.0	1319.9	1309.0
175°	1320.9	1315.0	1315.9	1324.8	1313.0
177.5°	1323.8	1316.9	1318.9	1326.8	1315.0
180°	1320.9	1320.9	1320.9	1320.9	1320.9

(END OF REPORT)