

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: NEO-RAY

Report Number: P1033442

Luminaire Tested: S124DIW-B350D1340UB50-4F0-XX-W2A-F1

Issue Date: 5/6/2025

Test Information

Test Method: LM-79-2019
Report Number: P1033442
REPORT IS A COMBINATION OF REPORTS P997409 AND P1007351
Test Lab: INNOVATION CENTER
Issue Date: 5/6/2025
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: NEO-RAY
Catalog Number: S124DIW-B350D1340UB50-4F0-XX-W2A-F1
Description: Define 4 Direct/Indirect Wall Mount with 5000K BioUP LEDs {m-DER=1.015} {m-EER=1.115}
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 5898.0 lumens
Efficiency: N/A
Efficacy: 107.0 lumens/watt
Spacing Criteria (0/90/45): 1.2 / 1.17 / 1.29
Luminous Opening: Rectangular w/ Sides (W: 0.33' x L: 4' x H: 0.1')
CIE Type: Semi-Indirect

Input Watts (W): 55.1
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1033442

CATALOG NUMBER: S124DIW-B350D1340UB50-4F0-XX-W2A-F1

Luminous Intensity Polar Plot



TEST NUMBER: P1033442

CATALOG NUMBER: S124DIW-B350D1340UB50-4F0-XX-W2A-F1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	101	101	101	101	90	90	90	90	69	69	69		50	50	50		32
1	92	88	84	81	82	78	75	72	60	58	56		44	42	41		28
2	84	77	71	66	74	68	63	59	53	49	47		38	36	34		25
3	76	67	60	55	68	60	54	49	46	42	39		34	31	29		22
4	70	59	52	46	62	53	47	42	41	37	33		30	27	25		20
5	64	53	45	39	56	47	41	36	37	32	28		27	24	21		18
6	59	47	39	34	52	42	36	31	33	28	25		24	21	19		16
7	54	42	35	29	48	38	31	27	30	25	22		22	19	16		15
8	50	38	31	26	44	34	28	24	27	22	19		20	17	14		13
9	46	35	28	23	41	31	25	21	25	20	17		18	15	13		12
10	43	32	25	20	38	29	23	19	23	18	15		17	14	12		11

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	4509	4509	4509
5°	4512	4379	4384
10°	4474	4257	4227
15°	4409	4112	4050
20°	4327	3956	3867
25°	4235	3791	3671
30°	4124	3612	3454
35°	4009	3430	3245
40°	3889	3233	3023
45°	3763	3036	2815
50°	3623	2844	2585
55°	3472	2621	2356
60°	3317	2376	2118
65°	3139	2124	1849
70°	2936	1819	1563
75°	2631	1466	1251
80°	2242	1061	879
85°	1739	589	474

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
Vertical Angle: 45°
Luminance: 3763 cd/sqm

TEST NUMBER: P1033442

CATALOG NUMBER: S124DIW-B350D1340UB50-4F0-XX-W2A-F1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	52.1	0.9
10°-20°	146.8	2.5
20°-30°	216.1	3.7
30°-40°	251.2	4.3
40°-50°	251.1	4.3
50°-60°	219.6	3.7
60°-70°	163.1	2.8
70°-80°	92.5	1.6
80°-90°	29.9	0.5
90°-100°	105.1	1.8
100°-110°	314.9	5.3
110°-120°	535.0	9.1
120°-130°	705.6	12.0
130°-140°	792.5	13.4
140°-150°	778.9	13.2
150°-160°	655.1	11.1
160°-170°	435.9	7.4
170°-180°	152.6	2.6
0°-30°	415.0	7.0
0°-40°	666.1	11.3
0°-60°	1136.9	19.3
0°-90°	1422.5	24.1
90°-120°	955.0	16.2
90°-150°	3232.0	54.8
90°-180°	4476.0	75.9
0°-180°	5898.0	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	553	553	553	553	553	
5°	552	551	546	551	550	52
15°	526	524	517	520	519	148
25°	476	473	467	467	466	219
35°	410	407	400	397	395	256
45°	334	331	324	319	318	258
55°	253	252	245	240	237	227
65°	171	169	165	160	158	170
75°	91	89	87	85	85	97
85°	24	24	23	23	23	26
90°	4	18	27	35	37	7
95°	75	86	95	99	99	81
105°	291	292	297	301	304	308
115°	544	544	541	540	539	536
125°	792	792	791	788	786	706
135°	1022	1029	1029	1027	1023	790
145°	1241	1246	1248	1246	1242	777
155°	1422	1422	1421	1426	1421	654
165°	1548	1544	1542	1549	1544	437
175°	1610	1604	1603	1612	1603	153
180°	1613	1613	1613	1613	1613	

TEST NUMBER: P1033442

CATALOG NUMBER: S124DIW-B350D1340UB50-4F0-XX-W2A-F1

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	552.9	552.9	552.9	552.9	552.9
2.5°	554.6	553.3	548.4	552.9	552.4
5°	552.4	550.6	545.8	550.6	549.8
7.5°	548.4	546.6	541.3	545.3	544.9
10°	542.7	540.9	535.1	538.7	537.8
12.5°	535.1	533.4	527.2	531.1	529.8
15°	525.8	524.1	517.4	520.1	518.7
17.5°	515.2	513.0	506.8	508.6	507.7
20°	503.2	501.0	494.4	495.7	494.8
22.5°	490.4	487.3	480.6	483.3	481.5
25°	476.2	473.1	466.9	467.4	465.6
27.5°	460.3	457.2	451.4	450.5	448.3
30°	444.3	440.8	435.0	433.2	431.0
32.5°	427.5	424.4	418.2	416.0	413.8
35°	409.8	406.7	400.5	397.4	395.1
37.5°	391.2	388.5	381.9	378.8	375.7
40°	373.0	369.5	362.8	358.4	356.2
42.5°	353.5	351.7	344.2	338.9	337.6
45°	334.5	331.4	324.3	319.4	318.1
47.5°	314.5	312.3	305.7	300.3	296.8
50°	294.1	292.4	286.2	280.0	277.3
52.5°	274.2	272.0	265.4	260.0	256.5
55°	252.9	251.6	245.4	240.1	237.4
57.5°	233.0	231.7	225.5	220.2	217.5
60°	212.2	210.0	204.2	200.2	198.0
62.5°	191.8	190.0	183.8	180.3	178.1
65°	171.4	169.2	164.8	160.4	158.1
67.5°	150.6	148.8	144.4	140.0	139.5
70°	131.6	128.5	124.9	121.4	120.1
72.5°	111.2	108.1	105.4	102.8	101.4
75°	91.3	89.0	86.8	85.1	84.6
77.5°	71.8	70.9	68.7	68.2	66.9
80°	54.5	53.2	52.3	51.4	50.9
82.5°	37.7	37.2	37.2	36.8	36.3
85°	23.9	23.9	23.0	23.0	22.6
87.5°	11.5	11.1	10.6	10.6	10.6
90°	3.7	17.5	27.4	34.9	37.4
92.5°	32.4	48.7	54.9	58.6	59.9
95°	74.9	86.1	94.8	98.6	98.6
97.5°	119.8	129.7	139.7	144.7	144.7
100°	174.7	179.6	190.9	193.4	193.4
102.5°	232.0	233.3	243.3	247.0	248.3
105°	290.7	291.9	296.9	300.6	304.4
107.5°	351.8	353.0	354.3	359.3	358.0
110°	414.2	416.7	415.4	412.9	416.7

TEST NUMBER: P1033442

CATALOG NUMBER: S124DIW-B350D1340UB50-4F0-XX-W2A-F1

CANDELA DISTRIBUTION (continued):

	0°	22.5°	45°	67.5°	90°
112.5°	479.0	479.0	476.5	476.5	476.5
115°	543.9	543.9	541.4	540.2	538.9
117.5°	605.0	605.0	603.8	600.1	596.3
120°	666.2	671.2	667.4	661.2	663.7
122.5°	729.8	731.0	729.8	726.0	719.8
125°	792.2	792.2	790.9	788.4	785.9
127.5°	848.3	852.0	849.6	847.1	845.8
130°	908.2	911.9	911.9	909.4	904.4
132.5°	969.3	971.8	970.6	968.1	966.8
135°	1021.7	1029.2	1029.2	1026.7	1023.0
137.5°	1080.3	1084.1	1086.6	1082.8	1084.1
140°	1139.0	1141.5	1141.5	1140.2	1139.0
142.5°	1192.6	1195.1	1193.9	1193.9	1193.9
145°	1241.3	1246.3	1247.5	1246.3	1242.5
147.5°	1291.2	1297.4	1296.2	1294.9	1293.7
150°	1336.1	1341.1	1341.1	1341.1	1339.8
152.5°	1378.5	1381.0	1382.2	1386.0	1382.2
155°	1422.2	1422.2	1420.9	1425.9	1420.9
157.5°	1459.6	1457.1	1457.1	1460.8	1457.1
160°	1492.0	1490.8	1489.5	1493.3	1487.0
162.5°	1522.0	1518.2	1517.0	1524.5	1518.2
165°	1548.2	1544.4	1541.9	1549.4	1544.4
167.5°	1569.4	1564.4	1564.4	1571.9	1564.4
170°	1586.8	1580.6	1581.8	1589.3	1580.6
172.5°	1599.3	1594.3	1594.3	1603.0	1594.3
175°	1610.5	1604.3	1603.0	1611.8	1603.0
177.5°	1615.5	1609.3	1609.3	1618.0	1608.0
180°	1613.0	1613.0	1613.0	1613.0	1613.0

(END OF REPORT)