

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: NEO-RAY

Report Number: P983235

Luminaire Tested: S124IW-B470UB2750-4F0-XX-W2A_2700K

Issue Date: 5/2/2025

Test Information

Test Method: LM-79-2019
Report Number: P983235
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-1807-864-6)
Test Lab: INNOVATION CENTER
Issue Date: 5/2/2025
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: NEO-RAY
Catalog Number: S124IW-B470UB2750-4F0-XX-W2A_2700K
Description: Define 4 Indirect Wall Mount with 2700K BioUP LEDs {m-DER=0.473} {m-EER=0.52}
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1881.0 lumens
Efficiency: N/A
Efficacy: 142.5 lumens/watt
Spacing Criteria (0/90/45): - / - / -
Luminous Opening: Rectangular (W 0.33' x L: 4' x H: 0')
CIE Type: Indirect

Input Watts (W): 13.2
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P983235

CATALOG NUMBER: S124IW-B470UB2750-4F0-XX-W2A_2700K

Luminous Intensity Polar Plot



TEST NUMBER: P983235

CATALOG NUMBER: S124IW-B470UB2750-4F0-XX-W2A_2700K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10
RCR																	
0	95	95	95	95	81	81	81	81	56	56	56	32	32	32	10	10	10
1	87	83	79	76	74	71	68	65	48	47	45	28	27	26	9	9	8
2	79	72	66	62	67	62	57	53	42	40	37	24	23	22	8	7	7
3	72	63	56	51	61	54	49	44	37	34	31	21	20	18	7	6	6
4	65	56	48	43	56	48	42	37	33	29	26	19	17	16	6	6	5
5	60	49	42	36	51	42	36	32	29	25	22	17	15	13	5	5	4
6	55	44	36	31	47	38	32	27	26	22	19	15	13	11	5	4	4
7	50	39	32	27	43	34	28	23	23	19	17	14	11	10	4	4	3
8	47	35	28	23	40	30	24	20	21	17	14	12	10	9	4	3	3
9	43	32	25	20	37	27	22	18	19	15	13	11	9	8	4	3	3
10	40	29	22	18	34	25	19	16	17	14	11	10	8	7	3	3	2

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	0	0	0
5°	0	0	0
10°	0	0	0
15°	0	0	0
20°	0	0	0
25°	0	0	0
30°	0	0	0
35°	0	0	0
40°	0	0	0
45°	0	0	0
50°	0	0	0
55°	0	0	0
60°	0	0	0
65°	0	0	0
70°	0	0	0
75°	0	0	0
80°	0	0	0
85°	0	0	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
Vertical Angle: 0°
Luminance: 0 cd/sqm

TEST NUMBER: P983235

CATALOG NUMBER: S124IW-B470UB2750-4F0-XX-W2A_2700K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	0.0	0.0
10°-20°	0.0	0.0
20°-30°	0.0	0.0
30°-40°	0.0	0.0
40°-50°	0.0	0.0
50°-60°	0.0	0.0
60°-70°	0.0	0.0
70°-80°	0.0	0.0
80°-90°	1.3	0.1
90°-100°	20.2	1.1
100°-110°	132.8	7.1
110°-120°	253.6	13.5
120°-130°	321.9	17.1
130°-140°	344.4	18.3
140°-150°	322.0	17.1
150°-160°	259.7	13.8
160°-170°	167.5	8.9
170°-180°	57.7	3.1
0°-30°	0.0	0.0
0°-40°	0.0	0.0
0°-60°	0.0	0.0
0°-90°	1.3	0.1
90°-120°	406.6	21.6
90°-150°	1394.9	74.2
90°-180°	1880.0	99.9
0°-180°	1881.0	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	0	0	0	0	0	
5°	0	0	0	0	0	0
15°	0	0	0	0	0	0
25°	0	0	0	0	0	0
35°	0	0	0	0	0	0
45°	0	0	0	0	0	0
55°	0	0	0	0	0	0
65°	0	0	0	0	0	0
75°	0	0	0	0	0	0
85°	0	0	0	0	0	0
90°	1	6	10	13	14	1
95°	25	10	10	13	13	31
105°	137	140	142	146	130	143
115°	255	257	256	257	257	251
125°	359	361	360	361	362	321
135°	445	445	447	448	448	343
145°	513	515	515	515	516	321
155°	563	563	562	564	562	260
165°	594	592	592	595	591	168
175°	608	605	605	609	604	58
180°	608	608	608	608	608	

TEST NUMBER: P983235

CATALOG NUMBER: S124IW-B470UB2750-4F0-XX-W2A_2700K

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	0.0	0.0	0.0	0.0	0.0
2.5°	0.0	0.0	0.0	0.0	0.0
5°	0.0	0.0	0.0	0.0	0.0
7.5°	0.0	0.0	0.0	0.0	0.0
10°	0.0	0.0	0.0	0.0	0.0
12.5°	0.0	0.0	0.0	0.0	0.0
15°	0.0	0.0	0.0	0.0	0.0
17.5°	0.0	0.0	0.0	0.0	0.0
20°	0.0	0.0	0.0	0.0	0.0
22.5°	0.0	0.0	0.0	0.0	0.0
25°	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0
90°	1.4	6.4	10.0	12.7	13.6
92.5°	6.8	5.9	9.5	12.3	12.3
95°	25.0	9.5	10.0	12.7	13.2
97.5°	47.7	57.7	10.0	12.3	12.7
100°	74.5	82.7	20.0	12.3	12.7
102.5°	104.5	110.0	115.4	13.2	13.2
105°	136.8	139.5	141.8	145.8	129.5
107.5°	166.3	167.7	170.8	173.1	174.9
110°	196.3	197.6	200.4	201.3	202.6

TEST NUMBER: P983235

CATALOG NUMBER: S124IW-B470UB2750-4F0-XX-W2A_2700K

CANDELA DISTRIBUTION (continued):

	0°	22.5°	45°	67.5°	90°
112.5°	225.4	228.1	229.0	228.5	230.4
115°	255.3	256.7	256.3	257.2	257.2
117.5°	282.2	284.0	285.3	284.9	284.9
120°	309.4	311.2	310.8	311.7	310.8
122.5°	334.9	335.8	336.7	337.1	336.2
125°	358.9	360.8	359.9	361.2	361.7
127.5°	382.1	382.6	384.8	384.4	383.9
130°	404.4	404.8	406.2	406.7	406.7
132.5°	424.8	425.7	427.6	428.0	427.6
135°	445.3	444.8	446.6	447.5	448.5
137.5°	463.4	463.4	465.7	466.6	466.2
140°	481.2	482.1	483.0	484.3	484.8
142.5°	497.1	498.9	499.3	500.2	500.2
145°	513.4	514.8	514.8	515.2	516.2
147.5°	526.1	528.9	528.4	528.9	529.3
150°	540.2	542.0	541.6	541.6	542.0
152.5°	552.0	553.4	552.5	553.4	553.0
155°	562.9	563.4	562.0	563.9	562.5
157.5°	572.5	572.5	570.7	572.9	570.7
160°	580.7	579.3	578.9	581.6	578.9
162.5°	587.9	586.1	585.7	588.4	585.2
165°	593.8	591.6	591.6	595.2	591.1
167.5°	598.8	596.6	596.1	600.2	595.7
170°	602.9	600.2	600.7	604.3	599.8
172.5°	605.7	602.9	603.4	607.0	602.0
175°	607.5	604.8	605.2	609.3	603.8
177.5°	608.8	605.7	606.6	610.2	604.8
180°	607.5	607.5	607.5	607.5	607.5

(END OF REPORT)