

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: NEO-RAY

Report Number: P983260

Luminaire Tested: S124IW-B770UB30-4F0-XX-W2A-1

Issue Date: 5/2/2025

Test Information

Test Method: LM-79-2019
Report Number: P983260
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-1807-864-10)
Test Lab: INNOVATION CENTER
Issue Date: 5/2/2025
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: NEO-RAY
Catalog Number: S124IW-B770UB30-4F0-XX-W2A-1
Description: Define 4 Indirect Wall Mount with 3000K BioUP LEDs {m-DER=0.589} {m-EER=0.647}
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 2711.0 lumens
Efficiency: N/A
Efficacy: 116.9 lumens/watt
Spacing Criteria (0/90/45): - / - / -
Luminous Opening: Rectangular (W 0.33' x L: 4' x H: 0')
CIE Type: Indirect

Input Watts (W): 23.2
Input Voltage (V):
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P983260

CATALOG NUMBER: S124IW-B770UB30-4F0-XX-W2A-1

Luminous Intensity Polar Plot





TEST NUMBER: P983260

CATALOG NUMBER: S124IW-B770UB30-4F0-XX-W2A-1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10
RCR																	
0	95	95	95	95	81	81	81	81	56	56	56	32	32	32	10	10	10
1	87	83	79	76	74	71	68	65	48	47	45	28	27	26	9	9	8
2	79	72	66	62	67	62	57	53	42	40	37	24	23	22	8	7	7
3	72	63	56	51	61	54	49	44	37	34	31	21	20	18	7	6	6
4	65	56	48	43	56	48	42	37	33	29	26	19	17	16	6	6	5
5	60	49	42	36	51	42	36	32	29	25	22	17	15	13	5	5	4
6	55	44	36	31	47	38	32	27	26	22	19	15	13	11	5	4	4
7	50	39	32	27	43	34	28	23	23	19	17	14	11	10	4	4	3
8	47	35	28	23	40	30	24	20	21	17	14	12	10	9	4	3	3
9	43	32	25	20	37	27	22	18	19	15	13	11	9	8	4	3	3
10	40	29	22	18	34	25	19	16	17	14	11	10	8	7	3	3	2

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	0	0	0
5°	0	0	0
10°	0	0	0
15°	0	0	0
20°	0	0	0
25°	0	0	0
30°	0	0	0
35°	0	0	0
40°	0	0	0
45°	0	0	0
50°	0	0	0
55°	0	0	0
60°	0	0	0
65°	0	0	0
70°	0	0	0
75°	0	0	0
80°	0	0	0
85°	0	0	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
Vertical Angle: 0°
Luminance: 0 cd/sqm

TEST NUMBER: P983260

CATALOG NUMBER: S124IW-B770UB30-4F0-XX-W2A-1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	0.0	0.0
10°-20°	0.0	0.0
20°-30°	0.0	0.0
30°-40°	0.0	0.0
40°-50°	0.0	0.0
50°-60°	0.0	0.0
60°-70°	0.0	0.0
70°-80°	0.0	0.0
80°-90°	2.1	0.1
90°-100°	63.6	2.3
100°-110°	190.6	7.0
110°-120°	323.8	11.9
120°-130°	427.1	15.8
130°-140°	479.7	17.7
140°-150°	471.4	17.4
150°-160°	396.5	14.6
160°-170°	263.8	9.7
170°-180°	92.4	3.4
0°-30°	0.0	0.0
0°-40°	0.0	0.0
0°-60°	0.0	0.0
0°-90°	2.1	0.1
90°-120°	578.0	21.3
90°-150°	1956.2	72.2
90°-180°	2709.0	99.9
0°-180°	2711.0	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	0	0	0	0	0	
5°	0	0	0	0	0	0
15°	0	0	0	0	0	0
25°	0	0	0	0	0	0
35°	0	0	0	0	0	0
45°	0	0	0	0	0	0
55°	0	0	0	0	0	0
65°	0	0	0	0	0	0
75°	0	0	0	0	0	0
85°	0	0	0	0	0	0
90°	2	11	17	21	23	3
95°	45	52	57	60	60	49
105°	176	177	180	182	184	187
115°	329	329	328	327	326	325
125°	480	480	479	477	476	427
135°	618	623	623	621	619	478
145°	751	754	755	754	752	470
155°	861	861	860	863	860	396
165°	937	935	933	938	935	264
175°	975	971	970	976	970	93
180°	976	976	976	976	976	

TEST NUMBER: P983260

CATALOG NUMBER: S124IW-B770UB30-4F0-XX-W2A-1

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	0.0	0.0	0.0	0.0	0.0
2.5°	0.0	0.0	0.0	0.0	0.0
5°	0.0	0.0	0.0	0.0	0.0
7.5°	0.0	0.0	0.0	0.0	0.0
10°	0.0	0.0	0.0	0.0	0.0
12.5°	0.0	0.0	0.0	0.0	0.0
15°	0.0	0.0	0.0	0.0	0.0
17.5°	0.0	0.0	0.0	0.0	0.0
20°	0.0	0.0	0.0	0.0	0.0
22.5°	0.0	0.0	0.0	0.0	0.0
25°	0.0	0.0	0.0	0.0	0.0
27.5°	0.0	0.0	0.0	0.0	0.0
30°	0.0	0.0	0.0	0.0	0.0
32.5°	0.0	0.0	0.0	0.0	0.0
35°	0.0	0.0	0.0	0.0	0.0
37.5°	0.0	0.0	0.0	0.0	0.0
40°	0.0	0.0	0.0	0.0	0.0
42.5°	0.0	0.0	0.0	0.0	0.0
45°	0.0	0.0	0.0	0.0	0.0
47.5°	0.0	0.0	0.0	0.0	0.0
50°	0.0	0.0	0.0	0.0	0.0
52.5°	0.0	0.0	0.0	0.0	0.0
55°	0.0	0.0	0.0	0.0	0.0
57.5°	0.0	0.0	0.0	0.0	0.0
60°	0.0	0.0	0.0	0.0	0.0
62.5°	0.0	0.0	0.0	0.0	0.0
65°	0.0	0.0	0.0	0.0	0.0
67.5°	0.0	0.0	0.0	0.0	0.0
70°	0.0	0.0	0.0	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0
90°	2.3	10.6	16.6	21.1	22.7
92.5°	19.6	29.4	33.2	35.5	36.2
95°	45.3	52.1	57.4	59.7	59.7
97.5°	72.5	78.5	84.6	87.6	87.6
100°	105.7	108.7	115.5	117.0	117.0
102.5°	140.4	141.2	147.2	149.5	150.3
105°	175.9	176.7	179.7	182.0	184.2
107.5°	212.9	213.7	214.4	217.5	216.7
110°	250.7	252.2	251.4	249.9	252.2

TEST NUMBER: P983260

CATALOG NUMBER: S124IW-B770UB30-4F0-XX-W2A-1

CANDELA DISTRIBUTION (continued):

	0°	22.5°	45°	67.5°	90°
112.5°	289.9	289.9	288.4	288.4	288.4
115°	329.2	329.2	327.7	326.9	326.2
117.5°	366.2	366.2	365.5	363.2	360.9
120°	403.2	406.2	404.0	400.2	401.7
122.5°	441.7	442.5	441.7	439.5	435.7
125°	479.5	479.5	478.7	477.2	475.7
127.5°	513.5	515.7	514.2	512.7	511.9
130°	549.7	552.0	552.0	550.5	547.4
132.5°	586.7	588.2	587.4	585.9	585.2
135°	618.4	622.9	622.9	621.4	619.2
137.5°	653.9	656.2	657.7	655.4	656.2
140°	689.4	690.9	690.9	690.1	689.4
142.5°	721.9	723.4	722.6	722.6	722.6
145°	751.3	754.3	755.1	754.3	752.1
147.5°	781.5	785.3	784.5	783.8	783.0
150°	808.7	811.7	811.7	811.7	811.0
152.5°	834.4	835.9	836.6	838.9	836.6
155°	860.8	860.8	860.0	863.1	860.0
157.5°	883.4	881.9	881.9	884.2	881.9
160°	903.1	902.3	901.6	903.8	900.1
162.5°	921.2	918.9	918.2	922.7	918.9
165°	937.1	934.8	933.3	937.8	934.8
167.5°	949.9	946.9	946.9	951.4	946.9
170°	960.5	956.7	957.4	962.0	956.7
172.5°	968.0	965.0	965.0	970.3	965.0
175°	974.8	971.0	970.3	975.6	970.3
177.5°	977.8	974.0	974.0	979.3	973.3
180°	976.3	976.3	976.3	976.3	976.3

(END OF REPORT)