

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: NEO-RAY

Report Number: P1035260

Luminaire Tested: S125DIW-B375D1050UB50-4F0-XX-W2A-D1

Issue Date: 5/6/2025

Test Information

Test Method: LM-79-2019
Report Number: P1035260
REPORT IS A COMBINATION OF REPORTS P1003440 AND P1007351
Test Lab: INNOVATION CENTER
Issue Date: 5/6/2025
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: NEO-RAY
Catalog Number: S125DIW-B375D1050UB50-4F0-XX-W2A-D1
Description: Define 5 Direct/Indirect Wall Mount with 5000K BioUP LEDs {m-DER=1.015} {m-EER=1.115}
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 4913.0 lumens
Efficiency: N/A
Efficacy: 110.4 lumens/watt
Spacing Criteria (0/90/45): 1.21 / 1.21 / 1.34
Luminous Opening: Rectangular w/ Sides (W: 0.42' x L: 4' x H: 0.1')
CIE Type: Semi-Indirect

Input Watts (W): 44.5
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1035260

CATALOG NUMBER: S125DIW-B375D1050UB50-4F0-XX-W2A-D1

Luminous Intensity Polar Plot



TEST NUMBER: P1035260

CATALOG NUMBER: S125DIW-B375D1050UB50-4F0-XX-W2A-D1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10
RCR																	
0	101	101	101	101	91	91	91	91	70	70	70	51	51	51	34	34	34
1	92	88	84	80	82	78	75	72	61	58	56	45	43	42	30	29	28
2	84	76	70	65	74	68	63	59	53	49	46	39	37	35	26	24	23
3	76	67	60	54	68	60	54	49	46	42	39	34	31	29	23	21	20
4	69	59	51	45	62	53	46	41	41	36	33	30	27	25	20	18	17
5	64	52	44	39	56	47	40	35	37	32	28	27	24	21	18	16	15
6	58	47	39	33	52	42	35	30	33	28	24	24	21	18	16	14	13
7	54	42	34	29	48	38	31	26	30	25	21	22	19	16	15	13	11
8	50	38	30	25	44	34	28	23	27	22	19	20	17	14	14	12	10
9	46	34	27	22	41	31	25	20	25	20	17	18	15	13	13	10	9
10	43	31	24	20	38	28	22	18	22	18	15	17	14	11	12	10	8

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	2827	2827	2827
5°	2832	2768	2775
10°	2811	2712	2704
15°	2777	2646	2616
20°	2730	2566	2530
25°	2676	2482	2425
30°	2609	2390	2330
35°	2547	2305	2242
40°	2485	2216	2153
45°	2413	2138	2074
50°	2345	2054	2002
55°	2263	1974	1919
60°	2173	1882	1833
65°	2079	1786	1736
70°	1972	1657	1636
75°	1802	1530	1514
80°	1580	1375	1378
85°	1361	1251	1308

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 2413 cd/sqm

TEST NUMBER: P1035260

CATALOG NUMBER: S125DIW-B375D1050UB50-4F0-XX-W2A-D1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	41.8	0.8
10°-20°	118.5	2.4
20°-30°	176.3	3.6
30°-40°	208.8	4.2
40°-50°	215.8	4.4
50°-60°	198.8	4.0
60°-70°	160.7	3.3
70°-80°	107.6	2.2
80°-90°	57.6	1.2
90°-100°	115.8	2.4
100°-110°	273.9	5.6
110°-120°	440.9	9.0
120°-130°	568.8	11.6
130°-140°	631.4	12.9
140°-150°	615.9	12.5
150°-160°	516.7	10.5
160°-170°	343.5	7.0
170°-180°	120.2	2.4
0°-30°	336.6	6.9
0°-40°	545.3	11.1
0°-60°	960.0	19.5
0°-90°	1285.8	26.2
90°-120°	830.6	16.9
90°-150°	2646.8	53.9
90°-180°	3627.0	73.8
0°-180°	4913.0	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	441	441	441	441	441	
5°	441	440	437	441	440	42
15°	421	422	419	421	420	119
25°	383	384	382	383	381	176
35°	331	334	333	334	334	207
45°	273	278	280	283	283	211
55°	210	217	224	228	230	188
65°	144	154	165	171	173	143
75°	80	91	105	113	116	84
85°	24	38	53	63	66	25
90°	8	30	51	66	72	9
95°	70	83	108	124	129	72
105°	229	241	260	274	281	244
115°	428	436	449	456	457	424
125°	623	629	638	643	644	558
135°	809	815	819	824	822	624
145°	980	983	986	988	987	612
155°	1121	1121	1122	1126	1121	516
165°	1218	1216	1218	1221	1216	344
175°	1267	1263	1263	1269	1262	120
180°	1270	1270	1270	1270	1270	

TEST NUMBER: P1035260

CATALOG NUMBER: S125DIW-B375D1050UB50-4F0-XX-W2A-D1

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	441.3	441.3	441.3	441.3	441.3
2.5°	442.6	441.7	438.7	441.7	441.3
5°	441.3	440.4	437.4	440.8	440.4
7.5°	438.2	437.8	434.8	437.8	437.4
10°	433.9	433.9	430.5	433.5	433.1
12.5°	427.9	428.3	425.7	427.9	426.6
15°	421.4	421.8	418.8	421.4	419.6
17.5°	413.2	414.0	411.0	413.2	411.9
20°	404.1	404.9	401.9	403.2	403.2
22.5°	393.7	395.4	392.0	393.7	392.4
25°	382.9	384.2	381.6	383.3	381.1
27.5°	371.2	372.9	369.9	371.2	370.3
30°	357.8	360.4	357.8	358.6	358.2
32.5°	345.7	347.8	346.1	347.0	346.5
35°	331.4	334.4	333.1	334.4	334.4
37.5°	317.5	320.1	319.7	321.4	321.0
40°	303.3	306.7	306.3	308.0	308.9
42.5°	287.7	292.5	293.8	295.9	295.9
45°	273.0	277.7	279.9	282.9	283.4
47.5°	257.8	262.2	265.6	270.0	270.8
50°	242.3	247.0	251.8	256.5	257.8
52.5°	225.8	231.9	237.9	243.1	244.0
55°	209.8	216.7	223.7	228.4	230.2
57.5°	193.4	201.6	209.4	214.6	215.9
60°	176.9	185.6	194.2	200.7	202.0
62.5°	160.9	169.6	179.1	186.5	188.2
65°	144.5	154.4	164.8	171.3	173.0
67.5°	129.4	138.9	149.3	157.0	159.2
70°	112.5	122.4	133.7	141.9	144.5
72.5°	96.0	106.4	119.0	128.1	129.8
75°	79.6	90.9	104.7	113.3	115.5
77.5°	63.6	76.6	89.6	99.1	100.8
80°	48.9	61.9	76.6	86.1	87.8
82.5°	35.5	49.3	64.5	73.5	77.0
85°	23.8	38.1	53.2	62.7	66.2
87.5°	15.1	29.0	43.7	53.6	56.7
90°	7.9	29.7	51.3	66.2	72.2
92.5°	35.7	53.2	77.2	93.7	98.7
95°	69.8	83.1	107.7	124.1	129.1
97.5°	104.0	115.4	143.5	158.5	162.6
100°	143.1	152.1	178.9	196.9	201.5
102.5°	185.1	198.3	216.7	235.2	240.8
105°	229.2	241.1	260.0	274.5	280.6
107.5°	277.2	288.2	305.7	317.3	319.9
110°	327.1	337.3	352.3	363.6	365.6

TEST NUMBER: P1035260

CATALOG NUMBER: S125DIW-B375D1050UB50-4F0-XX-W2A-D1

CANDELA DISTRIBUTION (continued):

	0°	22.5°	45°	67.5°	90°
112.5°	378.5	384.4	400.0	408.8	409.9
115°	428.5	435.5	448.7	455.6	457.2
117.5°	479.5	482.6	495.4	503.8	502.8
120°	526.9	533.2	544.1	551.5	550.1
122.5°	577.8	579.3	591.8	597.7	597.3
125°	623.3	628.8	638.5	643.4	644.5
127.5°	673.3	675.8	684.1	689.6	690.3
130°	717.7	722.3	730.3	735.4	735.5
132.5°	761.8	770.7	774.0	779.0	777.9
135°	809.3	814.7	818.8	824.4	822.5
137.5°	853.7	859.1	862.9	869.1	865.9
140°	895.7	900.7	904.1	910.8	907.7
142.5°	938.2	941.8	945.7	950.6	947.4
145°	979.7	983.3	986.2	988.4	987.2
147.5°	1017.8	1020.8	1022.8	1026.7	1019.5
150°	1056.4	1055.4	1059.4	1059.4	1057.8
152.5°	1088.0	1090.0	1091.0	1093.9	1090.0
155°	1120.6	1120.6	1121.6	1125.6	1120.6
157.5°	1150.3	1148.3	1149.3	1153.2	1146.3
160°	1176.0	1173.0	1174.0	1177.9	1173.0
162.5°	1198.7	1196.7	1196.7	1201.7	1195.7
165°	1218.5	1216.5	1217.5	1221.4	1215.5
167.5°	1236.2	1232.3	1232.3	1238.2	1232.3
170°	1250.1	1246.1	1246.1	1252.1	1245.1
172.5°	1260.0	1256.0	1256.0	1261.9	1256.0
175°	1266.9	1262.9	1262.9	1268.9	1261.9
177.5°	1271.8	1267.9	1266.9	1272.8	1265.9
180°	1269.8	1269.8	1269.8	1269.8	1269.8

(END OF REPORT)