

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P225133

Luminaire Tested: **LSRWM2B10FL409027D010 2LBD*GPH**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P225133
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P14831)
Test Lab: INNOVATION CENTER (G1)
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LSRWM2B10FL409027D010 2LBD*GPH
Description: 1000 Lumen, 2inch Portfolio LED Cylinder
FLOOD OPTIC
SPUN ROUND TRIM WITH GRAPHITE FINISH
Light Source: -
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 799.2 lumens
Efficiency: N/A
Efficacy: 77.6 lumens/watt
Spacing Criteria (0/90/45): 0.61 / 0.61 / 0.59
Luminous Opening: Rectangular (W 0.17' x L: 0.17' x H: 0')
CIE Type: Direct


Input Watts (W): 10.3
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P225133

CATALOG NUMBER: LSRWM2B10FL409027D010 2LBD*GPH

Luminous Intensity Polar Plot





TEST NUMBER: P225133

CATALOG NUMBER: LSRWM2B10FL409027D010 2LBD*GPH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20					20					20					20
RC	80				70					50					30					10
RW	70	50	30	10	70	50	30	10		50	30	10			50	30	10			50
RCR																				
0	119	119	119	119	116	116	116	116		111	111	111			106	106	106			102
1	114	112	110	108	112	110	108	106		106	104	103			102	101	100			99
2	110	106	102	100	108	104	101	98		101	99	96			98	96	94			95
3	106	100	96	93	104	99	95	92		96	93	91			94	92	89			92
4	102	95	91	87	100	94	90	87		92	89	86			90	87	85			89
5	98	91	86	83	96	90	85	82		88	84	81			87	83	81			85
6	94	87	82	78	93	86	81	78		85	81	78			83	80	77			82
7	91	83	78	75	89	82	78	74		81	77	74			80	76	74			79
8	87	80	75	71	86	79	74	71		78	74	71			77	73	71			76
9	84	76	72	68	83	76	71	68		75	71	68			74	70	68			73
10	81	73	69	65	80	73	68	65		72	68	65			72	68	65			71

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	724995
5°	710345
10°	631202
15°	495207
20°	333062
25°	193778
30°	97057
35°	45300
40°	21136
45°	8929
50°	4278
55°	2769
60°	1549
65°	0
70°	0
75°	0
80°	0
85°	0



TEST NUMBER: P225133

CATALOG NUMBER: LSRWM2B10FL409027D010 2LBD*GPH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	167.2	20.9
10°-20°	335.2	41.9
20°-30°	212.0	26.5
30°-40°	65.9	8.3
40°-50°	14.7	1.8
50°-60°	3.7	0.5
60°-70°	0.5	0.1
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	714.4	89.4
0°-40°	780.3	97.6
0°-60°	798.7	99.9
0°-90°	799.2	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	799.2	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1872	
5°	1827	167
15°	1235	335
25°	453	212
35°	96	66
45°	16	15
55°	4	4
65°	0	0
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P225133

CATALOG NUMBER: LSRWM2B10FL409027D010 2LBD*GPH

CANDELA DISTRIBUTION (FULL):

0°	
0°	1871.7
2.5°	1863.6
5°	1826.9
7.5°	1740.3
10°	1604.8
12.5°	1433.6
15°	1234.9
17.5°	1019.9
20°	808.0
22.5°	617.5
25°	453.4
27.5°	317.9
30°	217.0
32.5°	143.7
35°	95.8
37.5°	64.2
40°	41.8
42.5°	25.5
45°	16.3
47.5°	11.2
50°	7.1
52.5°	5.1
55°	4.1
57.5°	3.1
60°	2.0
62.5°	1.0
65°	0.0
67.5°	0.0
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)