

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P224545

Luminaire Tested: **LSRWM2B10FL409727D010 2LBDL*GPH**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P224545
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P14831)
Test Lab: INNOVATION CENTER (G1)
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LSRWM2B10FL409727D010 2LBDL*GPH
Description: 1000 Lumen, 2inch Portfolio LED Cylinder
FLOOD OPTIC
LENSED SPUN ROUND TRIM WITH GRAPHITE FINISH
Light Source: -
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 675.1 lumens
Efficiency: N/A
Efficacy: 65.5 lumens/watt
Spacing Criteria (0/90/45): 0.61 / 0.61 / 0.59
Luminous Opening: Rectangular (W 0.17' x L: 0.17' x H: 0')
CIE Type: Direct


Input Watts (W): 10.3
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P224545

CATALOG NUMBER: LSRWM2B10FL409727D010 2LBDL*GPH

Luminous Intensity Polar Plot





TEST NUMBER: P224545

CATALOG NUMBER: LSRWM2B10FL409727D010 2LBDL*GPH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10				0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0			
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	114	112	110	108	112	110	108	106	106	104	103	102	101	100	99	98	97	95			
2	110	106	102	100	108	104	101	98	101	99	96	98	96	94	95	94	92	91			
3	106	100	96	93	104	99	95	92	96	93	91	94	92	89	92	90	88	87			
4	102	95	91	87	100	94	90	87	92	89	86	90	87	85	89	86	84	83			
5	98	91	86	83	96	90	85	82	88	84	81	87	83	81	85	82	80	79			
6	94	87	82	78	93	86	81	78	85	81	78	83	80	77	82	79	77	75			
7	91	83	78	75	89	82	78	74	81	77	74	80	76	74	79	76	73	72			
8	87	80	75	71	86	79	74	71	78	74	71	77	73	71	76	73	70	69			
9	84	76	72	68	83	76	71	68	75	71	68	74	70	68	73	70	68	66			
10	81	73	69	65	80	73	68	65	72	68	65	72	68	65	71	67	65	64			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	612433
5°	600036
10°	533187
15°	418334
20°	281330
25°	163690
30°	81984
35°	38255
40°	17849
45°	7560
50°	3616
55°	2296
60°	1317
65°	0
70°	0
75°	0
80°	0
85°	0



TEST NUMBER: P224545

CATALOG NUMBER: LSRWM2B10FL409727D010 2LBDL*GPH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	141.3	20.9
10°-20°	283.2	41.9
20°-30°	179.0	26.5
30°-40°	55.7	8.3
40°-50°	12.4	1.8
50°-60°	3.1	0.5
60°-70°	0.4	0.1
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	603.5	89.4
0°-40°	659.2	97.6
0°-60°	674.7	99.9
0°-90°	675.1	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	675.1	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1581	
5°	1543	141
15°	1043	283
25°	383	179
35°	81	56
45°	14	12
55°	3	3
65°	0	0
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P224545

CATALOG NUMBER: LSRWM2B10FL409727D010 2LBDL*GPH

CANDELA DISTRIBUTION (FULL):

	0°
0°	1581.1
2.5°	1574.2
5°	1543.2
7.5°	1470.1
10°	1355.6
12.5°	1211.0
15°	1043.2
17.5°	861.5
20°	682.5
22.5°	521.6
25°	383.0
27.5°	268.5
30°	183.3
32.5°	121.4
35°	80.9
37.5°	54.2
40°	35.3
42.5°	21.5
45°	13.8
47.5°	9.5
50°	6.0
52.5°	4.3
55°	3.4
57.5°	2.6
60°	1.7
62.5°	0.9
65°	0.0
67.5°	0.0
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)