

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P224917

Luminaire Tested: **LSSQWM2B10FL409727D010 2LBD*H**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P224917
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (156)
Test Lab: INNOVATION CENTER-P2
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LSSQWM2B10FL409727D010 2LBD*H
Description: 1000 Lumen, 2inch Portfolio LED Cylinder
FLOOD OPTIC
SPUN ROUND TRIM WITH HAZE FINISH
Light Source: -
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 711.1 lumens
Efficiency: N/A
Efficacy: 69.0 lumens/watt
Spacing Criteria (0/90/45): 0.6 / 0.6 / 0.59
Luminous Opening: Rectangular (W 0.17' x L: 0.17' x H: 0')
CIE Type: Direct


Input Watts (W): 10.3
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P224917

CATALOG NUMBER: LSSQWM2B10FL409727D010 2LBD*H

Luminous Intensity Polar Plot





TEST NUMBER: P224917

CATALOG NUMBER: LSSQWM2B10FL409727D010 2LBD*H

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20					20					20					20
RC	80				70					50					30					10
RW	70	50	30	10	70	50	30	10		50	30	10			50	30	10			50
RCR																				
0	119	119	119	119	116	116	116	116		111	111	111			106	106	106			102
1	114	112	110	108	112	110	108	106		106	104	103			102	101	100			99
2	110	106	103	100	108	104	101	99		101	99	97			98	96	94			96
3	106	100	96	93	104	99	95	92		97	94	91			94	92	90			92
4	102	96	91	88	100	94	90	87		92	89	86			91	88	85			89
5	98	91	86	83	96	90	86	82		89	85	82			87	84	81			86
6	94	87	82	79	93	86	82	78		85	81	78			84	80	77			82
7	91	83	78	75	90	83	78	75		82	77	74			80	77	74			79
8	88	80	75	72	87	79	75	72		78	74	71			77	74	71			77
9	85	77	72	69	84	76	72	69		75	71	68			75	71	68			74
10	82	74	69	66	81	73	69	66		73	69	66			72	68	66			71

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	659573
5°	645762
10°	568743
15°	446204
20°	296334
25°	170101
30°	85294
35°	39389
40°	16029
45°	7176
50°	3736
55°	2296
60°	1085
65°	0
70°	0
75°	0
80°	0
85°	0



TEST NUMBER: P224917

CATALOG NUMBER: LSSQWM2B10FL409727D010 2LBD*H

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	151.7	21.3
10°-20°	301.2	42.4
20°-30°	187.1	26.3
30°-40°	56.4	7.9
40°-50°	11.6	1.6
50°-60°	3.0	0.4
60°-70°	0.2	0.0
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	640.0	90.0
0°-40°	696.4	97.9
0°-60°	710.9	100.0
0°-90°	711.1	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	711.1	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1703	
5°	1661	152
15°	1113	301
25°	398	187
35°	83	56
45°	13	12
55°	3	3
65°	0	0
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P224917

CATALOG NUMBER: LSSQWM2B10FL409727D010 2LBD*H

CANDELA DISTRIBUTION (FULL):

	0°
0°	1702.8
1°	1697.3
2°	1689.7
3°	1684.2
4°	1675.9
5°	1660.8
6°	1636.7
7°	1603.6
8°	1556.1
9°	1502.4
10°	1446.0
11°	1386.1
12°	1323.4
13°	1258.0
14°	1186.4
15°	1112.7
17.5°	915.1
20°	718.9
22.5°	545.3
25°	398.0
27.5°	280.9
30°	190.7
32.5°	125.3
35°	83.3
37.5°	51.6
40°	31.7
42.5°	20.7
45°	13.1
47.5°	8.3
50°	6.2
52.5°	4.1
55°	3.4
57.5°	2.1
60°	1.4
62.5°	0.0
65°	0.0
67.5°	0.0
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0



TEST NUMBER: P224917

CATALOG NUMBER: LSSQWM2B10FL409727D010 2LBD*H

CANDELA DISTRIBUTION (continued):

0°
90° | 0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







85°	0.0
87.5°	0.0



(END OF REPORT)