

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P224866

Luminaire Tested: **LSSQ2B10FL409030D010 2LBD*B**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P224866
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P14834)
Test Lab: INNOVATION CENTER (G1)
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LSSQ2B10FL409030D010 2LBD*B
Description: 1000 Lumen, 2inch Portfolio LED Cylinder
FLOOD OPTIC
SPUN ROUND TRIM WITH BLACK FINISH
Light Source: -
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 812.5 lumens
Efficiency: N/A
Efficacy: 78.9 lumens/watt
Spacing Criteria (0/90/45): 0.61 / 0.61 / 0.6
Luminous Opening: Rectangular (W 0.17' x L: 0.17' x H: 0')
CIE Type: Direct


Input Watts (W): 10.3
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P224866

CATALOG NUMBER: LSSQ2B10FL409030D010 2LBD*B

Luminous Intensity Polar Plot





TEST NUMBER: P224866

CATALOG NUMBER: LSSQ2B10FL409030D010 2LBD*B

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20					20					20					20					20
RC	80					70					50					30					10
RW	70	50	30	10		70	50	30	10		50	30	10			50	30	10			0
RCR																					
0	119	119	119	119		116	116	116	116		111	111	111			106	106	106			100
1	114	112	110	108		112	110	108	106		106	104	103			102	101	100			95
2	110	106	103	100		108	104	101	99		101	99	96			98	96	94			91
3	106	100	96	93		104	99	95	92		97	93	91			94	92	89			87
4	102	95	91	87		100	94	90	87		92	89	86			90	87	85			83
5	98	91	86	83		96	90	86	82		88	85	82			87	84	81			79
6	94	87	82	79		93	86	82	78		85	81	78			84	80	77			76
7	91	83	78	75		90	83	78	75		81	77	74			80	77	74			72
8	87	80	75	72		86	79	75	71		78	74	71			77	74	71			69
9	84	77	72	69		83	76	72	68		75	71	68			74	71	68			67
10	82	74	69	66		81	73	69	66		73	68	65			72	68	65			64

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	735144
5°	722360
10°	644418
15°	509363
20°	339616
25°	197026
30°	98623
35°	46388
40°	18153
45°	8107
50°	3796
55°	2161
60°	852
65°	0
70°	0
75°	0
80°	0
85°	0



TEST NUMBER: P224866

CATALOG NUMBER: LSSQ2B10FL409030D010 2LBD*B

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	170.3	21.0
10°-20°	343.8	42.3
20°-30°	216.3	26.6
30°-40°	66.1	8.1
40°-50°	13.0	1.6
50°-60°	2.9	0.4
60°-70°	0.1	0.0
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	730.4	89.9
0°-40°	796.5	98.0
0°-60°	812.4	100.0
0°-90°	812.5	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	812.5	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1898	
5°	1858	170
15°	1270	344
25°	461	216
35°	98	66
45°	15	13
55°	3	3
65°	0	0
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P224866

CATALOG NUMBER: LSSQ2B10FL409030D010 2LBD*B

CANDELA DISTRIBUTION (FULL):

	0°
0°	1897.9
2.5°	1893.7
5°	1857.8
7.5°	1773.4
10°	1638.4
12.5°	1469.6
15°	1270.2
17.5°	1048.6
20°	823.9
22.5°	631.9
25°	461.0
27.5°	324.9
30°	220.5
32.5°	148.8
35°	98.1
37.5°	60.1
40°	35.9
42.5°	23.2
45°	14.8
47.5°	9.5
50°	6.3
52.5°	4.2
55°	3.2
57.5°	2.1
60°	1.1
62.5°	0.0
65°	0.0
67.5°	0.0
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)