

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P222219

Luminaire Tested: **LSRWM2B10NFL259730D010 2LBDL\*WMH**

Issue Date: 3/3/2020

**Test Information**

Test Method: LM-41-14  
Report Number: P222219  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (155)  
Test Lab: INNOVATION CENTER-P2  
Issue Date: 3/3/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: io LED  
Catalog Number: LSRWM2B10NFL259730D010 2LBDL\*WMH  
Description: 1000 Lumen, 2inch Portfolio LED Cylinder  
NARROW FLOOD OPTIC  
LENSED SPUN ROUND TRIM WITH WHEAT METALLIC HAZE FINISH  
Light Source: -  
Ballast/Driver: -

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 708.5 lumens  
Efficiency: N/A  
Efficacy: 68.8 lumens/watt  
Spacing Criteria (0/90/45): 0.39 / 0.39 / 0.35  
Luminous Opening: Rectangular (W 0.17' x L: 0.17' x H: 0')  
CIE Type: Direct


Input Watts (W): 10.3  
Input Voltage (V): NR  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P222219

CATALOG NUMBER: LSRWM2B10NFL259730D010 2LBDL\*WMH

### Luminous Intensity Polar Plot





TEST NUMBER: P222219

CATALOG NUMBER: LSRWM2B10NFL259730D010 2LBDL\*WMH

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

|     |     |     |     |     |  |     |     |     |     |  |     |     |     |  |     |     |     |  |     |     |     |
|-----|-----|-----|-----|-----|--|-----|-----|-----|-----|--|-----|-----|-----|--|-----|-----|-----|--|-----|-----|-----|
| RF  | 20  |     |     |     |  | 20  |     |     |     |  | 20  |     |     |  |     | 20  |     |  |     |     | 20  |
| RC  | 80  |     |     |     |  | 70  |     |     |     |  | 50  |     |     |  |     | 30  |     |  |     |     | 10  |
| RW  | 70  | 50  | 30  | 10  |  | 70  | 50  | 30  | 10  |  | 50  | 30  | 10  |  | 50  | 30  | 10  |  | 50  | 30  | 10  |
| RCR |     |     |     |     |  |     |     |     |     |  |     |     |     |  |     |     |     |  |     |     |     |
| 0   | 119 | 119 | 119 | 119 |  | 116 | 116 | 116 | 116 |  | 111 | 111 | 111 |  | 106 | 106 | 106 |  | 102 | 102 | 102 |
| 1   | 115 | 113 | 112 | 110 |  | 113 | 111 | 110 | 108 |  | 107 | 106 | 105 |  | 104 | 103 | 102 |  | 100 | 100 | 99  |
| 2   | 112 | 109 | 106 | 104 |  | 110 | 107 | 104 | 102 |  | 104 | 102 | 100 |  | 101 | 99  | 98  |  | 98  | 97  | 96  |
| 3   | 109 | 105 | 101 | 99  |  | 107 | 103 | 100 | 98  |  | 101 | 98  | 96  |  | 99  | 97  | 95  |  | 96  | 95  | 93  |
| 4   | 106 | 101 | 97  | 95  |  | 104 | 100 | 97  | 94  |  | 98  | 95  | 93  |  | 96  | 94  | 92  |  | 95  | 93  | 91  |
| 5   | 103 | 98  | 94  | 91  |  | 102 | 97  | 94  | 91  |  | 95  | 92  | 90  |  | 94  | 91  | 89  |  | 93  | 90  | 89  |
| 6   | 101 | 95  | 91  | 89  |  | 99  | 94  | 91  | 88  |  | 93  | 90  | 88  |  | 92  | 89  | 87  |  | 91  | 88  | 87  |
| 7   | 98  | 92  | 89  | 86  |  | 97  | 92  | 88  | 86  |  | 91  | 88  | 85  |  | 90  | 87  | 85  |  | 89  | 86  | 85  |
| 8   | 96  | 90  | 86  | 84  |  | 95  | 90  | 86  | 84  |  | 89  | 86  | 83  |  | 88  | 85  | 83  |  | 87  | 85  | 83  |
| 9   | 94  | 88  | 84  | 82  |  | 93  | 88  | 84  | 82  |  | 87  | 84  | 82  |  | 86  | 83  | 81  |  | 85  | 83  | 81  |
| 10  | 92  | 86  | 82  | 80  |  | 91  | 86  | 82  | 80  |  | 85  | 82  | 80  |  | 84  | 82  | 80  |  | 84  | 81  | 79  |

**AVERAGE LUMINANCE (cd/sqm):**

|     |         |
|-----|---------|
|     | 0°      |
| 0°  | 1628131 |
| 5°  | 1503277 |
| 10° | 1017523 |
| 15° | 346192  |
| 20° | 127165  |
| 25° | 67399   |
| 30° | 34663   |
| 35° | 16172   |
| 40° | 5309    |
| 45° | 2684    |
| 50° | 1265    |
| 55° | 473     |
| 60° | 542     |
| 65° | 0       |
| 70° | 0       |
| 75° | 0       |
| 80° | 0       |
| 85° | 0       |



TEST NUMBER: P222219

CATALOG NUMBER: LSRWM2B10NFL259730D010 2LBDL\*WMH

**ZONAL LUMENS:**

| Zone      | Lumens | % Fixture |
|-----------|--------|-----------|
| 0°-10°    | 328.9  | 46.4      |
| 10°-20°   | 276.5  | 39.0      |
| 20°-30°   | 75.9   | 10.7      |
| 30°-40°   | 22.1   | 3.1       |
| 40°-50°   | 4.1    | 0.6       |
| 50°-60°   | 0.9    | 0.1       |
| 60°-70°   | 0.1    | 0.0       |
| 70°-80°   | 0.0    | 0.0       |
| 80°-90°   | 0.0    | 0.0       |
| 90°-100°  | 0.0    | 0.0       |
| 100°-110° | 0.0    | 0.0       |
| 110°-120° | 0.0    | 0.0       |
| 120°-130° | 0.0    | 0.0       |
| 130°-140° | 0.0    | 0.0       |
| 140°-150° | 0.0    | 0.0       |
| 150°-160° | 0.0    | 0.0       |
| 160°-170° | 0.0    | 0.0       |
| 170°-180° | 0.0    | 0.0       |
| 0°-30°    | 681.3  | 96.2      |
| 0°-40°    | 703.4  | 99.3      |
| 0°-60°    | 708.4  | 100.0     |
| 0°-90°    | 708.5  | 100.0     |
| 90°-120°  | 0.0    | 0.0       |
| 90°-150°  | 0.0    | 0.0       |
| 90°-180°  | 0.0    | 0.0       |
| 0°-180°   | 708.5  | 100.0     |

**CANDELA DISTRIBUTION:**

|     | 0°   | Flux |
|-----|------|------|
| 0°  | 4203 |      |
| 5°  | 3866 | 329  |
| 15° | 863  | 277  |
| 25° | 158  | 76   |
| 35° | 34   | 22   |
| 45° | 5    | 4    |
| 55° | 1    | 1    |
| 65° | 0    | 0    |
| 75° | 0    | 0    |
| 85° | 0    | 0    |
| 90° | 0    |      |



TEST NUMBER: P222219

CATALOG NUMBER: LSRWM2B10NFL259730D010 2LBDL\*WMH

**CANDELA DISTRIBUTION (FULL):**

|       | 0°     |
|-------|--------|
| 0°    | 4203.3 |
| 1°    | 4178.8 |
| 2°    | 4135.6 |
| 3°    | 4073.5 |
| 4°    | 3988.3 |
| 5°    | 3866.2 |
| 6°    | 3699.4 |
| 7°    | 3490.7 |
| 8°    | 3236.0 |
| 9°    | 2935.2 |
| 10°   | 2587.0 |
| 11°   | 2205.3 |
| 12°   | 1808.2 |
| 13°   | 1429.2 |
| 14°   | 1106.1 |
| 15°   | 863.3  |
| 17.5° | 487.1  |
| 20°   | 308.5  |
| 22.5° | 219.8  |
| 25°   | 157.7  |
| 27.5° | 111.7  |
| 30°   | 77.5   |
| 32.5° | 54.4   |
| 35°   | 34.2   |
| 37.5° | 14.0   |
| 40°   | 10.5   |
| 42.5° | 7.7    |
| 45°   | 4.9    |
| 47.5° | 2.8    |
| 50°   | 2.1    |
| 52.5° | 1.4    |
| 55°   | 0.7    |
| 57.5° | 0.7    |
| 60°   | 0.7    |
| 62.5° | 0.0    |
| 65°   | 0.0    |
| 67.5° | 0.0    |
| 70°   | 0.0    |
| 72.5° | 0.0    |
| 75°   | 0.0    |
| 77.5° | 0.0    |
| 80°   | 0.0    |
| 82.5° | 0.0    |



TEST NUMBER: P222219

CATALOG NUMBER: LSRWM2B10NFL259730D010 2LBDL\*WMH

CANDELA DISTRIBUTION (continued):

0°  
90° | 0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







|       |     |
|-------|-----|
| 85°   | 0.0 |
| 87.5° | 0.0 |



(END OF REPORT)