

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P222209

Luminaire Tested: **LSSQ2B20NFL259730D010 2LBDLC\*MB**

Issue Date: 3/3/2020

**Test Information**

Test Method: LM-41-14  
Report Number: P222209  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (155)  
Test Lab: INNOVATION CENTER-P2  
Issue Date: 3/3/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: io LED  
Catalog Number: LSSQ2B20NFL259730D010 2LBDLC\*MB  
Description: 2000 Lumen, 2inch Portfolio LED Cylinder  
NARROW FLOOD OPTIC  
LENSED CAST ROUND TRIM WITH MATTE BLACK FINISH  
Light Source: -  
Ballast/Driver: -

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 1269.6 lumens  
Efficiency: N/A  
Efficacy: 60.7 lumens/watt  
Spacing Criteria (0/90/45): 0.39 / 0.39 / 0.35  
Luminous Opening: Rectangular (W 0.17' x L: 0.17' x H: 0')  
CIE Type: Direct


Input Watts (W): 20.9  
Input Voltage (V): NR  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P222209

CATALOG NUMBER: LSSQ2B20NFL259730D010 2LBDLC\*MB

### Luminous Intensity Polar Plot





TEST NUMBER: P222209

CATALOG NUMBER: LSSQ2B20NFL259730D010 2LBDLC\*MB

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

|     |     |     |     |     |     |     |     |     |  |     |     |     |  |  |     |     |     |  |  |     |
|-----|-----|-----|-----|-----|-----|-----|-----|-----|--|-----|-----|-----|--|--|-----|-----|-----|--|--|-----|
| RF  | 20  |     |     |     | 20  |     |     |     |  | 20  |     |     |  |  | 20  |     |     |  |  | 20  |
| RC  | 80  |     |     |     | 70  |     |     |     |  | 50  |     |     |  |  | 30  |     |     |  |  | 0   |
| RW  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  |  | 50  | 30  | 10  |  |  | 50  | 30  | 10  |  |  | 0   |
| RCR |     |     |     |     |     |     |     |     |  |     |     |     |  |  |     |     |     |  |  |     |
| 0   | 119 | 119 | 119 | 119 | 116 | 116 | 116 | 116 |  | 111 | 111 | 111 |  |  | 106 | 106 | 106 |  |  | 100 |
| 1   | 115 | 113 | 112 | 110 | 113 | 111 | 110 | 108 |  | 107 | 106 | 105 |  |  | 104 | 103 | 102 |  |  | 97  |
| 2   | 112 | 109 | 106 | 104 | 110 | 107 | 104 | 102 |  | 104 | 102 | 100 |  |  | 101 | 99  | 98  |  |  | 95  |
| 3   | 109 | 105 | 101 | 99  | 107 | 103 | 100 | 98  |  | 101 | 98  | 96  |  |  | 99  | 97  | 95  |  |  | 92  |
| 4   | 106 | 101 | 97  | 95  | 104 | 100 | 97  | 94  |  | 98  | 95  | 93  |  |  | 96  | 94  | 92  |  |  | 90  |
| 5   | 103 | 98  | 94  | 91  | 102 | 97  | 94  | 91  |  | 95  | 92  | 90  |  |  | 94  | 91  | 89  |  |  | 88  |
| 6   | 101 | 95  | 91  | 89  | 99  | 94  | 91  | 88  |  | 93  | 90  | 88  |  |  | 92  | 89  | 87  |  |  | 86  |
| 7   | 98  | 92  | 89  | 86  | 97  | 92  | 88  | 86  |  | 91  | 88  | 85  |  |  | 90  | 87  | 85  |  |  | 84  |
| 8   | 96  | 90  | 86  | 84  | 95  | 90  | 86  | 84  |  | 89  | 86  | 83  |  |  | 88  | 85  | 83  |  |  | 82  |
| 9   | 94  | 88  | 84  | 82  | 93  | 88  | 84  | 82  |  | 87  | 84  | 82  |  |  | 86  | 83  | 81  |  |  | 80  |
| 10  | 92  | 86  | 82  | 80  | 91  | 86  | 82  | 80  |  | 85  | 82  | 80  |  |  | 84  | 82  | 80  |  |  | 79  |

**AVERAGE LUMINANCE (cd/sqm):**

|     |         |
|-----|---------|
|     | 0°      |
| 0°  | 2917296 |
| 5°  | 2693589 |
| 10° | 1823202 |
| 15° | 620282  |
| 20° | 227826  |
| 25° | 120780  |
| 30° | 62081   |
| 35° | 28986   |
| 40° | 9506    |
| 45° | 4821    |
| 50° | 2290    |
| 55° | 878     |
| 60° | 1007    |
| 65° | 0       |
| 70° | 0       |
| 75° | 0       |
| 80° | 0       |
| 85° | 0       |



TEST NUMBER: P222209

CATALOG NUMBER: LSSQ2B20NFL259730D010 2LBDLC\*MB

**ZONAL LUMENS:**

| Zone      | Lumens | % Fixture |
|-----------|--------|-----------|
| 0°-10°    | 589.3  | 46.4      |
| 10°-20°   | 495.5  | 39.0      |
| 20°-30°   | 136.0  | 10.7      |
| 30°-40°   | 39.6   | 3.1       |
| 40°-50°   | 7.4    | 0.6       |
| 50°-60°   | 1.7    | 0.1       |
| 60°-70°   | 0.2    | 0.0       |
| 70°-80°   | 0.0    | 0.0       |
| 80°-90°   | 0.0    | 0.0       |
| 90°-100°  | 0.0    | 0.0       |
| 100°-110° | 0.0    | 0.0       |
| 110°-120° | 0.0    | 0.0       |
| 120°-130° | 0.0    | 0.0       |
| 130°-140° | 0.0    | 0.0       |
| 140°-150° | 0.0    | 0.0       |
| 150°-160° | 0.0    | 0.0       |
| 160°-170° | 0.0    | 0.0       |
| 170°-180° | 0.0    | 0.0       |
| 0°-30°    | 1220.7 | 96.2      |
| 0°-40°    | 1260.4 | 99.3      |
| 0°-60°    | 1269.4 | 100.0     |
| 0°-90°    | 1269.6 | 100.0     |
| 90°-120°  | 0.0    | 0.0       |
| 90°-150°  | 0.0    | 0.0       |
| 90°-180°  | 0.0    | 0.0       |
| 0°-180°   | 1269.6 | 100.0     |

**CANDELA DISTRIBUTION:**

|     | 0°   | Flux |
|-----|------|------|
| 0°  | 7532 |      |
| 5°  | 6928 | 589  |
| 15° | 1547 | 495  |
| 25° | 283  | 136  |
| 35° | 61   | 40   |
| 45° | 9    | 7    |
| 55° | 1    | 2    |
| 65° | 0    | 0    |
| 75° | 0    | 0    |
| 85° | 0    | 0    |
| 90° | 0    |      |



TEST NUMBER: P222209

CATALOG NUMBER: LSSQ2B20NFL259730D010 2LBDLC\*MB

**CANDELA DISTRIBUTION (FULL):**

|       | 0°     |
|-------|--------|
| 0°    | 7531.5 |
| 1°    | 7487.7 |
| 2°    | 7410.2 |
| 3°    | 7298.9 |
| 4°    | 7146.3 |
| 5°    | 6927.5 |
| 6°    | 6628.6 |
| 7°    | 6254.8 |
| 8°    | 5798.3 |
| 9°    | 5259.4 |
| 10°   | 4635.4 |
| 11°   | 3951.4 |
| 12°   | 3239.9 |
| 13°   | 2560.9 |
| 14°   | 1982.0 |
| 15°   | 1546.8 |
| 17.5° | 872.8  |
| 20°   | 552.7  |
| 22.5° | 393.9  |
| 25°   | 282.6  |
| 27.5° | 200.1  |
| 30°   | 138.8  |
| 32.5° | 97.5   |
| 35°   | 61.3   |
| 37.5° | 25.0   |
| 40°   | 18.8   |
| 42.5° | 13.8   |
| 45°   | 8.8    |
| 47.5° | 5.0    |
| 50°   | 3.8    |
| 52.5° | 2.5    |
| 55°   | 1.3    |
| 57.5° | 1.3    |
| 60°   | 1.3    |
| 62.5° | 0.0    |
| 65°   | 0.0    |
| 67.5° | 0.0    |
| 70°   | 0.0    |
| 72.5° | 0.0    |
| 75°   | 0.0    |
| 77.5° | 0.0    |
| 80°   | 0.0    |
| 82.5° | 0.0    |



TEST NUMBER: P222209

CATALOG NUMBER: LSSQ2B20NFL259730D010 2LBDLC\*MB

CANDELA DISTRIBUTION (continued):

0°  
90° | 0.0



Report Generated By E9808895 / USPTCWHP6082093







— 0°-180°







|       |     |
|-------|-----|
| 85°   | 0.0 |
| 87.5° | 0.0 |



(END OF REPORT)