

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P264055

Luminaire Tested: **LD2B20D010 EU2B2010SP158035 2LBD*LI**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P264055
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G2-1805-787-1)
Test Lab: INNOVATION CENTER(G2)
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LD2B20D010 EU2B2010SP158035 2LBD*LI
Description: 2000 Lumen, 2inch Portfolio LED Downlight
Light Source: -
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1769.0 lumens
Efficiency: N/A
Efficacy: 84.6 lumens/watt
Spacing Criteria (0/90/45): 0.28 / 0.28 / 0.28
Luminous Opening: Circular (Dia: 0.17' x H: 0')
CIE Type: Direct


Input Watts (W): 20.9
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P264055

CATALOG NUMBER: LD2B20D010 EU2B2010SP158035 2LBD*LI

Luminous Intensity Polar Plot





TEST NUMBER: P264055

CATALOG NUMBER: LD2B20D010 EU2B2010SP158035 2LBD*LI

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	116	114	112	111	113	112	110	109	108	107	106		104	103	102		101
2	113	109	107	105	111	108	106	104	105	103	101		102	101	99		99
3	110	106	103	100	108	105	102	100	102	100	98		100	98	97		98
4	107	103	99	97	106	102	99	96	100	97	95		98	96	94		96
5	105	100	97	94	104	99	96	94	98	95	93		96	94	92		95
6	103	98	94	92	102	97	94	91	96	93	91		95	92	90		93
7	101	95	92	90	100	95	92	89	94	91	89		93	90	89		92
8	99	93	90	88	98	93	90	88	92	89	87		91	89	87		91
9	97	92	88	86	96	91	88	86	91	88	86		90	87	86		89
10	95	90	87	85	95	90	87	85	89	86	85		89	86	84		88

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	8347237
5°	6690679
10°	2920220
15°	904975
20°	315487
25°	139357
30°	63064
35°	32824
40°	18677
45°	8861
50°	5603
55°	3097
60°	1776
65°	2101
70°	0
75°	0
80°	0
85°	0



TEST NUMBER: P264055

CATALOG NUMBER: LD2B20D010 EU2B2010SP158035 2LBD*LI

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	1025.9	58.0
10°-20°	561.9	31.8
20°-30°	128.1	7.2
30°-40°	36.8	2.1
40°-50°	11.4	0.6
50°-60°	3.4	0.2
60°-70°	1.6	0.1
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1715.8	97.0
0°-40°	1752.6	99.1
0°-60°	1767.4	99.9
0°-90°	1769.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1769.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	16919	
5°	13510	###
15°	1772	562
25°	256	128
35°	54	37
45°	13	11
55°	4	3
65°	2	2
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P264055

CATALOG NUMBER: LD2B20D010 EU2B2010SP158035 2LBD*LI

CANDELA DISTRIBUTION (FULL):

	0°
0°	16919.1
1°	16708.5
2°	16271.0
3°	15592.0
4°	14659.0
5°	13509.8
6°	12101.1
7°	10527.2
8°	8884.3
9°	7294.1
10°	5829.1
11°	4589.2
12°	3612.5
13°	2842.8
14°	2245.6
15°	1771.8
16°	1397.8
17°	1112.8
18°	895.0
19°	728.0
20°	600.9
22.5°	388.5
25°	256.0
26°	216.0
27°	183.4
28°	154.3
29°	128.9
30°	110.7
32.5°	76.2
35°	54.5
37.5°	39.9
40°	29.0
42.5°	20.0
45°	12.7
47.5°	9.1
50°	7.3
52.5°	5.4
55°	3.6
57.5°	1.8
60°	1.8
62.5°	1.8
65°	1.8
67.5°	1.8



TEST NUMBER: P264055

CATALOG NUMBER: LD2B20D010 EU2B2010SP158035 2LBD*LI

CANDELA DISTRIBUTION (continued):

	0°
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







70°	0.0
72.5°	0.0



(END OF REPORT)