

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P743940

Luminaire Tested: LD4D20D010-EU4DR2015309024-4LBDP1B

Issue Date: 2/2/2024

Test Information

Test Method: LM-79-2019
Report Number: P743940
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2310-195-36)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/2/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD4D20D010-EU4DR2015309024-4LBDP1B
Description: 4 INCH ROUND DEEP 45° CUTOFF SPECULAR BLACK TRIM, WITH 20° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 2400K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1461.3 lumens
Efficiency: N/A
Efficacy: 63.3 lumens/watt
Spacing Criteria (0/90/45): 0.34 / 0.34 / 0.36
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 23.1
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight



TEST NUMBER: P743940

CATALOG NUMBER: LD4D20D010-EU4DR2015309024-4LBDP1B

Luminous Intensity Polar Plot





TEST NUMBER: P743940

CATALOG NUMBER: LD4D20D010-EU4DR2015309024-4LBDP1B

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	115	113	111	109	113	111	109	108	107	106	104		103	102	101		100
2	111	108	105	102	109	106	104	101	103	101	99		100	99	97		98
3	108	103	100	97	106	102	99	96	100	97	95		97	95	93		95
4	105	99	96	93	103	98	95	92	96	93	91		95	92	90		93
5	102	96	92	89	100	95	91	89	94	90	88		92	89	87		91
6	99	93	89	86	98	92	88	86	91	87	85		90	87	84		88
7	96	90	86	83	95	89	86	83	88	85	82		87	84	82		86
8	94	87	83	81	93	87	83	80	86	83	80		85	82	80		84
9	91	85	81	78	91	85	81	78	84	80	78		83	80	78		82
10	89	83	79	76	88	82	79	76	82	78	76		81	78	76		81

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	908776
5°	819888
10°	460161
15°	233911
20°	99030
25°	45715
30°	24198
35°	13045
40°	6975
45°	4126
50°	2397
55°	1276
60°	809
65°	569
70°	224
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 4126 cd/sqm



TEST NUMBER: P743940

CATALOG NUMBER: LD4D20D010-EU4DR2015309024-4LBDP1B

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	592.2	40.5
10°-20°	583.1	39.9
20°-30°	190.5	13.0
30°-40°	64.9	4.4
40°-50°	21.8	1.5
50°-60°	6.6	0.5
60°-70°	2.2	0.1
70°-80°	0.1	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1365.8	93.5
0°-40°	1430.7	97.9
0°-60°	1459.1	99.8
0°-90°	1461.3	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1461.3	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	8318	
5°	7475	592
15°	2068	583
25°	379	190
35°	98	65
45°	27	22
55°	7	7
65°	2	2
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P743940

CATALOG NUMBER: LD4D20D010-EU4DR2015309024-4LBDP1B

CANDELA DISTRIBUTION (FULL):

	0°
0°	8317.5
0.5°	8317.5
1°	8307.1
1.5°	8286.4
2°	8248.6
2.5°	8198.2
3°	8127.1
3.5°	8027.9
4°	7880.5
4.5°	7701.3
5°	7475.4
5.5°	7178.4
6°	6874.0
6.5°	6525.1
7°	6183.7
7.5°	5783.7
8°	5426.7
8.5°	5067.5
9°	4735.7
9.5°	4431.3
10°	4147.6
12.5°	2978.1
15°	2067.9
17.5°	1350.9
20°	851.7
22.5°	551.8
25°	379.2
27.5°	266.6
30°	191.8
32.5°	137.8
35°	97.8
37.5°	68.1
40°	48.9
42.5°	35.6
45°	26.7
47.5°	20.7
50°	14.1
52.5°	8.9
55°	6.7
57.5°	5.2
60°	3.7
62.5°	3.0
65°	2.2



TEST NUMBER: P743940

CATALOG NUMBER: LD4D20D010-EU4DR2015309024-4LBDP1B

CANDELA DISTRIBUTION (continued):

	0°
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670245859 / DESKTOP-T8S5UU9





— 0°-180°







67.5°	1.5
70°	0.7



(END OF REPORT)