

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P744737

Luminaire Tested: LD4D20D010-EU4DR7020359027-4LBS1B

Issue Date: 1/30/2024

Test Information

Test Method: LM-79-2019
Report Number: P744737
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-76)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 1/30/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD4D20D010-EU4DR7020359027-4LBS1B
Description: 4 INCH ROUND SHALLOW SPECULAR BLACK TRIM, WITH 70° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 2700K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1766.2 lumens
Efficiency: N/A
Efficacy: 76.5 lumens/watt
Spacing Criteria (0/90/45): 1.1 / 1.1 / 1.04
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 23.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight



TEST NUMBER: P744737

CATALOG NUMBER: LD4D20D010-EU4DR7020359027-4LBS1B

Luminous Intensity Polar Plot





TEST NUMBER: P744737

CATALOG NUMBER: LD4D20D010-EU4DR7020359027-4LBS1B

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20					20					20					20					20
RC	80					70					50					30					10
RW	70	50	30	10		70	50	30	10		50	30	10		50	30	10		50	30	10
RCR																					
0	119	119	119	119		116	116	116	116		111	111	111		106	106	106		102	102	102
1	113	110	107	105		111	108	106	103		104	102	100		100	99	97		97	95	94
2	107	102	97	94		105	100	96	92		97	93	90		94	91	88		91	89	87
3	101	94	88	84		99	92	87	83		90	85	82		87	84	81		85	82	79
4	95	87	81	76		93	86	80	76		83	78	75		81	77	74		79	76	73
5	89	80	74	69		88	79	73	69		78	72	68		76	71	68		74	70	67
6	84	75	68	63		83	74	68	63		72	67	63		71	66	62		69	65	62
7	80	69	63	58		78	69	63	58		67	62	58		66	61	57		65	61	57
8	75	65	58	54		74	64	58	54		63	57	53		62	57	53		61	56	53
9	71	61	54	50		70	60	54	50		59	53	50		58	53	49		57	53	49
10	67	57	50	46		66	56	50	46		55	50	46		55	50	46		54	49	46

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	152309
5°	151937
10°	151608
15°	151563
20°	150085
25°	140978
30°	125684
35°	100210
40°	66537
45°	39773
50°	20636
55°	10839
60°	3824
65°	52
70°	0
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 39773 cd/sqm



TEST NUMBER: P744737

CATALOG NUMBER: LD4D20D010-EU4DR7020359027-4LBS1B

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	131.7	7.5
10°-20°	377.8	21.4
20°-30°	533.0	30.2
30°-40°	460.1	26.1
40°-50°	206.1	11.7
50°-60°	53.9	3.1
60°-70°	3.5	0.2
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1042.6	59.0
0°-40°	1502.7	85.1
0°-60°	1762.7	99.8
0°-90°	1766.2	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1766.2	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1394	
5°	1385	132
15°	1340	378
25°	1169	533
35°	751	460
45°	257	206
55°	57	54
65°	0	3
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P744737

CATALOG NUMBER: LD4D20D010-EU4DR7020359027-4LBS1B

CANDELA DISTRIBUTION (FULL):

0°	
0°	1394.0
2.5°	1392.6
5°	1385.3
7.5°	1379.3
10°	1366.5
12.5°	1355.0
15°	1339.9
17.5°	1322.6
20°	1290.8
22.5°	1238.4
25°	1169.4
27.5°	1089.5
30°	996.2
32.5°	882.2
35°	751.3
37.5°	606.9
40°	466.5
42.5°	354.5
45°	257.4
47.5°	177.5
50°	121.4
52.5°	83.7
55°	56.9
57.5°	34.3
60°	17.5
62.5°	5.5
65°	0.2
67.5°	0.0
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670245859 / DESKTOP-T8S5UU9





— 0°-180°







(END OF REPORT)