

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P744374

Luminaire Tested: LD4D20D010-EU4DR4520359035-4LBS1H

Issue Date: 1/30/2024

Test Information

Test Method: LM-79-2019
Report Number: P744374
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-36)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 1/30/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD4D20D010-EU4DR4520359035-4LBS1H
Description: 4 INCH ROUND SHALLOW SEMI-SPECULAR CLEAR TRIM, WITH 45° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 3500K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 2098.7 lumens
Efficiency: N/A
Efficacy: 90.9 lumens/watt
Spacing Criteria (0/90/45): 0.75 / 0.75 / 0.69
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 23.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight



TEST NUMBER: P744374

CATALOG NUMBER: LD4D20D010-EU4DR4520359035-4LBS1H

Luminous Intensity Polar Plot



TEST NUMBER: P744374

CATALOG NUMBER: LD4D20D010-EU4DR4520359035-4LBS1H

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	114	112	110	108	112	110	108	106	106	104	103		102	101	100		98
2	109	105	102	99	107	103	100	98	100	98	95		97	95	93		95
3	105	99	95	91	103	98	94	91	95	92	89		93	90	88		91
4	100	94	89	85	99	93	88	85	91	87	84		89	86	83		87
5	96	89	84	80	95	88	83	80	86	82	79		85	81	79		83
6	92	85	80	76	91	84	79	76	83	78	75		81	77	75		80
7	89	81	75	72	87	80	75	72	79	74	71		78	74	71		77
8	85	77	72	68	84	76	71	68	75	71	68		74	70	67		73
9	82	73	68	65	81	73	68	65	72	68	65		71	67	64		71
10	79	70	65	62	78	70	65	62	69	65	62		68	64	61		68

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	405303
5°	393755
10°	376718
15°	344775
20°	273532
25°	170767
30°	94118
35°	42256
40°	16645
45°	7850
50°	3723
55°	1943
60°	961
65°	233
70°	96
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 7850 cd/sqm



TEST NUMBER: P744374

CATALOG NUMBER: LD4D20D010-EU4DR4520359035-4LBS1H

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	337.3	16.1
10°-20°	830.2	39.6
20°-30°	657.4	31.3
30°-40°	218.9	10.4
40°-50°	43.5	2.1
50°-60°	9.9	0.5
60°-70°	1.4	0.1
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1825.0	87.0
0°-40°	2043.9	97.4
0°-60°	2097.2	99.9
0°-90°	2098.7	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2098.7	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	3710	
5°	3590	337
15°	3048	830
25°	1416	657
35°	317	219
45°	51	43
55°	10	10
65°	1	1
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P744374

CATALOG NUMBER: LD4D20D010-EU4DR4520359035-4LBS1H

CANDELA DISTRIBUTION (FULL):

	0°
0°	3709.5
2.5°	3685.2
5°	3590.1
7.5°	3511.7
10°	3395.5
12.5°	3240.9
15°	3048.0
17.5°	2758.0
20°	2352.5
22.5°	1869.3
25°	1416.5
27.5°	1037.2
30°	746.0
32.5°	507.3
35°	316.8
37.5°	187.9
40°	116.7
42.5°	76.7
45°	50.8
47.5°	32.7
50°	21.9
52.5°	14.6
55°	10.2
57.5°	6.7
60°	4.4
62.5°	2.3
65°	0.9
67.5°	0.3
70°	0.3
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670245859 / DESKTOP-T8S5UU9





— 0°-180°







(END OF REPORT)