

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P748088

Luminaire Tested: LD4D40BD010-EU4DR6540509027-4LBDP1H

Issue Date: 2/5/2024

Test Information

Test Method: LM-79-2019
Report Number: P748088
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-59)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/5/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD4D40BD010-EU4DR6540509027-4LBDP1H
Description: 4 INCH ROUND DEEP 45° CUTOFF SEMI-SPECULAR CLEAR TRIM, WITH 65° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 2700K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 3199.7 lumens
Efficiency: N/A
Efficacy: 90.9 lumens/watt
Spacing Criteria (0/90/45): 0.98 / 0.98 / 0.92
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 35.2
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight

TEST NUMBER: P748088

CATALOG NUMBER: LD4D40BD010-EU4DR6540509027-4LBDP1H

Luminous Intensity Polar Plot



TEST NUMBER: P748088

CATALOG NUMBER: LD4D40BD010-EU4DR6540509027-4LBDP1H

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20					20					20					20					20
RC	80					70					50					30					10
RW	70	50	30	10		70	50	30	10		50	30	10		50	30	10		50	30	10
RCR																					
0	119	119	119	119		116	116	116	116		111	111	111		106	106	106		102	102	102
1	113	111	108	106		111	108	106	104		104	103	101		101	99	98		97	96	95
2	108	103	99	95		106	101	97	94		98	95	92		95	92	90		92	90	88
3	102	96	91	87		100	94	90	86		92	88	85		89	86	83		87	84	82
4	97	89	84	79		95	88	83	79		86	82	78		84	80	77		82	79	76
5	92	83	78	73		90	83	77	73		81	76	72		79	75	72		77	74	71
6	87	78	72	68		86	77	72	68		76	71	67		74	70	67		73	69	66
7	83	73	67	63		81	73	67	63		71	66	62		70	66	62		69	65	62
8	79	69	63	59		77	68	63	59		67	62	58		66	62	58		65	61	58
9	75	65	59	55		74	65	59	55		64	58	55		63	58	55		62	58	54
10	71	61	56	52		70	61	55	52		60	55	51		59	55	51		59	54	51

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	344204
5°	344488
10°	356615
15°	357206
20°	328866
25°	280220
30°	214516
35°	151549
40°	89457
45°	36312
50°	13156
55°	7334
60°	4217
65°	2327
70°	2428
75°	1900
80°	1951
85°	1630

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 36312 cd/sqm

TEST NUMBER: P748088

CATALOG NUMBER: LD4D40BD010-EU4DR6540509027-4LBDP1H

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	303.3	9.5
10°-20°	875.0	27.3
20°-30°	1049.9	32.8
30°-40°	705.5	22.1
40°-50°	211.2	6.6
50°-60°	37.3	1.2
60°-70°	10.6	0.3
70°-80°	5.2	0.2
80°-90°	1.6	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2228.2	69.6
0°-40°	2933.8	91.7
0°-60°	3182.2	99.5
0°-90°	3199.7	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	3199.7	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	3150	
5°	3141	303
15°	3158	875
25°	2324	1050
35°	1136	706
45°	235	211
55°	38	37
65°	9	11
75°	4	5
85°	1	2
90°	0	



TEST NUMBER: P748088

CATALOG NUMBER: LD4D40BD010-EU4DR6540509027-4LBDP1H

CANDELA DISTRIBUTION (FULL):

	0°
0°	3150.3
2.5°	3163.8
5°	3140.9
7.5°	3188.4
10°	3214.3
12.5°	3208.1
15°	3157.9
17.5°	3035.3
20°	2828.4
22.5°	2584.9
25°	2324.4
27.5°	2030.2
30°	1700.3
32.5°	1401.2
35°	1136.2
37.5°	874.3
40°	627.2
42.5°	409.6
45°	235.0
47.5°	124.5
50°	77.4
52.5°	53.7
55°	38.5
57.5°	27.8
60°	19.3
62.5°	12.5
65°	9.0
67.5°	8.1
70°	7.6
72.5°	5.8
75°	4.5
77.5°	4.0
80°	3.1
82.5°	2.2
85°	1.3
87.5°	0.9
90°	0.0



Report Generated By 670245859 / DESKTOP-T8S5UU9





— 0°-180°







(END OF REPORT)