

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P750730

Luminaire Tested: LD4D60D010-EU4DR3555659024-4LBS1B

Issue Date: 1/30/2024

Test Information

Test Method: LM-79-2019
Report Number: P750730
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-20)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 1/30/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD4D60D010-EU4DR3555659024-4LBS1B
Description: 4 INCH ROUND SHALLOW SPECULAR BLACK TRIM, WITH 35° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 2400K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 4822.6 lumens
Efficiency: N/A
Efficacy: 74.9 lumens/watt
Spacing Criteria (0/90/45): 0.6 / 0.6 / 0.54
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 64.4
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight

TEST NUMBER: P750730

CATALOG NUMBER: LD4D60D010-EU4DR3555659024-4LBS1B

Luminous Intensity Polar Plot





TEST NUMBER: P750730

CATALOG NUMBER: LD4D60D010-EU4DR3555659024-4LBS1B

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20					20					20					20
RC	80				70					50					30					0
RW	70	50	30	10	70	50	30	10		50	30	10			50	30	10			0
RCR																				
0	119	119	119	119	116	116	116	116		111	111	111			106	106	106			100
1	115	112	110	108	112	110	108	107		106	105	103			103	101	100			96
2	110	106	103	101	108	105	102	99		102	99	97			99	97	95			92
3	106	101	97	94	105	100	96	93		97	95	92			95	93	91			88
4	103	97	92	89	101	96	92	89		94	90	88			92	89	87			84
5	99	93	88	85	98	92	87	84		90	86	84			89	85	83			81
6	96	89	84	81	94	88	84	81		87	83	80			85	82	80			78
7	93	85	81	78	91	85	80	77		84	80	77			83	79	77			75
8	90	82	78	74	88	82	77	74		81	77	74			80	76	74			72
9	87	79	75	72	86	79	75	72		78	74	71			77	74	71			70
10	84	77	72	69	83	76	72	69		76	72	69			75	71	69			68

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	1449836
5°	1415769
10°	1275982
15°	990368
20°	561714
25°	218532
30°	81527
35°	44683
40°	29211
45°	17785
50°	11321
55°	8001
60°	5856
65°	3180
70°	224
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 17785 cd/sqm



TEST NUMBER: P750730

CATALOG NUMBER: LD4D60D010-EU4DR3555659024-4LBS1B

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	1187.2	24.6
10°-20°	2317.9	48.1
20°-30°	945.3	19.6
30°-40°	226.2	4.7
40°-50°	94.3	2.0
50°-60°	39.0	0.8
60°-70°	12.2	0.3
70°-80°	0.3	0.0
80°-90°	0.2	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	4450.4	92.3
0°-40°	4676.6	97.0
0°-60°	4810.0	99.7
0°-90°	4822.6	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	4822.6	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	13270	
5°	12908	###
15°	8755	2318
25°	1813	945
35°	335	226
45°	115	94
55°	42	39
65°	12	12
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P750730

CATALOG NUMBER: LD4D60D010-EU4DR3555659024-4LBS1B

CANDELA DISTRIBUTION (FULL):

0°	
0°	13269.5
2.5°	13189.9
5°	12908.4
7.5°	12346.8
10°	11500.9
12.5°	10309.7
15°	8755.4
17.5°	6854.4
20°	4831.0
22.5°	3080.6
25°	1812.7
27.5°	1024.7
30°	646.2
32.5°	453.7
35°	335.0
37.5°	259.1
40°	204.8
42.5°	157.8
45°	115.1
47.5°	86.1
50°	66.6
52.5°	52.8
55°	42.0
57.5°	34.0
60°	26.8
62.5°	19.5
65°	12.3
67.5°	4.3
70°	0.7
72.5°	0.7
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.7
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670245859 / DESKTOP-T8S5UU9





— 0°-180°







(END OF REPORT)