

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P751121

Luminaire Tested: LD4D60D010-EU4DR6055659024-4LBS1H

Issue Date: 1/30/2024

Test Information

Test Method: LM-79-2019
Report Number: P751121
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-60)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 1/30/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD4D60D010-EU4DR6055659024-4LBS1H
Description: 4 INCH ROUND SHALLOW SEMI-SPECULAR CLEAR TRIM, WITH 60° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 2400K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 5442.4 lumens
Efficiency: N/A
Efficacy: 84.5 lumens/watt
Spacing Criteria (0/90/45): 0.98 / 0.98 / 0.92
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 64.4
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight

TEST NUMBER: P751121

CATALOG NUMBER: LD4D60D010-EU4DR6055659024-4LBS1H

Luminous Intensity Polar Plot





TEST NUMBER: P751121

CATALOG NUMBER: LD4D60D010-EU4DR6055659024-4LBS1H

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	114	111	108	106	111	109	106	104	105	103	101		101	99	98		97
2	108	103	99	96	106	101	98	95	98	95	92		95	93	90		92
3	102	96	91	87	100	95	90	86	92	88	85		90	86	84		87
4	97	90	84	80	95	88	83	79	86	82	78		84	81	78		82
5	92	84	78	74	91	83	77	73	81	76	73		79	75	72		78
6	87	79	73	68	86	78	72	68	76	71	68		75	70	67		74
7	83	74	68	63	82	73	67	63	72	67	63		71	66	63		69
8	79	69	63	59	78	69	63	59	68	63	59		67	62	59		66
9	75	65	59	55	74	65	59	55	64	59	55		63	58	55		62
10	72	62	56	52	71	61	56	52	61	55	52		60	55	52		59

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	595078
5°	593622
10°	613344
15°	613977
20°	564923
25°	480500
30°	366126
35°	258909
40°	152043
45°	61344
50°	20483
55°	9867
60°	4043
65°	595
70°	0
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 61344 cd/sqm



TEST NUMBER: P751121

CATALOG NUMBER: LD4D60D010-EU4DR6055659024-4LBS1H

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	522.1	9.6
10°-20°	1503.7	27.6
20°-30°	1799.7	33.1
30°-40°	1203.7	22.1
40°-50°	356.9	6.6
50°-60°	51.3	0.9
60°-70°	4.9	0.1
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	3825.6	70.3
0°-40°	5029.3	92.4
0°-60°	5437.5	99.9
0°-90°	5442.4	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	5442.4	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	5446	
5°	5412	522
15°	5428	1504
25°	3986	1800
35°	1941	1204
45°	397	357
55°	52	51
65°	2	5
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P751121

CATALOG NUMBER: LD4D60D010-EU4DR6055659024-4LBS1H

CANDELA DISTRIBUTION (FULL):

0°	
0°	5446.4
2.5°	5439.4
5°	5412.4
7.5°	5485.8
10°	5528.3
12.5°	5520.5
15°	5427.9
17.5°	5209.3
20°	4858.6
22.5°	4437.6
25°	3985.7
27.5°	3476.7
30°	2902.0
32.5°	2389.1
35°	1941.1
37.5°	1492.3
40°	1066.0
42.5°	702.9
45°	397.0
47.5°	203.1
50°	120.5
52.5°	78.0
55°	51.8
57.5°	33.2
60°	18.5
62.5°	7.7
65°	2.3
67.5°	0.8
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670245859 / DESKTOP-T8S5UU9





— 0°-180°







(END OF REPORT)