

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P751071

Luminaire Tested: LD4D60D010-EU4DR5555659030-4LBS1MW

Issue Date: 1/30/2024

Test Information

Test Method: LM-79-2019
Report Number: P751071
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-52)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 1/30/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD4D60D010-EU4DR5555659030-4LBS1MW
Description: 4 INCH ROUND SHALLOW MATTE WHITE TRIM, WITH 55° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 3000K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 6153.4 lumens
Efficiency: N/A
Efficacy: 95.6 lumens/watt
Spacing Criteria (0/90/45): 0.89 / 0.89 / 0.87
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 64.4
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight

TEST NUMBER: P751071

CATALOG NUMBER: LD4D60D010-EU4DR5555659030-4LBS1MW

Luminous Intensity Polar Plot





TEST NUMBER: P751071

CATALOG NUMBER: LD4D60D010-EU4DR5555659030-4LBS1MW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20					20					20					20					20
RC	80					70					50					30					10
RW	70	50	30	10		70	50	30	10		50	30	10		50	30	10		50	30	10
RCR																					
0	119	119	119	119		116	116	116	116		111	111	111		106	106	106		102	102	102
1	114	111	108	106		111	109	106	104		105	103	101		101	99	98		97	96	95
2	108	103	99	96		106	101	98	95		98	95	92		95	93	90		92	90	89
3	102	96	91	87		100	95	90	86		92	88	85		90	86	84		87	85	82
4	97	90	84	80		95	88	83	79		86	82	78		84	81	78		82	79	77
5	92	84	78	74		91	83	77	73		81	76	73		79	75	72		78	74	71
6	88	79	73	68		86	78	72	68		76	71	68		75	70	67		74	70	67
7	83	74	68	64		82	73	67	63		72	67	63		71	66	63		70	65	62
8	79	69	63	59		78	69	63	59		68	63	59		67	62	59		66	62	58
9	75	66	60	56		74	65	59	55		64	59	55		63	58	55		62	58	55
10	72	62	56	52		71	61	56	52		61	56	52		60	55	52		59	55	52

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	753910
5°	723963
10°	721240
15°	700522
20°	628118
25°	519102
30°	392116
35°	284319
40°	181953
45°	83100
50°	27180
55°	11734
60°	5048
65°	672
70°	0
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 83100 cd/sqm



TEST NUMBER: P751071

CATALOG NUMBER: LD4D60D010-EU4DR5555659030-4LBS1MW

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	628.1	10.2
10°-20°	1714.2	27.9
20°-30°	1953.5	31.7
30°-40°	1329.9	21.6
40°-50°	458.3	7.4
50°-60°	63.3	1.0
60°-70°	6.2	0.1
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	4295.8	69.8
0°-40°	5625.7	91.4
0°-60°	6147.3	99.9
0°-90°	6153.4	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	6153.4	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	6900	
5°	6601	628
15°	6193	1714
25°	4306	1953
35°	2132	1330
45°	538	458
55°	62	63
65°	3	6
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P751071

CATALOG NUMBER: LD4D60D010-EU4DR5555659030-4LBS1MW

CANDELA DISTRIBUTION (FULL):

	0°
0°	6900.1
2.5°	6741.9
5°	6600.8
7.5°	6531.5
10°	6500.8
12.5°	6398.2
15°	6193.0
17.5°	5867.2
20°	5402.1
22.5°	4865.1
25°	4305.9
27.5°	3723.6
30°	3108.0
32.5°	2586.5
35°	2131.6
37.5°	1698.9
40°	1275.7
42.5°	884.1
45°	537.8
47.5°	289.9
50°	159.9
52.5°	94.9
55°	61.6
57.5°	39.3
60°	23.1
62.5°	10.3
65°	2.6
67.5°	0.9
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670245859 / DESKTOP-T8S5UU9





— 0°-180°







(END OF REPORT)