

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P751318

Luminaire Tested: LD4D60D010-EU4DR7055659035-4LBS1MW

Issue Date: 1/30/2024

Test Information

Test Method: LM-79-2019
Report Number: P751318
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-76)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 1/30/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD4D60D010-EU4DR7055659035-4LBS1MW
Description: 4 INCH ROUND SHALLOW MATTE WHITE TRIM, WITH 70° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 3500K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 6134.6 lumens
Efficiency: N/A
Efficacy: 95.3 lumens/watt
Spacing Criteria (0/90/45): 1.1 / 1.1 / 1.04
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 64.4
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight

TEST NUMBER: P751318

CATALOG NUMBER: LD4D60D010-EU4DR7055659035-4LBS1MW

Luminous Intensity Polar Plot





TEST NUMBER: P751318

CATALOG NUMBER: LD4D60D010-EU4DR7055659035-4LBS1MW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20					20					20					20
RC	80				70					50					30					0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100		
1	113	110	107	105	111	108	106	103	104	102	100	100	99	97	97	95	94	93		
2	107	102	97	94	105	100	96	92	97	93	90	94	91	88	91	89	87	85		
3	101	94	88	84	99	92	87	83	90	85	82	87	84	81	85	82	79	78		
4	95	87	81	76	93	86	80	76	83	78	75	81	77	74	79	76	73	71		
5	89	80	74	69	88	79	73	69	78	72	68	76	71	68	74	70	67	65		
6	84	75	68	63	83	74	68	63	72	67	63	71	66	62	69	65	62	60		
7	80	69	63	58	78	69	62	58	67	62	58	66	61	57	65	61	57	56		
8	75	65	58	54	74	64	58	54	63	57	53	62	57	53	61	56	53	51		
9	71	61	54	50	70	60	54	50	59	53	50	58	53	49	57	53	49	48		
10	67	57	50	46	66	56	50	46	55	50	46	55	50	46	54	49	46	44		

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	529030
5°	527716
10°	526573
15°	526426
20°	521275
25°	489674
30°	436538
35°	348062
40°	231117
45°	138170
50°	71629
55°	37641
60°	13308
65°	233
70°	0
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 138170 cd/sqm



TEST NUMBER: P751318

CATALOG NUMBER: LD4D60D010-EU4DR7055659035-4LBS1MW

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	457.6	7.5
10°-20°	1312.3	21.4
20°-30°	1851.3	30.2
30°-40°	1598.2	26.1
40°-50°	715.7	11.7
50°-60°	187.3	3.1
60°-70°	12.2	0.2
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	3621.2	59.0
0°-40°	5219.3	85.1
0°-60°	6122.4	99.8
0°-90°	6134.6	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	6134.6	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	4842	
5°	4812	458
15°	4654	1312
25°	4062	1851
35°	2610	1598
45°	894	716
55°	198	187
65°	1	12
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P751318

CATALOG NUMBER: LD4D60D010-EU4DR7055659035-4LBS1MW

CANDELA DISTRIBUTION (FULL):

0°	
0°	4841.9
2.5°	4836.7
5°	4811.5
7.5°	4790.6
10°	4746.2
12.5°	4706.1
15°	4653.9
17.5°	4593.8
20°	4483.2
22.5°	4301.2
25°	4061.8
27.5°	3784.0
30°	3460.1
32.5°	3064.0
35°	2609.5
37.5°	2108.0
40°	1620.4
42.5°	1231.2
45°	894.2
47.5°	616.5
50°	421.4
52.5°	290.8
55°	197.6
57.5°	119.3
60°	60.9
62.5°	19.2
65°	0.9
67.5°	0.0
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670245859 / DESKTOP-T8S5UU9





— 0°-180°







(END OF REPORT)