

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P751025

Luminaire Tested: LD4D60D010-EU4DR5055659050-4LBDP1B

Issue Date: 1/30/2024

Test Information

Test Method: LM-79-2019
Report Number: P751025
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-44)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 1/30/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD4D60D010-EU4DR5055659050-4LBDP1B
Description: 4 INCH ROUND DEEP 45° CUTOFF SPECULAR BLACK TRIM, WITH 50° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 5000K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 5929.2 lumens
Efficiency: N/A
Efficacy: 92.1 lumens/watt
Spacing Criteria (0/90/45): 0.8 / 0.8 / 0.73
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 64.4
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight

TEST NUMBER: P751025

CATALOG NUMBER: LD4D60D010-EU4DR5055659050-4LBDP1B

Luminous Intensity Polar Plot





TEST NUMBER: P751025

CATALOG NUMBER: LD4D60D010-EU4DR5055659050-4LBDP1B

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20					20					20					20
RC	80				70					50					30					0
RW	70	50	30	10	70	50	30	10		50	30	10			50	30	10			0
RCR																				
0	119	119	119	119	116	116	116	116		111	111	111			106	106	106			100
1	114	112	109	107	112	110	108	106		106	104	102			102	101	99			95
2	109	105	101	98	107	103	100	97		100	98	95			97	95	93			90
3	105	99	95	91	103	98	94	90		95	92	89			93	90	88			85
4	100	94	89	85	99	93	88	85		90	87	84			89	85	83			80
5	96	89	84	80	95	88	83	79		86	82	79			85	81	78			76
6	92	84	79	75	91	83	79	75		82	78	74			81	77	74			72
7	88	80	75	71	87	79	74	71		78	74	71			77	73	70			69
8	85	76	71	67	84	76	71	67		75	70	67			74	70	67			65
9	81	73	68	64	80	72	67	64		71	67	64			71	67	64			62
10	78	70	64	61	77	69	64	61		68	64	61			68	64	61			59

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	1043812
5°	1032872
10°	1015868
15°	925021
20°	769726
25°	546396
30°	289204
35°	117857
40°	43773
45°	20041
50°	8210
55°	4305
60°	2120
65°	620
70°	0
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 20041 cd/sqm

TEST NUMBER: P751025

CATALOG NUMBER: LD4D60D010-EU4DR5055659050-4LBDP1B

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	890.1	15.0
10°-20°	2249.5	37.9
20°-30°	2020.7	34.1
30°-40°	632.7	10.7
40°-50°	110.8	1.9
50°-60°	22.1	0.4
60°-70°	3.3	0.1
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	5160.3	87.0
0°-40°	5793.0	97.7
0°-60°	5925.9	99.9
0°-90°	5929.2	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	5929.2	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	9553	
5°	9417	890
15°	8178	2250
25°	4532	2021
35°	884	633
45°	130	111
55°	23	22
65°	2	3
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P751025

CATALOG NUMBER: LD4D60D010-EU4DR5055659050-4LBDP1B

CANDELA DISTRIBUTION (FULL):

	0°
0°	9553.4
2.5°	9505.9
5°	9417.3
7.5°	9282.0
10°	9156.4
12.5°	8753.6
15°	8177.7
17.5°	7446.4
20°	6620.0
22.5°	5663.9
25°	4532.3
27.5°	3332.1
30°	2292.3
32.5°	1492.5
35°	883.6
37.5°	507.4
40°	306.9
42.5°	199.8
45°	129.7
47.5°	78.9
50°	48.3
52.5°	33.0
55°	22.6
57.5°	15.3
60°	9.7
62.5°	5.6
65°	2.4
67.5°	0.8
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670245859 / DESKTOP-T8S5UU9





— 0°-180°







(END OF REPORT)