

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P751109

Luminaire Tested: LD4D60D010-EU4DR5555659050-4LBS1LI

Issue Date: 1/30/2024

Test Information

Test Method: LM-79-2019
Report Number: P751109
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-52)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 1/30/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD4D60D010-EU4DR5555659050-4LBS1LI
Description: 4 INCH ROUND SHALLOW SPECULAR CLEAR TRIM, WITH 55° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 5000K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 7244.4 lumens
Efficiency: N/A
Efficacy: 112.5 lumens/watt
Spacing Criteria (0/90/45): 0.89 / 0.89 / 0.87
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 64.4
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight

TEST NUMBER: P751109

CATALOG NUMBER: LD4D60D010-EU4DR5555659050-4LBS1LI

Luminous Intensity Polar Plot





TEST NUMBER: P751109

CATALOG NUMBER: LD4D60D010-EU4DR5555659050-4LBS1LI

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	114	111	108	106	111	109	106	104	105	103	101		101	99	98		97
2	108	103	99	96	106	101	98	95	98	95	92		95	93	90		92
3	102	96	91	87	100	95	90	86	92	88	85		90	86	84		87
4	97	90	84	80	95	88	83	79	86	82	78		84	81	78		82
5	92	84	78	74	91	83	77	73	81	76	73		79	75	72		78
6	88	79	73	68	86	78	72	68	76	71	68		75	70	67		74
7	83	74	68	64	82	73	67	63	72	67	63		71	66	63		70
8	79	69	63	59	78	69	63	59	68	63	59		67	62	59		66
9	75	66	60	56	74	65	59	55	64	59	55		63	58	55		62
10	72	62	56	52	71	61	56	52	61	56	52		60	55	52		59

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	887569
5°	852320
10°	849105
15°	824711
20°	739472
25°	611134
30°	461645
35°	334724
40°	214216
45°	97841
50°	31990
55°	13811
60°	5944
65°	776
70°	0
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 97841 cd/sqm



TEST NUMBER: P751109

CATALOG NUMBER: LD4D60D010-EU4DR5555659050-4LBS1LI

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	739.5	10.2
10°-20°	2018.1	27.9
20°-30°	2299.8	31.7
30°-40°	1565.6	21.6
40°-50°	539.5	7.4
50°-60°	74.6	1.0
60°-70°	7.2	0.1
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	5057.4	69.8
0°-40°	6623.1	91.4
0°-60°	7237.1	99.9
0°-90°	7244.4	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	7244.4	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	8123	
5°	7771	739
15°	7291	2018
25°	5069	2300
35°	2510	1566
45°	633	539
55°	72	75
65°	3	7
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P751109

CATALOG NUMBER: LD4D60D010-EU4DR5555659050-4LBS1LI

CANDELA DISTRIBUTION (FULL):

	0°
0°	8123.4
2.5°	7937.2
5°	7771.1
7.5°	7689.6
10°	7653.3
12.5°	7532.5
15°	7290.9
17.5°	6907.4
20°	6359.8
22.5°	5727.7
25°	5069.3
27.5°	4383.8
30°	3659.1
32.5°	3045.0
35°	2509.5
37.5°	2000.2
40°	1501.9
42.5°	1040.8
45°	633.2
47.5°	341.2
50°	188.2
52.5°	111.7
55°	72.5
57.5°	46.3
60°	27.2
62.5°	12.1
65°	3.0
67.5°	1.0
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670245859 / DESKTOP-T8S5UU9





— 0°-180°







(END OF REPORT)