

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P751260

Luminaire Tested: LD4D60D010-EU4DR6555659050-4LBDP1H

Issue Date: 2/5/2024

Test Information

Test Method: LM-79-2019
Report Number: P751260
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-59)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/5/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD4D60D010-EU4DR6555659050-4LBDP1H
Description: 4 INCH ROUND DEEP 45° CUTOFF SEMI-SPECULAR CLEAR TRIM, WITH 65° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 5000K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 5616.6 lumens
Efficiency: N/A
Efficacy: 87.2 lumens/watt
Spacing Criteria (0/90/45): 0.98 / 0.98 / 0.92
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 64.4
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight

TEST NUMBER: P751260

CATALOG NUMBER: LD4D60D010-EU4DR6555659050-4LBDP1H

Luminous Intensity Polar Plot





TEST NUMBER: P751260

CATALOG NUMBER: LD4D60D010-EU4DR6555659050-4LBDP1H

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20					20					20					20					20
RC	80					70					50					30					10
RW	70	50	30	10		70	50	30	10		50	30	10		50	30	10		50	30	10
RCR																					
0	119	119	119	119		116	116	116	116		111	111	111		106	106	106		102	102	102
1	113	111	108	106		111	108	106	104		104	103	101		101	99	98		97	96	95
2	108	103	99	95		106	101	97	94		98	95	92		95	92	90		92	90	88
3	102	96	91	87		100	94	90	86		92	88	85		89	86	83		87	84	82
4	97	89	84	79		95	88	83	79		86	82	78		84	80	77		82	79	76
5	92	83	78	73		90	83	77	73		81	76	72		79	75	72		77	74	71
6	87	78	72	68		86	77	72	68		76	71	67		74	70	67		73	69	66
7	83	73	67	63		81	73	67	63		71	66	62		70	66	62		69	65	62
8	79	69	63	59		77	68	63	59		67	62	58		66	62	58		65	61	58
9	75	65	59	55		74	65	59	55		64	58	55		63	58	55		62	58	54
10	71	61	56	52		70	61	55	52		60	55	51		59	55	51		59	54	51

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	604201
5°	604699
10°	625992
15°	627031
20°	577283
25°	491868
30°	376547
35°	266019
40°	157035
45°	63754
50°	23100
55°	12877
60°	7386
65°	4059
70°	4281
75°	3335
80°	3461
85°	3009

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 63754 cd/sqm



TEST NUMBER: P751260

CATALOG NUMBER: LD4D60D010-EU4DR6555659050-4LBDP1H

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	532.5	9.5
10°-20°	1536.0	27.3
20°-30°	1842.9	32.8
30°-40°	1238.5	22.1
40°-50°	370.7	6.6
50°-60°	65.4	1.2
60°-70°	18.6	0.3
70°-80°	9.1	0.2
80°-90°	2.9	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	3911.3	69.6
0°-40°	5149.8	91.7
0°-60°	5586.0	99.5
0°-90°	5616.6	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	5616.6	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	5530	
5°	5513	532
15°	5543	1536
25°	4080	1843
35°	1994	1238
45°	413	371
55°	68	65
65°	16	19
75°	8	9
85°	2	3
90°	0	



TEST NUMBER: P751260

CATALOG NUMBER: LD4D60D010-EU4DR6555659050-4LBDP1H

CANDELA DISTRIBUTION (FULL):

	0°
0°	5529.9
2.5°	5553.5
5°	5513.4
7.5°	5596.7
10°	5642.3
12.5°	5631.3
15°	5543.3
17.5°	5327.9
20°	4964.9
22.5°	4537.4
25°	4080.0
27.5°	3563.8
30°	2984.6
32.5°	2459.7
35°	1994.4
37.5°	1534.7
40°	1101.0
42.5°	719.0
45°	412.6
47.5°	218.5
50°	135.9
52.5°	94.3
55°	67.6
57.5°	48.7
60°	33.8
62.5°	22.0
65°	15.7
67.5°	14.1
70°	13.4
72.5°	10.2
75°	7.9
77.5°	7.1
80°	5.5
82.5°	3.9
85°	2.4
87.5°	1.6
90°	0.0



Report Generated By 670245859 / DESKTOP-T8S5UU9





— 0°-180°







(END OF REPORT)