

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P752332

Luminaire Tested: LD4D70BD010-EU4DR3570959035-4LBS1MW

Issue Date: 1/30/2024

Test Information

Test Method: LM-79-2019
Report Number: P752332
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-20)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 1/30/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD4D70BD010-EU4DR3570959035-4LBS1MW
Description: 4 INCH ROUND SHALLOW MATTE WHITE TRIM, WITH 35° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 3500K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 6551.2 lumens
Efficiency: N/A
Efficacy: 98.4 lumens/watt
Spacing Criteria (0/90/45): 0.6 / 0.6 / 0.54
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 66.6
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight

TEST NUMBER: P752332

CATALOG NUMBER: LD4D70BD010-EU4DR3570959035-4LBS1MW

Luminous Intensity Polar Plot



TEST NUMBER: P752332

CATALOG NUMBER: LD4D70BD010-EU4DR3570959035-4LBS1MW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	115	112	110	108	112	110	108	107	106	105	103		103	101	100		99
2	110	106	103	101	108	105	102	99	102	99	97		99	97	95		96
3	106	101	97	94	105	100	96	93	97	95	92		95	93	91		93
4	103	97	92	89	101	96	92	89	94	90	88		92	89	87		90
5	99	93	88	85	98	92	87	84	90	86	84		89	85	83		87
6	96	89	84	81	94	88	84	81	87	83	80		85	82	80		84
7	93	85	81	78	91	85	80	77	84	80	77		83	79	77		82
8	90	82	78	74	88	82	77	74	81	77	74		80	76	74		79
9	87	79	75	72	86	79	75	72	78	74	71		77	74	71		77
10	84	77	72	69	83	76	72	69	76	72	69		75	71	69		74

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	1969480
5°	1923206
10°	1733314
15°	1345334
20°	763052
25°	296857
30°	110746
35°	60702
40°	39680
45°	24151
50°	15366
55°	10858
60°	7954
65°	4318
70°	319
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 24151 cd/sqm



TEST NUMBER: P752332

CATALOG NUMBER: LD4D70BD010-EU4DR3570959035-4LBS1MW

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	1612.7	24.6
10°-20°	3148.7	48.1
20°-30°	1284.1	19.6
30°-40°	307.3	4.7
40°-50°	128.1	2.0
50°-60°	53.0	0.8
60°-70°	16.6	0.3
70°-80°	0.4	0.0
80°-90°	0.3	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	6045.5	92.3
0°-40°	6352.8	97.0
0°-60°	6533.9	99.7
0°-90°	6551.2	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	6551.2	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	18026	
5°	17535	###
15°	11894	3149
25°	2462	1284
35°	455	307
45°	156	128
55°	57	53
65°	17	17
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P752332

CATALOG NUMBER: LD4D70BD010-EU4DR3570959035-4LBS1MW

CANDELA DISTRIBUTION (FULL):

0°	
0°	18025.5
2.5°	17917.4
5°	17535.0
7.5°	16772.2
10°	15623.0
12.5°	14005.0
15°	11893.5
17.5°	9311.1
20°	6562.6
22.5°	4184.7
25°	2462.4
27.5°	1391.9
30°	877.8
32.5°	616.3
35°	455.1
37.5°	351.9
40°	278.2
42.5°	214.3
45°	156.3
47.5°	117.0
50°	90.4
52.5°	71.8
55°	57.0
57.5°	46.2
60°	36.4
62.5°	26.5
65°	16.7
67.5°	5.9
70°	1.0
72.5°	1.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	1.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670245859 / DESKTOP-T8S5UU9





— 0°-180°







(END OF REPORT)