

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P756281

Luminaire Tested: LD4D95BD010-EU4DR4070959027-4LBS1B

Issue Date: 1/30/2024

Test Information

Test Method: LM-79-2019
Report Number: P756281
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-28)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 1/30/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD4D95BD010-EU4DR4070959027-4LBS1B
Description: 4 INCH ROUND SHALLOW SPECULAR BLACK TRIM, WITH 40° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 2700K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 8818.6 lumens
Efficiency: N/A
Efficacy: 88.9 lumens/watt
Spacing Criteria (0/90/45): 0.68 / 0.68 / 0.6
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 99.2
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight

TEST NUMBER: P756281

CATALOG NUMBER: LD4D95BD010-EU4DR4070959027-4LBS1B

Luminous Intensity Polar Plot





TEST NUMBER: P756281

CATALOG NUMBER: LD4D95BD010-EU4DR4070959027-4LBS1B

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	115	112	110	108	112	110	108	107	106	105	103		103	101	100		99
2	110	106	103	100	108	105	102	99	102	99	97		99	97	95		96
3	106	101	97	94	104	100	96	93	97	94	92		95	93	90		93
4	102	97	92	89	101	95	91	88	93	90	87		92	89	86		90
5	99	92	88	84	97	91	87	84	90	86	83		88	85	83		87
6	95	88	84	80	94	88	83	80	86	82	80		85	82	79		84
7	92	85	80	77	91	84	80	77	83	79	76		82	79	76		81
8	89	82	77	74	88	81	77	74	80	76	73		79	76	73		78
9	86	79	74	71	85	78	74	71	77	73	71		76	73	70		76
10	83	76	71	68	82	75	71	68	75	71	68		74	70	68		73

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	2243342
5°	2232443
10°	2110143
15°	1793892
20°	1222667
25°	510144
30°	160404
35°	74548
40°	41234
45°	18898
50°	9179
55°	5029
60°	2622
65°	931
70°	383
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 18898 cd/sqm



TEST NUMBER: P756281

CATALOG NUMBER: LD4D95BD010-EU4DR4070959027-4LBS1B

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	1900.6	21.6
10°-20°	4257.8	48.3
20°-30°	2131.3	24.2
30°-40°	390.7	4.4
40°-50°	107.8	1.2
50°-60°	25.3	0.3
60°-70°	4.8	0.1
70°-80°	0.2	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	8289.8	94.0
0°-40°	8680.5	98.4
0°-60°	8813.6	99.9
0°-90°	8818.6	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	8818.6	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	20532	
5°	20354	###
15°	15859	4258
25°	4232	2131
35°	559	391
45°	122	108
55°	26	25
65°	4	5
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P756281

CATALOG NUMBER: LD4D95BD010-EU4DR4070959027-4LBS1B

CANDELA DISTRIBUTION (FULL):

	0°
0°	20532.0
2.5°	20502.0
5°	20354.5
7.5°	19884.3
10°	19019.5
12.5°	17671.3
15°	15859.0
17.5°	13502.1
20°	10515.5
22.5°	7169.0
25°	4231.6
27.5°	2237.0
30°	1271.4
32.5°	821.6
35°	558.9
37.5°	399.4
40°	289.1
42.5°	197.9
45°	122.3
47.5°	78.0
50°	54.0
52.5°	38.4
55°	26.4
57.5°	16.8
60°	12.0
62.5°	7.2
65°	3.6
67.5°	2.4
70°	1.2
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670245859 / DESKTOP-T8S5UU9





— 0°-180°







(END OF REPORT)