

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P756435

Luminaire Tested: LD4D95BD010-EU4DR5070959027-4LBDP1LI

Issue Date: 1/30/2024

Test Information

Test Method: LM-79-2019
Report Number: P756435
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-44)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 1/30/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD4D95BD010-EU4DR5070959027-4LBDP1LI
Description: 4 INCH ROUND DEEP 45° CUTOFF SPECULAR CLEAR TRIM, WITH 50° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 2700K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 9307.8 lumens
Efficiency: N/A
Efficacy: 93.8 lumens/watt
Spacing Criteria (0/90/45): 0.8 / 0.8 / 0.73
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 99.2
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight

TEST NUMBER: P756435

CATALOG NUMBER: LD4D95BD010-EU4DR5070959027-4LBDP1LI

Luminous Intensity Polar Plot



TEST NUMBER: P756435

CATALOG NUMBER: LD4D95BD010-EU4DR5070959027-4LBDP1LI

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20					20					20					20
RC	80				70					50					30					10
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100		
1	114	112	109	107	112	110	108	106	106	104	102	102	101	99	98	97	97	95		
2	109	105	101	98	107	103	100	97	100	98	95	97	95	93	95	93	91	90		
3	105	99	95	91	103	98	94	90	95	92	89	93	90	88	91	88	86	85		
4	100	94	89	85	99	93	88	85	90	87	84	89	85	83	87	84	82	80		
5	96	89	84	80	95	88	83	79	86	82	79	85	81	78	83	80	77	76		
6	92	84	79	75	91	83	79	75	82	78	74	81	77	74	79	76	74	72		
7	88	80	75	71	87	79	74	71	78	74	71	77	73	70	76	73	70	69		
8	85	76	71	67	84	76	71	67	75	70	67	74	70	67	73	69	66	65		
9	81	73	68	64	80	72	67	64	71	67	64	71	67	64	70	66	63	62		
10	78	70	64	61	77	69	64	61	68	64	61	68	64	61	67	63	60	59		

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	1638605
5°	1621426
10°	1594720
15°	1452115
20°	1208331
25°	857731
30°	453999
35°	185015
40°	68705
45°	31460
50°	12901
55°	6743
60°	3322
65°	982
70°	0
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 31460 cd/sqm



TEST NUMBER: P756435

CATALOG NUMBER: LD4D95BD010-EU4DR5070959027-4LBDP1LI

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	1397.3	15.0
10°-20°	3531.4	37.9
20°-30°	3172.1	34.1
30°-40°	993.2	10.7
40°-50°	173.9	1.9
50°-60°	34.7	0.4
60°-70°	5.3	0.1
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	8100.8	87.0
0°-40°	9094.0	97.7
0°-60°	9302.5	99.9
0°-90°	9307.8	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	9307.8	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	14997	
5°	14784	###
15°	12838	3531
25°	7115	3172
35°	1387	993
45°	204	174
55°	35	35
65°	4	5
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P756435

CATALOG NUMBER: LD4D95BD010-EU4DR5070959027-4LBDP1LI

CANDELA DISTRIBUTION (FULL):

	0°
0°	14997.2
2.5°	14922.6
5°	14783.5
7.5°	14571.0
10°	14373.8
12.5°	13741.6
15°	12837.5
17.5°	11689.5
20°	10392.2
22.5°	8891.3
25°	7114.8
27.5°	5230.9
30°	3598.5
32.5°	2342.9
35°	1387.1
37.5°	796.6
40°	481.7
42.5°	313.6
45°	203.6
47.5°	123.9
50°	75.9
52.5°	51.8
55°	35.4
57.5°	24.0
60°	15.2
62.5°	8.9
65°	3.8
67.5°	1.3
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670245859 / DESKTOP-T8S5UU9





— 0°-180°







(END OF REPORT)