

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P756566

Luminaire Tested: LD4D95BD010-EU4DR5570959050-4LBDP1MW

Issue Date: 1/30/2024

Test Information

Test Method: LM-79-2019
Report Number: P756566
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-52)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 1/30/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD4D95BD010-EU4DR5570959050-4LBDP1MW
Description: 4 INCH ROUND DEEP 45° CUTOFF MATTE WHITE TRIM, WITH 55° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 5000K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 8779.5 lumens
Efficiency: N/A
Efficacy: 88.5 lumens/watt
Spacing Criteria (0/90/45): 0.89 / 0.89 / 0.87
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 99.2
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight

TEST NUMBER: P756566

CATALOG NUMBER: LD4D95BD010-EU4DR5570959050-4LBDP1MW

Luminous Intensity Polar Plot





TEST NUMBER: P756566

CATALOG NUMBER: LD4D95BD010-EU4DR5570959050-4LBDP1MW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	114	111	108	106	111	109	106	104	105	103	101		101	99	98		97
2	108	103	99	96	106	101	98	95	98	95	92		95	93	90		92
3	102	96	91	87	100	95	90	86	92	88	85		90	86	84		87
4	97	90	84	80	95	88	83	79	86	82	78		84	81	78		82
5	92	84	78	74	91	83	77	73	81	76	73		79	75	72		78
6	88	79	73	68	86	78	72	68	76	71	68		75	70	67		74
7	83	74	68	64	82	73	67	63	72	67	63		71	66	63		70
8	79	69	63	59	78	69	63	59	68	63	59		67	62	59		66
9	75	66	60	56	74	65	59	55	64	59	55		63	58	55		62
10	72	62	56	52	71	61	56	52	61	56	52		60	55	52		59

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	1075650
5°	1032937
10°	1029038
15°	999473
20°	896173
25°	740647
30°	559459
35°	405657
40°	259600
45°	118562
50°	38772
55°	16725
60°	7189
65°	957
70°	0
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 118562 cd/sqm



TEST NUMBER: P756566

CATALOG NUMBER: LD4D95BD010-EU4DR5570959050-4LBDP1MW

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	896.2	10.2
10°-20°	2445.8	27.9
20°-30°	2787.2	31.7
30°-40°	1897.4	21.6
40°-50°	653.8	7.4
50°-60°	90.4	1.0
60°-70°	8.7	0.1
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	6129.1	69.8
0°-40°	8026.5	91.4
0°-60°	8770.7	99.9
0°-90°	8779.5	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	8779.5	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	9845	
5°	9418	896
15°	8836	2446
25°	6144	2787
35°	3041	1897
45°	767	654
55°	88	90
65°	4	9
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P756566

CATALOG NUMBER: LD4D95BD010-EU4DR5570959050-4LBDP1MW

CANDELA DISTRIBUTION (FULL):

0°	
0°	9844.8
2.5°	9619.1
5°	9417.9
7.5°	9319.0
10°	9275.1
12.5°	9128.7
15°	8835.9
17.5°	8371.2
20°	7707.5
22.5°	6941.4
25°	6143.6
27.5°	5312.8
30°	4434.4
32.5°	3690.3
35°	3041.3
37.5°	2424.0
40°	1820.1
42.5°	1261.4
45°	767.3
47.5°	413.6
50°	228.1
52.5°	135.4
55°	87.8
57.5°	56.1
60°	32.9
62.5°	14.6
65°	3.7
67.5°	1.2
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670245859 / DESKTOP-T8S5UU9





— 0°-180°







(END OF REPORT)