

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P748474

Luminaire Tested: LD4D45BD010-EU4DR4040509027-4LBCSSQMB

Issue Date: 1/30/2024

Test Information

Test Method: LM-79-2019
Report Number: P748474
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-28)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 1/30/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD4D45BD010-EU4DR4040509027-4LBCSSQMB
Description: 4 INCH SQAURE SHALLOW CAST MATTE BLACK TRIM, WITH 40° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 2700K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 3936.9 lumens
Efficiency: N/A
Efficacy: 101.7 lumens/watt
Spacing Criteria (0/90/45): 0.68 / 0.68 / 0.6
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct


Input Watts (W): 38.7
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



TEST NUMBER: P748474

CATALOG NUMBER: LD4D45BD010-EU4DR4040509027-4LBCSSQMB

Luminous Intensity Polar Plot





TEST NUMBER: P748474

CATALOG NUMBER: LD4D45BD010-EU4DR4040509027-4LBCSSQMB

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20					20					20					20
RC	80				70					50					30					10
RW	70	50	30	10	70	50	30	10		50	30	10			50	30	10			50
RCR																				
0	119	119	119	119	116	116	116	116		111	111	111			106	106	106			102
1	115	112	110	108	112	110	108	107		106	105	103			103	101	100			99
2	110	106	103	100	108	105	102	99		102	99	97			99	97	95			96
3	106	101	97	94	104	100	96	93		97	94	92			95	93	90			93
4	102	97	92	89	101	95	91	88		93	90	87			92	89	86			90
5	99	92	88	84	97	91	87	84		90	86	83			88	85	83			87
6	95	88	84	80	94	88	83	80		86	82	80			85	82	79			84
7	92	85	80	77	91	84	80	77		83	79	76			82	79	76			81
8	89	82	77	74	88	81	77	74		80	76	73			79	76	73			78
9	86	79	74	71	85	78	74	71		77	73	71			76	73	70			76
10	83	76	71	68	82	75	71	68		75	71	68			74	70	68			73

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	1001506
5°	996645
10°	942045
15°	800855
20°	545843
25°	227742
30°	71610
35°	33279
40°	18399
45°	8437
50°	4097
55°	2248
60°	1180
65°	414
70°	160
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 8437 cd/sqm



TEST NUMBER: P748474

CATALOG NUMBER: LD4D45BD010-EU4DR4040509027-4LBCSSQMB

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	848.5	21.6
10°-20°	1900.9	48.3
20°-30°	951.5	24.2
30°-40°	174.4	4.4
40°-50°	48.1	1.2
50°-60°	11.3	0.3
60°-70°	2.2	0.1
70°-80°	0.1	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	3700.8	94.0
0°-40°	3875.3	98.4
0°-60°	3934.7	99.9
0°-90°	3936.9	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	3936.9	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	9166	
5°	9087	848
15°	7080	1901
25°	1889	952
35°	250	174
45°	55	48
55°	12	11
65°	2	2
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P748474

CATALOG NUMBER: LD4D45BD010-EU4DR4040509027-4LBCSSQMB

CANDELA DISTRIBUTION (FULL):

	0°
0°	9166.2
2.5°	9152.8
5°	9087.0
7.5°	8877.1
10°	8491.0
12.5°	7889.1
15°	7080.0
17.5°	6027.8
20°	4694.5
22.5°	3200.5
25°	1889.1
27.5°	998.7
30°	567.6
32.5°	366.8
35°	249.5
37.5°	178.3
40°	129.0
42.5°	88.4
45°	54.6
47.5°	34.8
50°	24.1
52.5°	17.1
55°	11.8
57.5°	7.5
60°	5.4
62.5°	3.2
65°	1.6
67.5°	1.1
70°	0.5
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670245859 / DESKTOP-T8S5UU9





— 0°-180°







(END OF REPORT)