

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P205898

Luminaire Tested: **LD4B15D010 EU4B10208027 4LBSGPH1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P205898
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LD4B15D010 EU4B10208027 4LBSGPH1
Description: PORTFOLIO 4 INCH SHALLOW RECESSED DOWNLIGHT
SHALLOW DISTRIBUTION WITH GRAPHITE HAZE TRIM
WATTAGE D010TR-14.39W DE010-14.29W D5LT-14.34W DMX-14.46W DL2-15.8W
DL3-15.28W DLE-15.432W
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1289.0 lumens
Efficiency: N/A
Efficacy: 90.1 lumens/watt
Spacing Criteria (0/90/45): 1.16 / 1.16 / 1.26
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 14.3
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P205898

CATALOG NUMBER: LD4B15D010 EU4B10208027 4LBSGPH1

Luminous Intensity Polar Plot






TEST NUMBER: P205898

CATALOG NUMBER: LD4B15D010 EU4B10208027 4LBSGPH1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20					20					20					20
RC	80				70					50					30					10
RW	70	50	30	10	70	50	30	10		50	30	10		50	30	10		50	30	10
RCR																				
0	119	119	119	119	116	116	116	116		111	111	111		106	106	106		102	102	102
1	111	107	103	100	108	105	102	99		101	98	96		97	95	93		93	91	90
2	102	95	89	84	100	93	88	83		90	85	82		87	83	80		84	81	78
3	94	85	78	72	92	83	77	71		80	75	70		78	73	69		75	71	68
4	87	76	68	62	85	75	67	62		72	66	61		70	65	60		68	63	59
5	80	68	60	54	78	67	60	54		65	59	53		63	58	53		62	56	52
6	74	62	54	48	73	61	53	48		59	52	47		58	52	47		56	51	47
7	69	57	48	43	68	56	48	43		54	47	42		53	47	42		52	46	42
8	65	52	44	38	63	51	44	38		50	43	38		49	42	38		48	42	38
9	60	48	40	35	59	47	40	35		46	39	35		45	39	34		44	38	34
10	57	44	37	32	56	44	36	32		43	36	32		42	36	31		41	35	31

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P205898

CATALOG NUMBER: LD4B15D010 EU4B10208027 4LBSGPH1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	56.4	4.4
10°-20°	158.2	12.3
20°-30°	230.8	17.9
30°-40°	263.2	20.4
40°-50°	252.5	19.6
50°-60°	193.3	15.0
60°-70°	106.1	8.2
70°-80°	28.2	2.2
80°-90°	0.4	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	445.4	34.6
0°-40°	708.6	55.0
0°-60°	1154.3	89.5
0°-90°	1289.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1289.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	599	
5°	594	56
15°	562	158
25°	501	231
35°	421	263
45°	328	252
55°	217	193
65°	107	106
75°	25	28
85°	0	0
90°	0	



TEST NUMBER: P205898

CATALOG NUMBER: LD4B15D010 EU4B10208027 4LBSGPH1

CANDELA DISTRIBUTION (FULL):

0°	
0°	598.7
2.5°	597.2
5°	594.1
7.5°	589.4
10°	583.2
12.5°	572.4
15°	561.6
17.5°	549.2
20°	535.3
22.5°	518.3
25°	501.2
27.5°	484.2
30°	462.6
32.5°	442.5
35°	420.8
37.5°	399.1
40°	377.5
42.5°	354.3
45°	328.0
47.5°	301.7
50°	273.8
52.5°	244.4
55°	216.6
57.5°	188.7
60°	159.3
62.5°	131.5
65°	106.7
67.5°	82.0
70°	60.3
72.5°	40.2
75°	24.8
77.5°	10.8
80°	3.1
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)