

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P205696

Luminaire Tested: **LD4B15D010 EU4B10209027 4LBSH1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P205696
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LD4B15D010 EU4B10209027 4LBSH1
Description: PORTFOLIO 4 INCH SHALLOW RECESSED DOWNLIGHT
SHALLOW DISTRIBUTION WITH SEMI-SPECULAR CLEAR TRIM
WATTAGE D010TR-14.39W DE010-14.29W D5LT-14.34W DMX-14.46W DL2-15.8W
DL3-15.28W DLE-15.432W
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1206.4 lumens
Efficiency: N/A
Efficacy: 84.4 lumens/watt
Spacing Criteria (0/90/45): 1.06 / 1.06 / 1.17
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 14.3
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P205696

CATALOG NUMBER: LD4B15D010 EU4B10209027 4LBSH1

Luminous Intensity Polar Plot





TEST NUMBER: P205696

CATALOG NUMBER: LD4B15D010 EU4B10209027 4LBSH1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20					20					20					20
RC	80				70					50					30					10
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100		
1	111	107	104	101	108	105	102	99	101	98	96	97	95	93	93	92	90	88		
2	102	96	90	85	100	94	88	84	90	86	82	87	83	80	84	81	79	77		
3	95	85	78	73	92	84	77	72	81	75	71	78	74	70	76	72	69	67		
4	87	77	69	63	85	75	68	63	73	67	62	71	65	61	69	64	60	58		
5	81	69	61	55	79	68	61	55	66	60	55	64	59	54	63	58	53	51		
6	75	63	55	49	73	62	54	49	60	54	49	59	53	48	57	52	48	46		
7	70	58	50	44	68	57	49	44	55	49	44	54	48	43	53	47	43	41		
8	65	53	45	40	64	52	45	40	51	44	39	50	44	39	49	43	39	37		
9	61	49	41	36	60	48	41	36	47	40	36	46	40	36	45	40	35	34		
10	58	45	38	33	56	45	38	33	44	37	33	43	37	33	42	37	33	31		

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P205696

CATALOG NUMBER: LD4B15D010 EU4B10209027 4LBSH1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	59.1	4.9
10°-20°	160.6	13.3
20°-30°	223.1	18.5
30°-40°	243.4	20.2
40°-50°	227.1	18.8
50°-60°	172.4	14.3
60°-70°	94.4	7.8
70°-80°	26.0	2.2
80°-90°	0.4	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	442.8	36.7
0°-40°	686.2	56.9
0°-60°	1085.7	90.0
0°-90°	1206.4	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1206.4	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	631	
5°	626	59
15°	572	161
25°	485	223
35°	389	243
45°	295	227
55°	193	172
65°	94	94
75°	23	26
85°	0	0
90°	0	



TEST NUMBER: P205696

CATALOG NUMBER: LD4B15D010 EU4B10209027 4LBSH1

CANDELA DISTRIBUTION (FULL):

	0°
0°	630.9
2.5°	630.9
5°	625.6
7.5°	617.6
10°	605.7
12.5°	589.7
15°	572.5
17.5°	551.2
20°	531.3
22.5°	507.4
25°	484.8
27.5°	462.2
30°	437.0
32.5°	413.1
35°	389.2
37.5°	365.3
40°	342.7
42.5°	318.8
45°	294.9
47.5°	271.0
50°	244.4
52.5°	219.2
55°	192.6
57.5°	167.4
60°	142.1
62.5°	116.9
65°	94.3
67.5°	73.1
70°	54.5
72.5°	37.2
75°	22.6
77.5°	10.6
80°	2.7
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)