

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P206419

Luminaire Tested: **LD4B15D010 EU4B10208030 4LBCSMB1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P206419
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LD4B15D010 EU4B10208030 4LBCSMB1
Description: PORTFOLIO 4 INCH SHALLOW RECESSED DOWNLIGHT
SHALLOW DISTRIBUTION WITH CAST MATTE METALLIC SILVER TRIM
WATTAGE D010TR-14.39W DE010-14.29W D5LT-14.34W DMX-14.46W DL2-15.8W
DL3-15.28W DLE-15.432W
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1460.8 lumens
Efficiency: N/A
Efficacy: 102.2 lumens/watt
Spacing Criteria (0/90/45): 1.23 / 1.23 / 1.33
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 14.3
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P206419

CATALOG NUMBER: LD4B15D010 EU4B10208030 4LBCSMB1

Luminous Intensity Polar Plot






TEST NUMBER: P206419

CATALOG NUMBER: LD4B15D010 EU4B10208030 4LBCSMB1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20					20					20					20
RC	80				70					50					30					10
RW	70	50	30	10	70	50	30	10		50	30	10		50	30	10		50	30	10
RCR																				
0	119	119	119	119	116	116	116	116		111	111	111		106	106	106		102	102	102
1	111	107	103	100	108	104	101	98		100	98	95		96	94	92		93	91	90
2	102	95	89	84	99	93	87	83		89	85	81		86	82	79		83	80	77
3	93	84	77	71	91	83	76	70		80	74	69		77	72	68		74	70	67
4	86	75	67	61	84	74	66	61		71	65	60		69	63	59		67	62	58
5	79	67	59	53	77	66	59	53		64	57	52		62	56	52		61	55	51
6	74	61	53	47	72	60	52	46		58	51	46		57	50	46		55	50	45
7	68	55	47	41	67	55	47	41		53	46	41		52	45	41		50	45	40
8	64	51	43	37	62	50	42	37		49	42	37		48	41	37		46	41	36
9	60	47	39	33	58	46	39	33		45	38	33		44	38	33		43	37	33
10	56	43	35	30	55	43	35	30		42	35	30		41	34	30		40	34	30

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P206419

CATALOG NUMBER: LD4B15D010 EU4B10208030 4LBCSMB1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	58.3	4.0
10°-20°	166.2	11.4
20°-30°	249.9	17.1
30°-40°	296.5	20.3
40°-50°	293.4	20.1
50°-60°	230.4	15.8
60°-70°	129.2	8.8
70°-80°	36.3	2.5
80°-90°	0.6	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	474.4	32.5
0°-40°	770.9	52.8
0°-60°	1294.7	88.6
0°-90°	1460.8	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1460.8	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	617	
5°	616	58
15°	590	166
25°	542	250
35°	476	296
45°	382	293
55°	260	230
65°	129	129
75°	31	36
85°	0	1
90°	0	



TEST NUMBER: P206419

CATALOG NUMBER: LD4B15D010 EU4B10208030 4LBCSMB1

CANDELA DISTRIBUTION (FULL):

0°	
0°	616.8
2.5°	614.7
5°	615.8
7.5°	610.6
10°	604.3
12.5°	596.9
15°	589.6
17.5°	580.2
20°	567.6
22.5°	555.0
25°	542.5
27.5°	528.9
30°	511.1
32.5°	493.3
35°	475.5
37.5°	454.5
40°	430.4
42.5°	407.4
45°	382.2
47.5°	354.0
50°	324.6
52.5°	291.1
55°	259.7
57.5°	224.1
60°	190.6
62.5°	160.2
65°	128.8
67.5°	101.6
70°	75.4
72.5°	51.3
75°	31.4
77.5°	15.7
80°	4.2
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)