

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P252075

Luminaire Tested: **LD4B15D010 EU4B10209730 4LBBA1MB**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P252075
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-1712-453-4)
Test Lab: INNOVATION CENTER(G1)
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LD4B15D010 EU4B10209730 4LBBA1MB
Description: PORTFOLIO 4 INCH BAFFLE RECESSED DOWNLIGHT, WITH MATTE BLACK TRIM
Light Source: (1) HIGH LUMEN LED 97CRI / 3000K CCT
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 558.0 lumens
Efficiency: N/A
Efficacy: 38.8 lumens/watt
Spacing Criteria (0/90/45): 1.04 / 1.04 / 0.94
Luminous Opening: Circular (Dia: 0.38' x H: 0')
CIE Type: Direct


Input Watts (W): 14.39
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P252075

CATALOG NUMBER: LD4B15D010 EU4B10209730 4LBBA1MB

Luminous Intensity Polar Plot





TEST NUMBER: P252075

CATALOG NUMBER: LD4B15D010 EU4B10209730 4LBBA1MB

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	111	108	106	111	109	106	104	105	103	101		101	99	98		97
2	108	103	99	96	106	101	98	94	98	95	92		95	93	90		92
3	102	96	91	87	100	95	90	86	92	88	85		90	86	84		87
4	97	90	84	80	95	88	83	79	86	82	78		84	81	77		82
5	92	84	78	74	91	83	77	73	81	76	73		79	75	72		78
6	88	79	73	68	86	78	72	68	76	71	68		75	70	67		74
7	83	74	68	63	82	73	67	63	72	67	63		71	66	63		69
8	79	69	63	59	78	69	63	59	68	63	59		67	62	59		66
9	75	65	59	55	74	65	59	55	64	59	55		63	58	55		62
10	72	62	56	52	71	61	56	52	60	55	52		60	55	52		59

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	54391
5°	54237
10°	53716
15°	52849
20°	51307
25°	47401
30°	38453
35°	23831
40°	11221
45°	3914
50°	1107
55°	748
60°	565
65°	507
70°	427
75°	264
80°	393
85°	0



TEST NUMBER: P252075

CATALOG NUMBER: LD4B15D010 EU4B10209730 4LBBA1MB

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	52.5	9.4
10°-20°	147.2	26.4
20°-30°	197.9	35.5
30°-40°	126.4	22.7
40°-50°	26.9	4.8
50°-60°	4.0	0.7
60°-70°	2.0	0.4
70°-80°	0.8	0.2
80°-90°	0.1	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	397.7	71.3
0°-40°	524.1	93.9
0°-60°	555.1	99.5
0°-90°	558.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	558.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	558	
5°	554	53
15°	524	147
25°	441	198
35°	200	126
45°	28	27
55°	4	4
65°	2	2
75°	1	1
85°	0	0
90°	0	



TEST NUMBER: P252075

CATALOG NUMBER: LD4B15D010 EU4B10209730 4LBBA1MB

CANDELA DISTRIBUTION (FULL):

0°	
0°	558.1
2.5°	557.3
5°	554.4
7.5°	549.3
10°	542.8
12.5°	534.0
15°	523.8
17.5°	510.7
20°	494.7
22.5°	472.1
25°	440.8
27.5°	397.1
30°	341.7
32.5°	273.2
35°	200.3
37.5°	137.0
40°	88.2
42.5°	52.5
45°	28.4
47.5°	14.6
50°	7.3
52.5°	5.1
55°	4.4
57.5°	3.6
60°	2.9
62.5°	2.2
65°	2.2
67.5°	1.5
70°	1.5
72.5°	0.7
75°	0.7
77.5°	0.7
80°	0.7
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)