

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P208386

Luminaire Tested: **LD4B20D010 EU4B10209024 4LBSLI1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P208386
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LD4B20D010 EU4B10209024 4LBSLI1
Description: PORTFOLIO 4 INCH SHALLOW RECESSED DOWNLIGHT
SHALLOW DISTRIBUTION WITH SPECULAR CLEAR TRIM
WATTAGE D010TR-21.86W DE010-20.46W D5LT-21.24W DMX-20.89W DL2-22.5W
DL3-21.8 6W DLE-22.46W
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1498.6 lumens
Efficiency: N/A
Efficacy: 72.0 lumens/watt
Spacing Criteria (0/90/45): 0.91 / 0.91 / 1
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 20.8
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P208386

CATALOG NUMBER: LD4B20D010 EU4B10209024 4LBSLI1

Luminous Intensity Polar Plot





TEST NUMBER: P208386

CATALOG NUMBER: LD4B20D010 EU4B10209024 4LBSLI1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20					20					20				20
RC	80				70					50					30				10
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30
RCR																			
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100	
1	112	108	105	102	109	106	103	101	102	100	98	98	96	95	95	93	92	90	
2	104	98	93	88	102	96	91	87	93	89	85	90	86	84	87	84	82	80	
3	97	89	82	77	95	87	81	77	84	79	75	82	78	74	79	76	73	71	
4	90	81	73	68	88	79	73	68	77	71	67	75	70	66	73	69	65	63	
5	84	73	66	61	82	72	65	60	70	64	60	69	63	59	67	62	59	57	
6	79	67	60	54	77	66	59	54	65	58	54	63	58	53	62	57	53	51	
7	74	62	54	49	72	61	54	49	60	53	49	58	53	48	57	52	48	46	
8	69	57	50	45	68	57	50	45	55	49	45	54	49	44	53	48	44	42	
9	65	53	46	41	64	53	46	41	52	45	41	51	45	41	50	44	41	39	
10	61	50	43	38	60	49	42	38	48	42	38	47	42	38	46	41	37	36	

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P208386

CATALOG NUMBER: LD4B20D010 EU4B10209024 4LBSLI1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	97.0	6.5
10°-20°	247.4	16.5
20°-30°	320.6	21.4
30°-40°	314.2	21.0
40°-50°	266.3	17.8
50°-60°	174.6	11.7
60°-70°	70.2	4.7
70°-80°	8.0	0.5
80°-90°	0.2	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	665.1	44.4
0°-40°	979.3	65.3
0°-60°	1420.2	94.8
0°-90°	1498.6	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1498.6	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1070	
5°	1042	97
15°	883	247
25°	700	321
35°	499	314
45°	347	266
55°	194	175
65°	68	70
75°	3	8
85°	0	0
90°	0	



TEST NUMBER: P208386

CATALOG NUMBER: LD4B20D010 EU4B10209024 4LBSLI1

CANDELA DISTRIBUTION (FULL):

	0°
0°	1070.0
2.5°	1061.7
5°	1041.8
7.5°	1008.6
10°	967.2
12.5°	922.4
15°	882.6
17.5°	839.4
20°	796.3
22.5°	749.8
25°	700.1
27.5°	648.6
30°	595.6
32.5°	545.8
35°	499.3
37.5°	461.2
40°	419.7
42.5°	383.2
45°	346.7
47.5°	308.6
50°	270.4
52.5°	232.3
55°	194.1
57.5°	159.3
60°	126.1
62.5°	96.2
65°	68.0
67.5°	44.8
70°	26.5
72.5°	11.6
75°	3.3
77.5°	1.7
80°	1.7
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)