

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P206229

Luminaire Tested: **LD4B20D010 EU4B10209027 4LBPSMW1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P206229
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LD4B20D010 EU4B10209027 4LBPSMW1
Description: PORTFOLIO 4 INCH SHALLOW RECESSED DOWNLIGHT
SHALLOW DISTRIBUTION WITH PLASTIC MATTE WHITE TRIM
WATTAGE D010TR-21.86W DE010-20.46W D5LT-21.24W DMX-20.89W DL2-22.5W
DL3-21.8 6W DLE-22.46W
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1773.0 lumens
Efficiency: N/A
Efficacy: 85.2 lumens/watt
Spacing Criteria (0/90/45): 1.24 / 1.24 / 1.34
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 20.8
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P206229

CATALOG NUMBER: LD4B20D010 EU4B10209027 4LBPSMW1

Luminous Intensity Polar Plot





TEST NUMBER: P206229

CATALOG NUMBER: LD4B20D010 EU4B10209027 4LBPSMW1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	110	106	102	99	107	104	100	97	99	97	94		96	93	91		92
2	101	93	87	82	98	92	86	81	88	83	79		85	81	77		82
3	93	83	75	69	90	81	74	69	78	72	67		76	70	66		73
4	85	74	66	59	83	72	65	59	70	63	58		68	62	57		66
5	78	66	58	51	76	65	57	51	63	56	51		61	55	50		59
6	73	60	51	45	71	59	51	45	57	50	44		55	49	44		54
7	67	54	46	40	66	54	46	40	52	45	40		51	44	39		49
8	63	50	41	36	61	49	41	36	48	41	35		46	40	35		45
9	59	46	38	32	57	45	37	32	44	37	32		43	36	32		42
10	55	42	34	29	54	42	34	29	41	34	29		40	33	29		39

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P206229

CATALOG NUMBER: LD4B20D010 EU4B10209027 4LBPSMW1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	67.7	3.8
10°-20°	192.9	10.9
20°-30°	290.6	16.4
30°-40°	345.7	19.5
40°-50°	345.1	19.5
50°-60°	280.6	15.8
60°-70°	172.7	9.7
70°-80°	66.9	3.8
80°-90°	10.7	0.6
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	551.2	31.1
0°-40°	896.9	50.6
0°-60°	1522.7	85.9
0°-90°	1773.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1773.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	714	
5°	712	68
15°	685	193
25°	632	291
35°	554	346
45°	449	345
55°	314	281
65°	173	173
75°	61	67
85°	8	11
90°	0	



TEST NUMBER: P206229

CATALOG NUMBER: LD4B20D010 EU4B10209027 4LBPSMW1

CANDELA DISTRIBUTION (FULL):

0°	
0°	714.4
2.5°	715.4
5°	712.3
7.5°	708.1
10°	702.8
12.5°	693.4
15°	684.9
17.5°	672.3
20°	658.7
22.5°	646.1
25°	632.4
27.5°	613.5
30°	594.6
32.5°	576.7
35°	553.6
37.5°	528.4
40°	505.3
42.5°	476.9
45°	448.6
47.5°	418.1
50°	385.5
52.5°	351.9
55°	314.1
57.5°	277.3
60°	241.6
62.5°	207.0
65°	173.3
67.5°	141.8
70°	112.4
72.5°	85.1
75°	60.9
77.5°	39.9
80°	24.2
82.5°	14.7
85°	8.4
87.5°	4.2
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)