

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P205913

Luminaire Tested: **LD4B20D010 EU4B10208035 4LBSGPH1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P205913
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LD4B20D010 EU4B10208035 4LBSGPH1
Description: PORTFOLIO 4 INCH SHALLOW RECESSED DOWNLIGHT
SHALLOW DISTRIBUTION WITH GRAPHITE HAZE TRIM
WATTAGE D010TR-21.86W DE010-20.46W D5LT-21.24W DMX-20.89W DL2-22.5W
DL3-21.8 6W DLE-22.46W
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1870.0 lumens
Efficiency: N/A
Efficacy: 89.9 lumens/watt
Spacing Criteria (0/90/45): 1.16 / 1.16 / 1.26
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 20.8
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P205913

CATALOG NUMBER: LD4B20D010 EU4B10208035 4LBSGPH1

Luminous Intensity Polar Plot





TEST NUMBER: P205913

CATALOG NUMBER: LD4B20D010 EU4B10208035 4LBSGPH1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20					20					20					20
RC	80				70					50					30					0
RW	70	50	30	10	70	50	30	10		50	30	10		50	30	10		50	30	10
RCR																				
0	119	119	119	119	116	116	116	116		111	111	111		106	106	106		102	102	102
1	111	107	103	100	108	105	102	99		101	98	96		97	95	93		93	91	90
2	102	95	89	84	100	93	88	83		90	85	82		87	83	80		84	81	78
3	94	85	78	72	92	83	77	71		80	75	70		78	73	69		75	71	68
4	87	76	68	62	85	75	67	62		72	66	61		70	65	60		68	63	59
5	80	68	60	54	78	67	60	54		65	59	53		63	58	53		62	56	52
6	74	62	54	48	73	61	53	48		59	52	47		58	52	47		56	51	47
7	69	57	48	43	68	56	48	43		54	47	42		53	47	42		52	46	42
8	65	52	44	38	63	51	44	38		50	43	38		49	42	38		48	42	38
9	60	48	40	35	59	47	40	35		46	39	35		45	39	34		44	38	34
10	57	44	37	32	56	44	36	32		43	36	31		42	36	31		41	35	31

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P205913

CATALOG NUMBER: LD4B20D010 EU4B10208035 4LBSGPH1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	81.8	4.4
10°-20°	229.5	12.3
20°-30°	334.8	17.9
30°-40°	381.8	20.4
40°-50°	366.2	19.6
50°-60°	280.5	15.0
60°-70°	153.9	8.2
70°-80°	40.9	2.2
80°-90°	0.6	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	646.1	34.6
0°-40°	1027.8	55.0
0°-60°	1674.5	89.5
0°-90°	1870.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1870.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	868	
5°	862	82
15°	815	230
25°	727	335
35°	610	382
45°	476	366
55°	314	280
65°	155	154
75°	36	41
85°	0	1
90°	0	



TEST NUMBER: P205913

CATALOG NUMBER: LD4B20D010 EU4B10208035 4LBSGPH1

CANDELA DISTRIBUTION (FULL):

0°	
0°	868.5
2.5°	866.3
5°	861.8
7.5°	855.0
10°	846.1
12.5°	830.4
15°	814.7
17.5°	796.7
20°	776.5
22.5°	751.8
25°	727.1
27.5°	702.4
30°	671.0
32.5°	641.8
35°	610.4
37.5°	579.0
40°	547.6
42.5°	513.9
45°	475.8
47.5°	437.6
50°	397.2
52.5°	354.6
55°	314.2
57.5°	273.8
60°	231.2
62.5°	190.8
65°	154.9
67.5°	118.9
70°	87.5
72.5°	58.3
75°	35.9
77.5°	15.7
80°	4.5
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)