

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P206122

Luminaire Tested: **LD4B20D010 EU4B10208040 4LBSMW1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P206122
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LD4B20D010 EU4B10208040 4LBSMW1
Description: PORTFOLIO 4 INCH SHALLOW RECESSED DOWNLIGHT
SHALLOW DISTRIBUTION WITH MATTE WHITE TRIM
WATTAGE D010TR-21.86W DE010-20.46W D5LT-21.24W DMX-20.89W DL2-22.5W
DL3-21.8 6W DLE-22.46W
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 2148.4 lumens
Efficiency: N/A
Efficacy: 103.3 lumens/watt
Spacing Criteria (0/90/45): 1.24 / 1.24 / 1.34
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 20.8
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P206122

CATALOG NUMBER: LD4B20D010 EU4B10208040 4LBSMW1

Luminous Intensity Polar Plot





TEST NUMBER: P206122

CATALOG NUMBER: LD4B20D010 EU4B10208040 4LBSMW1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20					20					20					20
RC	80				70					50					30					10
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100		
1	110	106	102	99	107	104	100	97	99	97	94	96	93	91	92	90	88	86		
2	101	93	87	82	98	92	86	81	88	83	79	85	81	77	82	79	76	74		
3	93	83	75	69	90	81	74	69	78	72	67	76	70	66	73	69	65	63		
4	85	74	66	59	83	72	65	59	70	63	58	68	62	57	66	61	56	54		
5	78	66	58	51	76	65	57	51	63	56	51	61	55	50	59	54	49	47		
6	73	60	51	45	71	59	51	45	57	50	44	55	49	44	54	48	44	42		
7	67	54	46	40	66	54	46	40	52	45	40	51	44	39	49	43	39	37		
8	63	50	41	36	61	49	41	36	48	41	35	46	40	35	45	39	35	33		
9	59	46	38	32	57	45	37	32	44	37	32	43	36	32	42	36	32	30		
10	55	42	34	29	54	42	34	29	41	34	29	40	33	29	39	33	29	27		

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P206122

CATALOG NUMBER: LD4B20D010 EU4B10208040 4LBSMW1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	82.0	3.8
10°-20°	233.8	10.9
20°-30°	352.1	16.4
30°-40°	418.9	19.5
40°-50°	418.2	19.5
50°-60°	340.1	15.8
60°-70°	209.2	9.7
70°-80°	81.1	3.8
80°-90°	13.0	0.6
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	667.9	31.1
0°-40°	1086.8	50.6
0°-60°	1845.1	85.9
0°-90°	2148.4	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2148.4	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	866	
5°	863	82
15°	830	234
25°	766	352
35°	671	419
45°	544	418
55°	381	340
65°	210	209
75°	74	81
85°	10	13
90°	0	



TEST NUMBER: P206122

CATALOG NUMBER: LD4B20D010 EU4B10208040 4LBSMW1

CANDELA DISTRIBUTION (FULL):

	0°
0°	865.6
2.5°	866.9
5°	863.0
7.5°	858.0
10°	851.6
12.5°	840.1
15°	829.9
17.5°	814.7
20°	798.1
22.5°	782.9
25°	766.3
27.5°	743.4
30°	720.5
32.5°	698.8
35°	670.8
37.5°	640.3
40°	612.3
42.5°	577.9
45°	543.5
47.5°	506.6
50°	467.2
52.5°	426.4
55°	380.6
57.5°	336.1
60°	292.8
62.5°	250.8
65°	210.0
67.5°	171.8
70°	136.2
72.5°	103.1
75°	73.8
77.5°	48.4
80°	29.3
82.5°	17.8
85°	10.2
87.5°	5.1
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)