

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P207778

Luminaire Tested: **LD4B20D010 EU4B10209040 4LBNGPH1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P207778
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LD4B20D010 EU4B10209040 4LBNGPH1
Description: PORTFOLIO 4 INCH 50 DEGREE CUTOFF RECESSED DOWNLIGHT
NARROW DISTRIBUTION WITH GRAPHITE HAZE TRIM
WATTAGE D010TR-21.86W DE010-20.46W D5LT-21.24W DMX-20.89W DL2-22.5W
DL3-21.8 6W DLE-22.46W
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 823.0 lumens
Efficiency: N/A
Efficacy: 39.6 lumens/watt
Spacing Criteria (0/90/45): 0.86 / 0.86 / 0.88
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 20.8
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P207778

CATALOG NUMBER: LD4B20D010 EU4B10209040 4LBNGPH1

Luminous Intensity Polar Plot





TEST NUMBER: P207778

CATALOG NUMBER: LD4B20D010 EU4B10209040 4LBNGPH1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20					20					20					20
RC	80				70					50					30					10
RW	70	50	30	10	70	50	30	10		50	30	10			50	30	10			50
RCR																				
0	119	119	119	119	116	116	116	116		111	111	111			106	106	106			102
1	114	111	108	106	111	109	106	104		105	103	101			101	100	98			97
2	108	103	99	96	106	101	98	95		98	95	93			95	93	91			92
3	103	96	91	87	101	95	90	87		92	88	85			90	87	84			88
4	97	90	84	80	96	89	84	80		87	82	79			85	81	78			83
5	93	84	78	74	91	83	78	74		82	77	73			80	76	73			78
6	88	79	73	69	86	78	73	69		77	72	68			75	71	68			74
7	84	74	68	64	82	74	68	64		72	67	64			71	67	63			70
8	80	70	64	60	78	70	64	60		68	63	60			67	63	59			66
9	76	66	60	56	75	66	60	56		65	60	56			64	59	56			63
10	72	63	57	53	71	62	57	53		61	56	53			61	56	53			60

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P207778

CATALOG NUMBER: LD4B20D010 EU4B10209040 4LBNGPH1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	89.7	10.9
10°-20°	224.9	27.3
20°-30°	274.1	33.3
30°-40°	180.9	22.0
40°-50°	41.7	5.1
50°-60°	8.0	1.0
60°-70°	3.0	0.4
70°-80°	0.8	0.1
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	588.8	71.5
0°-40°	769.7	93.5
0°-60°	819.3	99.5
0°-90°	823.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	823.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	987	
5°	963	90
15°	806	225
25°	602	274
35°	289	181
45°	46	42
55°	8	8
65°	2	3
75°	0	1
85°	0	0
90°	0	



TEST NUMBER: P207778

CATALOG NUMBER: LD4B20D010 EU4B10209040 4LBNGPH1

CANDELA DISTRIBUTION (FULL):

	0°
0°	986.9
2.5°	984.9
5°	963.0
7.5°	933.1
10°	893.2
12.5°	853.4
15°	805.5
17.5°	755.7
20°	703.8
22.5°	658.0
25°	602.1
27.5°	546.3
30°	474.5
32.5°	386.8
35°	289.1
37.5°	201.4
40°	129.6
42.5°	79.8
45°	45.9
47.5°	23.9
50°	14.0
52.5°	12.0
55°	8.0
57.5°	6.0
60°	6.0
62.5°	4.0
65°	2.0
67.5°	2.0
70°	2.0
72.5°	2.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)