

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P206851

Luminaire Tested: **LD4B20D010 EU4B10209040 4LBWGPH1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P206851
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LD4B20D010 EU4B10209040 4LBWGPH1
Description: PORTFOLIO 4 INCH 60 DEGREE CUTOFF RECESSED DOWNLIGHT
WIDE DISTRIBUTIONWITH GRAPHITE HAZE TRIM
WATTAGE D010TR-21.86W DE010-20.46W D5LT-21.24W DMX-20.89W DL2-22.5W
DL3-21.8 6W DLE-22.46W
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1149.8 lumens
Efficiency: N/A
Efficacy: 55.3 lumens/watt
Spacing Criteria (0/90/45): 1.12 / 1.12 / 1.08
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 20.8
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P206851

CATALOG NUMBER: LD4B20D010 EU4B10209040 4LBWGPH1

Luminous Intensity Polar Plot





TEST NUMBER: P206851

CATALOG NUMBER: LD4B20D010 EU4B10209040 4LBWGPH1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	110	107	104	110	107	105	103	103	101	99		100	98	96		96
2	106	100	96	92	104	99	95	91	95	92	89		92	90	87		90
3	100	92	87	82	98	91	86	81	88	84	80		86	82	79		83
4	94	85	78	74	92	84	78	73	81	76	72		79	75	71		77
5	88	78	72	67	86	77	71	66	75	70	66		74	69	65		72
6	83	72	65	61	81	71	65	60	70	64	60		68	63	59		67
7	78	67	60	55	76	66	60	55	65	59	55		64	58	55		63
8	73	62	56	51	72	62	55	51	61	55	50		59	54	50		58
9	69	58	51	47	68	58	51	47	57	51	47		56	50	46		55
10	65	54	48	43	64	54	48	43	53	47	43		52	47	43		51

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P206851

CATALOG NUMBER: LD4B20D010 EU4B10209040 4LBWGPH1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	78.1	6.8
10°-20°	221.2	19.2
20°-30°	317.3	27.6
30°-40°	298.7	26.0
40°-50°	165.0	14.3
50°-60°	52.9	4.6
60°-70°	13.2	1.2
70°-80°	3.2	0.3
80°-90°	0.3	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	616.5	53.6
0°-40°	915.3	79.6
0°-60°	1133.2	98.6
0°-90°	1149.8	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1149.8	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	828	
5°	824	78
15°	784	221
25°	696	317
35°	485	299
45°	209	165
55°	54	53
65°	12	13
75°	2	3
85°	0	0
90°	0	



TEST NUMBER: P206851

CATALOG NUMBER: LD4B20D010 EU4B10209040 4LBWGPH1

CANDELA DISTRIBUTION (FULL):

	0°
0°	827.6
2.5°	821.6
5°	823.6
7.5°	817.6
10°	807.6
12.5°	797.6
15°	783.7
17.5°	771.7
20°	751.8
22.5°	723.9
25°	695.9
27.5°	658.1
30°	608.2
32.5°	552.4
35°	484.6
37.5°	412.8
40°	339.0
42.5°	271.2
45°	209.4
47.5°	157.5
50°	113.7
52.5°	79.8
55°	53.8
57.5°	35.9
60°	25.9
62.5°	17.9
65°	12.0
67.5°	8.0
70°	6.0
72.5°	4.0
75°	2.0
77.5°	2.0
80°	2.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)