

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P206031

Luminaire Tested: **LD4B30D010 EU4B30508040 4LBSB1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P206031
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LD4B30D010 EU4B30508040 4LBSB1
Description: PORTFOLIO 4 INCH SHALLOW RECESSED DOWNLIGHT
SHALLOW DISTRIBUTION WITH SPECULAR BLACK TRIM
WATTAGE D010TR-27.4W DE010-27.95W D5LT-27.65W DMX-27.73W DL2-29.56W
DL3-29.67W DLE-29.73W
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 2609.4 lumens
Efficiency: N/A
Efficacy: 93.2 lumens/watt
Spacing Criteria (0/90/45): 1.2 / 1.2 / 1.3
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 28
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P206031

CATALOG NUMBER: LD4B30D010 EU4B30508040 4LBSB1

Luminous Intensity Polar Plot





TEST NUMBER: P206031

CATALOG NUMBER: LD4B30D010 EU4B30508040 4LBSB1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20					20					20					20
RC	80				70					50					30					10
RW	70	50	30	10	70	50	30	10		50	30	10		50	30	10		50	30	10
RCR																				
0	119	119	119	119	116	116	116	116		111	111	111		106	106	106		102	102	102
1	111	107	103	100	108	105	101	98		100	98	95		97	94	93		93	91	90
2	102	95	89	84	100	93	88	83		90	85	81		86	83	79		84	80	78
3	94	84	77	72	91	83	76	71		80	74	70		77	73	68		75	71	67
4	86	76	68	62	84	74	67	61		72	65	60		70	64	60		68	63	59
5	80	68	60	54	78	67	59	53		65	58	53		63	57	52		61	56	52
6	74	62	53	47	72	61	53	47		59	52	47		57	51	46		56	50	46
7	69	56	48	42	67	55	48	42		54	47	42		52	46	41		51	45	41
8	64	51	43	38	63	51	43	38		49	42	37		48	42	37		47	41	37
9	60	47	39	34	59	47	39	34		46	39	34		45	38	34		44	38	34
10	56	44	36	31	55	43	36	31		42	36	31		41	35	31		40	35	31

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P206031

CATALOG NUMBER: LD4B30D010 EU4B30508040 4LBSB1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	108.6	4.2
10°-20°	308.3	11.8
20°-30°	458.6	17.6
30°-40°	533.6	20.4
40°-50°	520.1	19.9
50°-60°	400.1	15.3
60°-70°	221.1	8.5
70°-80°	58.6	2.2
80°-90°	0.4	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	875.5	33.6
0°-40°	1409.1	54.0
0°-60°	2329.3	89.3
0°-90°	2609.4	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2609.4	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1151	
5°	1144	109
15°	1092	308
25°	996	459
35°	857	534
45°	675	520
55°	447	400
65°	222	221
75°	50	59
85°	0	0
90°	0	



TEST NUMBER: P206031

CATALOG NUMBER: LD4B30D010 EU4B30508040 4LBSB1

CANDELA DISTRIBUTION (FULL):

0°	
0°	1151.1
2.5°	1151.1
5°	1144.5
7.5°	1134.6
10°	1128.0
12.5°	1108.1
15°	1091.6
17.5°	1075.0
20°	1051.9
22.5°	1028.7
25°	995.6
27.5°	962.6
30°	929.5
32.5°	893.1
35°	856.7
37.5°	810.4
40°	770.7
42.5°	727.7
45°	674.8
47.5°	625.2
50°	568.9
52.5°	509.4
55°	446.6
57.5°	387.0
60°	330.8
62.5°	274.5
65°	221.6
67.5°	172.0
70°	125.7
72.5°	86.0
75°	49.6
77.5°	23.2
80°	3.3
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)