

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P1500391

Luminaire Tested: LD4C25D010 EU4259027 4LBMH

Issue Date: 2/8/2022

Test Information

Test Method: LM-79-2019
Report Number: P1500391
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P207151)
Test Lab: INNOVATION CENTER
Issue Date: 2/8/2022
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD4C25D010 EU4259027 4LBMH
Description: 4 INCH 2500 LUMEN PORTFOLIO LED DOWNLIGHT WITH, 2700K, 90CRI LEDS AND 4LBM TRIM FINISH
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1810.0 lumens
Efficiency: N/A
Efficacy: 57.5 lumens/watt
Spacing Criteria (0/90/45): 0.95 / 0.95 / 0.93
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 31.5
Input Voltage (V):
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1500391

CATALOG NUMBER: LD4C25D010 EU4259027 4LBMH

Luminous Intensity Polar Plot



TEST NUMBER: P1500391

CATALOG NUMBER: LD4C25D010 EU4259027 4LBMH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	110	108	105	111	108	106	104	104	102	100		100	99	97		97
2	107	102	98	94	105	100	96	93	97	94	91		94	91	89		91
3	101	94	89	85	99	93	88	84	90	86	83		88	84	82		86
4	96	88	82	77	94	86	81	77	84	80	76		82	78	75		80
5	90	82	75	71	89	81	75	70	79	74	70		77	73	69		75
6	86	76	70	65	84	75	69	65	74	68	64		72	68	64		71
7	81	71	65	60	80	70	64	60	69	64	60		68	63	59		67
8	77	67	60	56	75	66	60	56	65	59	56		64	59	55		63
9	73	63	56	52	72	62	56	52	61	56	52		60	55	52		59
10	69	59	53	49	68	59	53	49	58	52	49		57	52	48		56

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	220485
5°	217282
10°	208206
15°	196657
20°	183569
25°	166636
30°	139121
35°	100784
40°	63091
45°	36069
50°	18807
55°	10538
60°	6708
65°	3983
70°	2945
75°	1282
80°	1910
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 36069 cd/sqm

TEST NUMBER: P1500391

CATALOG NUMBER: LD4C25D010 EU4259027 4LBMH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	165.1	9.1
10°-20°	433.2	23.9
20°-30°	556.8	30.8
30°-40°	418.9	23.1
40°-50°	168.3	9.3
50°-60°	47.8	2.6
60°-70°	15.1	0.8
70°-80°	4.3	0.2
80°-90°	0.4	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1155.2	63.8
0°-40°	1574.1	87.0
0°-60°	1790.2	98.9
0°-90°	1810.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1810.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1795	
5°	1762	165
15°	1546	433
25°	1229	557
35°	672	419
45°	208	168
55°	49	48
65°	14	15
75°	3	4
85°	0	0
90°	0	

TEST NUMBER: P1500391

CATALOG NUMBER: LD4C25D010 EU4259027 4LBMH

CANDELA DISTRIBUTION (FULL):

0°	
0°	1794.7
2.5°	1783.8
5°	1761.9
7.5°	1720.9
10°	1669.0
12.5°	1606.3
15°	1546.2
17.5°	1477.8
20°	1404.1
22.5°	1324.9
25°	1229.3
27.5°	1114.5
30°	980.7
32.5°	830.4
35°	672.0
37.5°	524.5
40°	393.4
42.5°	289.6
45°	207.6
47.5°	142.1
50°	98.4
52.5°	68.3
55°	49.2
57.5°	35.5
60°	27.3
62.5°	19.1
65°	13.7
67.5°	10.9
70°	8.2
72.5°	5.5
75°	2.7
77.5°	2.7
80°	2.7
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)